



SECURITY ELECTRONIC EQUIPMENT CO., LTD - Hotline Vietnam: 0903228633

X Ray Baggage Scanner AT5030A



AT5030A High Clear Images Displayed





Model: AT-5030A ----- Popular economic Version

The AT-5030A easily accommodates the inspection of hand baggage and parcels.

General Specification

Tunnel Size: 503(W)*303(H)mm

Conveyor Speed: 0.22m/s

Conveyor Max Load: 150kg

Conveyor height: 750mm

Dose per Inspection: <2.0μSv

Wire Resolution: 36AWG

Steel Penetration: 8mm

Film Safety: Guarantee ISO1600 Film

X-ray Leakage: <0.87μSv/h (at a distance of 5cm From external housing)

X-ray Generator

Generate direct: Upward

Generate angle: 80 degree

Anode Voltage: 80Kv

Anode power: 0.6mA

Cooling / Duty Cycle: Oil Cooling /100%

Image System

X-ray Sensor: L-Shaped Photodiode Array , 12bit Deep

Monitor: High Resolution Color, LCD Accord, 17 inch

Image Processing: Black / white, super-enhance, reversed color, Edge enhancement, image strengthening, image lightening,, reducing darkening, image returning, image retrieval.

Image Grey Level: 4096

Image Max Resolution: 1024 * 1280 pixel

Image Processing: 24bit for processing real time

Image storage: Storage 60000 pictures in real time

Zoom: 2,4,8,16,32 Times Enlarge, Whole screen continuous observation

Computer

- Brand GRANTECH.
- CPU: Intl Core 2 Duo 3400, 2.6GHz, 1MB, L2 Cache and 800Mhz FSB Little low version
- Motherboards: Intel G41
- Bus architecture: Integrated Graphics, 5PCI, 1PCI Express *1 and 1PCI BX press *16
- Memory: 2GB 1333MHz DDR3 RAM, with Minimum 2 total DIMM slots. Better
- Hard Disk drive: 500GB 7200 rpm serial ATA HDD. Better
- Operating System: Windows XP

Other Characters

Extension Rollers: Optional



UPS: Optional

TIP (Threat Image Projection) : Optional

CD DVR/RW unit: Optional

Certificates: ISO, CE

LCD monitor: 17inch or 19 inch

Operating Environment

Operation temperature/Humidity: 0°C-45°C/10%-95%(non-condensing)

Storage Temperature/Humidity: -40°C-60°C/10%-95%(non-condensing)

Operation Power: 220VAC(±10%), 50Hz

Power Consumption: 1.0 KW (max), 0.3KW(working)

Noise: <58db

Dimension Drawing

