

Kurento: The WebRTC Modular Media Server

Boni García

boni.garcia@urjc.es




Universidad
Rey Juan Carlos

Multimedia development implies **complexity**




The Kurento formula



Key concepts: Media elements and Pipelines

■ Media Element


- Provides a specific media functionality
 - › Send/receive media. These are the **Endpoints**
 - › Process media
 - › Transform media
- Ready to be used
- New media elements can be added




Key concepts: Media elements and Pipelines


■ Media Pipeline

- Chain of media elements implementing the desired media logic
- The Media Server provides the capability of creating media pipelines by joining media elements of the toolbox





Kurento Toolbox








ubuntu 14.04 LTS

boni@demo: ~

```
$ echo "deb http://ubuntu.kurento.org trusty kms6" | sudo tee /etc/apt/sources.list.d/kurento.list
$ wget -O - http://ubuntu.kurento.org/kurento.gpg.key | sudo apt-key add -
$ sudo apt-get update
$ sudo apt-get install kurento-media-server-6.0
```

Kurento Development with Java

@Autowired

```
private KurentoClient kurentoClient;
```

```
MediaPipeline pipeline = kurentoClient.createMediaPipeline();  
WebRtcEndpoint webRtcEndpoint = new WebRtcEndpoint.Builder(pipeline)  
    .build();  
FaceOverlayFilter faceOverlayFilter = new FaceOverlayFilter.Builder(  
    pipeline).build();  
webRtcEndpoint.connect(faceOverlayFilter);  
faceOverlayFilter.connect(webRtcEndpoint);
```



pom.xml

```
<dependencies>  
  <dependency>  
    <groupId>org.kurento</groupId>  
    <artifactId>kurento-client</artifactId>  
    <version>6.6.0</version>  
  </dependency>  
  <dependency>  
    <groupId>org.kurento</groupId>  
    <artifactId>kurento-utils-js</artifactId>  
    <version>6.6.0</version>  
  </dependency>  
</dependencies>
```

Kurento Development with JavaScript for browser

JavaScript

```
kurentoClient.create("MediaPipeline", function(error, pipeline) {  
  pipeline.create('WebRtcEndpoint', function(error, webRtc) {  
    if (error) return onError(error);  
    pipeline.create('FaceOverlayFilter', function(error, filter) {  
      if (error) return onError(error);  
      webRtc.connect(filter, function(error) {  
        if (error) return onError(error);  
        filter.connect(webRtc, function(error) {  
          if (error) return onError(error);  
        });  
      });  
    });  
  });  
});  
});
```

JS



bower.json

```
"dependencies": {  
  "kurento-client": "6.6.0",  
  "kurento-utils": "6.6.0"  
}
```

Kurento Development with JavaScript for Node.js

JavaScript

```
kurentoClient.create("MediaPipeline", function(error, pipeline) {  
  pipeline.create('WebRtcEndpoint', function(error, webRtc) {  
    if (error) return onError(error);  
    pipeline.create('FaceOverlayFilter', function(error, filter) {  
      if (error) return onError(error);  
      webRtc.connect(filter, function(error) {  
        if (error) return onError(error);  
        filter.connect(webRtc, function(error) {  
          if (error) return onError(error);  
        });  
      });  
    });  
  });  
});  
});
```



bower.json


```
"dependencies": {  
  "kurento-utils": "6.6.0"  
}
```



package.json

```
"dependencies": {  
  "kurento-client": "6.6.0"  
}
```

“Magic Mirror” Example



Kurento Tutorial 1: M. x

localhost:8080

Kurento Tutorial


Source Code

Tutorial 2: Magic Mirror


This application shows a *WebRtcEndpoint* connected to itself (loopback) with a *FaceOverlay* filter in the middle (take a look to the [Media Pipeline](#)). To run this demo follow these steps:

1. Open this page with a browser compliant with WebRTC (Chrome, Firefox).
2. Click on Start button.
3. Grant the access to the camera and microphone. After the SDP negotiation the loopback should start.
4. Click on Stop to finish the communication.

Local stream



Remote stream



Start

Stop

Console



```
Created SDP offer
Local description set
ICE negotiation completed
Invoking SDP offer callback function localhost:8080
SDP answer received, setting remote description
```

© 2014 Kurento


Universidad Rey Juan Carlos

NaevA

Magic Mirror Media Pipeline



Video call one to one



Kurento Tutorial 2: V... x

localhost:8080

Kurento Tutorial Source Code

Tutorial 4: Video Call 1 to 1 with WebRTC

This web application consists on an one to one video call using [WebRTC](#). In other words, this application is similar to a phone but also with video. The [Media Pipeline](#) is composed by two interconnected *WebRtcEndpoints*. To run this demo follow these steps:

1. Open this page with a browser compliant with WebRTC (Chrome, Firefox).
2. Type a nick in the field *Name* and click on *Register*.
3. In a different machine (or a different tab in the same browser) follow the same procedure to register another user.
4. Type the name of the user to be called in the field *Peer* and click *Call*.
5. Grant the access to the camera and microphone for both users. After the SDP negotiation the communication should start.
6. The called user should accept the incoming call (by a confirmation dialog).
7. Click on *Stop* to finish the communication.

Name


+ Register

Peer


▶ Call ■ Stop


Console

```
Sending message: {"id": "register", "name": "boni"}
Received message: {"id": "registerResponse", "response": "accepted"}
Created SDP offer
Local description set
ICE negotiation completed
Invoking SDP offer callback function
Sending message:
{"id": "call", "from": "boni", "to": "mica", "sdpOffer": "v=0/r/n=--"}
4
```




© 2014 Kurento

 Universidad Rey Juan Carlos

 NaevA Tec

Advanced video call one to one



Kurento Tutorial 3: A x

localhost:8080

Kurento Tutorial

Source Code

Tutorial 5: Advanced Video Call 1 to 1 with WebRTC

This web application consists of an advanced one to one video call using WebRTC. It uses the following Kurento capabilities: the recording of the video communication, and also an augmented reality filter (face overlay) in the remote stream. This application implements two different Media Pipelines. The first Media Pipeline is used to communicate two peers and it is composed by two interconnected WebRtcEndpoints with (FaceOverlayFilter) in between and also a RecorderEndpoint to carry out the recording. The recorded stream will be stored in the file system of the Kurento Media Server. Then, a second Media Pipeline is used to play the recorded media. To run this demo follow these steps:

1. Open this page with a browser compliant with WebRTC (Chrome, Firefox).
2. Type a nick in the field Name and click on Register.
3. In a different machine (or a different tab in the same browser) follow the same procedure to register another user.
4. Type the name of the user to be called in the field Peer and click on Call.
5. Grant the access to the camera and microphone for both users. After the SDP negotiation the communication should start.
6. The called user should accept the incoming call (by a confirmation dialog).
7. Click on Stop to finish the communication.
8. Type the name of the user to play its recording in the field Peer and click on Play Rec

Name
boni + Register


Peer
mica ▶ Call ■ Stop ▶ Play Rec

Console

```
Sending message: {"id":"register","name":"boni"}
Received message: {"id":"","registerResponse","response":"accepted"}
Created SDP offer
Local description set
ICE negotiation completed
Invoking SDP offer callback function
Sending message:
{"id":"call","from":"boni","to":"mica","sdpOffer":"","vno":--
```

© 2014 Kurento

Video call one to many



Further information

- Home page

<http://www.kurento.org/>

- Source code

<https://github.com/kurento>

- Developers guide

<http://doc-kurento.readthedocs.io/>

- Support

<https://groups.google.com/forum/#!forum/kurento>

- Twitter

<https://twitter.com/kurentoms>



 **Read *the* Docs**

