

A near-optimal recovery algorithm for the Stokes equations with incomplete information on the boundary conditions *

Andrea Bonito¹ and Diane Guignard²

¹Texas A&M University, Department of Mathematics, College Station, TX 77843, USA (bonito@tamu.edu)

²Department of Mathematics and Statistics, University of Ottawa, Canada (dguignar@uottawa.ca)

April 30, 2026

Abstract

We address the problem of numerically approximating the velocity and pressure governed by the Stokes system when the boundary conditions are only partially known and thus do not uniquely determine the velocity-pressure couple. We propose an algorithm that takes advantage of available linear measurements of the velocity and pressure to construct a numerical approximation. This approximation is guaranteed to be near-optimal in the sense that it approximates the velocity-pressure couple that minimizes, in the energy norm, the distance to all other solutions satisfying the measurements and the Stokes system.

1 Introduction

We consider the Stokes system

$$-\mathbf{div}(\nabla \mathbf{u} + \nabla \mathbf{u}^T) + \nabla p = \mathbf{f} \quad \text{and} \quad \mathbf{div}(\mathbf{u}) = 0 \quad \text{in } \Omega \quad (1)$$

relating the velocity $\mathbf{u} : \Omega \rightarrow \mathbb{R}^d$ with the pressure $p : \Omega \rightarrow \mathbb{R}$ of a fluid in a bounded domain $\Omega \subset \mathbb{R}^d$, $d = 2, 3$, with Lipschitz boundary $\partial\Omega$. Here, $\mathbf{f} : \Omega \rightarrow \mathbb{R}^3$ is a given force applied to the fluid. Typically, the Stokes system is supplemented by boundary conditions on $\partial\Omega$ that either set the velocity, the force $(\nabla \mathbf{u} + \nabla \mathbf{u}^T)\mathbf{n} - p\mathbf{n}$, where $\mathbf{n}$ stands for the outward pointing normal to Ω , or a combination of both. We refer for instance to [27, 14, 25, 2] for details.

Instead, this work is concerned with situations where the type of boundary condition or its value is (partially) unknown. Missing boundary conditions in complex systems are the result of a lack of understanding of the physics [22, 24], the inaccessibility of the actual value to impose at the boundary [18], or the modification/truncations of the physical domain to design efficient numerical approximations [12, 23]. We refer in particular to [29, 10, 11] for examples where boundary conditions are missing in fluid dynamics, for which the Stokes system considered here is a prototype.

For the moment, consider the case where the velocity is known on $\partial\Omega$, say

$$\mathbf{u} = \mathbf{g} \quad \text{on } \partial\Omega \quad (2)$$

for some $\mathbf{g} : \partial\Omega \rightarrow \mathbb{R}^d$ satisfying $\int_{\partial\Omega} \mathbf{g} \cdot \mathbf{n} = 0$. Standard results, see Theorem I.5.1 and Remarks I.5.1 in [16], guarantee that for $\mathbf{g} \in H^{\frac{1}{2}}(\partial\Omega)$ and $\mathbf{f} \in H^{-1}(\Omega)^d$, there exists a unique solution $(\mathbf{u}(\mathbf{g}), p(\mathbf{g})) \in X$ with $\int_{\Omega} p(\mathbf{g}) = 0$, where

$$X := \left\{ (\mathbf{v}, q) \in H^1(\Omega)^d \times L^2(\Omega) : \int_{\partial\Omega} \mathbf{v} \cdot \mathbf{n} = 0 \right\}$$

*This research was supported in part by the NSF Grant DMS-2409807 (AB) and the NSERC Discovery Grant RGPIN-2021-04311 (DG).

is equipped with the graph norm; see Section 1.1 for the definition of these spaces. The velocity-pair is also unique when restricting the mean value of the pressure $|\Omega|^{-1} \int_{\Omega} p = P$ for some given $P \in \mathbb{R}$. In that case, the data $(\mathbf{g}, P)$ and the solution $(\mathbf{u}(\mathbf{g}, P), p(\mathbf{g}, P)) \in X$ satisfy

$$\|\mathbf{u}(\mathbf{g}, P), p(\mathbf{g}, P)\|_X \leq C \left(\|\mathbf{f}\|_{H^{-1}(\Omega)} + \|\mathbf{g}\|_{H^{\frac{1}{2}}(\partial\Omega)} + |P| \right) \quad (3)$$

for some constant C only depending on Ω ; refer to Remarks I.5.1 and I.5.3 in [16].

In contrast, the velocity and pressure that satisfy the Stokes system (1) cannot be uniquely determined without a boundary condition. To alleviate some of this uncertainty, we propose a recovery algorithm that relies on a model class assumption, or prior, to construct the “best” velocity-pressure as defined below. It consists of restricting our search for velocities-pressures such that for some $s > 1/2$ and some $C_{\text{data}} > 0$

$$(\mathbf{u}, p) \in K := \left\{ (\mathbf{v}, q) \in X : (\mathbf{v}, q) \text{ satisfies (1), } \|\mathbf{v}\|_{H^s(\partial\Omega)} + \left| |\Omega|^{-1} \int_{\Omega} q \right| \leq C_{\text{data}} \right\}. \quad (4)$$

Such velocities possess slightly more smoothness than the standard boundary regularity $H^{\frac{1}{2}}(\partial\Omega)$. However, we observe that, in any case, higher regularity is necessary for any algorithm to construct a meaningful approximation of the exact velocity. We also emphasize that it is not assumed that the target solution of (1) satisfies any specific type of boundary condition and that although the pressures in K must satisfy $|\Omega|^{-1} \int_{\Omega} p \leq C_{\text{data}}$, the mean value of the pressure is not prescribed and therefore becomes part of the recovery process.

In addition, we assume that measurements $\omega_i := \lambda_i(\mathbf{u}, p) \in \mathbb{R}$, $i = 1, \dots, m$, of some $(\mathbf{u}, p)$ satisfying (1) and (4) are available, where the λ_i are fixed measurement functionals on X . We then gather all the information about the function to be recovered in

$$K_{\mathbf{w}}^s := \{(\mathbf{v}, q) \in K : \lambda_i(\mathbf{u}, q) = \omega_i, i = 1, \dots, m\}.$$

The set $K_{\mathbf{w}}^s$ is generally not reduced to one element (the solution to recover). In fact, any element in $K_{\mathbf{w}}^s$ is a possible recovery for $(\mathbf{u}, p)$. We say that $(\mathbf{u}^*, p^*)$ is the best recovery in $K_{\mathbf{w}}^s$ if

$$\sup_{(\mathbf{v}, q) \in K_{\mathbf{w}}^s} \|(\mathbf{v}, q) - (\mathbf{u}^*, p^*)\|_X \leq \inf_{(\mathbf{u}, p) \in X} \sup_{(\mathbf{v}, q) \in K_{\mathbf{w}}^s} \|(\mathbf{v}, q) - (\mathbf{u}, p)\|_X =: R(K_{\mathbf{w}}^s)_X =: R(K_{\mathbf{w}}^s). \quad (5)$$

Geometrically, $(\mathbf{u}^*, p^*)$ is the center of the smallest ball in X (with radius $R(K_{\mathbf{w}}^s)$) containing $K_{\mathbf{w}}^s$. It is called the Chebyshev center of $K_{\mathbf{w}}^s$ and $R(K_{\mathbf{w}}^s)$ is the Chebyshev radius [4, 20, 21, 28]. The latter serves as a benchmark for recovery algorithms.

When $\mathbf{f} = \mathbf{0}$, the Chebyshev center $(\mathbf{u}^*, p^*)$ in the recovery setting considered here is characterized as element in $K_{\mathbf{w}}^s$ whose norm is minimal [20, 21]. In particular, $K_{\mathbf{w}}^s = K \cap \text{span}(\phi_1, \dots, \phi_m)$, where ϕ_j are appropriate Riesz representers of the measurement functionals λ_j . They are the solutions to the Stokes system (1) with $\mathbf{f} = \mathbf{0}$ and satisfy a fractional partial differential equation on $\partial\Omega$; refer to Section 3 for more details. Hence, the Chebyshev center satisfies

$$(\mathbf{u}^*, p^*) = \sum_{j=1}^m \alpha_j^* \phi_j, \quad (6)$$

for some $\boldsymbol{\alpha}^* = (\alpha_j^*) \in \mathbb{R}^m$ determined so that $(\mathbf{u}^*, p^*)$ satisfies the measurements. The general case where $\mathbf{f} \neq \mathbf{0}$ is obtained by shifting expression (6) by the solution to (1) supplemented by vanishing Dirichlet condition.

The minimal norm property is exploited in [1] to design a kernel method algorithm for the approximation of an optimal recovery of general, possibly nonlinear, partial differential equations. In [3] and later in [6, 5], the representation (6) is advocated to design near-optimal algorithms for the Poisson problem. In these works, fully practical and near-optimal algorithms based on the approximation of the Riesz representers are

proposed. The challenges that arise in the Stokes system, compared to the Poisson problem, stem from the added complexity and efficiency requirements to determine the Riesz representer ϕ_j , the inherent nontrivial compatibility conditions that admissible boundary data must satisfy, and the need to recover the pressure average within the recovery process.

Inspired by [3, 6], we consider an algorithm that constructs Riesz representers that are within a tolerance $\varepsilon > 0$ in $H^1(\Omega)^d \times L^2(\Omega)$ of the exact Riesz representer. We show that using these approximate Riesz representers in (6) yields $(\mathbf{u}^\varepsilon, p^\varepsilon)$ such that

$$\sup_{(\mathbf{v}, q) \in K_{\mathbf{w}}^s} \|(\mathbf{v}, q) - (\mathbf{u}^\varepsilon, p^\varepsilon)\|_X \leq C(\varepsilon)R(K_{\mathbf{w}}^s), \quad (7)$$

where $C(\varepsilon) \rightarrow 1^+$ as $\varepsilon \rightarrow 0^+$. In that case, we say that the algorithm $A : \varepsilon \mapsto (\mathbf{u}^\varepsilon, p^\varepsilon)$ is near-optimal.

We further address the question of near-optimal performance for quantities of interest $Q : X \rightarrow \mathbb{R}$ such as drag or lift. In particular, we show that the algorithm $A_Q : \varepsilon \mapsto Q(\mathbf{u}^\varepsilon, p^\varepsilon) \in \mathbb{R}$ is near-optimal for the quantity of interest, that is,

$$\sup_{(\mathbf{v}, q) \in K_{\mathbf{w}}^s} |Q(\mathbf{v}, q) - Q(\mathbf{u}^\varepsilon, p^\varepsilon)| \leq C(\varepsilon) \inf_{l \in \mathbb{R}} \sup_{(\mathbf{v}, q) \in K_{\mathbf{w}}^s} |Q(\mathbf{v}, q) - l|, \quad (8)$$

where again $C(\varepsilon) \rightarrow 1^+$ as $\varepsilon \rightarrow 0$.

A concrete/practical realization of the algorithm is then obtained by approximating the Riesz representers using a finite element method. For each ϕ_j it consists of three successive steps. We employ Lagrange multipliers to ensure that $(\mathbf{w}_j, r_j) := \phi_j$ satisfies (1) in Ω and the first step of the algorithm consists of approximating a Stokes-like system to determine the approximate Lagrange multipliers. Then, the solution to a fractional partial differential equation on $\partial\Omega$ is approximated to determine the approximation of $\mathbf{w}_j|_{\partial\Omega}$. In the last step, the approximation of ϕ_j inside Ω is determined solving again a Stokes-like system in Ω .

In Section 2, we describe in more detail the concept of an optimal algorithm in the present context and present in Section 3 the analysis of conceptual near-optimal algorithms, i.e., producing $(\mathbf{u}^\varepsilon, p^\varepsilon)$ satisfying (7) and (8). A finite element method for the approximation of the Riesz representers is described in Section 4 followed by numerical illustrations of the performance of the practical algorithms in Section 5. But before we start with some preliminaries and notation.

1.1 Preliminaries and notations

Let $\Omega \subset \mathbb{R}^d$, $d \in \{2, 3\}$, be a bounded domain with Lipschitz boundary $\Gamma := \partial\Omega$ and let $\mathcal{R} = \Omega$ or $\mathcal{R} = \Gamma$.

We denote by $L^q(\mathcal{R})$, $1 \leq q \leq \infty$, the standard Lebesgue spaces of measurable functions. When $q = 2$ the space of square integrable functions $L^2(\mathcal{R})$ is a Hilbert space with the inner product and associated norm

$$\langle v, w \rangle_{L^2(\mathcal{R})} := \int_{\mathcal{R}} vw \quad \text{and} \quad \|v\|_{L^2(\mathcal{R})} := \sqrt{\langle v, v \rangle_{L^2(\mathcal{R})}}, \quad v, w \in L^2(\mathcal{R}).$$

For a function $q \in L^1(\Omega)$, we use $\bar{q}$ to denote its mean (average) defined by

$$\bar{q} := \text{mean}(q) := \frac{1}{|\Omega|} \int_{\Omega} q. \quad (9)$$

Moreover, we introduce the space $L_0^2(\Omega) := \{q \in L^2(\Omega) : \text{mean}(q) = 0\}$ of square integrable functions with mean value zero.

We equip the Sobolev space $H^1(\mathcal{R})$ with the standard norm $\|\cdot\|_{H^1(\mathcal{R})}$ induced by the inner product

$$\langle v, w \rangle_{H^1(\mathcal{R})} := \int_{\mathcal{R}} vw + \int_{\mathcal{R}} \nabla_{\mathcal{R}} v \cdot \nabla_{\mathcal{R}} w, \quad v, w \in H^1(\mathcal{R}), \quad (10)$$

where $\nabla_{\Omega} := \nabla$ and ∇_{Γ} is the tangential gradient to Γ . We denote by $H_0^1(\Omega)$ the space of $H^1(\Omega)$ functions whose trace vanishes on Γ , and by $H^{-1}(\Omega)$ the dual of $H_0^1(\Omega)$. The $H^{-1}(\Omega) - H_0^1(\Omega)$ duality product is denoted $\langle \cdot, \cdot \rangle$.

We also need the fractional (interpolation) Sobolev space $H^s(\Gamma)$, $0 < s < 1$, which are Hilbert spaces with the inner product and associated norm defined for $v, w \in H^s(\Gamma)$ by

$$\langle v, w \rangle_{H^s(\Gamma)} := \langle (I - \Delta_\Gamma)^{s/2} v, (I - \Delta_\Gamma)^{s/2} w \rangle_{L^2(\Gamma)} \quad \text{and} \quad \|v\|_{H^s(\Gamma)} := \sqrt{\langle v, v \rangle_{H^s(\Gamma)}}. \quad (11)$$

Here $(I - \Delta_\Gamma)^{s/2}$ are the fractional powers of the operator $I - \Delta_\Gamma$ [19] with I the identity and Δ_Γ the Laplace–Beltrami operator. This special choice of inner products, which are equivalent to the standard Slobodeckij inner products, is preferred to facilitate their approximations needed by the proposed recovery algorithm; see Section 2.2 in [6] for more details. We recall that there is $r^* > 1$ depending on the regularity of Ω such that

$$\|v|_\Gamma\|_{H^{\frac{1}{2}+r}(\Gamma)} \leq C \|v\|_{H^{1+r}(\Omega)}, \quad 1 \leq r \leq r^*, \quad (12)$$

for some constant C only depending on Ω and where $v|_\Gamma$ denotes the (extension to $H^1(\Omega)$ of the) trace operator. When confusion is not possible, we will simply write v for the trace of v .

The inner products and norms of scalar-valued functions are extended to vector-valued functions by a component-wise application. More precisely, if H is a Hilbert space with inner product $\langle \cdot, \cdot \rangle_H$ and associated norm $\|\cdot\|_H$, then for $\mathbf{v} = (v_1, \dots, v_d)$, $\mathbf{w} = (w_1, \dots, w_d) \in H^d$ we define

$$\langle \mathbf{v}, \mathbf{w} \rangle_H := \sum_{i=1}^d \langle v_i, w_i \rangle_H \quad \text{and} \quad \|\mathbf{v}\|_H := \sqrt{\sum_{i=1}^d \|v_i\|_H^2}. \quad (13)$$

In particular, we recall that we defined the functional space for the velocity-pressure couple by

$$X = \left\{ (\mathbf{v}, q) \in H^1(\Omega)^d \times L^2(\Omega) : \int_\Gamma \mathbf{v} \cdot \mathbf{n} = 0 \right\} \quad (14)$$

with $\|(\mathbf{v}, q)\|_X := \sqrt{\|\mathbf{v}\|_{H^1(\Omega)}^2 + \|q\|_{L^2(\Omega)}^2}$.

Similarly, an operator acting on a scalar-valued function will be extended to vector-valued functions by component-wise application.

We end this section with some notational conventions. Given a functional $F : X \rightarrow \mathbb{R}$, we will often write $F(\mathbf{v}, q) := F((\mathbf{v}, q))$ for $(\mathbf{v}, q) \in X$ and similarly $\|\mathbf{v}, q\|_X := \|(\mathbf{v}, q)\|_X$.

2 Optimal recovery problem

We assume that the boundary conditions on Γ are not known. This could reflect a lack of knowledge of the boundary data, but also of the actual physics, namely, the type of boundary conditions. To simplify the presentation, we suppose for now that no information is available on boundary conditions and postpone the discussion of partially known boundary data to Section 2.2. Not knowing the boundary conditions means (1) does not uniquely determine $\mathbf{u}$ and p . This lack of knowledge is alleviated by the following assumptions on the velocity-pressure $(\mathbf{u}^{\text{ex}}, p^{\text{ex}})$ to recover. We recall that r^* is defined in (12).

(H1) **Regularity:** The boundary trace of the velocity satisfies $\mathbf{u}^{\text{ex}}|_\Gamma \in H^s(\Gamma)^d$ for some $\frac{1}{2} < s \leq r^*$;

$$\|\mathbf{u}^{\text{ex}}\|_{H^s(\Gamma)} + |\text{mean}(p^{\text{ex}})| \leq C_{\text{data}}.$$

(H2) **Measurements:** We have access to measurements of $(\mathbf{u}^{\text{ex}}, p^{\text{ex}})$, namely we know the measurement vector

$$\mathbf{w} := \boldsymbol{\lambda}(\mathbf{u}^{\text{ex}}, p^{\text{ex}}) := \left(\lambda_1(\mathbf{u}^{\text{ex}}, p^{\text{ex}}), \lambda_2(\mathbf{u}^{\text{ex}}, p^{\text{ex}}), \dots, \lambda_m(\mathbf{u}^{\text{ex}}, p^{\text{ex}}) \right) \in \mathbb{R}^m,$$

where λ_j , $j = 1, \dots, m$, are linearly independent functionals on X .

We note that the regularity and boundedness assumptions (H1) are on the trace of the velocity and the pressure average. This indicates that we chose to recover these quantities from the measurements. An alternative approach would be, for example, to recover the boundary force $(2\varepsilon(\mathbf{u}^{\text{ex}}) - p^{\text{ex}}I)\mathbf{n}$ in $H^{-\frac{1}{2}}(\Gamma)$ (the dual of $H^{\frac{1}{2}}(\Gamma)$) along with the average velocity, but this approach is less favorable to the design of a practical recovery algorithm because it would involve negative norms on Γ .

We also anticipate that the recovery algorithm discussed in Section 3 explicitly uses the value of s but not that of C_{data} . This explains why only the dependence on s is indicated for the set gathering all the a-priori knowledge:

$$K_{\mathbf{w}}^s := \{(\mathbf{u}, p) \in K^s : \boldsymbol{\lambda}(\mathbf{u}, p) = \mathbf{w}\},$$

where

$$K^s := \{(\mathbf{u}, p) \in X : (\mathbf{u}, p) \text{ satisfies (1) and } \|\mathbf{u}\|_{H^s(\Gamma)} + |\text{mean}(p)| \leq C_{\text{data}}\}$$

is the so-called model class and is compact in X .

The *optimal recovery problem* consists of determining the best representative $(\mathbf{u}^*, p^*) \in X$ for all elements of $K_{\mathbf{w}}^s$, i.e.,

$$(\mathbf{u}^*, p^*) \in \arg \min_{(\mathbf{u}, p) \in X} \sup_{(\mathbf{v}, q) \in K_{\mathbf{w}}^s} \|(\mathbf{v}, q) - (\mathbf{u}, p)\|_X. \quad (15)$$

2.1 Decomposition of functions in X and associated recovery problem

We define the Stokes operator $\mathcal{S} : X \rightarrow H^{-1}(\Omega)^d \times \mathbb{R}$ for $(\mathbf{v}, q) \in X$ by

$$\mathcal{S}(\mathbf{v}, q) := \begin{pmatrix} -\text{div}(2\varepsilon(\mathbf{v})) + \nabla q \\ \text{div}(\mathbf{v}) \end{pmatrix}, \quad \varepsilon(\mathbf{v}) := \frac{1}{2}(\nabla \mathbf{v} + (\nabla \mathbf{v})^T).$$

Given $\mathbf{f} \in H^{-1}(\Omega)^d$, we consider velocity-pressure couples $(\mathbf{u}, p) \in X$ satisfying

$$\mathcal{S}(\mathbf{u}, p) = \begin{pmatrix} \mathbf{f} \\ 0 \end{pmatrix} \quad (16)$$

in the weak sense, that is

$$\langle 2\varepsilon(\mathbf{u}), \varepsilon(\mathbf{v}) \rangle_{L^2(\Omega)} - \langle p, \text{div}(\mathbf{v}) \rangle_{L^2(\Omega)} - \langle q, \text{div}(\mathbf{u}) \rangle_{L^2(\Omega)} = \langle \mathbf{f}, \mathbf{v} \rangle, \quad \forall (\mathbf{v}, q) \in H_0^1(\Omega)^d \times L_0^2(\Omega).$$

We recall that Theorem 5.1 in [16], see also Remarks 5.1 and 5.3 in [16], guarantees the existence and uniqueness of $(\mathbf{u}_{\mathbf{f}}, p_{\mathbf{f}}) \in X \cap (H_0^1(\Omega)^d \times L_0^2(\Omega))$ satisfying (16). Therefore, it will be convenient to decompose any couple $(\mathbf{u}, p) \in X$ satisfying (16) into two parts and introduce

$$(\mathbf{u}_{\mathcal{S}}, p_{\mathcal{S}}) := (\mathbf{u}, p) - (\mathbf{u}_{\mathbf{f}}, p_{\mathbf{f}}). \quad (17)$$

Since $\mathbf{f}$ is known, $(\mathbf{u}_{\mathbf{f}}, p_{\mathbf{f}})$ is uniquely determined and the challenge is to recover $(\mathbf{u}_{\mathcal{S}}, p_{\mathcal{S}}) \in X$. Notice that the latter satisfies $\mathcal{S}(\mathbf{u}_{\mathcal{S}}, p_{\mathcal{S}}) = \mathbf{0}$ and that if $(\mathbf{u}, p) \in K^s$, we also have $\|\mathbf{u}_{\mathcal{S}}\|_{H^s(\Gamma)} + |\text{mean}(p_{\mathcal{S}})| \leq C_{\text{data}}$. In other words, $(\mathbf{u}, p) \in K^s$ if and only if $(\mathbf{u}, p) = (\mathbf{u}_{\mathbf{f}}, p_{\mathbf{f}}) + (\mathbf{u}_{\mathcal{S}}, p_{\mathcal{S}})$ for some $(\mathbf{u}_{\mathcal{S}}, p_{\mathcal{S}}) \in \mathcal{K}^s$, where

$$\mathcal{K}^s := \{(\mathbf{v}, q) \in X^s : \|\mathbf{v}\|_{H^s(\Gamma)} + |\text{mean}(q)| \leq C_{\text{data}}\} \quad (18)$$

with

$$\mathcal{X}^s := \left\{ (\mathbf{v}, q) \in X : \mathcal{S}(\mathbf{v}, q) = \mathbf{0} \text{ and } \mathbf{v}|_{\Gamma} \in H^s(\Gamma)^d \right\} \subset X. \quad (19)$$

This indicates that the recovery of $(\mathbf{u}, p) \in K^s$ is equivalent to the recovery of $(\mathbf{u}_{\mathcal{S}}, p_{\mathcal{S}}) \in \mathcal{K}^s$ provided measurements of the latter are accessible. We take advantage of the linearity of the measurements to define $\mathbf{w}_{\mathcal{S}} := \mathbf{w} - \boldsymbol{\lambda}(\mathbf{u}_{\mathbf{f}}, p_{\mathbf{f}})$ so that $\mathbf{w}_{\mathcal{S}} = \boldsymbol{\lambda}(\mathbf{u}_{\mathcal{S}}, p_{\mathcal{S}})$ are the desired measurements of $(\mathbf{u}_{\mathcal{S}}, p_{\mathcal{S}})$. This leads to the definition of

$$\mathcal{K}_{\mathbf{w}_{\mathcal{S}}}^s := \{(\mathbf{u}, p) \in K^s : \boldsymbol{\lambda}(\mathbf{u}, p) = \mathbf{w}_{\mathcal{S}}\}.$$

We are now in a position to restate the optimal recovery problem in terms of $\mathcal{K}_{\mathbf{w}_S}^s$: given $s > 1/2$ and $\mathbf{w} \in \mathbb{R}^m$, find

$$(\mathbf{u}_S^*, p_S^*) \in \arg \min_{(\mathbf{u}, p) \in X} \sup_{(\mathbf{v}, q) \in \mathcal{K}_{\mathbf{w}_S}^s} \|(\mathbf{v}, q) - (\mathbf{u}, p)\|_X \quad (20)$$

and set $(\mathbf{u}^*, p^*) := (\mathbf{u}_f, p_f) + (\mathbf{u}_S^*, p_S^*)$ to obtain (15).

We end this section noting that thanks to (3) with $\mathbf{f} = \mathbf{0}$, the functional space $\mathcal{X}^s$ is a Hilbert space when equipped with the inner product and the associated norm

$$\langle (\mathbf{v}, q), (\mathbf{u}, p) \rangle_{\mathcal{X}^s} := \langle \mathbf{v}, \mathbf{u} \rangle_{H^s(\Gamma)} + \text{mean}(q)\text{mean}(p), \quad \|\mathbf{v}, q\|_{\mathcal{X}^s} := \sqrt{\langle (\mathbf{v}, q), (\mathbf{v}, q) \rangle_{\mathcal{X}^s}}. \quad (21)$$

Moreover, from the a-priori estimate (3) and the continuous embedding $H^s(\Gamma) \subset H^{\frac{1}{2}}(\Gamma)$, we infer the existence of some constant $C_s > 0$ depending only on Ω such that $\|\mathbf{v}, q\|_X \leq C_s \|\mathbf{v}, q\|_{\mathcal{X}^s}$ for $(\mathbf{v}, q) \in \mathcal{X}^s$ and in particular $\|\mathbf{v}, q\|_X \leq C_s C_{\text{data}}$ for $(\mathbf{v}, q) \in \mathcal{K}^s$.

2.2 Partial knowledge of the boundary conditions

In several applications, the boundary conditions are known on part of the boundary Γ . We briefly remark that the strategy developed in this work easily extends to that case.

Consider the decomposition $\Gamma = \Gamma_k \cup \Gamma_u$ of the boundary into two disjoint non-empty portions, where Γ_k is the part where the boundary conditions are known while no information about boundary data is available on Γ_u . To simplify the discussion, we assume that the velocity is known on Γ_k , i.e., $\mathbf{u} = \mathbf{g}_k$ for some known function $\mathbf{g}_k : \Gamma_k \rightarrow \mathbb{R}$, but the method can be extended to accommodate other types of known boundary conditions.

We are seeking a velocity-pressure couple $(\mathbf{u}, p)$ such that $\mathcal{S}(\mathbf{u}, p) = (\mathbf{f}, 0)^T$ and $\mathbf{u} = \mathbf{g}_k$ on Γ_k . Taking advantage of the splitting strategy (17), we define $(\mathbf{u}_f, p_f) \in X$ as satisfying $\mathcal{S}(\mathbf{u}_f, p_f) = (\mathbf{f}, 0)^T$ together with the boundary conditions

$$\mathbf{u} = \mathbf{g}_k \quad \text{on } \Gamma_k \quad \text{and} \quad 2\varepsilon(\mathbf{u})\mathbf{n} - p\mathbf{n} = \mathbf{0} \quad \text{on } \Gamma_u.$$

Note that since we impose (homogeneous) Neumann boundary conditions on Γ_u , the pressure is uniquely determined in $Q = L^2(\Omega)$. The recovery problem then reduces to finding $(\mathbf{u}_S, p_S)$ in $\mathcal{X}^s$ satisfying the modified measurement vector $\mathbf{w}_S := \mathbf{w} - \lambda(\mathbf{u}_f, p_f)$, where now

$$\mathcal{X}^s := \left\{ (\mathbf{v}, q) \in X : \mathcal{S}(\mathbf{v}, q) = \mathbf{0}, \mathbf{v}|_{\Gamma_k} = \mathbf{0}, \mathbf{v}|_{\Gamma_u} \in \left[H^s(\Gamma_u) \cap H_{00}^{\frac{1}{2}}(\Gamma_u) \right]^d \right\}$$

and $H_{00}^{\frac{1}{2}}(\Gamma_u)$ denotes the space of $H^{\frac{1}{2}}(\Gamma_u)$ functions whose extension by zero to Γ belongs to $H^{\frac{1}{2}}(\Gamma)$. Note that the latter reduces to $H^{\frac{1}{2}}(\Gamma_u)$ when Γ_u is a closed hyper-surface, which occurs when the closures of Γ_k and Γ_u are disjoint.

Unless specified otherwise, in the rest of the paper, we assume that the boundary condition is unknown on the entire boundary Γ , i.e., $\Gamma_k = \emptyset$.

3 Near optimal algorithm

In the setting considered in this work, the optimization problem (20) has a unique solution $(\mathbf{u}_S^*, p_S^*)$, which is the center of the smallest ball B in X containing $\mathcal{K}_{\mathbf{w}_S}^s$. It is called the Chebyshev center of $\mathcal{K}_{\mathbf{w}_S}^s$ and the best recovery performance is the radius $R(\mathcal{K}_{\mathbf{w}_S}^s)$ of B , see (5) which serves as benchmark for recovery algorithms. Moreover, in the present setting, $(\mathbf{u}_S^*, p_S^*) \in \mathcal{K}_{\mathbf{w}_S}^s$ is the element with minimal norm in $\mathcal{X}^s$:

$$(\mathbf{u}_S^*, p_S^*) = \arg \min_{(\mathbf{v}, q) \in \mathcal{K}_{\mathbf{w}_S}^s} \|\mathbf{v}, q\|_{\mathcal{X}^s} \quad (22)$$

and has thus the following favorable representation for its numerical approximation

$$(\mathbf{u}_S^*, p_S^*) = \sum_{j=1}^m \alpha_j^* \phi_j. \quad (23)$$

Here, for each $j = 1, 2, \dots, m$, ϕ_j is the Riesz representer of λ_j in the Hilbert space $\mathcal{X}^s \subset X$, i.e., $\phi_j \in \mathcal{X}^s$ solves

$$\langle \phi_j, \boldsymbol{\eta} \rangle_{\mathcal{X}^s} = \lambda_j(\boldsymbol{\eta}) \quad \forall \boldsymbol{\eta} \in \mathcal{X}^s. \quad (24)$$

Moreover, $\boldsymbol{\alpha}^* = (\alpha_j^*) \in \mathbb{R}^m$ is the solution to

$$G\boldsymbol{\alpha} = \mathbf{w}_S, \quad (25)$$

where $G = (g_{ij}) \in \mathbb{R}^{m \times m}$ is the Gram matrix with entries $g_{ij} := \lambda_i(\phi_j) = \langle \phi_i, \phi_j \rangle_{\mathcal{X}^s}$, $i, j = 1, 2, \dots, m$.

The idea, introduced in [3] and further considered in [6, 5], is to approximate the Riesz representers $\{\phi_j\}_{j=1}^m$ using a finite element method. The proposed strategy is summarised in Algorithm 1.

Algorithm 1 Recovery Algorithm

Require: Tolerances $\varepsilon_1 > 0$, $\varepsilon_2 > 0$

Ensure: Approximation $(\hat{\mathbf{u}}, \hat{p})$ of $(\mathbf{u}^*, p^*)$

1: Compute an approximation $(\hat{\mathbf{u}}_f, \hat{p}_f)$ of the solution $(\mathbf{u}_f, p_f) \in H_0^1(\Omega)^d \times L_0^2(\Omega)$ of (16) such that

$$\|(\mathbf{u}_f, p_f) - (\hat{\mathbf{u}}_f, \hat{p}_f)\|_X \leq \varepsilon_1; \quad (26)$$

2: Set $\hat{\mathbf{w}}_S := \mathbf{w} - \boldsymbol{\lambda}(\hat{\mathbf{u}}_f, \hat{p}_f)$;

3: For each $j \in \{1, 2, \dots, m\}$, compute an approximation $\hat{\phi}_j$ of the solution $\phi_j \in \mathcal{X}^s$ of (24) such that

$$\|\phi_j - \hat{\phi}_j\|_X \leq \varepsilon_2; \quad (27)$$

4: Set $\hat{G} = (\hat{g}_{ij}) \in \mathbb{R}^{m \times m}$ with $\hat{g}_{ij} := \lambda_i(\hat{\phi}_j)$ for $i, j = 1, 2, \dots, m$;

5: Solve

$$\hat{G}\hat{\boldsymbol{\alpha}} = \hat{\mathbf{w}}_S \quad (28)$$

and set

$$(\hat{\mathbf{u}}, \hat{p}) := (\hat{\mathbf{u}}_f, \hat{p}_f) + (\hat{\mathbf{u}}_S, \hat{p}_S), \quad \text{where} \quad (\hat{\mathbf{u}}_S, \hat{p}_S) := \sum_{j=1}^m \hat{\alpha}_j \hat{\phi}_j. \quad (29)$$

We have

Theorem 3.1 (Near optimal algorithm). *Let $(\hat{\mathbf{u}}, \hat{p})$ be the output of Algorithm 1. If ε_2 is small enough so that $\hat{G}$ is invertible, then*

$$\|(\mathbf{u}^*, p^*) - (\hat{\mathbf{u}}, \hat{p})\|_X \leq \varepsilon, \quad (30)$$

where $\varepsilon > 0$ satisfies $\varepsilon \in O(\varepsilon_1 + \varepsilon_2)$ and depends only on ε_1 , ε_2 , m , $\{\lambda_i\}_{i=1}^m$, $\{\phi_i\}_{i=1}^m$, G , $\hat{G}$, C_{data} , and C_s . In particular, we have

$$\sup_{(\mathbf{v}, q) \in K_{\mathbf{w}}^s} \|(\mathbf{v}, q) - (\hat{\mathbf{u}}, \hat{p})\|_X \leq R(K_{\mathbf{w}}^s)_X + \varepsilon.$$

The proof of this result directly follows the argument provided in [3], see also [5], for the Poisson problem. It is therefore omitted for the sake of brevity. In contrast, an optimal recovery result for a quantity of interest $Q \in X^\#$ - the dual of X - appears to be not directly available in the literature. The next result guarantees the optimality relation (32).

Theorem 3.2 (Near optimal for quantity of interest). *The unique optimal solution $(\mathbf{u}^*, p^*) \in X$ to (15) satisfies $(\mathbf{u}^*, p^*) \in K_{\mathbf{w}}^s$ and the optimality relation*

$$\sup_{(\mathbf{v}, q) \in K_{\mathbf{w}}^s} |Q(\mathbf{v}, q) - Q(\mathbf{u}^*, p^*)| = \inf_{l \in \mathbb{R}} \sup_{(\mathbf{v}, q) \in K_{\mathbf{w}}^s} |Q(\mathbf{v}, q) - l| =: R(K_{\mathbf{w}}^s; Q). \quad (31)$$

Moreover, under the assumption of Theorem 3.1, the output $(\hat{\mathbf{u}}, \hat{p})$ of Algorithm 1 satisfies

$$\sup_{(\mathbf{v}, q) \in K_{\mathbf{w}}^s} |Q(\mathbf{v}, q) - Q(\hat{\mathbf{u}}, \hat{p})| \leq R(K_{\mathbf{w}}^s; Q) + \varepsilon \|Q\|_{X^\#}. \quad (32)$$

Proof. To prove (31), we follow [13] where this result is derived for a different model class assumption.

We first derive the optimality result for $Q(\mathbf{u}_{\mathcal{S}}^*, p_{\mathcal{S}}^*)$ in $\mathcal{K}_{\mathbf{w}_{\mathcal{S}}}^s$, where $\zeta_{\mathcal{S}}^* := (\mathbf{u}_{\mathcal{S}}^*, p_{\mathcal{S}}^*) \in \mathcal{K}_{\mathbf{w}_{\mathcal{S}}}^s$ is given by (20). We assume that $\mathcal{K}_{\mathbf{w}_{\mathcal{S}}}^s$ does not reduce to a point, in which case the proof is trivial. In particular, this implies that $\|\zeta_{\mathcal{S}}^*\|_{\mathcal{X}^s} < C_{\text{data}}$.

We denote by $Q_{\mathcal{N}} : \mathcal{N} \rightarrow \mathbb{R}$ the restriction of Q to the null space $\mathcal{N} := \{(\mathbf{v}, q) \in \mathcal{X}^s : \lambda(\mathbf{v}, q) = 0\}$ and by $Q_{\mathcal{N}}^*$ its adjoint. Let ψ be an eigenfunction associated with the largest eigenvalue of $Q_{\mathcal{N}}^* Q_{\mathcal{N}} : \mathcal{N} \rightarrow \mathcal{N}$ and normalized such that $\|\psi\|_{\mathcal{X}^s}^2 = C_{\text{data}}^2 - \|\zeta_{\mathcal{S}}^*\|_{\mathcal{X}^s}^2 > 0$.

Observe that $\zeta_{\mathcal{S}}^* \pm \psi \in \mathcal{X}^s$ and $\lambda(\zeta_{\mathcal{S}}^* \pm \psi) = \lambda(\zeta_{\mathcal{S}}^*) \pm \lambda(\psi) = \lambda(\zeta_{\mathcal{S}}^*) = \mathbf{w}_{\mathcal{S}}$. Since, according to (22), $\zeta_{\mathcal{S}}^*$ is the element of minimal norm in $\mathcal{X}^s$ satisfying the measurements, we deduce

$$\|\zeta_{\mathcal{S}}^* \pm \psi\|_{\mathcal{X}^s}^2 = \|\zeta_{\mathcal{S}}^*\|_{\mathcal{X}^s}^2 + \|\psi\|_{\mathcal{X}^s}^2 = C_{\text{data}}^2.$$

This implies that $\zeta_{\mathcal{S}}^* \pm \psi \in \mathcal{K}_{\mathbf{w}_{\mathcal{S}}}^s$ and for any $l \in \mathbb{R}$ we have

$$\sup_{(\mathbf{v}, q) \in \mathcal{K}_{\mathbf{w}_{\mathcal{S}}}^s} |Q(\mathbf{v}, q) - l|^2 \geq \frac{1}{2} |Q(\zeta_{\mathcal{S}}^* + \psi) - l|^2 + \frac{1}{2} |Q(\zeta_{\mathcal{S}}^* - \psi) - l|^2 = \frac{1}{2} |Q(\zeta_{\mathcal{S}}^*) - l + Q(\psi)|^2 + \frac{1}{2} |Q(\zeta_{\mathcal{S}}^*) - l - Q(\psi)|^2.$$

Estimating further using the parallelogram law, we find that

$$\sup_{(\mathbf{v}, q) \in \mathcal{K}_{\mathbf{w}_{\mathcal{S}}}^s} |Q(\mathbf{v}, q) - l|^2 \geq |Q(\zeta_{\mathcal{S}}^*) - l|^2 + |Q(\psi)|^2 \geq |Q(\psi)|^2.$$

Moreover, because $\psi \in \mathcal{N}$ corresponds to the largest eigenvalue of $Q_{\mathcal{N}}^* Q_{\mathcal{N}}$, we find that

$$|Q(\psi)|^2 = \sup_{\substack{\boldsymbol{\eta} \in \mathcal{N}, \\ \|\boldsymbol{\eta}\|_{\mathcal{X}^s}^2 \leq C_{\text{data}}^2 - \|\zeta_{\mathcal{S}}^*\|_{\mathcal{X}^s}^2}} |Q(\boldsymbol{\eta})|^2 = \sup_{(\mathbf{v}, q) \in \mathcal{K}_{\mathbf{w}_{\mathcal{S}}}^s} |Q((\mathbf{v}, q) - \zeta_{\mathcal{S}}^*)|^2 = \sup_{(\mathbf{v}, q) \in \mathcal{K}_{\mathbf{w}_{\mathcal{S}}}^s} |Q(\mathbf{v}, q) - Q(\zeta_{\mathcal{S}}^*)|^2.$$

Combining the above relations, we find that

$$\sup_{(\mathbf{v}, q) \in \mathcal{K}_{\mathbf{w}_{\mathcal{S}}}^s} |Q(\mathbf{v}, q) - Q(\zeta_{\mathcal{S}}^*)|^2 \leq \sup_{(\mathbf{v}, q) \in \mathcal{K}_{\mathbf{w}_{\mathcal{S}}}^s} |Q(\mathbf{v}, q) - l|^2$$

and thus

$$\sup_{(\mathbf{v}, q) \in \mathcal{K}_{\mathbf{w}_{\mathcal{S}}}^s} |Q(\mathbf{v}, q) - Q(\zeta_{\mathcal{S}}^*)| = \inf_{l \in \mathbb{R}} \sup_{(\mathbf{v}, q) \in \mathcal{K}_{\mathbf{w}_{\mathcal{S}}}^s} |Q(\mathbf{v}, q) - l|, \quad (33)$$

which is the desired optimality result for $Q(\mathbf{u}_{\mathcal{S}}^*, p_{\mathcal{S}}^*) = Q(\zeta_{\mathcal{S}}^*)$.

The estimate (31) follows recalling that $(\mathbf{u}, p) \in K_{\mathbf{w}}^s$ if and only if $(\mathbf{u}, p) = (\mathbf{u}_{\mathbf{f}}, p_{\mathbf{f}}) + (\mathbf{u}_{\mathcal{S}}, p_{\mathcal{S}})$, where $(\mathbf{u}_{\mathbf{f}}, p_{\mathbf{f}}) \in H_0^1(\Omega)^d \times L_0^2(\Omega)$ solves (16) and $(\mathbf{u}_{\mathcal{S}}, p_{\mathcal{S}}) \in \mathcal{K}_{\mathbf{w}_{\mathcal{S}}}^s$. Therefore, for $(\mathbf{v}, q) \in K_{\mathbf{w}}^s$ we have

$$Q(\mathbf{v}, q) - Q(\mathbf{u}^*, p^*) = Q((\mathbf{v}, q) - (\mathbf{u}_{\mathbf{f}}, p_{\mathbf{f}})) - Q(\zeta_{\mathcal{S}}^*)$$

so that (33) yields

$$\sup_{(\mathbf{v}, q) \in K_{\mathbf{w}}^s} |Q(\mathbf{v}, q) - Q(\mathbf{u}^*, p^*)| \leq \inf_{l \in \mathbb{R}} \sup_{(\mathbf{v}, q) \in \mathcal{K}_{\mathbf{w}_{\mathcal{S}}}^s} |Q(\mathbf{v}, q) - l| = \inf_{l \in \mathbb{R}} \sup_{(\mathbf{v}, q) \in K_{\mathbf{w}}^s} |Q(\mathbf{v}, q) - l|.$$

The proof of (32) directly follows from (31) and the estimate for the approximation of the Chebyshev center (30) given in Theorem 3.1:

$$\sup_{(\mathbf{v}, q) \in K_{\mathbf{w}}^s} |Q(\mathbf{v}, q) - Q(\hat{\mathbf{u}}, \hat{p})| \leq R(K_{\mathbf{w}}^s; Q) + |Q(\mathbf{u}^*, p^*) - Q(\hat{\mathbf{u}}, \hat{p})| \leq R(K_{\mathbf{w}}^s; Q) + \varepsilon \|Q\|_{X^\#}.$$

□

Remark 3.1. *It is possible to relate $R(K_{\mathbf{w}}^s; Q) = R(\mathcal{K}_{\mathbf{w}_S}^s; Q)$ with $R(K_{\mathbf{w}}^s) = R(\mathcal{K}_{\mathbf{w}}^s)$. Indeed, it transpires from the argument provided in the proof of Theorem 3.2 that $|Q(\psi)|^2 = R(\mathcal{K}_{\mathbf{w}_S}^s; Q)^2$, where we recall that ψ is an eigenfunction corresponding to the largest eigenvalue of $Q_N^* Q_N$, say μ . Therefore,*

$$R(K_{\mathbf{w}}^s; Q)^2 = \mu \|\psi\|_{\mathcal{X}^s}^2 = \mu(C_{data}^2 - \|\mathbf{u}_S^*, p_S^*\|_{\mathcal{X}^s}^2) = \mu \inf_{(\mathbf{u}, p) \in X} \sup_{(\mathbf{v}, q) \in \mathcal{K}_{\mathbf{w}_S}^s} \|(\mathbf{v}, q) - (\mathbf{u}, p)\|_X = \mu R(K_{\mathbf{w}}^s)^2.$$

4 Computation of the Riesz representers

The key ingredient in the near-optimal recovery algorithm presented in Section 3 is the computation of the Riesz representers ϕ_j of the measurement functionals λ_j , $j = 1, 2, \dots, m$, when viewed as functionals on $\mathcal{X}^s$. In view of the definition of the inner product on $\mathcal{X}^s$, see (21), we have that for $j = 1, 2, \dots, m$, $\phi_j = (\mathbf{w}_j, r_j) \in \mathcal{X}^s$ solves

$$\langle \mathbf{w}_j, \mathbf{v} \rangle_{H^s(\Gamma)} + \text{mean}(r_j) \text{mean}(q) = \lambda_j(\mathbf{v}, q) \quad \forall (\mathbf{v}, q) \in \mathcal{X}^s. \quad (34)$$

In this section, we discuss a practical algorithm that can be used to approximate ϕ_j , $j = 1, 2, \dots, m$. We start by describing a simple technique to handle the nonlocal mean value terms in (34) without extra expense. We then propose a practical finite element method to approximate the Riesz representers.

For simplicity, we describe the procedure considering a generic measurement functional λ by omitting the index $j \in \{1, \dots, m\}$.

4.1 Mean value constraint

The mean value of the pressure requires a special treatment that we discuss here. The idea is to decompose the pressure component r of ϕ into a mean-free part plus a constant and observe that the latter can be explicitly determined by (34). Subtracting this constant from r at the outset, all subsequent calculations are done for pressures with vanishing average, that is, looking for velocity-pressure couples in

$$\mathcal{X}_0^s := \left\{ (\mathbf{v}, q) \in \mathcal{X}^s : q \in L_0^2(\Omega) \right\} \subset \mathcal{X}^s. \quad (35)$$

Notice that $\|\mathbf{v}, q\|_{\mathcal{X}^s} = \|\mathbf{v}\|_{H^s(\Gamma)}$ for $(\mathbf{v}, q) \in \mathcal{X}_0^s$.

Let $\phi = (\mathbf{w}, r) \in \mathcal{X}^s$ be the Riesz representer of λ in $\mathcal{X}^s$. Letting $(\mathbf{v}, q) = (\mathbf{0}, 1) \in \mathcal{X}^s$ in (34), we find that the mean of r is explicitly given by

$$\text{mean}(r) = \lambda(\mathbf{0}, 1) =: \Lambda \in \mathbb{R}.$$

We then introduce $r_0 := r - \Lambda \in L_0^2(\Omega)$ so that

$$(\mathbf{w}, r) = (\mathbf{w}, r_0) + (\mathbf{0}, \Lambda), \quad \text{or} \quad \phi = \phi_0 + (\mathbf{0}, \Lambda), \quad (36)$$

where $\phi_0 := (\mathbf{w}, r_0) \in \mathcal{X}_0^s$ solves

$$\langle \mathbf{w}, \mathbf{v} \rangle_{H^s(\Gamma)} = \lambda(\mathbf{v}, q) \quad \forall (\mathbf{v}, q) \in \mathcal{X}_0^s; \quad (37)$$

compare with (34). We refer to ϕ_0 as the Riesz representer in $\mathcal{X}_0^s$ of λ (restricted to pressures with vanishing mean value).

4.2 Saddle-point formulation

The Stokes and compatibility constraints in $\mathcal{X}_0^s$ makes the finite element discretization of (37) challenging. To address this difficulty, we adopt a standard approach based on Lagrange multipliers, which allows the constraints to be enforced weakly rather than built directly into the functional space.

We define the functional space

$$X_0^s = \left\{ (\mathbf{v}, q) \in H^1(\Omega)^d \times L_0^2(\Omega) : \mathbf{v}|_\Gamma \in H^s(\Gamma)^d \right\}$$

relaxing the Stokes and compatibility constraints in $\mathcal{X}_0^s$ and equip it with the norm

$$\|(\mathbf{v}, q)\|_{X_0^s} := \sqrt{\|\nabla \mathbf{v}\|_{L^2(\Omega)}^2 + \|\mathbf{v}\|_{H^s(\Gamma)}^2 + \|q\|_{L^2(\Omega)}^2}. \quad (38)$$

The saddle-point formulation of (37) using Lagrange multipliers read: find $(\mathbf{w}, r_0) \in X_0^s$ and $(\boldsymbol{\pi}, \rho) \in H_0^1(\Omega)^d \times L^2(\Omega)$ such that

$$\begin{cases} a_s(\mathbf{w}, \mathbf{v}) + \mathcal{A}((\mathbf{v}, q), (\boldsymbol{\pi}, \rho)) &= \lambda(\mathbf{v}, q), \quad \forall (\mathbf{v}, q) \in X_0^s, \\ \mathcal{A}((\mathbf{w}, r_0), (\mathbf{z}, \tau)) &= 0, \quad \forall (\mathbf{z}, \tau) \in H_0^1(\Omega)^d \times L^2(\Omega), \end{cases} \quad (39)$$

where $a_s(\mathbf{z}, \mathbf{v}) := \langle \mathbf{z}, \mathbf{v} \rangle_{H^s(\Gamma)}$ and $\mathcal{A}((\mathbf{v}, q), (\mathbf{z}, \tau)) := k(\mathbf{v}, \mathbf{z}) + b(\mathbf{v}, \tau) + b(\mathbf{z}, q)$ with $k(\mathbf{v}, \mathbf{z}) := \int_\Omega 2\varepsilon(\mathbf{v}) : \varepsilon(\mathbf{z})$ and $b(\mathbf{v}, q) := -\int_\Omega q \operatorname{div}(\mathbf{v})$.

The proof of existence and uniqueness for the saddle-point problem is technical but rather standard. It is therefore given in Appendix A. However, we point out that the solution $(\mathbf{w}, r_0)$ of the above system is also the unique solution to (37). Indeed, taking $(\mathbf{z}, \tau) = (\mathbf{0}, 1)$ in the second equation in (39) yields $b(\mathbf{w}, 1) = 0$, and thus $\int_\Gamma \mathbf{w} \cdot \mathbf{n} = 0$ thanks to the divergence theorem. Furthermore, the second equation of (39) restricted to $(\mathbf{z}, \tau) \in H_0^1(\Omega)^d \times L_0^2(\Omega)$ shows that $(\mathbf{w}, r_0) \in X_0^s$ satisfies $\mathcal{S}(\mathbf{w}, r_0) = \mathbf{0}$ and thus $(\mathbf{w}, r_0) \in \mathcal{X}_0^s$. Lastly, restricting to test functions $(\mathbf{v}, q) \in \mathcal{X}_0^s$ in the first equation in (39) so that $\mathcal{A}((\mathbf{v}, q), (\boldsymbol{\pi}, \rho)) = 0$ yields

$$a_s(\mathbf{w}, \mathbf{v}) = \lambda(\mathbf{v}, q) \quad \forall (\mathbf{v}, q) \in \mathcal{X}_0^s$$

and $(\mathbf{w}, r_0)$ satisfies (37).

From the previous argumentation, we realize that if $\rho = \rho_0 + \bar{\rho}$ with $\rho_0 \in L_0^2(\Omega)$ and $\bar{\rho} := \operatorname{mean}(\rho) \in \mathbb{R}$, $(\boldsymbol{\pi}, \rho_0)$ are the Lagrange multipliers enforcing the Stokes constraint, while $\bar{\rho}$ is the Lagrange multiplier enforcing the compatibility condition $\int_\Gamma \mathbf{w} \cdot \mathbf{n} = 0$. The latter is critical not only for the equivalence between (39) and (37) but also for the existence and uniqueness proof presented in Appendix A.

4.3 Finite element approximation

Let $\{\mathcal{T}_h\}_{h>0}$ be a family of quasi-uniform and shape-regular subdivisions of $\bar{\Omega}$ made either of simplices or quadrilaterals/hexahedrons, possibly curved to match Γ . For each mesh $\mathcal{T}_h$, and let $\mathbb{V}_h$ be a Lagrange (nodal) finite element space for $H^1(\Omega)^d$, let $\mathbb{W}_h := \mathbb{V}_h \cap H_0^1(\Omega)^d$ be the subspace of $\mathbb{V}_h$ with vanishing trace.

It will be convenient to distinguish between nodal basis functions associated with interior degrees of freedom and boundary ones. We let $N := \dim(\mathbb{W}_h)$ and $N_b := \dim(\mathbb{V}_h) - N$ and denote by $\boldsymbol{\varphi}_i$, $i = 1, \dots, N + N_b$, the nodal basis functions associated to the degrees of freedom parameterizing $\mathbb{V}_h$ numbered so as to start with the nodal basis associated with the interior degrees of freedom. With this notation we have

$$\begin{aligned} \mathbb{W}_h &= \operatorname{span}\{\boldsymbol{\varphi}_1, \dots, \boldsymbol{\varphi}_N\} \subset H_0^1(\Omega)^d, & \mathbb{V}_h^b &:= \operatorname{span}\{\boldsymbol{\varphi}_{N+1}, \dots, \boldsymbol{\varphi}_{N+N_b}\} \subset H^1(\Omega)^d, \\ \mathbb{V}_h &= \mathbb{W}_h \oplus \mathbb{V}_h^b \subset H^1(\Omega)^d. \end{aligned}$$

Regarding the pressure space, let $\mathbb{M}_h$ be a conforming finite element space for $L^2(\Omega)$ and let $\mathbb{Q}_h := \mathbb{M}_h \cap L_0^2(\Omega)$ be the subspace with zero average. We suppose that $\mathbb{W}_h \times \mathbb{Q}_h$ satisfies the (Stokes) inf-sup condition, namely that there exists a constant $\beta > 0$ (independent of h) such that

$$\inf_{q_h \in \mathbb{Q}_h} \sup_{\mathbf{v}_h \in \mathbb{W}_h} \frac{\int_\Omega q_h \operatorname{div}(\mathbf{v}_h)}{\|\nabla \mathbf{v}_h\|_{L^2(\Omega)} \|q_h\|_{L^2(\Omega)}} \geq \beta.$$

We let $\tilde{N} := \dim(\mathbb{Q}_h)$ and denote by ϕ_i , $i = 1, \dots, \tilde{N}$, a basis of $\mathbb{Q}_h$.

Using the decomposition $L^2(\Omega) = L_0^2(\Omega) \oplus \mathbb{R}$, the discrete counterpart of the saddle-point system (39) reads: find $(\mathbf{w}_h, r_{0,h}) \in \mathbb{V}_h \times \mathbb{Q}_h$ and $(\boldsymbol{\pi}_h, \rho_h, \gamma) \in \mathbb{W}_h \times \mathbb{Q}_h \times \mathbb{R}$ such that

$$\begin{cases} a_s(\mathbf{w}_h, \mathbf{v}_h) + \mathcal{A}((\mathbf{v}_h, q_h), (\boldsymbol{\pi}_h, \rho_h)) + b(\mathbf{v}_h, \gamma) &= \lambda(\mathbf{v}_h, q_h), & \forall (\mathbf{v}_h, q_h) \in \mathbb{V}_h \times \mathbb{Q}_h, \\ \mathcal{A}((\mathbf{w}_h, r_{0,h}), (\mathbf{z}_h, \tau_h)) + b(\mathbf{w}_h, \delta) &= 0, & \forall (\mathbf{z}_h, \tau_h, \delta) \in \mathbb{W}_h \times \mathbb{Q}_h \times \mathbb{R}. \end{cases} \quad (40)$$

In Section 4.3.1 we describe an efficient way to solve (40) based on the partition of interior and boundary velocity degrees of freedom. The practical aspects are then discussed in Sections 4.3.2 and 4.3.3. But before proceeding, we note that based on the analysis performed in [6] for the Poisson problem, we expect ε in Theorems 3.1 and 3.2 to behave like $\varepsilon \in O(h^{\tilde{s}})$ for some $\tilde{s} > 0$ depending on s , Ω and the polynomial degree used in $\mathbb{V}_h \times \mathbb{Q}_h$.

4.3.1 Decoupled algorithm

The use of Lagrangian finite elements for $\mathbb{V}_h$ gives the saddle point system (40) a particular structure that allows for an efficient solver. Indeed, writing

$$\mathbf{w}_h = \mathbf{w}_h^0 + \mathbf{w}_h^b, \quad \text{where } \mathbf{w}_h^0 \in \mathbb{W}_h \quad \text{and} \quad \mathbf{w}_h^b \in \mathbb{V}_h^b,$$

and splitting the velocity-pressure couple as $(\mathbf{w}_h, r_{0,h}) = (\mathbf{w}_h^0, r_{0,h}) + (\mathbf{w}_h^b, 0)$, the following iterative procedure can be used to solve the system (40):

Step 1. Restricting test functions to $(\mathbf{v}_h^0, q_h) \in \mathbb{W}_h \times \mathbb{Q}_h$ in the first equation of (40) and using the fact that $\mathbf{v}_h^0|_\Gamma = \mathbf{0}$ and $b(\mathbf{v}_h^0, \gamma) = 0$ for all $\gamma \in \mathbb{R}$, we arrive at the following system for the Lagrange multiplier $(\boldsymbol{\pi}_h, \rho_h) \in \mathbb{W}_h \times \mathbb{Q}_h$:

$$\mathcal{A}((\mathbf{v}_h^0, q_h), (\boldsymbol{\pi}_h, \rho_h)) = \lambda(\mathbf{v}_h^0, q_h), \quad \forall (\mathbf{v}_h^0, q_h) \in \mathbb{W}_h \times \mathbb{Q}_h. \quad (41)$$

Notice that (41) is Stokes system with forcing λ and vanishing velocity on Γ (and thus the pressure is with vanishing mean value).

Step 2. Restricting to test functions $(\mathbf{v}_h^b, 0) \in \mathbb{V}_h^b \times \mathbb{Q}_h$, $\mathbf{z}_h = \mathbf{0}$, $\tau_h = 0$ and using that $\mathbf{w}_h^0|_\Gamma = \mathbf{0}$ yield a coercive fractional diffusion system on Γ with constraint

$$\begin{cases} a_s(\mathbf{w}_h^b, \mathbf{v}_h^b) + b(\mathbf{v}_h^b, \gamma) &= \lambda(\mathbf{v}_h^b, 0) - k(\mathbf{v}_h^b, \boldsymbol{\pi}_h) - b(\mathbf{v}_h^b, \rho_h), & \forall \mathbf{v}_h^b \in \mathbb{V}_h^b, \\ b(\mathbf{w}_h^b, \delta) &= 0, & \forall \delta \in \mathbb{R}, \end{cases} \quad (42)$$

which uniquely determine $\mathbf{w}_h^b \in \mathbb{V}_h^b$, and the constant $\gamma \in \mathbb{R}$ necessary to enforce the compatibility condition $\int_\Gamma \mathbf{w}_h^b \cdot \mathbf{n} = 0$.

Step 3. The remaining unknown $(\mathbf{w}_h^0, r_{0,h}) \in \mathbb{W}_h \times \mathbb{Q}_h$ is uniquely determined by another Stokes system corresponding to the second equation of (40) with $\delta = 0$

$$\mathcal{A}((\mathbf{w}_h^0, r_{0,h}), (\mathbf{z}_h, \tau_h)) = -\mathcal{A}((\mathbf{w}_h^b, 0), (\mathbf{z}_h, \tau_h)) \quad \forall (\mathbf{z}_h, \tau_h) \in \mathbb{W}_h \times \mathbb{Q}_h. \quad (43)$$

Notice that (43) is Stokes system for $(\mathbf{w}_h, r_{0,h})$ without forcing term but with boundary condition $\mathbf{w}_h|_\Gamma = \mathbf{w}_h^b$ (and thus the pressure is with vanishing mean value). It has a unique solution because, thanks to the previous step, the boundary data satisfies the compatibility condition.

4.3.2 Linear systems

In this section, we explicit the linear systems associated to steps 1 to 3. We suppose here that the computation of $H^s(\Gamma)$ is exact and postpone the discussion of a practical algorithm for non-integer s to Section 4.3.3.

We write each unknown function in their respective basis, namely

$$\mathbf{w}_h = \sum_{j=1}^{N+N_b} \mathbf{w}_j \boldsymbol{\varphi}_j, \quad r_{0,h} = \sum_{j=1}^{\tilde{N}} r_{0,j} \phi_j, \quad \boldsymbol{\pi}_h = \sum_{j=1}^N \pi_j \boldsymbol{\varphi}_j, \quad \text{and} \quad \rho_h = \sum_{j=1}^{\tilde{N}} \rho_j \phi_j$$

and collect the unknown coefficients in the vectors $W_0 := (w_i)_{i=1}^N \in \mathbb{R}^N$, $W_b := (w_{N+i})_{i=1}^{N_b} \in \mathbb{R}^{N_b}$, $R_0 := (r_{0,i})_{i=1}^{\tilde{N}}$, $\Pi := (\pi_i)_{i=0}^N$, $P := (\rho_i)_{i=1}^{\tilde{N}}$. Notice that the coefficients for $\mathbf{w}_h$ are decomposed according to $\mathbb{V}_h = \mathbb{W}_h \oplus \mathbb{V}_h^b$.

We now make explicit the linear systems corresponding to the three steps of the decoupled algorithm described in Section 4.3.1.

Step 1. The discrete system (41) for the Lagrange multipliers reads

$$\begin{pmatrix} K_0 & B_0^T \\ B_0 & 0 \end{pmatrix} \begin{pmatrix} \Pi \\ P \end{pmatrix} = \begin{pmatrix} F_0 \\ G \end{pmatrix}. \quad (44)$$

Here, $K_0 := (k(\boldsymbol{\varphi}_j, \boldsymbol{\varphi}_i))_{i,j=1}^{N,N} \in \mathbb{R}^{N \times N}$ and $B_0 := (b(\boldsymbol{\varphi}_j, \phi_i))_{i,j=1}^{\tilde{N},N} \in \mathbb{R}^{\tilde{N} \times N}$ are the finite element matrices associated to the bilinear forms $k(\cdot, \cdot)$ restricted to $\mathbb{W}_h \times \mathbb{W}_h$ and $b(\cdot, \cdot)$ restricted to $\mathbb{W}_h \times \mathbb{Q}_h$, while $F_0 := (\lambda(\boldsymbol{\varphi}_i, 0))_{i=1}^N \in \mathbb{R}^N$ and $G := (\lambda(\mathbf{0}, \phi_i))_{i=1}^{\tilde{N}} \in \mathbb{R}^{\tilde{N}}$. Since K_0 is invertible, we have

$$B_0 K_0^{-1} B_0^T P = B_0 K_0^{-1} F_0 - G \quad \text{and} \quad K_0 \Pi = F_0 - B_0^T P. \quad (45)$$

Step 2. The vector W_b and the Lagrange multiplier γ for the compatibility condition satisfy

$$\begin{pmatrix} A_s & D \\ D^T & 0 \end{pmatrix} \begin{pmatrix} W_b \\ \gamma \end{pmatrix} = \begin{pmatrix} F_b - K_b^T \Pi - B_b^T P \\ 0 \end{pmatrix}, \quad (46)$$

where $A_s := (a_s(\boldsymbol{\varphi}_{N+j}, \boldsymbol{\varphi}_{N+i}))_{i,j=1}^{N_b, N_b} \in \mathbb{R}^{N_b \times N_b}$ is the finite element matrices corresponding to $a_s(\cdot, \cdot)$ restricted to $\mathbb{V}_h^b \times \mathbb{V}_h^b$, $D := (b(\boldsymbol{\varphi}_{N+i}, 1))_{i=1}^{N_b} \in \mathbb{R}^{N_b}$ is the finite element vector corresponding to $b(\cdot, \cdot)$ restricted to $\mathbb{V}_h^b \times \mathbb{R}$, and $F_b := (\lambda(\boldsymbol{\varphi}_{N+i}, 0))_{i=1}^{N_b} \in \mathbb{R}^{N_b}$. The above linear system is decoupled:

$$\gamma = \frac{1}{D^T A_s^{-1} D} D^T A_s^{-1} (F_b - K_b^T \Pi - B_b^T P) \quad \text{and} \quad A_s W_b = F_b - K_b^T \Pi - B_b^T P - \gamma D. \quad (47)$$

The computation of γ and W_b requires the approximation of $A_s^{-1} D$ (which is independent of the measurements and can be reused for all Riesz representers) and of $A_s^{-1} (F_b - K_b^T \Pi - B_b^T P)$.

Step 3. The remaining unknown vectors W_N and R_0 are solution to the linear system

$$\begin{pmatrix} K_0 & B_0^T \\ B_0 & 0 \end{pmatrix} \begin{pmatrix} W_0 \\ R_0 \end{pmatrix} = \begin{pmatrix} -K_b W_b \\ -B_b W_b \end{pmatrix} \quad (48)$$

and so

$$B_0 K_0^{-1} B_0^T R_0 = (B_b - B_0 K_0^{-1} K_b) W_b \quad \text{and} \quad K_0 W_0 = -K_b W_b - B_0^T R_0. \quad (49)$$

We note that (45)-(47)-(49) require the approximation of linear system involving A_s and K_0 . For K_0 this can be either performed by its *LU* decomposition once for all or by using an iterative solver. Since these matrices are the same for all Riesz representers, we used the former approach for the numerical illustrations provided in Section 5. Furthermore the system for P in (45)-left and for R_0 in (49)-left are solved using a conjugate gradient algorithm. The situation is more complicated for A_s . When $s = 1$, we can proceed similarly than for K_0 . However, when s is an integer larger than 1 the restrictions to Γ of functions in $\mathbb{W}_h$ are not in $H^s(\Gamma)$. Furthermore, when s is not integral, the matrix A_s is full since it corresponds to a fractional diffusion, and thus nonlocal, system. In the next section, we present an algorithm to circumvent these issues.

4.3.3 Approximation of A_s^{-1}

In this section, we discuss the resolution of (47) when s is non integral or/and $s > 1$. For the latter, it suffices to observe that $A_s^{-1} = A_{s-1}^{-1} A_1^{-1}$ so that this inverse reduces to $\lfloor s \rfloor$ application of A_1^{-1} and one application of A_t^{-1} with $t := s - \lfloor s \rfloor$, which is between 0 and 1. Therefore, it remains to discuss the case $0 < s < 1$.

Observe that the matrix A_s is full. Rather than assembling it, we provide an approximation of A_s^{-1} following the technology proposed in [6]. This approach takes advantage of the spectral definition of the inner product of $H^s(\Gamma)$, see (11), and relies on one of the well-established numerical methods for fractional diffusion problems. Refer to [9, 8] for elliptic operators acting on functions defined on Euclidean domains and to [7] for an extension to functions defined on hyper-surfaces as needed in the present work.

We introduce the mass matrix $M := (\langle \varphi_{N+j}, \varphi_{N+i} \rangle_{L^2(\Gamma)})_{i,j=1}^{N_b, N_b} \in \mathbb{R}^{N_b \times N_b}$ and stiffness matrix $L := (\langle \nabla_\Gamma \varphi_{N+j}, \nabla_\Gamma \varphi_{N+i} \rangle_{L^2(\Gamma)})_{i,j=1}^{N_b, N_b} \in \mathbb{R}^{N_b \times N_b}$ and recall the Balakrishnan formula

$$A_s^{-1} := \frac{\sin(\pi s)}{\pi} \int_{-\infty}^{\infty} e^{(1-s)y} ((e^y + 1)M + L)^{-1} dy. \quad (50)$$

A sinc quadrature is then used to approximate the improper integrals. Given a spacing parameter $k > 0$, we set $M := \left\lceil \frac{\pi^2}{2(1-s)k^2} \right\rceil$ and $N := \left\lceil \frac{\pi^2}{2sk^2} \right\rceil$, and advocate the approximation of A_s^{-1} by

$$A_s^{-1} \approx \mathcal{Q}_k^{-s} := \frac{k \sin(\pi s)}{\pi} \sum_{l=-M}^N e^{(1-s)y_l} ((e^{y_l} + 1)M + L)^{-1}, \quad y_l := kl. \quad (51)$$

We refer to [8, 7] for the exponential (in k) convergence properties of this approximation and to [6] for its influence on an optimal recovery problem for the Poisson problem.

5 Numerical experiments

In this section, we illustrate the performance of Algorithm 1 when the Riesz representers are approximated using a finite element method as described in Section 4. The measurements are Gaussian functionals serving as proxy for point evaluations of the component of the velocity and the pressure. More precisely, given a point (center) $\mathbf{z} \in \Omega$ we define

$$\lambda_{\mathbf{z},i}(\psi) = \frac{1}{\sqrt{2\pi r^2}} \int_{\Omega} \exp\left(-\frac{|\mathbf{x} - \mathbf{z}|^2}{2r^2}\right) \psi_i(\mathbf{x}) d\mathbf{x}, \quad r = 0.1, \quad (52)$$

where $i \in \{1, 2, \dots, d+1\}$ and $\psi := ((\psi_1, \dots, \psi_d), \psi_{d+1}) \in H^1(\Omega)^d \times L^2(\Omega)$. The number and the distribution of the points $\mathbf{z}$ will be indicated for each test case.

We recall that the approximation of each Riesz representer is performed using the decoupled algorithm presented in Section 4.3.2. We store an LU decomposition of K_0 and A_1 and use a conjugate gradient algorithm for the resolution of (45)-left and (49)-left. The conjugate gradient algorithms are stopped when the l_2 -norm of the system residual is smaller than 10^{-9} times the l_2 -norm of the right-hand side of the system. The same process is used for the finite element approximation of $(\mathbf{u}_f, p_f) \in H_0^1(\Omega)^d \times L_0^2(\Omega)$ satisfying (16). To limit numerical errors due to the poor conditioning of $\widehat{G}$ in (28), which becomes more pronounced as the number of measurements increases, we employ a diagonal preconditioner as well as a thresholding strategy with parameter $\epsilon = 10^{-10}$; refer to Section 5.4 for details.

In Section 5.1, we consider a square computational domain with two manufactured solutions and investigate the impact of the number of measurements on the recovery error. In Section 5.2, we extend this study to a square domain with a circular hole, where only the boundary conditions on the hole boundary are unknown and the pressure to be recovered does not have vanishing mean value. Building on these results, Section 5.3 considers the flow around an airfoil, for which both the outflow boundary condition and the

boundary condition on the airfoil are unknown. In absence of an exact solution, we use a numerical solution with prescribed boundary conditions to draw the measurements and assess the recovery error. We also report recovery errors for the drag and lift coefficients. Section 5.4 is devoted to the numerical study of different strategies to cope with the conditioning of $\widehat{G}$ 5.4. We end the numerical section by presenting the recovery of functions defined on a three-dimensional domain in Section 5.5.

All numerical studies are conducted with regularity parameter $s = 1$ and with Taylor–Hood $\mathbb{Q}_2^d \times \mathbb{Q}_1$ element for the finite element space; the influence of the regularity parameter s is examined at the end of Section 5.1.

5.1 Square domain

In this section, we provide a numerical study on the influence of the number of measurements on the recovery error. We set $\Omega = (0, 1)^2$ and consider two different solutions to be recovered, namely

$$u_1(\mathbf{x}) = e^{x_1} \cos(x_2), \quad u_2(\mathbf{x}) = -e^{x_1} \sin(x_2) + 2x_1^2, \quad p(\mathbf{x}) = 2(2x_2 - 1) \quad (53)$$

and

$$u_1(\mathbf{x}) = -\cos(\pi x_1) \sin(\pi x_2), \quad u_2(\mathbf{x}) = \sin(\pi x_1) \cos(\pi x_2), \quad p(\mathbf{x}) = -\cos(2\pi x_1) - \cos(2\pi x_2), \quad (54)$$

where $\mathbf{x} = (x_1, x_2) \in \Omega$. Note that in the first case (53), $\mathbf{f} = \mathbf{0}$ as well as $\|\mathbf{u}\|_{H^1(\Omega)} = 3.274$ and $\|p\|_{L^2(\Omega)} = 1.155$. We have $\mathbf{f} \neq \mathbf{0}$ in the second case (54) and $\|\mathbf{u}\|_{H^1(\Omega)} = 3.220$, $\|p\|_{L^2(\Omega)} = 1$.

Given a square integer $m = l^2$, the points controlling the centers of the Gaussian measurements defined in (52) are uniformly distributed in Ω :

$$\mathbf{z}_{i,j} = \left(\frac{i}{l+1}, \frac{j}{l+1} \right), \quad i, j = 1, 2, \dots, l. \quad (55)$$

Finally, given an integer n (refinement level), the domain Ω is discretized into 2^{2n} squares of side-length 2^{-n} , yielding a uniform mesh with mesh size $h = \sqrt{2}2^{-n}$.

We report results for two refinements corresponding to $n = 6$ (33282 degrees of freedom for the velocity and 4225 for the pressure) and $n = 8$ (526338 degrees of freedom for the velocity and 66049 for the pressure).

We start with the case (53). Figure 1 contains the exact and recovery solutions obtained for different numbers of measurements and with a subdivision corresponding to $n = 8$ refinements. Note that the solution to (16) in $H_0^1(\Omega)^2 \times L_0^2(\Omega)$ vanishes in the case (53) since $\mathbf{f} = \mathbf{0}$. The recovery errors

$$\text{err}_u := \|\mathbf{u} - \widehat{\mathbf{u}}_h\|_{H^1(\Omega)}, \quad \text{err}_p := \|p - \widehat{p}_h\|_{H^1(\Omega)} \quad \text{and} \quad \text{err} := \sqrt{\text{err}_u^2 + \text{err}_p^2}$$

are reported in Table 1. Here $(\widehat{\mathbf{u}}_h, \widehat{p}_h)$ is the output of the recovery algorithm.

(m_{u_1}, m_{u_2}, m_p)	(0,0,36)	(36,0,0)	(36,36,0)	(36,36,36)
err_u	3.12811	1.59357	0.28662	0.27723
err_p	0.08480	0.87312	0.23818	0.22850
err	3.12925	1.81708	0.37267	0.35926

Table 1: Recovery error by the discrete approximations depicted in Figure 1.

The results for the recovery of the velocity are as expected. Indeed, Figure 1 indicates that the velocity is poorly recovered when there is no measurement of the velocity (col 2), only the first component u_1 is accurately recovered when we have measurements of the first component only (col 3), while having measurements of both components leads to an accurate recovery of the velocity field (cols 4 and 5). Regarding the recovery of the pressure, we observe that the recovered solution is accurate inside the domain but present oscillations near the boundary. Moreover, the quality of the recovered pressure deteriorates when adding




Figure 1: Exact solution (col 1) and recovery solution (col 2 to 5) for the case (53) when (m_{u_1}, m_{u_2}, m_p) is equal to $(0, 0, 36)$, $(36, 0, 0)$, $(36, 36, 0)$ and $(36, 36, 36)$ using $n = 8$ refinements for the mesh. From top to bottom, the rows correspond to the recovery of u_1 , u_2 and p . For the color map, black corresponds to $\min_{\mathbf{x} \in \Omega} v(\mathbf{x})$ and white to $\max_{\mathbf{x} \in \Omega} v(\mathbf{x})$ for $v \in \{u_1, u_2, p\}$, and the constants for the level curves are the same in each row.

velocity measurements, namely the oscillations are amplified. Note that this behaviour is observed in most numerical tests performed and is not ruled out by Theorem 3.1. However, we expect from Theorem 3.1 that up to the space discretization error, the total recovery error err does not increase as the number of measurements increases; which is indeed observed in Table 1 (last row).

We report in Table 2 the recovery errors err_u and err_p for a mesh with $n = 6$ refinements. We set $m_{u_1} = m_{u_2} = m_u$ (i.e., we use the same number of measurements of each component of the velocity field) and analyze the effect of increasing the number of velocity and pressure measurements. We observe that when $m_u = 0$ (no measurements of the velocity), the pressure recovery error decreases as the number of pressure measurement increases while the velocity recovery error is more or less constant. On the other extreme, when $m_p = 0$ (no measurements of the pressure), we see that increasing the number of velocity measurements has a positive impact on both the velocity and the pressure. Moreover, we observe that when $m_p > 0$, the pressure recovery error first increases and then decreases when more velocity measurements are added. Again the total recovery errors decrease as the number of measurements increases.

$m_u \setminus m_p$	err_u					err_p				
	0	4	16	36	64	0	4	16	36	64
0	–	3.2739	3.1324	3.1281	3.1287	–	0.6234	0.2772	0.0849	0.0460
4	1.7727	1.6270	0.8222	0.7291	0.7365	1.4252	1.2337	0.5022	0.1430	0.0730
16	0.6324	0.6203	0.4957	0.3165	0.2536	0.5073	0.4931	0.3985	0.2406	0.1517
36	0.2866	0.2874	0.2795	0.2772	0.2155	0.2383	0.2387	0.2333	0.2286	0.1654
64	0.2032	0.1977	0.1801	0.2201	0.1893	0.1657	0.1675	0.1418	0.1855	0.1443

Table 2: Velocity recovery error err_u and pressure recovery error err_p for the case (53), for which $\|\mathbf{u}\|_{H^1(\Omega)} = 3.274$ and $\|p\|_{L^2(\Omega)} = 1.155$, using $n = 6$ refinements for the mesh.

We now move to the case (54), for which $\mathbf{f} \neq \mathbf{0}$ and thus the solution $(\mathbf{u}_f, p_f) \in H_0^1(\Omega)^2 \times L_0^2(\Omega)$ to (16) is not trivial. Table 3 reports the recovery errors err_u and err_p for various numbers of velocity and pressure measurements, again using a mesh with $n = 6$ refinements. The results are similar to those obtained for the case (53), except that now the pressure recovery error decreases monotonically as m_u increases when $m_p \leq 16$.

$m_u \setminus m_p$	err_u					err_p				
	0	4	16	36	64	0	4	16	36	64
0	–	3.1996	1.5363	1.1077	1.0743	–	2.0747	0.7921	0.2415	0.1253
4	1.1007	1.1007	0.8068	0.5965	0.5967	0.7089	0.7089	0.5822	0.1992	0.1055
16	0.6807	0.6807	0.5893	0.3604	0.2915	0.5395	0.5395	0.4511	0.2721	0.1901
36	0.3114	0.3114	0.3190	0.3344	0.2489	0.2618	0.2618	0.2675	0.2792	0.1888
64	0.2413	0.2413	0.2258	0.2611	0.2394	0.1875	0.1875	0.1705	0.2228	0.1876

Table 3: Velocity recovery error err_u and pressure recovery error err_p for the case (54), for which $\|\mathbf{u}\|_{H^1(\Omega)} = 3.220$ and $\|p\|_{L^2(\Omega)} = 1$, using $n = 6$ refinements for the mesh.

5.1.1 Influence of the regularity parameter s

We now study the effect of the parameter s , which dictates the regularity assumption for the trace of the velocity on Γ . We use the same setting as in the previous section but focus on the case (54). However, for non integral s , we must resort to the algorithm described in Section 4.3.3 and we use (51) with $k = 0.4$ for the approximation of A_s^{-1} . Table 4 reports the recovery errors for different numbers of measurements and different values of s . Note that the functions to be recovered are smooth inside Ω . However, since Ω is a square domain, the value of s is limited to $s < 3/2$ for the definition of $H^s(\Gamma)$. We observe in all cases that the larger the value of s , the smaller the recovery error. Moreover, increasing the value of s has the effect of

reducing the oscillations in the pressure that can be observed near the boundary of the domain, see Figure 2 for an illustration.

	$m_u = 0, m_p = 64$		$m_u = 64, m_p = 0$		$m_u = 16, m_p = 16$	
s	err_u	err_p	err_u	err_p	err_u	err_p
0.6	1.44987	0.26324	0.31373	0.27224	0.70380	0.55222
0.8	1.28371	0.17485	0.29098	0.23551	0.66682	0.51844
1.0	1.07426	0.12531	0.24127	0.18747	0.58931	0.45114
1.2	0.81662	0.09599	0.22255	0.18016	0.50884	0.38185
1.4	0.62243	0.07565	0.19807	0.15376	0.44041	0.32288

Table 4: Velocity recovery error err_u and pressure recovery error err_p for the case (54) using $n = 6$ refinements for the mesh and different values of m_u , m_p and s .




Figure 2: Recovery of the pressure for the case (54) using $n = 6$ refinements for the mesh: exact solution (left) and recovery solution with $m_u = 0$ and $m_p = 64$ using $s = 0.6$ (middle) and $s = 1.4$ (right). For the color map, black corresponds to $\min_{\mathbf{x} \in \Omega} p(\mathbf{x}) = -2$ and white to $\max_{\mathbf{x} \in \Omega} p(\mathbf{x}) = 2$. Note that when $s = 0.6$, $\hat{p} \in [-5.14, 2.00]$ while $\hat{p} \in [-2.86, 2.00]$ when $s = 1.4$.

5.2 Square domain with a hole

In this subsection, we consider an example in which partial knowledge of the boundary data is available. The domain is the unit square with a hole in the middle, namely $\Omega = (0, 1)^2 \setminus B$, where B is the closed ball of radius 0.1 centered at $(0.5, 0.5)$. We assume that the velocity is known on the outside boundary but unknown on the boundary of B . The functions to be recovered are the ones in (54), but, due to the hole, the pressure does not have a vanishing mean value. Moreover, we have $\|\mathbf{u}\|_{H^1(\Omega)} = 3.127$ and $\|p\|_{L^2(\Omega)} = 0.941$. For the measurements, we consider the Gaussian functionals (52) with centers as in (55) but discarding the points that falls inside B . We present results for two different uniform subdivisions: $n = 4$ refinements corresponding to 10240 quadrilateral, 82944 degrees of freedom for $\mathbf{u}$, and 10496 for p ; $n = 5$ refinements corresponding to 40960 quadrilaterals, 329728 degrees of freedom for the velocity, and 41472 for the pressure. Note that we use do not use curved elements but rather a piecewise linear approximation of the circle.

The velocity and pressure recovery errors for different numbers of measurements when using $n = 4$ and $n = 5$ are provided in Table 5 and 6, respectively. We find that with $n = 4$ the errors err_u and err_p reach a plateau at about $2.45 \cdot 10^{-3}$ and $1.91 \cdot 10^{-4}$, respectively, after which increasing the number of measurements does not decrease the error. Since smaller recover errors are observed with $n = 5$, we conclude that these plateaus are due to the finite element error. We also observe that without measurements of the pressure ($m_p = 0$), the mean value of the pressure cannot be recovered and the algorithm constructs a pressure approximation with vanishing mean value, leading to a large recovery error err_p . We illustrate the behaviour of the recovery error for the pressure by comparing two measurement configurations in Figure 3. We observe large oscillations near the hole when using $m_u = m_p = 4$ measurements. These oscillations are significantly reduced when using $m_u = m_p = 16$ measurements.

$m_u \setminus m_p$	err_u				
	0	4	8	16	24
0	–	$1.1091 \cdot 10^{-0}$	$4.1886 \cdot 10^{-3}$	$4.2215 \cdot 10^{-3}$	$2.4567 \cdot 10^{-3}$
4	$2.5497 \cdot 10^{-1}$	$2.5497 \cdot 10^{-1}$	$2.7100 \cdot 10^{-3}$	$2.4634 \cdot 10^{-3}$	$2.4544 \cdot 10^{-3}$
8	$3.1285 \cdot 10^{-3}$	$3.1323 \cdot 10^{-3}$	$2.4558 \cdot 10^{-3}$	$2.4543 \cdot 10^{-3}$	$2.4544 \cdot 10^{-3}$
16	$2.4549 \cdot 10^{-3}$	$2.4549 \cdot 10^{-3}$	$2.4543 \cdot 10^{-3}$	$2.4548 \cdot 10^{-3}$	$2.4542 \cdot 10^{-3}$
24	$2.4542 \cdot 10^{-3}$	$2.4542 \cdot 10^{-3}$	$2.4543 \cdot 10^{-3}$	$2.4542 \cdot 10^{-3}$	$2.4543 \cdot 10^{-3}$

$m_u \setminus m_p$	err_p				
	0	4	8	16	24
0	–	$1.4431 \cdot 10^{-0}$	$1.4527 \cdot 10^{-3}$	$2.4817 \cdot 10^{-4}$	$1.9117 \cdot 10^{-4}$
4	$1.8012 \cdot 10^{-0}$	$2.8270 \cdot 10^{-1}$	$1.3397 \cdot 10^{-3}$	$3.1139 \cdot 10^{-4}$	$1.9102 \cdot 10^{-4}$
8	$1.7789 \cdot 10^{-0}$	$2.2452 \cdot 10^{-3}$	$1.9174 \cdot 10^{-4}$	$1.9099 \cdot 10^{-4}$	$1.9102 \cdot 10^{-4}$
16	$1.7789 \cdot 10^{-0}$	$2.0284 \cdot 10^{-4}$	$1.9240 \cdot 10^{-4}$	$2.0055 \cdot 10^{-4}$	$1.9104 \cdot 10^{-4}$
24	$1.7789 \cdot 10^{-0}$	$1.9104 \cdot 10^{-4}$	$1.9252 \cdot 10^{-4}$	$1.9101 \cdot 10^{-4}$	$1.9108 \cdot 10^{-4}$

Table 5: Velocity recovery error err_u and pressure recovery error err_p for the domain with a hole using $n = 4$ refinements for the mesh. In this setting, we have $\|\mathbf{u}\|_{H^1(\Omega)} = 3.127$, $\|p\|_{L^2(\Omega)} = 0.941$ and $\text{mean}(p) \neq 0$.

$m_u \setminus m_p$	err_u				
	0	4	8	16	24
0	–	$1.1092 \cdot 10^{-0}$	$3.5309 \cdot 10^{-3}$	$3.5522 \cdot 10^{-3}$	$8.6152 \cdot 10^{-4}$
4	$2.5503 \cdot 10^{-1}$	$2.5503 \cdot 10^{-1}$	$1.4741 \cdot 10^{-3}$	$8.7577 \cdot 10^{-4}$	$8.6019 \cdot 10^{-4}$
8	$2.1678 \cdot 10^{-3}$	$2.1733 \cdot 10^{-3}$	$8.6355 \cdot 10^{-4}$	$8.6019 \cdot 10^{-4}$	$8.6020 \cdot 10^{-4}$
16	$8.6017 \cdot 10^{-4}$	$8.6029 \cdot 10^{-4}$	$8.6040 \cdot 10^{-4}$	$8.6020 \cdot 10^{-4}$	$8.6017 \cdot 10^{-4}$
24	$8.6018 \cdot 10^{-4}$	$8.6017 \cdot 10^{-4}$	$8.6042 \cdot 10^{-4}$	$8.6018 \cdot 10^{-4}$	$8.6018 \cdot 10^{-4}$

$m_u \setminus m_p$	err_p				
	0	4	8	16	24
0	–	$1.4433 \cdot 10^{-0}$	$1.4968 \cdot 10^{-3}$	$1.1313 \cdot 10^{-4}$	$4.1624 \cdot 10^{-5}$
4	$1.8012 \cdot 10^{-0}$	$2.8281 \cdot 10^{-1}$	$1.3824 \cdot 10^{-3}$	$1.9465 \cdot 10^{-4}$	$4.1802 \cdot 10^{-5}$
8	$1.7788 \cdot 10^{-0}$	$2.2949 \cdot 10^{-3}$	$5.0334 \cdot 10^{-5}$	$4.1712 \cdot 10^{-5}$	$4.1761 \cdot 10^{-5}$
16	$1.7788 \cdot 10^{-0}$	$4.4890 \cdot 10^{-5}$	$4.7888 \cdot 10^{-5}$	$4.2479 \cdot 10^{-5}$	$4.1787 \cdot 10^{-5}$
24	$1.7788 \cdot 10^{-0}$	$4.1778 \cdot 10^{-5}$	$4.8227 \cdot 10^{-5}$	$4.1846 \cdot 10^{-5}$	$4.1977 \cdot 10^{-5}$

Table 6: Velocity recovery error err_u (top) and pressure recovery error err_p (bottom) for the domain with a hole, for which $\|\mathbf{u}\|_{H^1(\Omega)} = 3.1269$ and $\|p\|_{L^2(\Omega)} = 0.9414$ with p not mean free, using $n = 5$ refinements for the mesh.




Figure 3: Recovery of the pressure for the domain with a hole using $n = 5$ refinements for the mesh: exact solution (left), recovery using $m_u = m_p = 4$ (middle) and $m_u = m_p = 16$ (right). For the color map, black corresponds to $\min_{\mathbf{x} \in \Omega} p(\mathbf{x}) = -2$ and white to $\max_{\mathbf{x} \in \Omega} p(\mathbf{x}) = 1.810$. Note that when $m_u = m_p = 4$, $\hat{p} \in [-2.00, 3.96]$ while $\hat{p} \in [-2.00, 1.81]$ when $m_u = m_p = 16$.

5.3 Airfoil

We consider in this subsection the flow around an airfoil, and we are interested in the recovery of specific quantities of interest, namely the drag and lift coefficients. The geometry of the domain is described in Figure 4-left. We assume that the boundary conditions are unknown around the airfoil and at the outflow, that $\mathbf{u} = (1, 0)^T$ for the remaining part of the boundary (the inflow, the top and the bottom), and that the forcing term is $\mathbf{f} = \mathbf{0}$. Denoting by Γ_A the boundary of the airfoil and following [26, Equation (2.2)], we compute the drag and lift coefficients using

$$(c_D, c_L)^T = - \int_{\Gamma_A} (2\varepsilon(\mathbf{u})\mathbf{n} - p\mathbf{n}) . \quad (56)$$

Note that the drag and lift coefficients could be alternatively computed using a variational formulation, see [26, Equation (2.9)]. The two formulations are equivalent at the continuous level, but the variational based formulation is more accurate after discretization, see for instance [15]. However, in our setting, the two approaches give comparable results and we only report those obtained using (56).

To compute the error in velocity, pressure, drag and lift coefficients, we use a numerically computed reference solution. The latter is obtained considering the same known boundary conditions as above, complemented by $\mathbf{u} = \mathbf{0}$ on Γ_A and $2\varepsilon(\mathbf{u})\mathbf{n} - p\mathbf{n} = \mathbf{0}$ on the outflow. Note that the pressure is not mean-free in this case. Moreover, we use the same mesh for the reference and recovery solution, see Figure 4-right, which consists of 15360 quadrilaterals (124032 degrees of freedom for the velocity and 15648 for the pressure).

For the measurements, we employ the Gaussian functionals (52) with the location of the centers, indicated with dots on Figure 4-left, given by $\mathbf{z}_1 = (-0.3, 0)$, $\mathbf{z}_2 = (2, 0)$, $\mathbf{z}_3 = (0.5, 0.15)$, $\mathbf{z}_4 = (0.5, -0.1)$, $\mathbf{z}_{5,6} = (0.7, \pm 0.1)$, $\mathbf{z}_{7,8} = (0.1, \pm 0.1)$, $\mathbf{z}_9 = (0.3, 0.15)$, $\mathbf{z}_{10} = (0.3, -0.1)$, and $\mathbf{z}_{11,12} = (2, \pm 0.6)$. The effect on the number of measurements is tested using $m = 2$, $m = 6$ and $m = 12$ measurements of (each component of) the velocity and of the pressure using $\{\mathbf{z}_i\}_{i=1}^m$ for the centers.




Figure 4: Geometry for the airfoil test case with the location of the measurements (left) and the mesh (right).

The velocity and pressure recovery errors err_u and err_p are reported in Table 7, while Table 8 contains the recovery errors in the drag and lift coefficients c_D and c_L . Overall, we observe that adding measurements improves the recovery of the pressure and the velocity as well as the specific quantities of interest c_D and c_L .

5.4 Ill-conditioning of the Gram matrix

As already mentioned above, the condition number of the Gram matrix $\hat{G}$ deteriorates as the number of measurements increases. The impact of this poor conditioning on the recovery error when solving (25) is studied numerically in this section. We study the effect of replacing $\hat{G}$ by $\hat{G}^\epsilon$ obtained by setting to zero the singular values of $\hat{G}$ smaller than $\epsilon \cdot \sigma_{\max}$, where $\sigma_{\max}$ is the largest singular value of $\hat{G}$.

$m_u \setminus m_p$	err_u				err_p			
	0	2	6	12	0	2	6	12
0	–	1.1650	0.8489	0.1267	–	3.0705	1.8428	0.1663
2	0.5355	0.6736	0.6090	0.1217	5.7651	1.2652	1.1309	0.1620
6	0.0696	0.3732	0.1628	0.0976	5.6704	0.6024	0.2425	0.1543
12	0.0042	0.0816	0.0726	0.0215	5.6691	0.1177	0.1055	0.0301

Table 7: Velocity recovery error err_u and pressure recovery error err_p for the airfoil test case.

$m_u \setminus m_p$	error in the drag coefficient c_D				error in the lift coefficient c_L			
	0	2	6	12	0	2	6	12
0	–	0.5698	0.4462	0.0378	–	$4.7070 \cdot 10^{-1}$	$1.0058 \cdot 10^{-1}$	$3.3610 \cdot 10^{-3}$
2	1.3036	0.3659	0.3019	0.0389	$5.8686 \cdot 10^{-2}$	$5.5617 \cdot 10^{-2}$	$3.1370 \cdot 10^{-2}$	$1.3332 \cdot 10^{-3}$
6	0.1066	0.2584	0.0453	0.0045	$1.5672 \cdot 10^{-2}$	$4.4071 \cdot 10^{-2}$	$8.2003 \cdot 10^{-3}$	$8.4000 \cdot 10^{-5}$
12	0.0004	0.0031	0.0009	0.0004	$7.9000 \cdot 10^{-6}$	$6.2620 \cdot 10^{-4}$	$2.0500 \cdot 10^{-4}$	$1.2530 \cdot 10^{-4}$

Table 8: Recovery error for the drag and lift coefficients c_D and c_L . Note that for the reference solution, $c_D = 12.4042$ and $c_L = -0.0738222$.

5.4.1 Effect of thresholding on the Schur complement tolerance

We start by examining the effect of the stopping criterion used for the conjugate gradient algorithm used to solve (45) and (49) as well as compute the finite element approximation of $(\mathbf{u}_f, p_f) \in H_0^1(\Omega)^2 \times L_0^2(\Omega)$ solving (16). We let s_{tol}^1 be the stopping criteria for (16) and s_{tol}^2 the one for (45) and (49). We report in Table 9 the recovery errors obtained when using $\epsilon = 0$ (no thresholding) and $\epsilon = 10^{-10}$ for different values of s_{tol} . We observe that it is counter-productive to use a small tolerance of the conjugate gradients without thresholding. In contrast, when $\epsilon = 10^{-10}$, the recovery error for both the velocity and the pressure are robust with respect to the tolerance parameters.

s_{tol}^1	s_{tol}^2	$\epsilon = 0$		$\epsilon = 10^{-10}$	
		err_u	err_p	err_u	err_p
10^{-6}	10^{-12}	1.09432	0.241753	1.07426	0.125310
10^{-6}	10^{-9}	1.07428	0.125512	1.07426	0.125309
10^{-9}	10^{-12}	1.07086	0.113884	1.07426	0.125309
10^{-9}	10^{-9}	1.07426	0.125350	1.07426	0.125308

Table 9: Velocity recovery error err_u and pressure recovery error err_p for the case (54) using $m_u = 0$, $m_p = 64$ and $n = 6$ refinements for the mesh. The tolerances s_{tol}^1 and s_{tol}^2 are used as stopping criteria for the conjugate gradient algorithm used for the resolution of (16) and (45)-(49).

5.4.2 Effect of thresholding and preconditioning

We explore numerically two preconditioning strategies for the resolution of system (25). We follow [17, Section 11.5] and rewrite (25) as

$$\hat{P}^{-\frac{1}{2}} \hat{G} \hat{P}^{-\frac{1}{2}} \tilde{\alpha} = \hat{P}^{-\frac{1}{2}} \mathbf{w}, \quad \tilde{\alpha} = \hat{P}^{-\frac{1}{2}} \alpha, \quad (57)$$

where $\hat{P} := \text{diag}(\hat{G})$ and $\hat{P}^{-\frac{1}{2}}$ is the principal square root of $\hat{P}^{-1}$. To solve the preconditioned linear system (57), we use the Moore–Penrose inverse obtained via a singular value decomposition of $\hat{G}_{\hat{P}} := \hat{P}^{-\frac{1}{2}} \hat{G} \hat{P}^{-\frac{1}{2}}$ with thresholding parameter $\epsilon = 10^{-10}$. This means that all singular values of magnitude smaller than $\epsilon \cdot \sigma_{\max}$ are set to zero, where $\sigma_{\max}$ is the largest singular value of $\hat{P}^{-\frac{1}{2}} \hat{G} \hat{P}^{-\frac{1}{2}}$. The resulting matrix is

denoted $\widehat{G}_{\widehat{P}}^\epsilon$. For comparison, observe that the original system without preconditioning corresponds to $\widehat{G}_I$, where I is the identity matrix, and thus $\widehat{G}^\epsilon := \widehat{G}_I^\epsilon$ will refer to the original matrix with thresholding.

We start with a numerical study of the influence of the thresholding parameter ϵ as well as the effect of preconditioner $\widehat{P}$. Tables 10 and 11 report the recovery errors obtained using $\widehat{G}$, $\widehat{G}_{\widehat{P}}$, or $\widehat{G}_{\widehat{P}}^\epsilon$ for two different subdivisions of Ω . The condition number of the various matrices is also provided. We observe that the condition number of the matrices increases as the number of measurements increases. Moreover, there is not a clear difference between the condition number of $\widehat{G}$ and its preconditioned version $\widehat{G}_{\widehat{P}}$. However, the condition number of $\widehat{G}_{\widehat{P}}^\epsilon$ is significantly smaller. In terms of recovery errors, we observe that for a small number of measurements, namely $m_u, m_p \in \{0, 4\}$, the recovery error is similar regardless of the matrix system used or the mesh refinement level. In the case $n = 2$, the effects of poor conditioning become more pronounced as additional measurements are incorporated, resulting in large recovery errors that are partially alleviated through thresholding. Moreover, for a smaller mesh size ($n = 6$), all three linear systems produce similar recovery errors for moderate number of measurements, while the performance is marginally better without thresholding ($\epsilon = 0$) for larger values of m_u and m_p because the error due to the thresholding becomes relevant.

m_u	m_p	$\widehat{G}$			$\widehat{G}_{\widehat{P}}$			$\widehat{G}_{\widehat{P}}^\epsilon$		
		err _u	err _p	cond	err _u	err _p	cond	err _u	err _p	cond
4	0	1.108	0.724	$1.02 \cdot 10^{03}$	1.108	0.724	$1.02 \cdot 10^{03}$	1.108	0.724	$1.02 \cdot 10^{03}$
16	0	0.928	0.648	$2.57 \cdot 10^{08}$	0.928	0.648	$2.66 \cdot 10^{08}$	0.928	0.648	$2.66 \cdot 10^{08}$
64	0	0.524	0.257	$1.65 \cdot 10^{16}$	0.570	0.281	$1.33 \cdot 10^{16}$	0.805	0.516	$7.48 \cdot 10^{09}$
0	4	3.200	2.075	$2.54 \cdot 10^{00}$	3.200	2.075	$2.54 \cdot 10^{00}$	3.200	2.075	$2.54 \cdot 10^{00}$
4	4	1.108	0.725	$3.98 \cdot 10^{03}$	1.108	0.725	$1.19 \cdot 10^{03}$	1.108	0.725	$1.19 \cdot 10^{03}$
16	4	0.928	0.650	$3.14 \cdot 10^{08}$	0.928	0.650	$2.70 \cdot 10^{08}$	0.928	0.650	$2.70 \cdot 10^{08}$
64	4	1.354	0.327	$2.28 \cdot 10^{16}$	1.310	0.302	$3.29 \cdot 10^{16}$	0.805	0.528	$7.50 \cdot 10^{09}$
0	16	1.925	2.393	$8.32 \cdot 10^{04}$	1.925	2.393	$3.95 \cdot 10^{04}$	1.925	2.393	$3.95 \cdot 10^{04}$
4	16	1.446	2.332	$9.64 \cdot 10^{04}$	1.446	2.332	$3.95 \cdot 10^{04}$	1.446	2.332	$3.95 \cdot 10^{04}$
16	16	2.216	1.510	$1.24 \cdot 10^{10}$	2.216	1.510	$2.60 \cdot 10^{09}$	2.216	1.510	$2.60 \cdot 10^{09}$
64	16	6.478	0.165	$2.03 \cdot 10^{16}$	5.794	0.206	$3.41 \cdot 10^{16}$	6.679	0.231	$3.26 \cdot 10^{09}$
0	64	9668	0.138	$1.16 \cdot 10^{16}$	3138	0.152	$2.17 \cdot 10^{16}$	5.045	0.152	$1.47 \cdot 10^{07}$
4	64	2661	0.136	$1.03 \cdot 10^{16}$	8698	0.146	$1.22 \cdot 10^{16}$	5.358	0.152	$2.05 \cdot 10^{07}$
16	64	196132	0.138	$8.43 \cdot 10^{16}$	204076	0.142	$1.40 \cdot 10^{16}$	10.749	0.152	$9.85 \cdot 10^{09}$
64	64	29.182	0.134	$3.75 \cdot 10^{16}$	7.613	0.134	$5.08 \cdot 10^{16}$	2.529	0.145	$3.27 \cdot 10^{09}$

Table 10: Condition number and recovery errors for the case (54) on the square domain $\Omega = (0, 1)^2$ using $n = 2$ refinements for the mesh, when considering the Gram matrix $\widehat{G}$ and its preconditioned versions $\widehat{G}_{\widehat{P}}$, or $\widehat{G}_{\widehat{P}}^\epsilon$ (with truncation $\epsilon = 10^{-10}$).

We note that the positive effect of the preconditioner $\widehat{P}$ could appear minimal. However, this depends on the situation. For example, we have observed (not reported for the sake of brevity) more robust recovery errors when the computational domain is a square domain with a hole (described in Section 5.2). In summary, the best option appears to be $\widehat{G}_{\widehat{P}}^\epsilon$, but further studies are warranted.

5.5 Three-dimensional problem

We now illustrate the proposed algorithm for the recovery of functions defined in $\Omega = (0, 1)^3$. The velocity and pressure to be recovered are given by

$$\mathbf{u}(\mathbf{x}) = \begin{pmatrix} \frac{1}{2} \sin(2\pi x_1) \cos(2\pi x_2) \cos(2\pi x_3) \\ \frac{1}{2} \cos(2\pi x_1) \sin(2\pi x_2) \cos(2\pi x_3) \\ -\cos(2\pi x_1) \cos(2\pi x_2) \sin(2\pi x_3) \end{pmatrix}, \quad p(\mathbf{x}) = \frac{\cos(2\pi x_1) + \cos(2\pi x_2)}{4} (\cos(2\pi x_3) + 2), \quad (58)$$

m_u	m_p	$\hat{G}$			$\hat{G}_{\hat{P}}$			$\hat{G}_{\hat{P}}^\epsilon$		
		err _u	err _p	cond	err _u	err _p	cond	err _u	err _p	cond
4	0	1.101	0.709	$9.08 \cdot 10^{02}$	1.101	0.709	$9.08 \cdot 10^{02}$	1.101	0.709	$9.08 \cdot 10^{02}$
16	0	0.681	0.540	$1.59 \cdot 10^{07}$	0.681	0.540	$1.64 \cdot 10^{07}$	0.681	0.540	$1.64 \cdot 10^{07}$
64	0	0.163	0.136	$2.64 \cdot 10^{16}$	0.163	0.137	$2.84 \cdot 10^{16}$	0.241	0.187	$8.44 \cdot 10^{09}$
0	4	3.200	2.075	$2.78 \cdot 10^{00}$	3.200	2.075	$2.78 \cdot 10^{00}$	3.200	2.075	$2.78 \cdot 10^{00}$
4	4	1.101	0.709	$3.66 \cdot 10^{03}$	1.101	0.709	$1.06 \cdot 10^{03}$	1.101	0.709	$1.06 \cdot 10^{03}$
16	4	0.681	0.540	$4.33 \cdot 10^{08}$	0.681	0.540	$3.80 \cdot 10^{08}$	0.681	0.540	$3.80 \cdot 10^{08}$
64	4	0.170	0.150	$1.79 \cdot 10^{16}$	0.172	0.153	$2.28 \cdot 10^{16}$	0.241	0.187	$9.85 \cdot 10^{09}$
0	16	1.536	0.792	$4.17 \cdot 10^{05}$	1.536	0.792	$1.85 \cdot 10^{05}$	1.536	0.792	$1.85 \cdot 10^{05}$
4	16	0.807	0.582	$4.22 \cdot 10^{05}$	0.807	0.582	$1.86 \cdot 10^{05}$	0.807	0.582	$1.86 \cdot 10^{05}$
16	16	0.589	0.451	$9.56 \cdot 10^{09}$	0.589	0.451	$2.21 \cdot 10^{09}$	0.589	0.451	$2.21 \cdot 10^{09}$
64	16	0.143	0.113	$2.96 \cdot 10^{16}$	0.142	0.111	$5.36 \cdot 10^{16}$	0.226	0.171	$8.93 \cdot 10^{09}$
0	64	1.074	0.125	$1.43 \cdot 10^{15}$	1.074	0.125	$4.03 \cdot 10^{14}$	1.074	0.125	$1.16 \cdot 10^{09}$
4	64	0.597	0.106	$1.44 \cdot 10^{15}$	0.597	0.106	$4.02 \cdot 10^{14}$	0.597	0.106	$1.16 \cdot 10^{09}$
16	64	0.252	0.152	$1.44 \cdot 10^{15}$	0.252	0.152	$4.11 \cdot 10^{14}$	0.292	0.190	$5.22 \cdot 10^{09}$
64	64	0.184	0.174	$7.98 \cdot 10^{16}$	0.166	0.153	$4.07 \cdot 10^{16}$	0.239	0.188	$6.80 \cdot 10^{09}$

Table 11: Condition number and recovery errors for the case (54) on the square domain $\Omega = (0, 1)^2$ using $n = 6$ refinements for the mesh, when considering the Gram matrix $\hat{G}$ and its preconditioned versions $\hat{G}_{\hat{P}}$, or $\hat{G}_{\hat{P}}^\epsilon$ (with truncation $\epsilon = 10^{-10}$).

where $\mathbf{x} = (x_1, x_2, x_3) \in \Omega$. Note that $\|\mathbf{u}\|_{H^1(\Omega)} = 4.732$ and $\|p\|_{L^2(\Omega)} = 0.530$. Moreover, the corresponding force $\mathbf{f}$ is not equal to zero, and thus the solution $(\mathbf{u}_f, p_f) \in H_0^1(\Omega)^3 \times L_0^2(\Omega)$ of (16) in the splitting (17) is not identically zero. The pressure is mean-free.

We suppose that the boundary data is unknown on the whole Γ . We set $s = 1$ and use $\epsilon = 10^{-10}$ for the thresholding parameter; see Section 5.4. For the measurements, we consider again the Gaussian functional as in (52) for $v \in \{u_1, u_2, u_3, p\}$ with centers uniformly distributed in Ω , i.e., for an integer $m = \tilde{l}^3$ we use

$$\mathbf{z}_{(i,j,l)} = \left(\frac{i}{\tilde{l}+1}, \frac{j}{\tilde{l}+1}, \frac{l}{\tilde{l}+1} \right), \quad i, j, l = 1, 2, \dots, \tilde{l}.$$

We take m_u measurements on each component velocity and m_p measurements of the pressure. The computational domain Ω is subdivided into 2^{12} squares of side-length 2^{-4} , yielding a uniform mesh with mesh size $h = \sqrt{3}2^{-4}$, 107811 degrees of freedom for the velocity and 4913 for the pressure. We report in Table 12 the velocity and pressure recovery error for different values of m_u and m_p .

$m_u \setminus m_p$	err _u				err _p			
	0	27	125	343	0	27	125	343
0	–	3.2387	3.2332	3.2272	–	0.4696	0.3545	0.2205
8	3.4836	3.2139	3.1990	3.1943	1.4946	0.5350	0.3429	0.2189
27	3.1626	2.8387	2.0882	1.7689	2.2798	2.4323	1.0895	0.2208
64	1.3862	1.3622	1.1954	1.1574	2.2798	2.4323	1.0895	0.2208
125	0.8409	0.8386	0.8165	0.7124	0.3869	0.4087	0.4121	0.2420

Table 12: Velocity recovery error err_u and pressure recovery error err_p for the case three-dimensional case (58). We have $\|\mathbf{u}\|_{H^1(\Omega)} = 4.7322$ and $\|p\|_{L^2(\Omega)} = 0.5303$.

A Well-posedness of System (39)

Let $Y := H_0^1(\Omega)^d \times L_0^2(\Omega) \times \mathbb{R}$ equipped with the norm $\|(\mathbf{z}, \tau, \ell)\|_Y := \sqrt{\|\nabla \mathbf{z}\|_{L^2(\Omega)}^2 + \|\tau\|_{L^2(\Omega)}^2 + |\ell|^2}$. Using the decomposition $L^2(\Omega) = L_0^2(\Omega) \oplus \mathbb{R}$, the saddle point system (39) can be rewritten as: find $(\mathbf{w}, r_0) \in X_0^s$ and $(\boldsymbol{\pi}, \rho_0, \bar{\rho}) \in Y$ such that

$$\begin{cases} a(\mathbf{w}, \mathbf{v}) + \mathcal{B}((\mathbf{v}, q), (\boldsymbol{\pi}, \rho_0, \bar{\rho})) &= \lambda(\mathbf{v}, q), \quad \forall (\mathbf{v}, q) \in X_0^s, \\ \mathcal{B}((\mathbf{w}, r_0), (\mathbf{z}, \tau, \ell)) &= 0, \quad \forall (\mathbf{z}, \tau, \ell) \in Y, \end{cases} \quad (59)$$

where for $(\mathbf{v}, q) \in X_0^s$ and $(\mathbf{z}, \tau, \ell) \in Y$

$$\mathcal{B}((\mathbf{v}, q), (\mathbf{z}, \tau, \ell)) := \mathcal{A}((\mathbf{v}, q), (\mathbf{z}, \tau + \ell)) = k(\mathbf{v}, \mathbf{z}) + b(\mathbf{v}, \tau) + b(\mathbf{z}, q) + b(\mathbf{v}, \ell).$$

To prove the existence and uniqueness, we show that $\mathcal{B}$ satisfies an inf-sup condition and that a is coercive on the kernel of $\mathcal{B}$.

Let $(\mathbf{v}, q) \in X_0^s$ be such that

$$\mathcal{B}((\mathbf{v}, q), (\mathbf{z}, \tau, \ell)) = 0 \quad \forall (\mathbf{z}, \tau, \ell) \in Y.$$

Restricting (39) to $(\mathbf{z}, \tau) \in H_0^1(\Omega)^d \times L_0^2(\Omega)$ shows that $(\mathbf{v}, q) \in X_0^s$ satisfies $\mathcal{S}(\mathbf{v}, q) = \mathbf{0}$. Moreover, taking $(\mathbf{z}, \tau) = (\mathbf{0}, 1)$ in the second equation in (39) yields $b(\mathbf{v}, 1) = 0$, and thus $\int_{\Gamma} \mathbf{v} \cdot \mathbf{n} = 0$ thanks to the divergence theorem. We thus find that the kernel of $\mathcal{B}$ is contained in

$$\mathcal{K} := \{(\mathbf{v}, q) \in H^1(\Omega)^d \times L_0^2(\Omega) : \int_{\Gamma} \mathbf{v} \cdot \mathbf{n} = 0 \quad \text{and} \quad \mathcal{S}(\mathbf{v}, q) = \mathbf{0}\}.$$

In particular, for $(\mathbf{v}, q) \in \mathcal{K}$, (3) yields

$$\|\nabla \mathbf{v}\|_{L^2(\Omega)}^2 + \|q\|_{L^2(\Omega)}^2 \leq C^2 \|\mathbf{v}\|_{H^s(\Gamma)}^2.$$

In view of the definition (38) of the X_0^s -norm defined, we directly deduce $a(\mathbf{v}, \mathbf{v}) = \|\mathbf{v}\|_{H^s(\Gamma)}^2 \geq \frac{1}{C^2+1} \|\mathbf{v}, q\|_{X_0^s}^2$, which proves the coercivity of a on $\mathcal{K}$ and thus on the kernel of a .

For the the inf-sup condition, we show that

$$\inf_{(\mathbf{z}, \tau, \ell) \in Y} \sup_{(\mathbf{v}, q) \in X_0^s} \frac{\mathcal{B}((\mathbf{v}, q), (\mathbf{z}, \tau, \ell))}{\|(\mathbf{v}, q)\|_{X_0^s} \|(\mathbf{z}, \tau, \ell)\|_Y} > 0.$$

To do so, for any $(\mathbf{z}, \tau, \ell) \in Y$, we construct $(\mathbf{v}, q) \in X_0^s$ such that

$$\mathcal{B}((\mathbf{v}, q), (\mathbf{z}, \tau, \ell)) \geq C_1 \|(\mathbf{z}, \tau, \ell)\|_Y^2 \quad \text{and} \quad \|(\mathbf{v}, q)\|_{X_0^s} \leq C_2 \|(\mathbf{z}, \tau, \ell)\|_Y \quad (60)$$

for some positive constants C_1 and C_2 .

The bilinear form b satisfies the inf-sup condition (see for instance [16]) on $H_0^1(\Omega)^d \times L_0^2(\Omega)$ and in particular, there is a constant $\beta > 0$ such that for all $\tau \in L_0^2(\Omega)$, there is $\mathbf{v}_\tau \in H_0^1(\Omega)$ such that

$$b(\mathbf{v}_\tau, \tau) \geq \beta \|\nabla \mathbf{v}_\tau\|_{L^2(\Omega)} \|\tau\|_{L^2(\Omega)}.$$

Upon rescaling $\mathbf{v}_\tau$, without loss of generality, we can assume that $\|\nabla \mathbf{v}_\tau\|_{L^2(\Omega)} = \eta \|\tau\|_{L^2(\Omega)}$ for some $\eta > 0$ to be determined. Hence, we have

$$b(\mathbf{v}_\tau, \tau) \geq \beta \eta \|\tau\|_{L^2(\Omega)}^2.$$

The last ingredient is $\mathbf{v}_\ell(\mathbf{x}) := -\frac{\ell}{d|\Omega|} \mathbf{x}$ for $\mathbf{x} \in \bar{\Omega}$ so that $b(\mathbf{v}, \ell) = \ell^2$ with $\mathbf{v}_\ell$ satisfying

$$\|\mathbf{v}_\ell\|_{H^s(\Gamma)} = C(\Omega, s) |\ell| \quad \text{and} \quad \|\nabla \mathbf{v}_\ell\|_{L^2(\Omega)} = (d|\Omega|)^{\frac{1}{2}} |\ell|$$

for some positive constant $C(\Omega, s)$ depending only on Ω and s .

We now set $\mathbf{v} := \mathbf{z} + \mathbf{v}_\tau + \mathbf{v}_\ell$ and $q := -\tau$ to get

$$b(\mathbf{v}, \tau) + b(\mathbf{z}, q) + b(\mathbf{v}, \ell) \geq \beta\eta\|\tau\|_{L^2(\Omega)}^2 + \ell^2.$$

Using Cauchy-Schwarz and Young's inequalities, we infer that for any $\delta, \alpha > 0$ we have

$$k(\mathbf{v}, \mathbf{z}) \geq \left(2 - \frac{1}{\delta} - \frac{1}{\alpha}\right) \|\boldsymbol{\varepsilon}(\mathbf{z})\|_{L^2(\Omega)}^2 - \alpha\|\boldsymbol{\varepsilon}(\mathbf{v}_\tau)\|_{L^2(\Omega)}^2 - \delta d^2 = \left(2 - \frac{1}{\delta} - \frac{1}{\alpha}\right) \|\boldsymbol{\varepsilon}(\mathbf{z})\|_{L^2(\Omega)}^2 - \alpha\|\tau\|_{L^2(\Omega)}^2 - \delta d^2.$$

Combining the last two relations yields

$$\mathcal{B}((\mathbf{v}, q), (\mathbf{z}, \tau, \ell)) \geq \left(2 - \frac{1}{\delta} - \frac{1}{\alpha}\right) \|\boldsymbol{\varepsilon}(\mathbf{z})\|_{L^2(\Omega)}^2 + (\beta\eta - \alpha\eta^2)\|\tau\|_{L^2(\Omega)}^2 + (1 - \delta)\ell^2.$$

Choosing for instance, $\delta = 3/4$, $\alpha = 2$ and $\eta = \beta/4$, and invoking the Korn's inequality

$$\|\nabla \mathbf{v}\|_{L^2(\Omega)} \leq C_K \|\boldsymbol{\varepsilon}(\mathbf{v})\| \quad \forall \mathbf{v} \in H_0^1(\Omega)^d,$$

where C_K only depends on Ω , proves the first relation in (60). It remains to show the second relation in (60). We estimate

$$\begin{aligned} \|(\mathbf{v}, q)\|_{X_0^s}^2 &= \|\nabla(\mathbf{z} + \mathbf{v}_\tau + \mathbf{v}_\ell)\|_{L^2(\Omega)}^2 + \|\tau\|_{L^2(\Omega)}^2 + \|\mathbf{v}_\ell\|_{H^s(\Omega)}^2 \\ &\leq 3 \left(\|\nabla \mathbf{z}\|_{L^2(\Omega)}^2 + \|\nabla \mathbf{v}_\tau\|_{L^2(\Omega)}^2 + \|\nabla \mathbf{v}_\ell\|_{L_0^2(\Omega)}^2 \right) + \|\tau\|_{L^2(\Omega)}^2 + C(\Omega, s)^2 \ell^2 \end{aligned}$$

and the second estimate in (60) follows from the scaling $\|\nabla \mathbf{v}_\tau\|_{L^2(\Omega)} = \eta\|\tau\|_{L^2(\Omega)}$ and $\|\nabla \mathbf{v}_\ell\|_{L_0^2(\Omega)} = (d|\Omega|)^{\frac{1}{2}}\ell$.

References

- [1] P. Batlle, Y. Chen, B. Hosseini, H. Owadi, and A. M. Stuart. Error analysis of kernel/GP methods for nonlinear and parametric PDEs. *Journal of Computational Physics*, 520:113488, 2025.
- [2] C. Bernardi, V. Girault, F. Hecht, P.-A. Raviart, and B. Rivière. *Mathematics and Finite Element Discretizations of Incompressible Navier–Stokes Flows*. SIAM, 2024.
- [3] P. Binev, A. Bonito, A. Cohen, W. Dahmen, R. DeVore, and G. Petrova. Solving PDEs with incomplete information. *SIAM J. Numer. Anal.*, 62(3):1278–1312, 2024.
- [4] B. Bojanov. Optimal recovery of functions and integrals. In *First European Congress of Mathematics: Paris, July 6-10, 1992 Volume I Invited Lectures (Part 1)*, pages 371–390. Springer, 1994.
- [5] A. Bonito, A. Demlow, and J. M. Siktari. Alleviating missing boundary conditions in elliptic partial differential equations using interior point measurements. *arXiv preprint arXiv:2511.20901*, 2025.
- [6] A. Bonito and D. Guignard. Approximating partial differential equations without boundary conditions. In *Multiscale, Nonlinear and Adaptive Approximation II, (eds) R. DeVore and A. Kunoth*, pages 145–176. Springer, 2024.
- [7] A. Bonito and W. Lei. Approximation of the spectral fractional powers of the Laplace-Beltrami operator. *Numerical Mathematics: Theory, Methods and Applications*, 15(4):1193–1218, 2022.
- [8] A. Bonito, W. Lei, and J. E. Pasciak. On sinc quadrature approximations of fractional powers of regularly accretive operators. *Journal of Numerical Mathematics*, 27(2):57–68, 2019.
- [9] A. Bonito and J. Pasciak. Numerical approximation of fractional powers of elliptic operators. *Mathematics of Computation*, 84(295):2083–2110, 2015.

- [10] S. L. Brunton, B. R. Noack, and P. Koumoutsakos. Machine learning for fluid mechanics. *Annual Review of Fluid Mechanics*, 52:477–508, 2020.
- [11] K. Duraisamy, G. Iaccarino, and H. Xiao. Turbulence modeling in the age of data. *Annual Review of Fluid Mechanics*, 51:357–377, 2019.
- [12] L. Formaggia, J.-F. Gerbeau, F. Nobile, and A. Quarteroni. Numerical treatment of defective boundary conditions for the Navier–Stokes equations. *SIAM Journal on Numerical Analysis*, 40(1):376–401, 2002.
- [13] S. Foucart and N. Hengartner. Worst-case learning under a multifidelity model. *SIAM/ASA Journal on Uncertainty Quantification*, 13(1):171–194, 2025.
- [14] G. Galdi. *An introduction to the mathematical theory of the Navier-Stokes equations: Steady-state problems*. Springer Science & Business Media, 2011.
- [15] M. Giles, M. G. Larson, J. M. Levenstam, and E. Süli. Adaptive error control for finite element approximations of the lift and drag coefficients in viscous flow. 1997.
- [16] V. Girault and P.-A. Raviart. *Finite Element Methods for Navier–Stokes Equations*. Springer Series in Computational Mathematics. Springer Berlin, Heidelberg, 1986.
- [17] G. H. Golub and C. F. V. Loan. *Matrix Computations*. Johns Hopkins University Press, 4th edition, 2013.
- [18] L. Grinberg and G. E. Karniadakis. Outflow boundary conditions for arterial networks with multiple outlets. *Annals of biomedical engineering*, 36(9):1496–1514, 2008.
- [19] A. Lunardi. *Interpolation theory*, volume 16. Springer, 2018.
- [20] C. A. Micchelli and T. J. Rivlin. Lectures on optimal recovery. numerical analysis, Lancaster 1984 (Lancaster, 1984), 21–93. *Lecture Notes in Math*, 1129, 1985.
- [21] C. A. Micchelli, T. J. Rivlin, and S. Winograd. The optimal recovery of smooth functions. *Numerische Mathematik*, 26:191–200, 1976.
- [22] K. Rajagopal. On boundary conditions for fluids of the differential type. In *Navier-Stokes Equations and Related Nonlinear Problems*, pages 273–278. Springer, 1995.
- [23] P. J. Richards and S. E. Norris. Appropriate boundary conditions for computational wind engineering models revisited. *Journal of Wind Engineering and Industrial Aerodynamics*, 99(4):257–266, 2011.
- [24] P. J. Richards and S. E. Norris. Appropriate boundary conditions for computational wind engineering: Still an issue after 25 years. *Journal of Wind Engineering and Industrial Aerodynamics*, 190:245–255, 2019.
- [25] H. Sohr. *The Navier–Stokes equations: An elementary functional analytic approach*. Springer Science & Business Media, 2012.
- [26] M. Tabata and D. Tagami. Error estimates for finite element approximations of drag and lift in non-stationary navier-stokes flows. *Japan Journal of Industrial and Applied Mathematics*, 17(3):371–389, 2000.
- [27] R. Temam. *Navier–Stokes equations: theory and numerical analysis*, volume 343. American Mathematical Society, 2024.
- [28] J. F. Traub. *Theory of optimal algorithms*. Carnegie-Mellon University. Department of Computer Science, 1973.
- [29] H. Xu, W. Zhang, and Y. Wang. Explore missing flow dynamics by physics-informed deep learning: The parameterized governing systems. *Physics of Fluids*, 33(9):095116, 2021.