4. Convex optimization problems

- optimization problem in standard form
- convex optimization problems
- quasiconvex optimization
- linear optimization
- quadratic optimization
- geometric programming
- generalized inequality constraints
- semidefinite programming
- vector optimization

Optimization problem in standard form

$$\begin{array}{ll}
\text{minimize} & f_0(x) \\
\text{subject to} & f_i(x) \leq 0, \quad i = 1, \ldots, m \\
& h_i(x) = 0, \quad i = 1, \ldots, p
\end{array}$$

- $x \in \mathbf{R}^n$ is the optimization variable
- $f_0 : \mathbf{R}^n \to \mathbf{R}$ is the objective or cost function
- $f_i : \mathbf{R}^n \to \mathbf{R}$, $i = 1, \ldots, m$, are the inequality constraint functions
- $h_i : \mathbf{R}^n \to \mathbf{R}$ are the equality constraint functions

optimal value:

$$p^\star = \inf\{f_0(x) \mid f_i(x) \leq 0, \ i = 1, \ldots, m, \ h_i(x) = 0, \ i = 1, \ldots, p\}$$

- $p^\star = \infty$ if problem is infeasible (no x satisfies the constraints)
- $p^\star = -\infty$ if problem is unbounded below

Optimal and locally optimal points

x is **feasible** if $x \in \mathbf{dom}\, f_0$ and it satisfies the constraints

a feasible x is **optimal** if $f_0(x) = p^\star$; $X_{\rm opt}$ is the set of optimal points

x is **locally optimal** if there is an $R > 0$ such that x is optimal for

$$
\begin{array}{ll}
\mbox{minimize (over } z) & f_0(z) \\
\mbox{subject to} & f_i(z) \leq 0, \quad i = 1, \ldots, m, \quad h_i(z) = 0, \quad i = 1, \ldots, p \\
& \|z - x\|_2 \leq R
\end{array}
$$

examples (with $n = 1$, $m = p = 0$)

- $f_0(x) = 1/x$, $\mathbf{dom}\, f_0 = \mathbf{R}_{++}$: $p^\star = 0$, no optimal point
- $f_0(x) = -\log x$, $\mathbf{dom}\, f_0 = \mathbf{R}_{++}$: $p^\star = -\infty$
- $f_0(x) = x \log x$, $\mathbf{dom}\, f_0 = \mathbf{R}_{++}$: $p^\star = -1/e$, $x = 1/e$ is optimal
- $f_0(x) = x^3 - 3x$, $p^\star = -\infty$, local optimum at $x = 1$

Local and global optima

any locally optimal point of a convex problem is (globally) optimal

proof: suppose x is locally optimal and y is optimal with $f_0(y) < f_0(x)$

x locally optimal means there is an $R > 0$ such that

$$z \text{ feasible}, \quad \|z - x\|_2 \leq R \quad \Longrightarrow \quad f_0(z) \geq f_0(x)$$

consider $z = \theta y + (1 - \theta)x$ with $\theta = R/(2\|y - x\|_2)$

- $\|y - x\|_2 > R$, so $0 < \theta < 1/2$
- z is a convex combination of two feasible points, hence also feasible
- $\|z - x\|_2 = R/2$ and

$$f_0(z) \leq \theta f_0(x) + (1 - \theta) f_0(y) < f_0(x)$$

which contradicts our assumption that x is locally optimal

Optimality criterion for differentiable f_0

x is optimal if and only if it is feasible and

$$\nabla f_0(x)^T(y - x) \geq 0 \quad \text{for all feasible } y$$



if nonzero, $\nabla f_0(x)$ defines a supporting hyperplane to feasible set X at x

Linear program (LP)

$$\begin{array}{ll} \text{minimize} & c^T x + d \\ \text{subject to} & Gx \preceq h \\ & Ax = b \end{array}$$

- convex problem with affine objective and constraint functions
- feasible set is a polyhedron



Examples

diet problem: choose quantities $x_1, \ldots, x_n$ of n foods

- one unit of food j costs c_j, contains amount a_{ij} of nutrient i
- healthy diet requires nutrient i in quantity at least b_i

to find cheapest healthy diet,

$$\begin{array}{ll} \text{minimize} & c^T x \\ \text{subject to} & Ax \succeq b, \quad x \succeq 0 \end{array}$$

piecewise-linear minimization

$$\text{minimize} \quad \max_{i=1,\ldots,m}(a_i^T x + b_i)$$

equivalent to an LP

$$\begin{array}{ll} \text{minimize} & t \\ \text{subject to} & a_i^T x + b_i \leq t, \quad i = 1, \ldots, m \end{array}$$

Chebyshev center of a polyhedron

Chebyshev center of

$$\mathcal{P} = \{x \mid a_i^T x \le b_i,\ i = 1, \dots, m\}$$



is center of largest inscribed ball

$$\mathcal{B} = \{x_c + u \mid \|u\|_2 \le r\}$$

- $a_i^T x \le b_i$ for all $x \in \mathcal{B}$ if and only if

$$\sup\{a_i^T(x_c + u) \mid \|u\|_2 \le r\} = a_i^T x_c + r\|a_i\|_2 \le b_i$$

- hence, x_c, r can be determined by solving the LP

$$\begin{array}{ll} \text{maximize} & r \\ \text{subject to} & a_i^T x_c + r\|a_i\|_2 \le b_i, \quad i = 1, \dots, m \end{array}$$

Quadratic program (QP)

$$\begin{array}{ll} \text{minimize} & (1/2)x^T P x + q^T x + r \\ \text{subject to} & Gx \preceq h \\ & Ax = b \end{array}$$

- $P \in \mathbf{S}^n_+$, so objective is convex quadratic
- minimize a convex quadratic function over a polyhedron



Examples

least-squares

$$\text{minimize} \quad \|Ax - b\|_2^2$$

- analytical solution $x^\star = A^\dagger b$ ($A^\dagger$ is pseudo-inverse)
- can add linear constraints, *e.g.*, $l \preceq x \preceq u$

linear program with random cost

$$\begin{array}{ll} \text{minimize} & \bar{c}^T x + \gamma x^T \Sigma x = \mathbf{E}\, c^T x + \gamma\, \mathbf{var}(c^T x) \\ \text{subject to} & Gx \preceq h, \quad Ax = b \end{array}$$

- c is random vector with mean $\bar{c}$ and covariance Σ
- hence, $c^T x$ is random variable with mean $\bar{c}^T x$ and variance $x^T \Sigma x$
- $\gamma > 0$ is risk aversion parameter; controls the trade-off between expected cost and variance (risk)

Norm approximation

$$\text{minimize} \quad \|Ax - b\|$$

($A \in \mathbf{R}^{m \times n}$ with $m \geq n$, $\|\cdot\|$ is a norm on $\mathbf{R}^m$)

interpretations of solution $x^\star = \operatorname{argmin}_x \|Ax - b\|$:

- **geometric**: $Ax^\star$ is point in $\mathcal{R}(A)$ closest to b
- **estimation**: linear measurement model

$$y = Ax + v$$

  y are measurements, x is unknown, v is measurement error

  given $y = b$, best guess of x is $x^\star$
- **optimal design**: x are design variables (input), Ax is result (output)

  $x^\star$ is design that best approximates desired result b

examples

- least-squares approximation ($\|\cdot\|_2$): solution satisfies normal equations

$$A^T Ax = A^T b$$

  ($x^\star = (A^T A)^{-1} A^T b$ if $\mathbf{rank}\, A = n$)

- Chebyshev approximation ($\|\cdot\|_\infty$): can be solved as an LP

$$\begin{array}{ll} \text{minimize} & t \\ \text{subject to} & -t\mathbf{1} \preceq Ax - b \preceq t\mathbf{1} \end{array}$$

- sum of absolute residuals approximation ($\|\cdot\|_1$): can be solved as an LP

$$\begin{array}{ll} \text{minimize} & \mathbf{1}^T y \\ \text{subject to} & -y \preceq Ax - b \preceq y \end{array}$$

Penalty function approximation

$$\begin{array}{ll} \text{minimize} & \phi(r_1) + \cdots + \phi(r_m) \\ \text{subject to} & r = Ax - b \end{array}$$

($A \in \mathbf{R}^{m \times n}$, $\phi : \mathbf{R} \to \mathbf{R}$ is a convex penalty function)

examples

- quadratic: $\phi(u) = u^2$
- deadzone-linear with width a:

$$\phi(u) = \max\{0, |u| - a\}$$

- log-barrier with limit a:

$$\phi(u) = \begin{cases} -a^2 \log(1 - (u/a)^2) & |u| < a \\ \infty & \text{otherwise} \end{cases}$$



example ($m = 100$, $n = 30$): histogram of residuals for penalties

$$\phi(u) = |u|, \quad \phi(u) = u^2, \quad \phi(u) = \max\{0, |u| - a\}, \quad \phi(u) = -\log(1 - u^2)$$



shape of penalty function has large effect on distribution of residuals

Huber penalty function (with parameter M)

$$\phi_{\mathrm{hub}}(u) = \begin{cases} u^2 & |u| \le M \\ M(2|u| - M) & |u| > M \end{cases}$$

linear growth for large u makes approximation less sensitive to outliers



- left: Huber penalty for $M = 1$
- right: affine function $f(t) = \alpha + \beta t$ fitted to 42 points t_i, y_i (circles) using quadratic (dashed) and Huber (solid) penalty

Least-norm problems

$$\begin{array}{ll} \text{minimize} & \|x\| \\ \text{subject to} & Ax = b \end{array}$$

($A \in \mathbf{R}^{m \times n}$ with $m \leq n$, $\| \cdot \|$ is a norm on $\mathbf{R}^n$)

interpretations of solution $x^\star = \operatorname{argmin}_{Ax=b} \|x\|$:

- **geometric:** $x^\star$ is point in affine set $\{x \mid Ax = b\}$ with minimum distance to 0
- **estimation:** $b = Ax$ are (perfect) measurements of x; $x^\star$ is smallest ('most plausible') estimate consistent with measurements
- **design:** x are design variables (inputs); b are required results (outputs)

  $x^\star$ is smallest ('most efficient') design that satisfies requirements

examples

- least-squares solution of linear equations ($\|\cdot\|_2$):

  can be solved via optimality conditions

$$2x + A^T\nu = 0, \qquad Ax = b$$

- minimum sum of absolute values ($\|\cdot\|_1$): can be solved as an LP

$$\begin{array}{ll} \text{minimize} & \mathbf{1}^T y \\ \text{subject to} & -y \preceq x \preceq y, \quad Ax = b \end{array}$$

  tends to produce sparse solution $x^\star$

extension: least-penalty problem

$$\begin{array}{ll} \text{minimize} & \phi(x_1) + \cdots + \phi(x_n) \\ \text{subject to} & Ax = b \end{array}$$

$\phi : \mathbf{R} \to \mathbf{R}$ is convex penalty function

Regularized approximation

$$\text{minimize (w.r.t. } \mathbf{R}^2_+) \quad (\|Ax - b\|, \|x\|)$$

$A \in \mathbf{R}^{m \times n}$, norms on $\mathbf{R}^m$ and $\mathbf{R}^n$ can be different

interpretation: find good approximation $Ax \approx b$ with small x

- **estimation:** linear measurement model $y = Ax + v$, with prior knowledge that $\|x\|$ is small
- **optimal design**: small x is cheaper or more efficient, or the linear model $y = Ax$ is only valid for small x
- **robust approximation:** good approximation $Ax \approx b$ with small x is less sensitive to errors in A than good approximation with large x

Scalarized problem

$$\text{minimize} \quad \|Ax - b\| + \gamma\|x\|$$

- solution for $\gamma > 0$ traces out optimal trade-off curve
- other common method: minimize $\|Ax - b\|^2 + \delta\|x\|^2$ with $\delta > 0$

Tikhonov regularization

$$\text{minimize} \quad \|Ax - b\|_2^2 + \delta\|x\|_2^2$$

can be solved as a least-squares problem

$$\text{minimize} \quad \left\| \begin{bmatrix} A \\ \sqrt{\delta} I \end{bmatrix} x - \begin{bmatrix} b \\ 0 \end{bmatrix} \right\|_2^2$$

solution $x^\star = (A^T A + \delta I)^{-1} A^T b$

Signal reconstruction

$$\text{minimize (w.r.t. } \mathbf{R}^2_+) \quad (\|\hat{x} - x_{\text{cor}}\|_2, \phi(\hat{x}))$$

- $x \in \mathbf{R}^n$ is unknown signal
- $x_{\text{cor}} = x + v$ is (known) corrupted version of x, with additive noise v
- variable $\hat{x}$ (reconstructed signal) is estimate of x
- $\phi : \mathbf{R}^n \to \mathbf{R}$ is regularization function or smoothing objective

examples: quadratic smoothing, total variation smoothing:

$$\phi_{\text{quad}}(\hat{x}) = \sum_{i=1}^{n-1} (\hat{x}_{i+1} - \hat{x}_i)^2, \qquad \phi_{\text{tv}}(\hat{x}) = \sum_{i=1}^{n-1} |\hat{x}_{i+1} - \hat{x}_i|$$

quadratic smoothing example



original signal x and noisy signal x_{cor}



three solutions on trade-off curve $\|\hat{x} - x_{\mathrm{cor}}\|_2$ versus $\phi_{\mathrm{quad}}(\hat{x})$

total variation reconstruction example



original signal x and noisy signal x_{cor}



three solutions on trade-off curve $\|\hat{x} - x_{\mathrm{cor}}\|_2$ versus $\phi_{\mathrm{quad}}(\hat{x})$

quadratic smoothing smooths out noise **and** sharp transitions in signal



original signal x and noisy signal x_{cor}



three solutions on trade-off curve $\|\hat{x} - x_{\text{cor}}\|_2$ versus $\phi_{\text{tv}}(\hat{x})$

total variation smoothing preserves sharp transitions in signal

Linear measurements with IID noise

linear measurement model

$$y_i = a_i^T x + v_i, \quad i = 1, \ldots, m$$

- $x \in \mathbf{R}^n$ is vector of unknown parameters
- v_i is IID measurement noise, with density $p(z)$
- y_i is measurement: $y \in \mathbf{R}^m$ has density $p_x(y) = \prod_{i=1}^m p(y_i - a_i^T x)$

maximum likelihood estimate: any solution x of

$$\text{maximize} \quad l(x) = \sum_{i=1}^m \log p(y_i - a_i^T x)$$

(y is observed value)

examples

- Gaussian noise $\mathcal{N}(0, \sigma^2)$: $p(z) = (2\pi\sigma^2)^{-1/2} e^{-z^2/(2\sigma^2)}$,

$$l(x) = -\frac{m}{2} \log(2\pi\sigma^2) - \frac{1}{2\sigma^2} \sum_{i=1}^{m} (a_i^T x - y_i)^2$$

  ML estimate is LS solution

- Laplacian noise: $p(z) = (1/(2a)) e^{-|z|/a}$,

$$l(x) = -m \log(2a) - \frac{1}{a} \sum_{i=1}^{m} |a_i^T x - y_i|$$

  ML estimate is ℓ_1-norm solution

- uniform noise on $[-a, a]$:

$$l(x) = \begin{cases} -m \log(2a) & |a_i^T x - y_i| \leq a, \quad i = 1, \ldots, m \\ -\infty & \text{otherwise} \end{cases}$$

  ML estimate is any x with $|a_i^T x - y_i| \leq a$

Logistic regression

random variable $y \in \{0, 1\}$ with distribution

$$p = \textbf{prob}(y = 1) = \frac{\exp(a^T u + b)}{1 + \exp(a^T u + b)}$$

- a, b are parameters; $u \in \mathbf{R}^n$ are (observable) explanatory variables
- estimation problem: estimate a, b from m observations (u_i, y_i)

log-likelihood function (for $y_1 = \cdots = y_k = 1$, $y_{k+1} = \cdots = y_m = 0$):

$$\begin{aligned} l(a, b) &= \log \left(\prod_{i=1}^{k} \frac{\exp(a^T u_i + b)}{1 + \exp(a^T u_i + b)} \prod_{i=k+1}^{m} \frac{1}{1 + \exp(a^T u_i + b)} \right) \\ &= \sum_{i=1}^{k} (a^T u_i + b) - \sum_{i=1}^{m} \log(1 + \exp(a^T u_i + b)) \end{aligned}$$

concave in a, b

example ($n = 1$, $m = 50$ measurements)



- circles show 50 points (u_i, y_i)
- solid curve is ML estimate of $p = \exp(au + b)/(1 + \exp(au + b))$

Minimum volume ellipsoid around a set

Löwner-John ellipsoid of a set C: minimum volume ellipsoid $\mathcal{E}$ s.t. $C \subseteq \mathcal{E}$

- parametrize $\mathcal{E}$ as $\mathcal{E} = \{v \mid \|Av + b\|_2 \leq 1\}$; w.l.o.g. assume $A \in \mathbf{S}^n_{++}$
- $\mathbf{vol}\,\mathcal{E}$ is proportional to $\det A^{-1}$; to compute minimum volume ellipsoid,

$$\begin{array}{ll} \text{minimize (over } A, b) & \log\det A^{-1} \\ \text{subject to} & \sup_{v \in C} \|Av + b\|_2 \leq 1 \end{array}$$

convex, but evaluating the constraint can be hard (for general C)

finite set $C = \{x_1, \ldots, x_m\}$:

$$\begin{array}{ll} \text{minimize (over } A, b) & \log\det A^{-1} \\ \text{subject to} & \|Ax_i + b\|_2 \leq 1, \quad i = 1, \ldots, m \end{array}$$

also gives Löwner-John ellipsoid for polyhedron $\mathbf{conv}\{x_1, \ldots, x_m\}$

Maximum volume inscribed ellipsoid

maximum volume ellipsoid $\mathcal{E}$ inside a convex set $C \subseteq \mathbf{R}^n$

- parametrize $\mathcal{E}$ as $\mathcal{E} = \{Bu + d \mid \|u\|_2 \leq 1\}$; w.l.o.g. assume $B \in \mathbf{S}^n_{++}$
- $\mathbf{vol}\,\mathcal{E}$ is proportional to $\det B$; can compute $\mathcal{E}$ by solving

$$\begin{array}{ll} \text{maximize} & \log\det B \\ \text{subject to} & \sup_{\|u\|_2 \leq 1} I_C(Bu + d) \leq 0 \end{array}$$

(where $I_C(x) = 0$ for $x \in C$ and $I_C(x) = \infty$ for $x \notin C$)

convex, but evaluating the constraint can be hard (for general C)

polyhedron $\{x \mid a_i^T x \leq b_i,\ i = 1, \ldots, m\}$:

$$\begin{array}{ll} \text{maximize} & \log\det B \\ \text{subject to} & \|Ba_i\|_2 + a_i^T d \leq b_i, \quad i = 1, \ldots, m \end{array}$$

(constraint follows from $\sup_{\|u\|_2 \leq 1} a_i^T (Bu + d) = \|Ba_i\|_2 + a_i^T d$)

Support vector classifier

$$
\begin{array}{ll}
\text{minimize} & \|a\|_2 + \gamma(\mathbf{1}^T u + \mathbf{1}^T v) \\
\text{subject to} & a^T x_i + b \geq 1 - u_i, \quad i = 1, \ldots, N \\
& a^T y_i + b \leq -1 + v_i, \quad i = 1, \ldots, M \\
& u \succeq 0, \quad v \succeq 0
\end{array}
$$

produces point on trade-off curve between inverse of margin $2/\|a\|_2$ and classification error, measured by total slack $\mathbf{1}^T u + \mathbf{1}^T v$

same example as previous page, with $\gamma = 0.1$:



quadratic discrimination: $f(z) = z^T P z + q^T z + r$

$$x_i^T P x_i + q^T x_i + r \geq 1, \qquad y_i^T P y_i + q^T y_i + r \leq -1$$

can add additional constraints (*e.g.*, $P \preceq -I$ to separate by an ellipsoid)

polynomial discrimination: $F(z)$ are all monomials up to a given degree



separation by ellipsoid



separation by 4th degree polynomial

Placement and facility location

- N points with coordinates $x_i \in \mathbf{R}^2$ (or $\mathbf{R}^3$)
- some positions x_i are given; the other x_i's are variables
- for each pair of points, a cost function $f_{ij}(x_i, x_j)$

placement problem

$$\text{minimize} \quad \sum_{i \neq j} f_{ij}(x_i, x_j)$$

variables are positions of free points

interpretations

- points represent plants or warehouses; f_{ij} is transportation cost between facilities i and j
- points represent cells on an IC; f_{ij} represents wirelength

example: minimize $\sum_{(i,j)\in\mathcal{A}} h(\|x_i - x_j\|_2)$, with 6 free points, 27 links

optimal placement for $h(z) = z$, $h(z) = z^2$, $h(z) = z^4$



histograms of connection lengths $\|x_i - x_j\|_2$