

Paredit Cheatsheet

Basic Insertion Commands

```
paredit-open-round (
(a b |c d)
(a b (|) c d)

(foo "bar |baz" quux)
(foo "bar (|baz" quux)

paredit-close-round )
(a b |c )
(a b c)|

; Hello,| world
; Hello,)| world

paredit-close-round-and-newline M-)
(defun f (x| ))
(defun f (x| ))
)

; (Foo.|
; (Foo.|

paredit-open-square [
(a b |c d)
(a b [|] c d)

(foo "bar |baz" quux)
(foo "bar [|baz" quux)

paredit-close-square ]
(define-key keymap [frob| ]
'frobnicate)
(define-key keymap [frob|]
'frobnicate)

; [Bar.|
; [Bar.|]

paredit-doublequote "
(frob grovel |full lexical)
(frob grovel "| " full lexical)

(foo "bar |baz" quux)
(foo "bar \"|baz" quux)

paredit-meta-doublequote M-"
(foo "bar |baz" quux)
(foo "bar baz"
|quux)

(foo | (bar #\x "baz \\ quux") zot)
(foo "| (bar #\\x \"baz \\\\ quux\"")
zot)

paredit-backslash \
(string #|)
Escaping character... (x)
(string #\x|)
"foo|bar"
Escaping character... (")
"foo\"|bar"
paredit-comment-dwim M-;
(foo |bar) ; baz
(foo bar) ; |baz
(frob grovel)|
(frob grovel) ;|
|(defun hello-world ...)
;;; |
(defun hello-world ...)
paredit-newline C-j
(let ((n (frobbotz))) |(display (+n 1)
port))
(let ((n (frobbotz)))
|(display (+n 1)
port))
```

Deleting & Killing

```
paredit-forward-delete
C-d, <delete>, <deletechar>
(quu|x "zot")
(quu| "zot")
(quux |"zot")
(quux "|zot")
(quux "|ot")
(foo (|) bar)
(foo | bar)
|(foo bar)
(|foo bar)
paredit-backward-delete DEL
("zot" q|uux)
("zot" |uux)
("zot"| quux)
("zot|" quux)
("zo|" quux)
(foo (|) bar)
(foo | bar)
(foo bar)|
(foo bar|)
paredit-kill C-k
(foo bar)| ; Useless comment!
(foo bar)|
(|foo bar) ; Useful comment!
(|) ; Useful comment!
|(foo bar) ; Useless line!
|
```

```
(foo "|bar baz"
quux)
(foo "| "
quux)
paredit-forward-kill-word M-d
|(foo bar) ; baz
(| bar) ; baz
(|) ; baz
() ;|
;;;| Frobnicate
(defun frobnicate ...)
;;;|
(defun frobnicate ...)
;;;
(| frobnicate ...)
```

Movement & Navigation

```
paredit-forward C-M-f
(foo | (bar baz) quux)
(foo (bar baz)| quux)
(foo (bar)|)
(foo (bar))|
paredit-backward C-M-b
(foo (bar baz)| quux)
(foo |(bar baz) quux)
(|(foo) bar)
|((foo) bar)
```

Depth-Changing Commands

```
paredit-wrap-around M-(
(foo |bar baz)
(foo (|bar) baz)
paredit-splice-sexp M-s
(foo (bar| baz) quux)
(foo bar| baz quux)
paredit-splice-sexp-killing-backward
M-<up>, ESC <up>
(foo (let ((x 5)) |(sqrt n)) bar)
(foo |(sqrt n) bar)
paredit-splice-sexp-killing-forward
M-<down>, ESC <down>
(a (b c| d e) f)
(a b c| f)
paredit-raise-sexp M-r
(dynamic-wind in (lambda () |body)
out)
(dynamic-wind in |body out)
|body
```

Barfage & Slurpage

```
paredit-forward-slurp-sexp C-), C-<right>
(foo (bar |baz) quux zot)
(foo (bar |baz quux) zot)

(a b ((c| d)) e f)
(a b ((c| d) e) f)

paredit-forward-barf-sexp C-}, C-<left>
(foo (bar |baz quux) zot)
(foo (bar |baz) quux zot)

paredit-backward-slurp-sexp
C-(, C-M-<left>, ESC C-<left>
(foo bar (baz| quux) zot)
(foo (bar| baz quux) zot)

(a b ((c| d)) e f)
(a (b (c| d) e) f)

paredit-backward-barf-sexp
C-{, C-M-<right>, ESC C-<right>
(foo (bar baz |quux) zot)
(foo bar (baz |quux) zot)
```

Miscellaneous Commands

```
paredit-split-sexp M-S
(hello| world)
(hello)| (world)

"Hello, |world!"
"Hello, "| "world!"

paredit-join-sexp M-J
(hello)| (world)
(hello| world)

"Hello, "| "world!"
"Hello, |world!"

hello-
| world
hello-|world

paredit-retcentre-on-sexp C-c C-M-l

No examples

paredit-retindent-defun M-q

No examples
```