#### Paredit Cheatsheet

#### **Basic Insertion Commands**

```
paredit-open-round (
(a b | c d)
(a b (|) c d)
(foo "bar | baz" quux)
(foo "bar (|baz" quux)
paredit-close-round)
(a b | c )
(a b c)
; Hello, | world
; Hello,) | world
paredit-close-round-and-newline M-)
(defun f (x | ))
(defun f (x | )
; (Foo.
; (Foo.
paredit-open-square [
(a b | c d)
(a b [ ] c d)
(foo "bar |baz" quux)
(foo "bar [ baz" quux)
paredit-close-square ]
(define-key keymap [frob]
'frobnicate)
(define-key keymap [frob] 'frobnicate)
; [Bar.
; [Bar.]
paredit-doublequote "
(frob grovel |full lexical)
(frob grovel "| " full lexical)
(foo "bar |baz" quux)
(foo "bar \" baz" quux)
paredit-meta-doublequote M-"
(foo "bar | baz" quux)
(foo "bar baz"
    quux)
```

```
(foo | (bar #\x "baz \\ quux") zot)
(foo "|(bar #\\x \"baz \\\\ guux\")"
zot)
paredit-backslash \
(string #|)
Escaping character... (x)
(string #\x|)
"foo bar"
Escaping character... (")
"foo\"|bar"
paredit-comment-dwim M-;
(foo |bar) ; baz
(foo bar)
                       ; |baz
(frob grovel)
(frob grovel)
                       ; |
(defun hello-world ...)
;;;
(defun hello-world ...)
paredit-newline C-j
(let ((n (frobbotz))) | (display (+n 1)
port))
(let ((n (frobbotz)))
(display (+n 1)
           port))
paredit-forward-delete
                            C-d, <delete>,
```

## Deleting & Killing

```
<deletechar>
(quu x "zot")
(quu | "zot")
(quux | "zot")
(quux "|zot")
(quux "|ot")
(foo (|) bar)
(foo | bar)
(foo bar)
(|foo bar)
paredit-backward-delete DEL
("zot" q uux)
("zot" |uux)
("zot" | quux)
("zot | " quux)
("zo|" quux)
```

```
(foo (|) bar)
(foo | bar)
(foo bar)
(foo bar|)
paredit-kill C-k
(foo bar)
             ; Useless comment!
(foo bar)
(|foo bar)
               : Useful comment!
       ; Useful comment!
( | )
              ; Useless line!
(foo bar)
(foo "|bar baz"
  quux)
(foo "|"
  quux)
paredit-forward-kill-word M-d
(foo bar)
              ; baz
(| bar) ; baz
(|)
     ; baz
      ; |
;;;| Frobnicate
(defun frobnicate ...)
;;;
(defun frobnicate ...)
(| frobnicate ...)
```

# Movement & Navigation

```
paredit-forward C-M-f
(foo | (bar baz) quux)
(foo (bar baz) | quux)
(foo (bar) |)
(foo (bar))
paredit-backward C-M-b
(foo (bar baz) | quux)
(foo | (bar baz) quux)
(|(foo) bar)
((foo) bar)
```

## **Depth-Changing Commands**

```
paredit-wrap-around M-(
(foo | bar baz)
(foo (|bar) baz)
paredit-splice-sexp M-s
(foo (bar| baz) quux)
(foo bar| baz quux)
paredit-splice-sexp-killing-backward M-<up>, ESC
(foo (let ((x 5)) | (sqrt n)) bar)
(foo | (sgrt n) bar)
paredit-splice-sexp-killing-forward M-<down>, ESC
<down>
(a (b c d e) f)
(a b c f)
paredit-raise-sexp M-r
(dynamic-wind in (lambda () | body) out)
(dynamic-wind in | body out)
body
```

## Barfage & Slurpage

```
paredit-forward-slurp-sexp C-), C-<right>
(foo (bar | baz) quux zot)
(foo (bar | baz quux) zot)
(a b ((c d)) e f)
(a b ((c d) e) f)
paredit-forward-barf-sexp C-}, C-<left>
(foo (bar | baz quux) zot)
(foo (bar | baz) quux zot)
paredit-backward-slurp-sexp C-(, C-M-<left>,
ESC C-<left>
(foo bar (baz | quux) zot)
(foo (bar baz quux) zot)
(a b ((c d)) e f)
(a (b (c d) e) f)
paredit-backward-barf-sexp C-{, C-M-<right>,
ESC C-<right>
(foo (bar baz |quux) zot)
(foo bar (baz |quux) zot)
```

### Miscellaneous Commands