Paredit Cheatsheet

Basic Insertion Commands

```
paredit-open-round (
(a b | c d)
(a b (|) c d)
(foo "bar |baz" quux)
(foo "bar (|baz" quux)
paredit-close-round)
(a b | c )
(a b c)
; Hello, world
; Hello,) | world
paredit-close-round-and-newline M-)
(defun f (x| ))
(defun f (x )
; (Foo.
; (Foo.
paredit-open-square [
(a b | c d)
(a b [ ] c d)
(foo "bar |baz" quux)
(foo "bar [|baz" quux)
paredit-close-square ]
(define-key keymap [frob] 'frobnicate)
(define-key keymap [frob] / frobnicate)
```

```
; [Bar.
; [Bar.]
paredit-doublequote "
(frob grovel |full lexical)
(frob grovel "|" full lexical)
(foo "bar |baz" quux)
(foo "bar \"|baz" quux)
paredit-meta-doublequote M-"
(foo "bar |baz" quux)
(foo "bar baz"
     |quux)
(foo | (bar #\x "baz \\ quux") zot)
(foo "| (bar #\\x \"baz \\\\ quux\") " zot)
paredit-backslash \
(string #|)
Escaping character... (x)
(string \#\x|)
"foo|bar"
Escaping character... (")
"foo\"|bar"
paredit-comment-dwim M-;
(foo |bar) ; baz
(foo bar)
                       ; |baz
(frob grovel)
(frob grovel)
                       ;
(defun hello-world ...)
(defun hello-world ...)
paredit-newline C-j
```

Deleting & Killing

```
paredit-forward-delete C-d, <delete>, <deletechar>
(quu x "zot")
(quu | "zot")
(quux | "zot")
(quux "|zot")
(quux "|ot")
(foo (|) bar)
(foo | bar)
(foo bar)
(|foo bar)
paredit-backward-delete DEL
("zot" q|uux)
("zot" |uux)
("zot" | quux)
("zot|" quux)
("zo|" quux)
(foo (|) bar)
(foo | bar)
(foo bar)
(foo bar|)
paredit-kill C-k
```

```
; Useless comment!
(foo bar)
(foo bar)
(|foo bar)
             ; Useful comment!
      ; Useful comment!
(foo bar)
             ; Useless line!
(foo "|bar baz"
 quux)
(foo "|"
 quux)
paredit-forward-kill-word M-d
(foo bar)
            ; baz
(| bar) ; baz
     ; baz
() ;
;;;| Frobnicate
(defun frobnicate ...)
;;;
(defun frobnicate ...)
;;;
(| frobnicate ...)
```

Movement & Navigation

Depth-Changing Commands

Barfage & Slurpage

Miscellaneous Commands

1