

# Paredit Cheatsheet

## Basic Insertion Commands

```
paredit-open-round (
(a b |c d)
(a b (|) c d)

(foo "bar |baz" quux)
(foo "bar (|baz" quux)

paredit-close-round )
(a b |c  )
(a b c)|
; Hello,| world
; Hello,)| world

paredit-close-round-and-newline M-)
(defun f (x|  ))
(defun f (x|  )
)

; (Foo.|
; (Foo.|

paredit-open-square [
(a b |c d)
(a b [|] c d)

(foo "bar |baz" quux)
(foo "bar [|baz" quux)

paredit-close-square ]
(define-key keymap [frob| ] 'frobnicate)
(define-key keymap [frob]| 'frobnicate)

; [Bar.|
; [Bar.]|
```

```
paredit-doublequote "
(frob grovel |full lexical)
(frob grovel "| " full lexical)
(foo "bar |baz" quux)
(foo "bar \"|baz" quux)
paredit-meta-doublequote M- "
(foo "bar |baz" quux)
(foo "bar baz"
    |quux)
(foo |(bar #\x "baz \\ quux") zot)
(foo "|(bar #\\x \"baz \\\\ quux\)") " zot)
paredit-backslash \
(string #|)
Escaping character...  (x)
(string #\x|)
"foo|bar"
Escaping character...  (")
"foo\"|bar"
paredit-comment-dwim M-;
(foo |bar)  ; baz
(foo bar)          ; |baz
(frob grovel)|
(frob grovel)      ;|
|(defun hello-world ...)
;;; |
(defun hello-world ...)
paredit-newline C-j
(let ((n (frobbotz))) |(display (+n 1)
port))
(let ((n (frobbotz)))
  |(display (+n 1)
            port))
```

## Deleting & Killing

```
paredit-forward-delete C-d, <delete>, <deletechar>
(quu|x "zot")
(quu| "zot")
(quux |"zot")
(quux "|zot")
(quux "|ot")
(foo (|) bar)
(foo | bar)

|(foo bar)
(|foo bar)

paredit-backward-delete DEL
("zot" q|uux)
("zot" |uux)
("zot"| quux)
("zot"| quux)
("zo|" quux)
(foo (|) bar)
(foo | bar)
(foo bar)|
(foo bar|)

paredit-kill C-k
(foo bar)|  ; Useless comment!
(foo bar)|
(|foo bar)  ; Useful comment!
(|)        ; Useful comment!
|(foo bar)  ; Useless line!
|

(foo "|bar baz"
  quux)
(foo "| "
  quux)
```

```
paredit-forward-kill-word M-d
|(foo bar)      ; baz
(| bar)        ; baz
(|)            ; baz
()             ;|

;;;| Frobnicate
(defun frobnicate ...)
;;;|
(defun frobnicate ...)
;;;
(| frobnicate ...)
```

## Movement & Navigation

```
paredit-forward C-M-f
(foo |(bar baz) quux)
(foo (bar baz)| quux)

(foo (bar)|)
(foo (bar))|

paredit-backward C-M-b
(foo (bar baz)| quux)
(foo |(bar baz) quux)

(|(foo) bar)
|((foo) bar)
```

## Depth-Changing Commands

### Barfage & Slurpage

### Miscellaneous Commands