

Paredit Cheatsheet

Basic Insertion Commands

```
paredit-open-round (  
  (a b |c d)  
  (a b (|) c d)  
  
  (foo "bar |baz" quux)  
  (foo "bar (|baz" quux)  
  
paredit-close-round )  
  (a b |c )  
  (a b c)|  
  
; Hello,| world  
; Hello,)| world  
  
paredit-close-round-and-newline M-)  
  (defun f (x| ) )  
  (defun f (x| ) )  
  )  
; (Foo.|  
; (Foo.|  
  
paredit-open-square [  
  (a b |c d)  
  (a b [|] c d)  
  
  (foo "bar |baz" quux)  
  (foo "bar [|baz" quux)  
  
paredit-close-square ]  
  (define-key keymap [frob| ]  
    'frobnicate)  
  (define-key keymap [frob]| 'frobnicate)  
  
; [Bar.|  
; [Bar.]|  
  
paredit-doublequote "  
  (frob grovel |full lexical)  
  (frob grovel "||" full lexical)  
  
  (foo "bar |baz" quux)  
  (foo "bar \"|baz" quux)  
  
paredit-meta-doublequote M-"  
  (foo "bar |baz" quux)  
  (foo "bar baz"  
    |quux)
```

```
(foo |(bar #\x "baz \\ quux") zot)  
(foo "|(bar #\\x \"baz \\|\\ quux\")" zot)  
  
paredit-backslash \  
  (string #|)  
  Escaping character... (x)  
  (string #\x|)  
  
  "foo|bar"  
  Escaping character... (")  
  "foo\"|bar"  
  
paredit-comment-dwim M-;  
  (foo |bar) ; baz  
  (foo bar) ; |baz  
  
  (frob grovel)|  
  (frob grovel) ;|  
  
  |(defun hello-world ...)  
  ;;; |  
  (defun hello-world ...)  
  
paredit-newline C-j  
  (let ((n (frobbotz))) |(display (+n 1)  
port))  
  (let ((n (frobbotz)))  
    |(display (+n 1)  
              port))  
  )
```

Deleting & Killing

```
paredit-forward-delete C-d, <delete>,  
<deletechar>  
  (quu|x "zot")  
  (quu| "zot")  
  
  (quux |"zot")  
  (quux "|zot")  
  (quux "|ot")  
  
  (foo (|) bar)  
  (foo | bar)  
  
  |(foo bar)  
  (|foo bar)  
  
paredit-backward-delete DEL  
  ("zot" q|uux)  
  ("zot" |uux)  
  
  ("zot"| quux)  
  ("zot|" quux)  
  ("zo|" quux)
```

```
(foo (|) bar)  
(foo | bar)  
  
(foo bar)|  
(foo bar|)  
  
paredit-kill C-k  
  
  (foo bar)| ; Useless comment!  
  (foo bar)|  
  
  (|foo bar) ; Useful comment!  
  (|) ; Useful comment!  
  
  |(foo bar) ; Useless line!  
  |  
  (foo "|bar baz"  
    quux)  
  (foo "|"  
    quux)  
  
paredit-forward-kill-word M-d  
  
  |(foo bar) ; baz  
  (| bar) ; baz  
  (|) ; baz  
  () ;|  
  
  ;;;| Frobnicate  
  (defun frobnicate ...)  
  ;;;|  
  (defun frobnicate ...)  
  ;;;  
  (| frobnicate ...)
```

Movement & Navigation

```
paredit-forward C-M-f  
  
  (foo |(bar baz) quux)  
  (foo (bar baz)| quux)  
  
  (foo (bar)|)  
  (foo (bar))|  
  
paredit-backward C-M-b  
  
  (foo (bar baz)| quux)  
  (foo |(bar baz) quux)  
  
  (|(foo) bar)  
  |((foo) bar)
```

Depth-Changing Commands

```
paredit-wrap-around M-  
  (foo |bar baz)  
  (foo (|bar) baz)  
  
paredit-splice-sexp M-s  
  (foo (bar| baz) quux)  
  (foo bar| baz quux)  
  
paredit-splice-sexp-killing-backward M-<up>, ESC  
<up>  
  (foo (let ((x 5)) |(sqrt n)) bar)  
  (foo |(sqrt n) bar)  
  
paredit-splice-sexp-killing-forward M-<down>, ESC  
<down>  
  (a (b c| d e) f)  
  (a b c| f)  
  
paredit-raise-sexp M-r  
  (dynamic-wind in (lambda () |body) out)  
  (dynamic-wind in |body out)  
  |body  
  
Barfage & Slurpage  
  
paredit-forward-slurp-sexp C-), C-<right>  
  (foo (bar |baz) quux zot)  
  (foo (bar |baz quux) zot)  
  
  (a b ((c| d)) e f)  
  (a b ((c| d) e) f)  
  
paredit-forward-barf-sexp C-}, C-<left>  
  (foo (bar |baz quux) zot)  
  (foo (bar |baz) quux zot)  
  
paredit-backward-slurp-sexp C-(, C-M-<left>,  
ESC C-<left>  
  (foo bar (baz| quux) zot)  
  (foo (bar| baz quux) zot)  
  
  (a b ((c| d)) e f)  
  (a (b (c| d) e) f)  
  
paredit-backward-barf-sexp C-{, C-M-<right>,  
ESC C-<right>  
  (foo (bar baz |quux) zot)  
  (foo bar (baz |quux) zot)  
  
Miscellaneous Commands
```