

# Paredit Cheatsheet

## Basic Insertion Commands

```
paredit-open-round (
(a b |c d)
(a b (|) c d)
(foo "bar |baz" quux)
(foo "bar (|baz" quux)
paredit-close-round )
(a b |c  )
(a b c)|
; Hello,| world
; Hello,)| world
paredit-close-round-and-newline M-)
(defun f (x|  ))
(defun f (x|  )
)
```

```
; (Foo.|
; (Foo.|
paredit-open-square [
(a b |c d)
(a b [|] c d)
(foo "bar |baz" quux)
(foo "bar [|baz" quux)
paredit-close-square ]
(define-key keymap [frob| ] 'froblicate)
(define-key keymap [frob]| 'froblicate)
; [Bar.|
; [Bar.]|
paredit-doublequote "
(frob grovel |full lexical)
(frob grovel "| " full lexical)
(foo "bar |baz" quux)
(foo "bar [|baz" quux)
paredit-meta-doublequote M-"
```

```
(foo "bar |baz" quux)
(foo "bar baz"
    |quux)
(foo | (bar #\x "baz \\\ quux") zot)
(foo "| (bar #\\x \"baz \\\\ quux\\") " zot)
paredit-backslash \
(string #|)
Escaping character...  (x)
(string #\x|)
"foo|bar"
Escaping character...  (")
"foo\"|bar"
paredit-comment-dwim M-;
(foo |bar)  ; baz
(foo bar)           ; |baz
(frob grovel)|
(frob grovel)      ;|
```

```
| (defun hello-world ...)
;;; |
(defun hello-world ...)
paredit-newline C-j
(let ((n (frobbotz))) | (display (+n 1)
port))
(let ((n (frobbotz)))
    | (display (+n 1)
              port))
```

## Deleting & Killing

## Movement & Navigation

## Depth-Changing Commands

## Barfage & Slurpage

## Miscellaneous Commands