# WARNING

- Loading Heavy Items on the Rack will change the vehicles "Center of Gravity" (C.G.) that could increase the potential for roll over which could result in serious injury or death!

- Maximum Combined Capacity of Cargo Rack is 60 lbs. - 160 lbs.
(Limited by Vehicle Capacity)

- Load Capacity of Top Rack is 60 lbs.
(Limited by Vehicle Capacity)

- Load Capacity of Side Rack is 30 lbs. per side
(Do Not Recommend Mount Spare Tires on Side Racks)

- Racks with a Tailgate the Load Capacity of the tailgate is 40 lbs.
(Limited by Vehicle Capacity)

- CAUTION Loads must be equally distributed

- Operator must use common sense when loading rack so as not to affect the vehicles safe operation.

- It Is the operators responsibility to follow all manufactures recommendations regarding safe operation of any vehicle.

-See operations manual for further information

WARNING

DOC0283


# WARNING

- Loading Heavy Items on the Rack will change the vehicles "Center of Gravity" (C.G.) that could increase the potential for roll over which could result in serious injury or death!

- Maximum Combined Capacity of Cargo Rack is 60 lbs. - 160 lbs.
(Limited by Vehicle Capacity)

- Load Capacity of Top Rack is 60 lbs.
(Limited by Vehicle Capacity)

- Load Capacity of Side Rack is 30 lbs. per side
(Do Not Recommend Mount Spare Tires on Side Racks)

- Racks with a Tailgate the Load Capacity of the tailgate is 40 lbs.
(Limited by Vehicle Capacity)

- CAUTION Loads must be equally distributed

- Operator must use common sense when loading rack so as not to affect the vehicles safe operation.

- It Is the operators responsibility to follow all manufactures recommendations regarding safe operation of any vehicle.

-See operations manual for further information

WARNING

DOC0283