Reference » mPDF functions

TOC_Entry()

(mPDF >= 1.0)

TOC_Entry - Insert an entry for the Table of Contents

Description

```
void TOC_Entry ( string $content [, int $level [, string $name ]])
```

Insert an entry for the Table of Contents referencing the current writing position in the document.

Note: The position for the Table of Contents must be specified using TOCpagebreak() or <tocpagebreak> at some point before Output() is called.

Note: From mPDF 2.3 you can use more than one **ToC** in the document using the parameter *name*.

Parameters

content

This parameter sets the text as it will appear in the ToC entry. content cannot contain any of the characters: < > & ' or " and must use the appropriate HTML entities e.g. <annotation content="This is < 40" />

It is recommended that you use htmlspecialchars('Content', ENT_QUOTES) for this.

REQUIRED

level

```
Specify the level of this entry i.e. like heading1,2,3
Starts at level 0
DEFAULT: 0
```

name

Specify which **ToC** to add this entry, if using more than one **ToC** in the document. *name* can be any alphanumeric characters (except just "0") and is case-insensitive.

BLANK or omitted or 0 uses the default ToC.

Values (case-insensitive)

"ALL" will add this entry to every ToC active in the document.

Changelog

Version Description2.3 name attribute was added.

Examples

```
Example #1
```

```
<?php

$mpdf=new mPDF();
$mpdf->WriteHTML('Introduction');
```

2015-08-05

```
$mpdf->TOCpagebreak();

$mpdf->TOC_Entry("Chapter 1",0);
$mpdf->WriteHTML('Chapter 1 ...');
$mpdf=Output();
?>
```

Notes

Note: Since mPDF 2.0 **insertTOC()** should **not** be called at the end of the document. Output() will automatically generate the ToC if it has been defined with either or TOCpagebreak() or <tocpagebreak>.

See Also

- TOCpagebreak() Insert a Table of Contents in the document
- <tocpagebreak> Insert a Table of Contents in the document
- <tocentry> Mark a ToC entry in the document

Printed on Wed 05 Aug 2015 12:17:49 GMT +0100 (DST)

2015-08-05