

TOC_Entry()

(mPDF >= 1.0)

TOC_Entry – Insert an entry for the Table of Contents

Description

```
void TOC_Entry ( string $content [, int $level [, string $name ]])
```

Insert an entry for the Table of Contents referencing the current writing position in the document.

Note: The position for the Table of Contents must be specified using TOCpagebreak() or <tocpagebreak> at some point before Output() is called.

Note: From mPDF 2.3 you can use more than one **TOC** in the document using the parameter *name*.

Parameters

content

This parameter sets the text as it will appear in the ToC entry.
content cannot contain any of the characters: < > & ' or " and must use the appropriate HTML entities e.g. <annotation content="This is < 40" />
It is recommended that you use htmlspecialchars('Content', ENT_QUOTES) for this.
REQUIRED

level

Specify the level of this entry i.e. like heading1,2,3
Starts at level 0
DEFAULT: 0

name

Specify which **TOC** to add this entry, if using more than one **TOC** in the document. *name* can be any alphanumeric characters (except just "0") and is case-insensitive.
BLANK or omitted or 0 uses the default **TOC**.

Values (case-insensitive)
"ALL" will add this entry to every ToC active in the document.

Changelog

Version	Description
2.3	<i>name</i> attribute was added.

Examples

Example #1

```
<?php
$mpdf=new mPDF();
$mpdf->WriteHTML('Introduction');
$mpdf->TOCpagebreak();

$mpdf->TOC_Entry("Chapter 1",0);
$mpdf->WriteHTML('Chapter 1 ...');
$mpdf=Output();

?>
```

Notes

Note: Since mPDF 2.0 **insertTOC()** should **not** be called at the end of the document. Output() will automatically generate the ToC if it has been defined with either or TOCpagebreak() or <tocpagebreak>.

See Also

- TOCpagebreak() - Insert a Table of Contents in the document
- <tocpagebreak> - Insert a Table of Contents in the document
- <tocentry> - Mark a ToC entry in the document

Printed on Wed 05 Aug 2015 12:17:48 GMT +0100 (DST)