

# pagefooter

(mPDF >= 2.0)

pagefooter - Define a page footer with a given name

## Description

```
<pagefooter [ name ] [ content-left ] [ content-center ] [ content-right ] [ footer-style ] [ footer-style-left ] [ footer-style-center ] [ footer-style-right ] [ line ] />
```

Define a page footer with a given name. Named footers can be referenced and set later in the document e.g. <setpagefooter>

**Note:** Do not name any header or footer starting with html\_ This prefix is reserved to identify an **HTML** header/footer when passing its name in a reference.

## Attributes

*name*

This attribute is a text string to use as the name for this footer.  
If name is **BLANK** or omitted, it is set as '\_default'.

*content-left*  
*content-center*  
*content-right*

Defines the text to appear in the page footer.  
At least one 'content-' must be defined.

### Values

*content-left*: Text to appear at left margin  
*content-center*: Text to appear in centre of page  
*content-right*: Text to appear at right margin

*footer-style*  
*footer-style-left*  
*footer-style-center*  
*footer-style-right*

This attribute can optionally set CSS style properties for the page footer.  
*footer-style* will set the same style for left, right and center content, whereas *footer-style-left*, *footer-style-center* and *footer-style-right* set the style for one part of the content only.

### Values

Valid CSS inline style declaration but only 5 properties can be set:

*font-family*  
*font-size*  
*font-weight*  
*font-style*  
*color*

If style is not set, the default values for the document are used.

*line*

If set to "1" or any positive value, a line will be drawn above the footer.

## Changelog

Version	Description
2.0	The tag was added.

## Examples

For examples and further information please see:

- Headers & Footers
- Headers & Footers - Method 3

## See Also

- DefFooterByName()
- <pageheader>
- SetFooterByName()
- <setpagefooter>

Printed on Wed 05 Aug 2015 12:19:32 GMT +0100 (DST)