User's Guide » Installation & Setup

## Upgrading to v4.x - Archived

## Where has it gone?

Some of the files - or their contents - have been moved or renamed in version 4. If you have made changes/modifications to previous versions, and want to make those changes to the new versions, this may help you find things:

Declarations of all variables have been moved to the top of the mPDF class.

Variables are now initialised (when required) either in the *function mpdf()* if they are internal variables, or in the config.php file.

The file htmltoolkit.php is removed:

- GetCodepage() is moved to config cp.php which contains configurable values for codepages
- most functions from htmltoolkit.php are now included within the mpdf class (at end of mpdf.php file)
- character substitutions are now in /includes/subs\_[codepage].php files
- a few remaining stand-alone functions have moved to /includes/functions.php

 ${\tt mpdf\_config.php} \ {\tt has} \ {\tt been} \ {\tt renamed} \ {\tt config\_fonts.php}$ 

gif.php has moved to /classes/gif.php

CJKdata.php has moved to /includes/

no\_img2.gif is now /includes/no\_image.jpg

## Additional notes for developers

split() has been replaced by preg\_split or explode as split is depracated in PHP 5.3

set\_magic\_quotes\_runtime has been wrapped in a check as it is depracated in PHP 5.3

A number of subroutine functions have been used to tidy up the code.

Handling of HTML Headers and Footers has been changed, so that all are 'written' at the end of the document.

The files in /patterns/\*.\* used for hyphenation are changed to ASCII safe text (were win-1252 encoded)

If a double-sided document is generated (*mirrorMargins/useOddEven*) then the PDF file is set to use Duplex printing by default

mPDFi altered - can now simply capture errors on reading file by editing mpdfi.php see fn. SetSourceFile()

Some internal variables have been changed:

- \$mb encoding -> \$mb enc
- \$saveHeaderLinksE\_N etc. -> \$saveHeaderLinks (array)
- \$saveFooterLinksE N etc. -> \$saveFooterLinks (array)
- \$saveHTMLHeaderE\_N etc. -> \$saveHTMLHeader (array)
- \$saveHTMLFooter\_N etc. -> \$saveHTMLFooter (array)
- \$tblborderstyles -> \$borderstyles

Script will die with an error message if *mb\_string* functions not enabled.

FPDF FONTPATH changed to MPDF FONTPATH

\_getfontpath() removed - replaced with MPDF\_FONTPATH

functions DottedRect and DrawDot removed (not used)

Printed on Wed 05 Aug 2015 12:37:17 GMT +0100 (DST)

2015-08-05