

# SetHTMLHeader()

(mPDF >= 1.2)

SetHTMLHeader - Sets an HTML page header

## Description

```
void SetHTMLHeader ( string $html [, string $side [, boolean $write ]])
```

Set an HTML page header.

## Parameters

*header*

This parameter specifies the content of the page header as a string of valid HTML code.

**DEFAULT: BLANK**

*side*

Specify whether to set the header for **ODD** or **EVEN** pages in a **DOUBLE-SIDED** document.

**DEFAULT: BLANK**

**Values** (case-sensitive)

O - set the header for **ODD** pages

E - set the header for **EVEN** pages

**BLANK** - sets **ODD** page headers

*write*

If **TRUE** it forces the Header to be written immediately to the current page. Use if the header is being set after the new page has been added.

**DEFAULT: FALSE**

**Note:** Important Difference - SetHeader() and SetFooter() called without specifying a *side* sets both **ODD** & **EVEN** headers/footers; **SetHTMLHeader()** and SetHTMLFooter() without a *side* - sets **ODD** page header/footer only as default

## Changelog

Version	Description
1.2	The function was added.

## Examples

For examples and further information please see:

- Headers & Footers
- Headers & Footers - Method 2

## See Also

- SetHTMLFooter()

Printed on Wed 05 Aug 2015 12:16:39 GMT +0100 (DST)