

Custom HTML Tags

mPDF uses a number of custom HTML tags (see [HTML Control Tags - Overview](#)).

In addition to those, the custom tags `<ttz>` `<tts>` and `<tta>` are reserved for use internally within the mPDF program to denote the core symbol, dingbat and arial characters.

Invalid HTML?

(mPDF >= 2.2)

If you want to hide mPDF custom tags from a browser, enclose any mPDF code within:

```
<!--mpdf .. anything you want to write ... mpdf-->
```

As these are the standard comment tags recognised by every browser, this will create valid HTML which should output correctly in any circumstances. mPDF will strip away the `<!--mpdf` tag and any following spaces, and the `mpdf-->` tag and any preceeding spaces, and process all enclosed code.

Note: Almost all mPDF custom tags are self closing e.g. `<pagebreak />`. If you do not use self-closing tags, the HTML may not show correctly in a browser unless you hide the tags in special comments as above.

Most browsers will ignore (self-closing) tags that are not recognised, but `<htmlpageheader>` and `<htmlpagefooter>` are different, as they contain innerHTML e.g.

```
<htmlpageheader name="phname">HTML code in here</htmlpageheader>
```

The enclosed innerHTML will be output by a browser, so you need to hide it; either use the special comment tags as above, or an alternative is to use CSS, e.g. add to your stylesheet

```
htmlpageheader { display : none; }  
htmlpagefooter { display : none; }
```

Yet another way is to use in-line CSS:

```
<htmlpageheader name="phname" style="display: none;">HTML code in here</htmlpageheader>
```

Printed on Wed 05 Aug 2015 12:06:20 GMT +0100 (DST)