

# tocentry

(mPDF >= 1.0)

tocentry – Insert an entry for the Table of Contents

## Description

```
<tocentry content [ level ] [ name ] />
```

Insert an entry for the Table of Contents referencing the current writing position in the document.

**Note:** The position for the Table of Contents must be specified using TOCpagebreak() or <tocpagebreak> at some point before Output() is called.

**Note:** From mPDF 2.3 you can use more than one **toc** in the document using the attribute *name*.

## Parameters

*content*

This parameter sets the text as it will appear in the ToC entry. Text should be UTF-8 encoded. *content* cannot contain any of the characters: < > & ' or " and must use the appropriate HTML entities e.g. <tocentry content="&lt; 40" /> It is recommended that you use htmlspecialchars('Content', ENT\_QUOTES) for this.

**REQUIRED**

*level*

Specify the level of this entry (i.e. like heading 1,2,3) as a positive integer  
Starts at level 0

**DEFAULT:** 0

*name*

Specify which **toc** to add this entry, if using more than one **toc** in the document. *name* can be any alphanumeric characters (except just "0") and is case-insensitive.

**BLANK** or omitted or 0 uses the default **toc**.

**Values** (case-insensitive)

"ALL" will add this entry to every ToC active in the document.

## Changelog

Version	Description
2.3	<i>name</i> attribute was added.

## Examples

Example #1

```
<?php
$mpdf=new mPDF();
```

```
$mpdf->WriteHTML('Introduction');  
$mpdf->WriteHTML('<tocpagebreak />');  
  
$mpdf->WriteHTML('<tocentry content="Chapter 1" />');  
$mpdf->WriteHTML('Chapter 1 ...');  
$mpdf=Output();  
  
?>
```

## Notes

**Note:** Since mPDF 2.0 **insertTOC()** should **not** be called at the end of the document. **Output()** will automatically generate the ToC if it has been defined with either **TOCpagebreak()** or **<tocpagebreak>**.

### Recommended placement

Recommended placement of ToC Entries is just after the first word following the opening tag of the block element:

```
<h2>First<tocentry... /> word of a heading or block</h2>
```

or alternatively just after the opening tag of the block element:

```
<h2><tocentry... />Heading or block</h2>
```

or just after a word to be marked:

```
... this is a word<tocentry... /> in the middle of text to be marked ...
```

## See Also

- **TOCpagebreak()** - Insert a Table of Contents in the document
- **<tocpagebreak>** - Insert a Table of Contents in the document
- **TOC\_Entry()** - Mark a ToC entry in the document

Printed on Wed 05 Aug 2015 12:19:54 GMT +0100 (DST)