

# DefFooterByName()

(mPDF >= 2.0)

DefFooterByName – Define a page footer with a given name

## Description

```
void DefFooterByName ([ string $name [, array $footer ]])
```

Define a page footer with a given name. Named footers can be referenced and set later in the document e.g. `SetFooterByName()`

**Note:** Do not name any header or footer starting with `html_`. This prefix is reserved to identify an **HTML** header/footer when passing its name in a reference.

**Note:** This function/method was altered in mPDF 2.2 by capitalising the first letter of the name. As function/method names in PHP have hitherto been case-insensitive, this should not cause any problems, but it is recommended where possible to use the preferred spelling.

## Parameters

*name*

User-defined name for the footer. If *name* = **BLANK** the name `'_default'` is used.

*footer*

This parameter specifies the content of the page footer as an array.  
**DEFAULT:** `array()`abov

**Values** in the array

*content:* **TEXT STRING**

*font-size:* **FLOAT** font size in **pts**

*font-style:* **B||B|BLANK STRING**

*font-family:* Any available font-family

*color:* CSS `'#RRGGBB'` string

*line:* 0|1 - specify whether to draw a line above the footer

```
$footer = array (
    'L' => array (
        'content' => '',
        'font-size' => 10,
        'font-style' => 'B',
        'font-family' => 'serif',
        'color' => '#000000'
    ),
    'C' => array (
        'content' => '',
        'font-size' => 10,
        'font-style' => 'B',
        'font-family' => 'serif',
        'color' => '#000000'
    ),
    'R' => array (
        'content' => 'My document',
        'font-size' => 10,
        'font-style' => 'B',
        'font-family' => 'serif',
        'color' => '#000000'
    ),
    'line' => 1,
);
```

## Changelog

| Version | Description             |
|---------|-------------------------|
| 2.0     | The function was added. |

### **Examples**

For examples and further information please see:

- Headers & Footers
- Headers & Footers - Method 3

### **See Also**

- DefHeaderByName()
- <pagefooter>
- SetFooterByName()
- <setpagefooter>

Printed on Wed 05 Aug 2015 12:14:10 GMT +0100 (DST)