

# DefHTMLFooterByName()

(mPDF >= 2.0)

DefHTMLFooterByName - Define an HTML page footer with a given name

## Description

```
void DefHTMLFooterByName ( string $name [, string $html ])
```

Define an HTML page footer with a given name. Named footers can be referenced and set later in the document e.g. SetHTMLFooterByName()

**Note:** Do not name any header or footer starting with `html_`. This prefix is reserved to identify an **HTML** header/footer when passing its name in a reference.

**Note:** This function/method was altered in mPDF 2.2 by capitalising the first letter of the name. As function/method names in PHP have hitherto been case-insensitive, this should not cause any problems, but it is recommended where possible to use the preferred spelling.

## Parameters

*name*

User-defined name for the footer. If *name* = **BLANK** the name `'_default'` is used.

*html*

This parameter specifies the content of the page footer as a string of valid HTML code.  
**DEFAULT: BLANK**

## Changelog

| Version | Description             |
|---------|-------------------------|
| 2.0     | The function was added. |

## Examples

For examples and further information please see:

- Headers & Footers
- Headers & Footers - Method 4

## See Also

- DefHTMLHeaderByName()
- `<htmlpagefooter>`
- SetHTMLFooterByName()
- `<sethtmlpagefooter>`