

SetSubject()

(mPDF >= 1.0)

SetSubject - Set the document metadata Subject

Description

```
void SetSubject ( string $text )
```

Set the Subject for the document. This metadata can be seen when inspecting the document properties in Adobe Reader.

Note: Adobe Reader uses system fonts to display the document metadata, therefore any Unicode text can be used, even if a unibyte codepage is being used for the document.

Parameters

text

Defines the text to appear as the document Subject. The text should be UTF-8 encoded, but should not contain HTML mark-up tags. `strcode2utf()` is a useful function provided with mPDF which converts HTML numerical entities to UTF-8 encoded string.

Examples

Example #1

```
<?php

$mpdf=new mPDF();
$mpdf->SetSubject('My Subject');
$mpdf->WriteHTML('<p>Hallo World</p>');
$mpdf->Output('filename.pdf');

?>
```

Example #2

```
// htmlentities contains a function strcode2utf() to convert htmlentities to UTF-8 encoded text

<?php

$mpdf=new mPDF();

$md = strcode2utf("&#1575;&#1610;&#1604;&#1575;&#1578; &#1601;&#1610;&#1605;&#1575;&#1575;&#1610;&#1604;&#1575;&#1578; &#1601;&#1610;&#1605;&#1575;");

$mpdf->SetSubject($md);
$mpdf->WriteHTML('<p>Hallo World</p>');
$mpdf->Output('filename.pdf');

?>
```

See Also

- `SetTitle()` - Set document Title in metadata
- `SetAuthor()` - Set document Author in metadata
- `SetCreator()` - Set document Creator in metadata

- SetKeywords() - Set document Keywords in metadata
- strcode2utf() - Convert HTML numerical entities to UTF-8 encoded string

Printed on Wed 05 Aug 2015 12:17:05 GMT +0100 (DST)