

DefHTMLFooterByName()

(mPDF >= 2.0)

DefHTMLFooterByName – Define an HTML page footer with a given name

Description

```
void DefHTMLFooterByName ( string $name [, string $html ])
```

Define an HTML page footer with a given name. Named footers can be referenced and set later in the document e.g. SetHTMLFooterByName()

Note: Do not name any header or footer starting with `html_`. This prefix is reserved to identify an **HTML** header/footer when passing its name in a reference.

Note: This function/method was altered in mPDF 2.2 by capitalising the first letter of the name. As function/method names in PHP have hitherto been case-insensitive, this should not cause any problems, but it is recommended where possible to use the preferred spelling.

Parameters

name

User-defined name for the footer. If *name* = **BLANK** the name `'_default'` is used.

html

This parameter specifies the content of the page footer as a string of valid HTML code.
DEFAULT: BLANK

Changelog

Version	Description
2.0	The function was added.

Examples

For examples and further information please see:

- Headers & Footers
- Headers & Footers - Method 4

See Also

- DefHTMLHeaderByName()
- `<htmlpagefooter>`
- SetHTMLFooterByName()
- `<sethtmlpagefooter>`

Printed on Wed 05 Aug 2015 12:14:17 GMT +0100 (DST)