Reference » mPDF functions

DefHeaderByName()

(mPDF >= 2.0)

DefHeaderByName - Define a page header with a given name

Description

```
void DefHeaderByName ([ string $name [, array $header ]])
```

Define a page header with a given name. Named headers can be referenced and set later in the document e.g. SetHeaderByName()

Note: Do not name any header or footer starting with html_ This prefix is reserved to identify an **HTML** header/footer when passing its name in a reference.

Note: This function/method was altered in mPDF 2.2 by capitalising the first letter of the name. As function/method names in PHP have hitherto been case-insensitive, this should not cause any problems, but it is recommended where possible to use the preferred spelling.

Parameters

name

User-defined name for the header. If name = **BLANK** the name '_default' is used.

header

This parameter specifies the content of the page header as an array. **DEFAULT**: array()

```
Values in the array content: TEXT STRING font-size: FLOAT font size in pts font-style: B|I|BI|BLANK STRING font-family: Any available font-family color: CSS '#RRGGBB' string
```

line: 0|1 - specify whether to draw a line under the Header

```
$header = array (
    'L' => array (
        'content' => '',
        'font-size' => 10,
        'font-family' => 'B',
        'color'=>'#000000'
),
    'C' => array (
        'content' => '',
        'font-size' => 10,
        'font-size' => 10,
        'font-family' => 'serif',
        'color'=>'#000000'
),
    'R' => array (
        'content' => 'My document',
        'font-size' => 10,
        'font-family' => 'serif',
        'color'=>'#000000'
),
        'line' => 1,
);
```

Changelog

Version Description

2.0 The function was added.

2015-08-05

Examples

For examples and further information please see:

- Headers & Footers
- Headers & Footers Method 3

See Also

- DefFooterByName()
- pageheader>
- SetHeaderByName()
- <setpageheader>

Printed on Wed 05 Aug 2015 12:14:13 GMT +0100 (DST)

2015-08-05