

# AliasNbPageGroups()

(mPDF >= 2.0)

AliasNbPageGroups – Defines the placeholder used to insert total page number into the document

## Description

```
void AliasNbPageGroups ( string $text )
```

Set the value for the variable string `aliasNbPgGp` which is used as a placeholder used to insert total page number into the document. If you have reset the page numbering with `AddPage()` or `<pagebreak>` the total number of pages in the current page group will be used (up to where the numbering is reset) rather the total number of pages in the whole document.

## Parameters

*text*

Defines the text for the variable *aliasNbPgGp*.  
**DEFAULT:** {nbpg}

## Examples

### Example #1

```
<?php
$mpdf=new mPDF();
$mpdf->AliasNbPageGroups('[pagetotal]');
$mpdf->WriteHTML('<p>There are [pagetotal] pages in this page group</p>');
$mpdf->Output();
?>
```

### Example #2

```
$mpdf->AliasNbPageGroups('[pagetotal]');

is the exact equivalent of:

$mpdf->aliasNbPgGp = '[pagetotal]';
```

## See Also

- Replaceable Aliases
- AliasNbPages() - Sets the placeholder alias for the total number of pages in the document

Printed on Wed 05 Aug 2015 12:13:44 GMT +0100 (DST)