

mPDF()

(mPDF >= 5.0)

mPDF – Initialise an instance of mPDF class

Description

```
class mPDF ([ string $mode [, mixed $format [, float $default_font_size [, string $default_font [, float $margin_left [, float $margin_right [, float $margin_top [, float $margin_bottom [, float $margin_header [, float $margin_footer [, string $orientation ]]]]]]]])
```

Initialise an instance of mPDF class.

Parameters

mode

This parameter specifies the mode of the new document.
DEFAULT: BLANK

Codepage Values (case-insensitive)

BLANK

"C"

"...-X"

"...-s" or "s"

"...+aCJK" or "+aCJK"

"...-aCJK" or "-aCJK"

where ... can be any string. Only language/country codes will have any effect, but other strings are parsed for backwards compatability (but have no effect).

Only some combinations make sense. See Choosing a configuration for more details.

Country/Language code values (case-insensitive)

Country/language codes are defined in `config_cp.php`

A country/language code can be passed as e.g. "en-GB" or "en_GB" or "en"

Note: If the *mode* is set by passing a country/language string, this may also set: available fonts, text justification, and directionality RTL (as determined by `config_cp.php`)

Note: There is a useful list of language/country codes at:
<http://www.i18nguy.com/unicode/language-identifiers.html>

format

format can be specified either as a pre-defined page size, or as an array of width and height in millimetres (see Example #2 below).

DEFAULT: "A4"

Values (case-insensitive)

A0 - A10, B0 - B10, C0 - C10

4A0, 2A0, RA0 - RA4, SRA0 - SRA4

Letter, Legal, Executive, Folio

Demy, Royal

A (Type A paperback 111x178mm)

B (Type B paperback 128x198mm)

Ledger, Tabloid*

All of the above values can be suffixed with "-L" to force a Landscape page orientation document e.g. "A4-L".

If *format* is defined as a string, the final *orientation* parameter will be ignored.

*Ledger and Tabloid are standard formats with the same page size but different orientation (Ledger is landscape, and Tabloid is portrait). mPDF treats these identically; if you wish to use Ledger, you should specify "Ledger-L" for landscape.

default_font_size

Sets the default document font size in **points** (pt)
BLANK or omitted or 0 uses the default value set in *defaultCSS*.

default_font

Sets the default font-family for the new document.
BLANK or omitted uses default value set in *defaultCSS* unless *codepage* has been set to "win-1252". If *codepage*="win-1252", the appropriate core Adobe font will be set i.e. Helvetica, Times, or Courier.

margin_left
margin_right
margin_top
margin_bottom
margin_header
margin_footer

Sets the page margins for the new document.
All values should be specified as **LENGTH** in millimetres.
If you are creating a **DOUBLE-SIDED** document, the margin values specified will be used for **ODD** pages; left and right margins will be mirrored for **EVEN** pages.
BLANK or omitted uses the default values.

DEFAULT Values

margin_left 15
margin_right 15
margin_top 16
margin_bottom 16
margin_header 9
margin_footer 9

orientation

This attribute specifies the default page orientation of the new document if *format* is defined as an array. This value will be ignored if *format* is a string value.
DEFAULT: "P"

Values (case-insensitive)

P: **DEFAULT** Portrait
L: Landscape

Changelog

Version	Description
2.0	The <i>orientation</i> parameter was added.
5.0	The <i>mode</i> parameter renamed (from <i>codepage</i>), and recognised values changed

Examples

Example #1

```
<?php
include("../mpdf.php");
$mpdf=new mPDF();
$mpdf->WriteHTML('<p>Hallo World</p>');
$mpdf->Output('filename.pdf');
```

```
exit;  
?>
```

Example #2

```
// Define a new mPDF document using utf-8 fonts  
$mpdf=new mPDF('utf-8');  
  
// Define a new mPDF document using win-1252 fonts based on a language/country code  
$mpdf=new mPDF('en-GB');  
  
// Define a Landscape page size/format by name  
$mpdf=new mPDF('utf-8', 'A4-L');  
  
// Define a page size/format by array - page will be 190mm wide x 236mm height  
$mpdf=new mPDF('utf-8', array(190,236));  
  
// Define a page using all default values except "L" for Landscape orientation  
$mpdf=new mPDF('', '', 0, '', 15, 15, 16, 16, 9, 9, 'L');
```

Notes

Note: `_MPDF_PATH` was required to be defined explicitly prior to mPDF 4.0 e.g. `define('_MPDF_PATH','../')`. From mPDF 4.0 the value should be automatically defined by the script itself when including the `mpdf.php` file.

See Also

- `WriteHTML()` - Write HTML to the document
- `Output()` - Finalise and output the document

Printed on Wed 05 Aug 2015 12:13:11 GMT +0100 (DST)