

SetFooterByName()

(mPDF >= 2.0)

SetFooterByName – Sets a page footer by a given name

Description

```
void SetFooterByName ( string $name [, string $side ])
```

Sets a page footer that has previously been defined by name.

Note: This function/method was altered in mPDF 2.2 by capitalising the first letter of the name. As function/method names in PHP have hitherto been case-insensitive, this should not cause any problems, but it is recommended where possible to use the preferred spelling.

Parameters

name

This parameter specifies the name of a previously defined page footer. If a **BLANK** string or **NULL** is passed, mPDF will use the value `'_default'` if such a page footer exists.

side

Specify whether to set the footer for **ODD** or **EVEN** pages in a **DOUBLE-SIDED** document.
DEFAULT: `'O'`

Values (case-sensitive)

O - set the footer for **ODD** pages in a **DOUBLE-SIDED** document, or for both **ODD** and **EVEN** in a **SINGLE-SIDED** document.

E - set the footer for **EVEN** pages

DEFAULT - sets the footer for **ODD** in a **DOUBLE-SIDED** document, or for both **ODD** and **EVEN** in a **SINGLE-SIDED** document.

Changelog

Version	Description
2.0	The function was added.

Examples

For examples and further information please see:

- Headers & Footers
- Headers & Footers - Method 3

See Also

- DefFooterByName()
- <pagefooter>
- SetHeaderByName()
- <setpagefooter>