

pageheader

(mPDF >= 2.0)

pageheader – Define a page header with a given name

Description

```
<pageheader [ name ] [ content-left ] [ content-center ] [ content-right ] [ header-style ] [ header-style-left ] [ header-style-center ] [ header-style-right ] [ line ] />
```

Define a page header with a given name. Named headers can be referenced and set later in the document e.g. <setpageheader>

Note: Do not name any header or footer starting with html_ This prefix is reserved to identify an HTML header/footer when passing its name in a reference.

Attributes

name

This attribute is a text string to use as the name for this header.
If name is **BLANK** or omitted, it is set as '_default'.

content-left
content-center
content-right

Defines the text to appear in the page header.
At least one 'content-' must be defined.

Values

content-left: Text to appear at left margin
content-center: Text to appear in centre of page
content-right: Text to appear at right margin

header-style
header-style-left
header-style-center
header-style-right

This attribute can optionally set CSS style properties for the page header.
header-style will set the same style for left, right and center content, whereas *header-style-left*, *header-style-center* and *header-style-right* set the style for one part of the content only.

Values

Valid CSS inline style declaration but only 5 properties can be set:

font-family
font-size
font-weight
font-style
color

If style is not set, the default values for the document are used.

line

If set to "1" or any positive value, a line will be drawn below the header.

Changelog

Version	Description
2.0	The tag was added.

Examples

For examples and further information please see:

- Headers & Footers
- Headers & Footers - Method 3

See Also

- DefHeaderByName()
- <pagefooter>
- SetHeaderByName()
- <setpageheader>

Printed on Wed 05 Aug 2015 12:19:28 GMT +0100 (DST)
