

Instruction Format

R-Type

op	rs	rt	rd	shamt	funct
6 bits	5 bits	5 bits	5 bits	5 bits	6 bits

I-Type

op	rs	rt	imm
6 bits	5 bits	5 bits	16 bits

J-Type

op	addr
6 bits	26 bits

Register Set

Name	Register Number	Usage
\$0	0	the constant value 0
\$at	1	assembler temporary
\$v0-\$v1	2-3	Function return values
\$a0-\$a3	4-7	Function arguments
\$t0-\$t7	8-15	temporaries
\$s0-\$s7	16-23	saved variables
\$t8-\$t9	24-25	more temporaries
\$k0-\$k1	26-27	OS temporaries
<u>\$gp</u>	28	global pointer
<u>\$sp</u>	29	stack pointer
<u>\$fp</u>	30	frame pointer
<u>\$ra</u>	31	Function return address

Instructions sorted by opcode

Opcode	Name	Description	Operation
000000 (0)	R-type	all R-type instructions	See the table below
000001 (1) (rt = 0/1)	bltz rs, label / bgez rs, label	branch less than zero/branch greater than or equal to zero	if ([rs] < 0) PC = BTA/ if ([rs] ≥ 0) PC = BTA
000010 (2)	j label	jump	PC = JTA
000011 (3)	jal label	jump and link	\$ra = PC + 4, PC = JTA
000100 (4)	beq rs, rt, label	branch if equal	if ([rs] == [rt]) PC = BTA
000101 (5)	bne rs, rt, label	branch if not equal	if ([rs] != [rt]) PC = BTA
000110 (6)	blez rs, label	branch if less than or equal to zero	if ([rs] ≤ 0) PC = BTA
000111 (7)	bgtz rs, label	branch if greater than zero	if ([rs] > 0) PC = BTA
001000 (8)	addi rt, rs, imm	add immediate	[rt] = [rs] + SignImm
001001 (9)	addiu rt, rs, imm	add immediate unsigned	[rt] = [rs] + SignImm
001010 (10)	slti rt, rs, imm	set less than immediate	[rs] < SignImm ? [rt] = 1 : [rt] = 0
001011 (11)	sltiu rt, rs, imm	set less than immediate unsigned	[rs] < SignImm ? [rt] = 1 : [rt] = 0
001100 (12)	andi rt, rs, imm	and immediate	[rt] = [rs] & ZeroImm
001101 (13)	ori rt, rs, imm	or immediate	[rt] = [rs] ZeroImm
001110 (14)	xori rt, rs, imm	xor immediate	[rt] = [rs] ^ ZeroImm
001111 (15)	lui rt, imm	load upper immediate	[rt] = {imm, 16'b0}
010000 (16) (rs = 0/4)	mfc0 rt, rd / mtc0 rt, rd	move from/to coprocessor 0	[rt] = [rd]/[rd] = [rt] (rd is in coprocessor 0)
010001 (17)	F-type	fop = 16/17: F-type instructions	See F-Type instructions Table
010001 (17) (rt = 0/1)	bc1f label/ bc1t label	fop = 8: branch if fpcond is FALSE/TRUE	if (fpcond == 0) PC = BTA/ if (fpcond == 1) PC = BTA
011100 (28) (func = 2)	mul rd, rs, rt	multiply (32-bit result)	[rd] = [rs] x [rt]
100000 (32)	lb rt, imm(rs)	load byte	[rt] = SignExt ([Address] _{7:0})
100001 (33)	lh rt, imm(rs)	load halfword	[rt] = SignExt ([Address] _{15:0})
100011 (35)	lw rt, imm(rs)	load word	[rt] = [Address]
100100 (36)	lbu rt, imm(rs)	load byte unsigned	[rt] = ZeroExt ([Address] _{7:0})
100101 (37)	lhu rt, imm(rs)	load halfword unsigned	[rt] = ZeroExt ([Address] _{15:0})
101000 (40)	sb rt, imm(rs)	store byte	[Address] _{7:0} = [rt] _{7:0}
101001 (41)	sh rt, imm(rs)	store halfword	[Address] _{15:0} = [rt] _{15:0}
101011 (43)	sw rt, imm(rs)	store word	[Address] = [rt]
110001 (49)	lwcl ft, imm(rs)	load word to FP coprocessor 1	[ft] = [Address]
111001 (56)	swcl ft, imm(rs)	store word to FP coprocessor 1	[Address] = [ft]

R-Type, sorted by function field

Funct	Name	Description	Operation
000000 (0)	sll rd, rt, shamt	shift left logical	$[rd] = [rt] \ll \text{shamt}$
000010 (2)	srl rd, rt, shamt	shift right logical	$[rd] = [rt] \gg \text{shamt}$
000011 (3)	sra rd, rt, shamt	shift right arithmetic	$[rd] = [rt] \ggg \text{shamt}$
000100 (4)	sllv rd, rt, rs	shift left logical variable	$[rd] = [rt] \ll [rs]_{4:0}$
000110 (6)	srlv rd, rt, rs	shift right logical variable	$[rd] = [rt] \gg [rs]_{4:0}$
000111 (7)	srav rd, rt, rs	shift right arithmetic variable	$[rd] = [rt] \ggg [rs]_{4:0}$
001000 (8)	jr rs	jump register	$PC = [rs]$
001001 (9)	jalr rs	jump and link register	$\$ra = PC + 4, PC = [rs]$
001100 (12)	syscall	system call	system call exception
001101 (13)	break	break	break exception
010000 (16)	mfhi rd	move from hi	$[rd] = [hi]$
010001 (17)	mthi rs	move to hi	$[hi] = [rs]$
010010 (18)	mflo rd	move from lo	$[rd] = [lo]$
010011 (19)	mtlo rs	move to lo	$[lo] = [rs]$
011000 (24)	mult rs, rt	multiply	$\{[hi], [lo]\} = [rs] \times [rt]$
011001 (25)	multu rs, rt	multiply unsigned	$\{[hi], [lo]\} = [rs] \times [rt]$
011010 (26)	div rs, rt	divide	$[lo] = [rs] / [rt],$ $[hi] = [rs] \% [rt]$
011011 (27)	divu rs, rt	divide unsigned	$[lo] = [rs] / [rt],$ $[hi] = [rs] \% [rt]$
100000 (32)	add rd, rs, rt	add	$[rd] = [rs] + [rt]$
100001 (33)	addu rd, rs, rt	add unsigned	$[rd] = [rs] + [rt]$
100010 (34)	sub rd, rs, rt	subtract	$[rd] = [rs] - [rt]$
100011 (35)	subu rd, rs, rt	subtract unsigned	$[rd] = [rs] - [rt]$
100100 (36)	and rd, rs, rt	and	$[rd] = [rs] \& [rt]$
100101 (37)	or rd, rs, rt	or	$[rd] = [rs] [rt]$
100110 (38)	xor rd, rs, rt	xor	$[rd] = [rs] \wedge [rt]$
100111 (39)	nor rd, rs, rt	nor	$[rd] = \sim([rs] [rt])$
101010 (42)	slt rd, rs, rt	set less than	$[rs] < [rt] ? [rd] = 1 : [rd] = 0$
101011 (43)	sltu rd, rs, rt	set less than unsigned	$[rs] < [rt] ? [rd] = 1 : [rd] = 0$

F-Type instructions

Funct	Name	Description	Operation
000000 (0)	add.s fd, fs, ft / add.d fd, fs, ft	FP add	[fd] = [fs] + [ft]
000001 (1)	sub.s fd, fs, ft / sub.d fd, fs, ft	FP subtract	[fd] = [fs] - [ft]
000010 (2)	mul.s fd, fs, ft / mul.d fd, fs, ft	FP multiply	[fd] = [fs] × [ft]
000011 (3)	div.s fd, fs, ft / div.d fd, fs, ft	FP divide	[fd] = [fs]/[ft]
000101 (5)	abs.s fd, fs / abs.d fd, fs	FP absolute value	[fd] = ([fs] < 0) ? [-fs] : [fs]
000111 (7)	neg.s fd, fs / neg.d fd, fs	FP negation	[fd] = [-fs]
111010 (58)	c.seq.s fs, ft / c.seq.d fs, ft	FP equality comparison	fpcond = ([fs] == [ft])
111100 (60)	c.lt.s fs, ft / c.lt.d fs, ft	FP less than comparison	fpcond = ([fs] < [ft])
111110 (62)	c.le.s fs, ft / c.le.d fs, ft	FP less than or equal comparison	fpcond = ([fs] ≤ [ft])

System Calls and Input output Operators

Service	Code in \$v0	Arguments	Results
print_int	1	\$a0 = integer to be printed	
print_float	2	\$f12 = float to be printed	
print_double	3	\$f12 = double to be printed	
print_string	4	\$a0 = address of string in memory	
read_int	5		integer returned in \$v0
read_float	6		float returned in \$v0
read_double	7		double returned in \$v0
read_string	8	\$a0 = memory address of string input buffer \$a1 = length of string buffer (n)	
sbrk	9	\$a0 = amount	address in \$v0
exit	10		