

CALIMESA FIRE DEPARTMENT

POLICY MANUAL

VOLUME 6

Policy: 600.24 Rehab

11/2023

Page 5 of 6

6. Glasgow Come Scale

d. Personnel will remain in the designated REHAB area until released by the REHAB personnel.

e. Hydration and passive, active, or emergency cooling or warming will be provided.

1. Passive Cooling- Occurs when natural, evaporative cooling can take place (i.e., shade, fans, removal of safety area, in-cab air conditioning).

2. Active Cooling⁰ takes place when external cooling measures are used to aid passive cooling (i.e., cold-water towels and/or submersion of forearms into ice water).

3. Emergency Cooling- rapid and aggressive cooling interventions to decrease the risk of serious complications (such as rhabdomyolysis) or death (i.e., full body cold water immersion intervention to patients as having a heat stroke).

4. Inclusion Criteria-Exertional activity of any kind with CNS compromise (A.L.O.C, unsteady gait, collapse, disoriented, headache, dizziness, etc.) and any elevated body temperature.

5. Procedure- Remove all protective equipment and clothing from patient (underwear ok to remain in place). Place patient in ice bath while ensuring the neck and head remain above water. Continuously stir-agitate water for maximum effect. Patient should remain immersed in water for a maximum of 15 minutes and then transported. Cold water immersion interventions may be terminated early if all CNS symptoms revolve, patient begins to shiver, or if ABC's are otherwise unable to be managed.

6. Rehab personnel will monitor signs & symptoms indicating the need for further REHAN or hospital transport

7. Prior to release from REHAB, a second set of vital signs will be taken.

f. No personnel will be allowed to resume working if while seated, their:

1. Heart Rate is greater than 120 BPM.

2. Diastolic Blood Pressure is greater than 105 mmHG.

3. Tympanic temperature is greater than 100.4F with associated CNS compromise.

4. Pulse Oximetry reading is less than 92%.

5. Carboxyhemoglobin reading is above 15ppm.

CALIMESA FIRE DEPARTMENT
POLICY MANUAL
VOLUME 6
Policy: 600.24 Rehab

11/2023

Page 6 of 6

6. Glasgow Coma Scale of less than 15.

g. If ANY vital signs are higher than the stated thresholds after rest and hydration, it will be discretion of REHAB personnel to offer further REHAB or hospital transport. In any case, vital signs will be taken immediately prior to releasing personnel from REHAB.

h. Medical monitoring will include all ALS components when indicated.

i. Personnel who have a chief complaint onset during REHAB will be transported to the closest most appropriate hospital evaluation.

j. Any injuries or illness found during REHAB will be communicated through the chain of command.

REASSIGNMENT:

A. It is the responsibility of the REHAB Group Supervisor to track resources and make notifications when resources are available for reassignment.

REHAB CACHE / EQUIPMENT AND REHAB LOCATIONS:

The following facilities will have and maintain (2) E-Z Ups, a minimum of (30) cases of water, (15) cases of Gatorade, and (2) large ice chest.

A. Calimesa Station # 1

City Facility (T.B.D.)

(Cross Reference Volume 2 Section 301.17 Employee Health and Safety – Heat Illness Prevention Policy and Volume 6 Section 602.11 Heat Stress Management)

- **601.00 – Station Operations – Volume. 6**

- 601.01 Facilities/Grounds Program Manger
- 601.02 Station Regulations
- 601.03 Station Safety
- 601.04 Apparatus Bay Doors
- 601.05 10 Day Cleaning Program
- 601.06 Kitchen - Refrigeration of Food
- 601.07 Facilities Inspections

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Station Operations

Guideline: 601.01 Facilities & Grounds Program Manager

12/2023

Page 1 of 1

The Designation of Facilities & Grounds Program Manager(s) shall be assigned as an ancillary duty to a Battalion Chief and Fire Captain for the purpose of assisting the Fire Chief in coordinating facilities inspections, maintenance needs and repairs of non-vehicular / fleet related fixed assets, or to evaluate Capital Improvement Projects related to facilities, grounds and or other closely related projects.

STANDARD

TBD

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 601.02 Station Regulations

12/2023

Page 1 of 2

The purpose of the Station Regulations Guideline is to provide uniformity for all personnel to adhere to while on duty and when at the station off duty and to provide personnel a course of action for the daily routine operations and maintenance of station activities.

STANDARD

1. Shift change will take place at 0800 hours. In the event a member is late for work his/her counterpart will remain on duty until properly relieved. Personnel that know they will be late need to call in before 0600.
2. The fire stations are places of business between the hours of 0800 hours and 1800 hours. Proper professional behavior as a place of business shall apply at all times. Members of the public, City Council members and personnel from other agencies will, on occasion, wish to take a tour or participate in business activities.
3. Apparatus maintenance and check will begin upon completion of information exchange between personnel at the Safety Briefing.
4. Daily station cleanup will be performed by station personnel after the completion of daily/weekly/monthly apparatus check. Station cleanup will be the 10 Day Cleaning Program
5. Facility repairs that are needed will be forwarded via chain of command to the Fire Chief.
6. Visitation hours are restricted to 1800-2100 hours. Any guest(s) that are causing annoyance to personnel will be asked to leave. It is the responsibility of the Station Captain to enforce any such occurrence.
7. Station security is to be maintained by all personnel.
 - a. All personnel are to take precautions to secure personal effects such as wallets, cash, credit cards, keys and day planners.
 - b. Any unclaimed personal belongings found in the stations during daily cleanup or during the shift should be placed in an area of safe keeping until the property is claimed.
8. Personnel are not allowed to be inside any Chief Officer's office without authorization or escorted by a Chief Officer. Personnel found in violation will be subject to disciplinary action and or termination.
9. Personnel are prohibited from having firearms of any kind within the fire stations, City apparatus or any other City property.
10. Personal vehicles shall not be parked in station apparatus rooms or in those areas that would restrict access or egress of department vehicles.
 - a. Personnel are prohibited from performing personal work on vehicles while on station property unless such work is of an emergency nature.
 - b. No washing and waxing of personal vehicles is allowed. Vehicles shall not be parked in areas that create a safety hazard for other personnel and impede the response capabilities of emergency units.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 601.02 Station Regulations

12/2023

Page 2 of 2

11. Station privileges are extended to off-duty personnel with the understanding that they will not disrupt or disturb the routine duties of on-duty personnel.
 - a. Personnel may, under certain circumstances request permission from the Fire Chief to live in the fire station while off-duty for short periods of time in case of emergency.
 - b. Those personnel who obtain permission to live at a station are subject to the same Policies as on-duty personnel.
 - c. Personnel living in the stations shall be expected to respond on all nighttime structure fire calls.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 601.03 Station Safety

12/2023

Page 1 of 2

The Station Safety Guideline does not supersede the standard operating policy.

A large percentage of personnel injuries occur while participating in routine activities at or around the station. Observing proper safety practices and adopting a safety conscious attitude could prevent most of these injuries.

STATION MAINTENANCE

Efforts should be made to keep apparatus floors free from slippery substances and obstructions; water, oil, hydraulic fluid, etc. should be mopped up whenever accumulations appear, especially on the traffic areas around and between the apparatus.

Station floors must be free of slippery substances. Traffic route areas, hallways, stairs, etc., should be clear of unnecessary obstacles and obstructions.

GROUNDS MAINTENANCE

Safety precautions shall be observed when using power lawn equipment: mowers, trimmers, edgers, etc.

- The blade guard on power edgers and trimmers shall be serviceable and in the proper position for the intended use before operating.
- Safety goggles will be available and shall be utilized to provide eye protection from rocks, twigs and other propelled objects when operating mowers, edger's, etc.
- When trimming, or pruning certain trees and bushes, gloves may be necessary to provide adequate hand protection. If gloves are needed, they shall be worn.
- Do not use defective equipment such as ladders with broken rungs, power equipment without the proper safety protection, etc. Repair or replace before use.

LIFTING/PULLING

Utilize the following proper lifting techniques when lifting moderate to heavy objects:

- Use your legs to lift; bend your knees.
- Keep your back straight.
- Do not twist your body while lifting; reposition your feet to avoid twisting.
- To lift heavy objects, get your body as close to the object as possible.
- Use of back support devices if previously had back problems.

Heavy objects should ideally be stored at approximately waist level to prevent unnecessary lifting.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 601.03 Station Safety

12/2023

Page 2 of 2

Do not attempt to lift or carry more than you can easily handle, if necessary get help!

When you are dragging, or raising hose with a halyard from a hose tower, do not pull more than you can pull with relative ease, if necessary get help!

PHYSICAL FITNESS

One of the main objectives of the Physical Fitness Program is to lessen the frequency and severity of employee injuries by increasing the muscular stress and physical stamina of the body. To fulfill this objective, the intent of the phases and steps of the program must be understood by all participants.

The Physical Fitness Guideline like most Operations Guidelines is intended to be reviewed periodically.

- Are you doing all aspects of the program in the manner intended?
- Do you follow the program warm-up procedures?
- Do you follow the prescribed exercises as illustrated?
- Do you have a proper attitude and approach toward the program?
- Do you follow prescribed cooling down procedures?
- Do you have proper exercise shoes, etc.?

If you are in doubt about any aspect of the program reread and follow the manual. It's your body, treat it right.

See Physical Fitness Program Guidelines.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6
Guideline: 601.04 Apparatus Bay Doors

12/2023

Page 1 of 1

The purpose of the Apparatus Bay Doors Guideline is to provide security for apparatus, equipment and to prevent undesirable contact between apparatus and apparatus bay doors.

STANDARD

1. Apparatus bay doors shall be in the fully open or completely closed position.
2. Apparatus bay doors shall be closed when personnel are not providing security for the apparatus bay.
3. Apparatus bay doors shall be closed when the fire station is vacant.
4. The apparatus driver shall be responsible for control and operation of the remote door controller. The remote door closer will be located on the apparatus driver's side.
5. The apparatus driver shall take all precautions to ensure that the apparatus is clear of the apparatus bay doors prior to closing the doors by using the remote door controller.
6. Stations that have multiple units that respond from the station;
 - a. The apparatus drivers of the units must be cognizant/aware of which units will be responding to the incident and in which order.
 - b. Apparatus drivers must take all precautions to ensure that both apparatus have cleared the apparatus bay doors prior to activating the remote door controller.
7. Personnel shall immediately report any malfunctions or damage to the Deputy Fire Chief or Company Officer.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6
Guideline: 601.05 10 Day Cleaning Program

12/2023

Page 1 of 2

This 10-Day Cleaning Program is to be done in addition to normal day-to-day station cleaning. This will assist maintaining station cleanliness on a fair rotation. Use the last number of the day within each month to correspond with the cleaning day. Ex: 11/06/12 would be day 6.

DAY 0: FIRST OUT APPRATUS AND RESERVE ENGINE

- Wax/polish if needed
- Detail cab & compartments

DAY 1: DETAIL DAY ROOM

- Clean all surface area
- Clean under furniture (sweep, mop)
- Clean windows, seals, & blinds

DAY 2: DETAIL KITCHEN

- Clean & organize all cabinets
- Clean all appliances (microwave, stove, toaster, range, fridge, coffee maker, coffee pots, water cooler)

DAY 3: DETAIL DORMS

- Wash all bedding
- Clean all windows, seals, & blinds including both bathrooms
- Clean all surface area
- Vacuum under all beds

DAY 4: DETAIL SHOWERS & LAUNDRY ROOM

- Clean front & back shower
- Clean under washer & dryer (sweep, mop)
- Clean exterior of washer & dryer

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 601.05 10 Day Cleaning Program

12/2023

Page 2 of 2

DAY 5: YARD WORK

- Pick up trash, pull weeds, & rake rocks
- Trim trees & bushes as needed
- Sweep apron, front entry, & scrub
- Roll up garden hose

DAY 6: YARD WORK

- Pick up trash & pull weeds
- Organize trash area & separate recycles
- Roll up garden hose
- Clean back patio

DAY 7: DETAIL BARBEQUE AREA

- Follow cleaning procedures via “owner’s manual”
- Clean barbeque area
- Clean hose rack area

DAY 8: DETAIL DAY ROOM

- Clean all surface area
- Clean under furniture (sweep, mop)
- Clean windows, seals, & blinds

DAY 9: DETAIL APPARATUS BAY

- Sweep, degrease, & wash apparatus bay
- Organize shelves, peg board, weights, hose rack, top of lockers
- Clean all windows & seals
- Clean around water jugs & ice machine

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6
Guideline: 601.06 Kitchen: Refrigeration of Food

12/2023

Page 1 of 1

This guideline is intended to reduce staff from eating other staff's food.

1. It is the responsibility of all staff to label all their food they bring in.
2. When a label is not placed on an individual's food other staff might accidentally eat it.
3. It is the responsibility of the staff member to remove or discarded his or her food when it is old or unusable.
4. All unlabeled food will be assumed that any staff member can eat it.

- **602.00 – Health and Fitness - Volume. 6**

- 602.01 Lifestyle Approach
- 602.02 Overview Exercise Basics
- 602.03 Overview Fitness Program Design
- 602.04 Over-Training
- 602.05 Warm-up
- 602.06 Stretching
- 602.07 Strength and Power
- 602.08 Cool Down
- 602.09 Fitness Menu

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 602.01 Lifestyle Approach

12/2023

Page 1 of 1

INTRODUCTION

A lifestyle approach to health and fitness is an attitude that suggests a lifelong commitment. Unfortunately, health and fitness objectives tend to involve short-term commitments, for example exercising to prepare for an upcoming medical exam. Once the exam is complete, exercising ceases and the inactive lifestyle is resumed. This is a recipe for disaster.

POSITIVE REINFORCEMENT

A lifelong commitment to health and fitness usually requires that the activities engaged in provide some meaningful benefit. Perhaps the most important being some form of immediate gratification.

By participating in an activity that provides immediate gratification an association is created that is positive and reinforces the behavior. This is particularly important in the adopting of behaviors to improve health and fitness, where many of the benefits are not experienced until many years down the road. Examples of immediate gratification include; stress relief, sense of accomplishment, social interaction, or how about just good old fashion fun.

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 602.02 Overview Exercise Basics

12/2023

Page 1 of 1

OVERVIEW

The Fire Service, by its very nature, includes risks of injury and disease. The exposure to hazardous situations, the immediate demand to perform at peak physical capabilities, and the ever-present stress all contribute to the risk of an injury. The old adage of "an ounce of prevention is worth a pound of cure" is of great significance in the Fire Service. It is the Calimesa Fire Department's belief, that the most beneficial and effective means to prevent injury is to follow standard safety procedures and increase the fitness levels through a comprehensive fitness program.

A statement that should be the foundation of any fitness program is entitled, "Pursuit of Excellence."

As individuals, we do not begin life with equal innate capacities for mental or physical achievement. Consequently, we cannot pursue excellence in physical fitness on an absolute scale; everyone should, however, strive for the highest level of fitness within the limitations of his or her own physical potential.

THAT IS THE TRUE GOAL OF THIS PROGRAM!

SPECIFICITY PRINCIPLE

The principle of specificity of training states that the way the body responds to physical activity is very specific to the activity itself.

For example, someone who jogs can expect that their jogging performance would improve as well as their aerobic conditioning. However, they should not expect their performance in other aerobic activities to increase significantly nor should they expect muscular strength or flexibility to improve.

This principle explains the importance of a well thought out multifaceted approach to fitness. The program should address health, job performance, and personal issues by including specific activities that improve each of these areas

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 602.03 Overview Fitness Program Design

12/2023

Page 1 of 1

ESSENTIAL COMPONENTS

Whenever the design of a fitness program is considered, it is essential that four components always exist:

- Muscular
- Aerobic
- Flexibility
- Lifestyle approach

PERSONALIZED

The differences between individual fitness programs should only be in which component of the program the emphasis is placed. A long-distance runner requires emphasis on cardiovascular fitness, but he needs to incorporate some of the other three components in his program to be successful. The same holds true for the power-lifter who places emphasis on the muscular component. To achieve total fitness, the other remaining factors must be addressed.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 602.04 Over-Training

12/2023

Page 1 of 1

The most common training error committed probably is the act of over-training. It's not that enthusiasm should be discouraged, but rather the concept that more is always better.

It is true that the body will experience a training effect only if an overload is introduced, but only if the overload is not carried to the extreme. The extreme being over-training which leads to injuries, injuries lead to inactivity and inactivity leads to decreased fitness levels.

SIGNS & SYMPTOMS

The signs and symptoms of over-training include:

- Lack of motivation
- Aching joints
- Tired and sore muscles
- Insomnia
- Irritability
- Increase in resting pulse of ten beats per minute over normal

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6
Guideline: 602.05 Warm-up

12/2023

Page 1 of 1

Before participating in any physical activity whether it be physical fitness or training, a warm-up period needs to be observed.

The purpose of the warm-up is to prepare the body for the demands of physical exertion.

The warm-up increases heart rate, blood flow to skeletal muscle and respiration, while at the same time relaxing and increasing the range of motion in the joints and assisting with the mobilization of energy stores.

The net effect is an increased level of performance as well as a decreased risk for injury

INTENSITY

The intensity of the warm-up is measured by two benchmarks.

- Heart rate should be elevated to 100-120 beats per minute.
- A light sweat should be experienced.

Remember the warm-up is designed to prepare the body for physical exertion, not to replace it.

ACTIVITIES

The type of activities performed may vary, but fall into a general category called whole body activities. Whole body denotes that the activities involve the major muscle groups of the body.

Aerobics and calisthenics are excellent example of whole body activities that are familiar to most.

It is also recommended that if possible the activity should mimic the event to follow. For example, before running a good warm-up would be a slow jog.

TIME ALLOTMENT

The warm-up period requires a minimal investment of time, approximately 5-10 minutes.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 602.05 Warm-up

12/2023

Page 1 of 1

Before participating in any physical activity whether it be physical fitness or training, a warm-up period needs to be observed.

The purpose of the warm-up is to prepare the body for the demands of physical exertion.

The warm-up increases heart rate, blood flow to skeletal muscle and respiration, while at the same time relaxing and increasing the range of motion in the joints and assisting with the mobilization of energy stores.

The net effect is an increased level of performance as well as a decreased risk for injury

INTENSITY

The intensity of the warm-up is measured by two benchmarks.

- Heart rate should be elevated to 100-120 beats per minute.
- A light sweat should be experienced.

Remember the warm-up is designed to prepare the body for physical exertion, not to replace it.

ACTIVITIES

The type of activities performed may vary, but fall into a general category called whole body activities. Whole body denotes that the activities involve the major muscle groups of the body.

Aerobics and calisthenics are excellent example of whole body activities that are familiar to most.

It is also recommended that if possible the activity should mimic the event to follow. For example, before running a good warm-up would be a slow jog.

TIME ALLOTMENT

The warm-up period requires a minimal investment of time, approximately 5-10 minutes.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6
Guideline: 602.06 Stretching

12/2023

Page 1 of 1

Stretching exercises must be included in a sound exercise program. Stretching correctly and consistently ensures that full range of motion in the joints is achieved which will enhance performance and reduce risk of injury.

INTENSITY

- **NEVER BOUNCE!** All stretches should be performed in a slow and deliberate manner.
- **NO PAIN!** All stretches should be performed only to a point where a gentle pull is experienced.

ACTIVITIES

The type of stretches performed is dictated by the activity to follow. For example, if the activity is a bench press then stretches for the shoulder joint should be performed.

It is also highly recommended that stretches for the lower back be included in all stretching programs.

TIME ALLOTMENT

Stretching is performed at the end of the warm-up and cool-down periods and requires 5-10 minutes to complete.

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 602.07 Strength and Power

12/2023

Page 1 of 2

Strength and power are often used in the same context, but are quite different. Strength is defined as the maximum ability to apply or to resist a force. This is the ability to lift a maximal weight one time. Power is the ability an individual must utilize strength in relation to time. It is often referred to as explosive strength.

TRAINING

The most common method for increasing levels of strength or power is through a progressive resistance program involving a variety of different equipment. These range from free weights to machines. Because most fire stations contain free weights, this manual will cover their use. The training guidelines presented in this manual are for a basic program. Specific or advanced training questions should be referred to the Wellness Center.

DURATION

Because of concerns with over-training and mental fatigue it is recommended to keep individual workout sessions to less than one hour.

FREQUENCY

Each major muscle group should be worked no more than three times a week and not on consecutive days.

INTENSITY

Between each set, allow ample recovery time, at least two minutes or until you get your wind back.

The optimal number of sets and repetitions vary depending on the program goals, but basically three sets of 6-10 repetitions per body part are considered acceptable.

The weights chosen for each exercise should be as follows:

- First, a determination should be made as to what weight could be lifted for a maximum effort of ten repetitions.
- Once this has been determined, the amount of weight used during the first two sets represents a percentage of the initial maximum weight. For example, a bench press of 100 lb. for a maximum of ten repetitions would use 50% of 100 lb. or 50 lb. for the first set. The weight you would use for your second set would be 75% of 100 lb. or 75 lb. The third set would use 85 to 100 lb.

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 602.07 Strength and Power

12/2023

Page 2 of 2

GENERAL GUIDELINES

- Incorporate basic exercises that work the major muscle group.
- Every exercise should be performed in a strict, slow and deliberate manner if maximal gains are to be achieved without injury. A good rule of thumb is to take two seconds to lift and four seconds to lower.
- Perform all exercises through full range of motion to maintain flexibility and prevent muscle soreness.
- While lifting, or in the positive phase, remember to breathe out. While lowering, or in the negative phase, remember to breathe in. This is important in aiding blood return to the heart.

SUMMARY

Again, this type of strength program is very basic. It is illustrated because it is a basic program from which a solid foundation can be built. It is not the only method one can follow to gain strength; the effectiveness of isometric, eccentric and circuit training has also been proven.

It is not within the scope of this manual to cover the specific characteristics of each, but to make aware that other avenues of training exist for the strength portion of a fitness program.

It is highly recommended that one of the department's personal trainers be consulted for assistance with program design.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 602.08 Cool Down

12/2023

Page 1 of 1

A cool-down period should follow all physical exertion because of its importance in assisting the body in returning to pre-exercise, resting levels and its association with reduced levels of post exercise muscle fatigue and soreness.

INTENSITY

The intensity of the cool-down is a steady decline from exercise levels back to resting levels. Heart rate is the best objective measure and consensus is when heart rate has dropped below 100 beats per minute the cool-down period has been sufficient.

ACTIVITIES

The type of activities performed may vary, but fall into a general category called whole body activities. Whole body denotes that the activities involve the major muscle groups of the body.

Aerobics and calisthenics-are excellent examples of whole body activities that are familiar to most.

It is also recommended that if possible the activity should mimic the event preceding. For example, after running a good cool-down would be a slow jog and then a walk.

TIME ALLOTMENT

The cool-down period requires approximately the same 5-10 minutes as the warm-up period did.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 602.09 Fitness Menu

12/2023

Page 1 of 1

Fitness can be achieved outside the four walls of a gym. Refer to the chart below and discover how activities generally thought of as recreational can be part of a well-rounded program.

Zero= No benefit, Ten= Maximum benefit

Activity	Fun	Upper Body Strength	Lower Body Strength	Aerobic	Flexibility	Agility	Coordination	Calories Burned Per Hour
Basketball	10	6	9	10	5	10	10	480-680
Volleyball	10	5	6	7	5	10	10	300-360
Racquetball	10	4	6	7	5	10	10	480-660
Tennis	10	5	8	8	5	10	10	420-480
Aerobics	10	7	8	10	10	10	0	480-660
Weight-lifting	10	10	10	8	5	6	0	400-500
Soccer	10	4	9	10	5	10	10	480-660
Snow-Skiing	10	5	9	8	5	10	0	400-500
Water-skiing	10	7	9	8	5	10	0	400-500
Golf	10	4	5	4	5	10	10	300-360
Bowling	10	5	5	4	5	10	3	240-300
Cycling 5 mph	10	4	8	7	5	7	0	150-240
Cycling 10mph	10	4	9	9	5	7	0	360-420
Walking 2mph	10	3	6	5	5	5	0	150-240
Jogging 5mph	10	3	7	8	5	6	0	480-600
Running 6-10mph	10	3	9	10	5	6	0	600+
Mtn. Climbing	10	8	10	10	5	7	0	480-600

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6
Guideline: 602.10 Fitness Testing

12/2023

Page 1 of 1

The purpose of this guideline is to ensure that all personnel are accurately fit tested each year for the health and safety of all employees.

Every staff member of the Calimesa Fire Department will be fit tested at the start of their employment and every year on their hire date.

Fit testing is to ensure all employees have a seal while wearing a Self Contained Breathing Apparatus (SCBA).

The company office will complete the Fitness Testing Form (# 402.16) on each employee and this form will be filed in his or her personal record.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6
Guideline: 602.11 Heat Stress Management

12/2023

Page 1 of 1

The purpose of this procedure is to establish guidelines and responsibilities for minimizing the effects of heat stress to department members.

GUIDELINE

The following directives are to be implemented effective June 1st to October 30th of each year or at the discretion of the on-duty Company Officer.

1. Each member will be responsible to:
 - a. Maintain proper rest/nutrition regimen
 - b. Observe appropriate work/rest cycles
 - c. Hydrate before, during, and after each shift (minimize coffee, tea, and cola products)
 - d. Inform supervisor of any ill effects due to heat
2. In addition to the above, Company Officers are responsible for monitoring and managing:
 - a. Cardiovascular activity (i.e., tennis, racquetball, running, etc.) shall be limited to a maximum of 30 minutes
 - b. A minimum of 64 ounces (2 quarts) of fluid should be consumed during the 24 hour shift
 - c. Work/rest cycles, request a relief company and assignment to rehab after crew has consumed two bottles of air
 - d. Company activity and request additional resources as necessary
3. During emergency operations the Incident Commander is responsible for the following:
 - a. Consider the establishment of a Rehab Group on all working fires
 - b. Assign companies to Rehab Group as needed or requested (companies shall remain in rehab for a minimum of 20 minutes)
 - c. Utilize the practice of first company in, first company out routine
 - d. Request additional resources as necessary

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 602.12 Fitness Equipment Inventory and Maintenance

12/2023

Page 1 of 1

This procedure establishes the guidelines for the inventory and maintenance of Fire Department fitness equipment.

INSPECTIONS

Inspections are designed to identify sources of possible injury and prevent injuries associated with the use of Fire Department issued fitness equipment. It is because of this benefit that visual and hands-on inspection of all fitness equipment will be conducted before and immediately after each use. This inspection is informal and completed by station personnel.

MAINTENANCE

Preventive maintenance is conducted on a quarterly basis. The specific schedule for performing the preventive maintenance is left to the discretion of the trained equipment technicians.

INVENTORY

Equipment inventories for each location containing fitness equipment will take place annually.

The equipment officer reviews inventories provided by equipment technicians and updates the inventory spreadsheet.

The hard copy files are purged of the previous year's inventory and replaced with the current inventory.

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 602.13 Fitness Equipment Repairs

12/2023

Page 1 of 1

This Guideline establishes the guidelines for the repair of fitness equipment and the recording of those activities.

REPORTING

All repairs on fitness equipment are to be performed by authorized personnel only.

Fitness equipment in need of repair that may cause a potential safety hazard should be red tagged and placed out of service.

Fitness equipment that needs minor repair and does not represent a hazard should be reported to the On-Duty Captain.

REPAIRS

Repairs are categorized by priority. There are two priority levels.

- Priority 1: repairs represent a safety hazard and cannot be immediately repaired on site, i.e., frayed cable on a lat machine. These repairs must be red tagged and placed out of service (rendered unusable).
- Priority 2: repairs do not represent a safety hazard, but cannot be repaired immediately, i.e., torn upholstery on a bench. These repairs are to be completed within three months.

After receiving the notification of repair request, the Deputy Fire Chief will make the necessary notifications and assignments to ensure their timely completion.

For equipment under warranty, the responsible vendor will be contacted.

Assigned vendor can perform repairs not under warranty.

All repair work must receive pre-authorization from the Fire Chief.

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 602.14 Health and Safety Officer

12/2023

Page 1 of 4

It is the policy of the Calimesa Fire Department to provide the highest level of safety and health for all members. The Department shall make every reasonable effort to provide a safe and healthy work environment, with the goal of the prevention and reduction of accidents, injuries and occupational illnesses. Appropriate training, supervision, procedures, program support and review shall be provided to achieve specific safety and health objectives in all functions and activities.

HEALTH AND SAFETY OFFICER

- A. A Health and Safety Officer shall be appointed, and will be responsible for managing the Departments Safety Program and shall report to the Fire Chief or his designee.
- B. The Health and Safety Officer duties shall include, but not be limited to:
 - 1. Chair the Safety Committee by preparing meeting agendas and notices;
 - 2. Act as the Incident Safety Officer at incidents, if needed;
 - 3. Provide input on equipment and protective clothing safety;
 - 4. Manage the safety inspection program;
 - 5. Assist with the investigation of all accidents, injuries and exposures;
 - 6. Maintain accident, injury and exposure statistics;
 - 7. Make recommendations to reduce or eliminate accidents, injuries or exposures;
 - 8. Provide for safety education to all Department members.
- C. The Health and Safety Officer qualifications;
 - 1. The Health and Safety Officer will have and maintain knowledge of current applicable laws, codes and standards regulating occupational safety and health to the fire service;
 - 2. The Health and Safety Officer will have and maintain knowledge of occupational safety and health hazards involved in emergency operations;
 - 3. The Health and Safety Officer will have and maintain knowledge of current principles and techniques of safety management;
 - 4. The Health and Safety Officer will have and maintain knowledge of current health maintenance and physical fitness issues that affect the fire service members;
- D. The Health and Safety Officer will have the responsibility to identify and cause correction of safety and health hazards.
- E. The Health and Safety Officer will have the authority to cause immediate correction of situations that create an imminent hazard to members.
- F. Where no imminent hazards are identified, the Health and Safety Officer shall develop actions to correct the situation within the administrative process of the Department. The Health and Safety Officer shall have the authority to bring notice of such hazards to whom ever has the ability to cause correction.

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 602.14 Health and Safety Officer

12/2023

Page 2 of 4

- G. Functions of the Health and Safety Office will include, but not be limited to:
1. Development, implementation, and management of a written risk management plan;
 2. Development, review and revision of rules, regulations and standard operating procedures pertaining to the Department occupational safety and health program and that ensure compliance to acceptable standards;
 3. Ensure training in safety procedures relating to all Department operations and functions is provided to all members;
 4. Manage an accident prevention program;
 5. Review specifications for new apparatus, equipment, protective clothing and protective equipment for compliance with applicable safety standards
 6. Submit recommendations on occupational safety and health to the Fire Chief or his designee;
 7. Ensure that the Departments infection control program meets or exceeds the requirements of 29CFR1910.1030, Occupational Exposure to Blood borne Pathogens (Refer to Policy# 301.18)
 8. Establish a critical incident stress management program.

INCIDENT SAFETY OFFICER

- A. An Incident Safety Officer should meet the following requirements:
1. Will have the knowledge, skill and ability to manage incident scene safety;
 2. Will have and maintain knowledge of safety and health hazards involved in emergency operations;
 3. Will have and maintain knowledge of building construction;
 4. Will have and maintain knowledge of the Departments Personnel Accountability System;
 5. Will have and maintain knowledge of incident scene rehabilitation.
- B. The Incident Safety Officer will have the authority at an emergency incident where activities are judged by the Officer to be unsafe or to involve an imminent hazard, have the authority to alter, suspend, or terminate those activities. The Incident Safety Officer will immediately inform the Incident Commander of any actions taken to correct imminent hazards at the emergency scene.
- C. At an emergency incident where an Incident Safety Officer identifies unsafe conditions, operations, or hazards that do not present an imminent danger, the Incident Safety Officer shall take appropriate action through the Incident Commander to mitigate or eliminate the unsafe condition, operation, or hazard at the incident scene.
- D. Functions of the Incident Safety Officer will include, but not be limited to:
1. Be integrated with the incident management system as a command staff member

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 602.14 Health and Safety Officer

12/2023

Page 3 of 4

2. Shall monitor conditions, activities and operations to determine whether they fall within the criteria as defined in the Departments risk management plan
3. Will ensure that the Incident Commander establishes an incident scene rehabilitation tactical level management unit during emergency operations
4. Will monitor the scene and report the status of conditions, hazards and risks to the Incident Commander
5. Will ensure that the Departments Personnel Accountability System is being utilized
6. Will obtain the incident action plan from the Incident Commander and will provide the Incident Commander with a risk assessment of incident scene operations
7. Ensure that established safety zones, collapse zones, hot zone and other designated hazard areas are communicated to all members present on scene
8. Will evaluate motor vehicle scene traffic hazards and apparatus placement and take appropriate actions to mitigate hazards
9. Monitor radio transmissions and stay alert to transmission barriers that could result in missed, unclear or incomplete communication
10. Survey and evaluate the hazards associated with the designation of a landing zone and interface with helicopters
11. Shall ensure that a Rapid Intervention Team is available and ready for deployment
12. Where a fire has involved a building or buildings, shall advise the Incident Commander of hazards, potential collapse and any fire extension in such building(s)
13. Will evaluate visible smoke and fire conditions and advise the Incident Commander, tactical level management unit officers and company officers on the potential for flashover, backdraft, blow-up or other fire event that could pose a threat to operating teams
14. Monitor accessibility of entry and egress of structures and the effect it has on the safety of members conducting interior operations
15. Assist with safety management of Hazardous Materials events

HEALTH AND SAFETY COMMITTEE

- A. The Health and Safety Committee will provide policy guidance pertaining to health and safety issues.
- B. The Health and Safety Officer shall report bi-annually to the Health and Safety Committee on the impact and implementation of the Safety Program and on the effectiveness of any specific program actions.
- C. The Health and Safety Committee will also act as a fact-finding and review entity with the authority to cause immediate corrective action when any hazardous condition or practice is detected or reported.

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 602.14 Health and Safety Officer

12/2023

Page 4 of 4

D. The Health and Safety Committee will:

1. Meet at least bi-annually to review safety issues and concerns;
2. Review effectiveness of safety activities;
3. Develop and implement safety procedures;
4. Make a written record of its meetings available to all fire fighters in the fire department.

E. The Health and Safety Committee may include:

1. Fire Chief
2. Deputy Fire Chief
3. Department Training Officer
4. Health and Safety Officer
5. Firefighters

INJURY AND ILLNESS REPORTING

If any member suffers an injury or illness, as a result of his or her duties while serving as a member of the Calimesa Fire Department, the provisions of the Worker's Compensation Act may cover his/her medical expenses. An injured or ill member must immediately notify his/her Commanding Officer or Fire Chief of the injury/illness and incident and complete appropriate paperwork.

- **602.00 – Health and Fitness - Volume. 6**

- 602.01 Lifestyle Approach
- 602.02 Overview Exercise Basics
- 602.03 Overview Fitness Program Design
- 602.04 Over-Training
- 602.05 Warm-up
- 602.06 Stretching
- 602.07 Strength and Power
- 602.08 Cool Down
- 602.09 Fitness Menu

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 603.00 Annual Preventive Maintenance/Calibration

12/2023

Page 1 of 1

- **603.00 – Annual Preventative Maintenance/Calibrations**

- 603.01 SCBA Program Manager
- 603.02 Annual SCBA Bench Test
- 603.03 SCBA Compressor Service - Air Quality Test
- 603.04 FIT Test Machine Calibration
- 603.05 Annual NFPA Pump Test
- 603.06 Annual NFPA Ladder Test
- 603.07 Annual NFPA Hose Test
- 603.08 NFPA 1851 – PPE Inspections
- 603.09 Annual Calibration – Hot Stick
- 603.10 Four Gas (4) Monitor Calibration
- 603.11 Extrication Equipment – Power

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 603.01 SCBA Program Manager

01/2024

Page 1 of 1

SCOPE

The purpose of the Self-Contained Breathing Apparatus (SCBA) Program Manager is to establish a system of oversight to regularly inspect, repair, replace respiratory protective equipment assigned to its members, and to set standards for the maintenance of these items.

The SCBA Program Manager shall be assigned as an ancillary duty to a Battalion Chief or Fire Captain. The program manager may designate “coordinators” as needed, to designate authority to complete maintenance task and records management needs, however the Manager shall be responsible for all compliance mandates.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6
Guideline: 603.02 Annual SCBA Flow Test

1/2024

Page 1 of 1

SCOPE

The City of Calimesa Fire Department SCBA program Manager shall maintain a master inventory and coordinate and document all devices or appliances associated with the Respiratory Protection Plan placed into service for use in IDLH environments.

Annual Flow Test shall be coordinated by qualified technicians as recommended by the manufacturer and or NFPA/OSHA guidelines (NFPA 1989) and documented and maintained in the appropriate records management system as directed by the Fire Chief or Department Safety Officer.

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 603.03 SCBA Compressor Service – Air Quality Test

1/2024

Page 1 of 1

SCOPE

The purpose of this policy is to establish a system of oversight to regularly inspect, repair, replace respiratory protective equipment assigned to its members, and to set standards for the maintenance of these items to include annual service, routine repairs or replacement of components as deemed necessary to ensure compliance with the required annual or quarterly maintenance of SCBA Compressor(s) and or fill stations, placed into service by the City of Calimesa Fire Department. (NFPA 1989)

The Facilities and Grounds Manager shall oversee the use, training, maintenance, and documentation via the appropriate records management system for any required repair, service, or replacement of components. Additionally, the facilities and grounds manager shall coordinate all mandated Air Quality Testing requirements as stipulated by manufacturer, NFPA, or OSHA guidelines. (March/June/September/December)

The Facilities and Grounds Manager shall ensure all required reporting and documentation are entered into the appropriate records management system and communicated to the SCBA Program Manager, Department Safety Officer, and Fire Chief.

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 603.04 Annual Fit Test Monitor Calibration

1/2024

Page 1 of 1

SCOPE

The purpose of this policy is to establish a system of oversight to regularly inspect, repair, replace respiratory protective equipment assigned to its members, and to set standards for the maintenance of these items to include annual service, routine repairs or replacement of components as deemed necessary to ensure compliance with the required annual inspection guidelines.

The Facilities and Grounds Manager shall oversee the use, training, maintenance, and documentation via the appropriate records management system for any required repair, service, or replacement of components. Additionally, the facilities and grounds manager shall coordinate all mandated calibration requirements as stipulated by the manufacturer, NFPA, or OSHA guidelines. (OSHA Standard 1910.134)

The Facilities and Grounds Manager shall ensure all required reporting and documentation are entered into the appropriate records management system and communicated to the SCBA Program Manager, Department Safety Officer, and Fire Chief.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6
Guideline: 603.05 Pump Testing

01/2024

Page 1 of 3

I PURPOSE

The purpose of this procedure is to provide an annual check standard for yearly pump testing.

II POLICY

All fire pumpers will be put through an annual pump test. This guideline is to provide an annual check standard and procedure for department operators in accordance with NFPA 1911.

III PROCEDURE

A. Dry Vacuum Test

1. With all discharge valves closed and uncapped, the primer pump must be able to pull a minimum of 22" of mercury.
2. The pump must hold a vacuum for 5 minutes and not lose more than 10" of mercury in that 5-minute time limit.
3. This test must be done with a hand-held vacuum gauge plumbed into the suction service port on the pump panel, not the compound gauge on the pump panel.
4. If the pump does not pass this test, all leaks must be repaired and pass the dry vacuum test before proceeding with the pump test. The results of this test will be noted on the pump test sheet.

B. Pump Test

1. All 750 – 1250 GPM pumps will be pump tested with 3 – 100' 2 ½" hose lays.
2. Mark hose at the coupling for movement; inspect throughout the test for movement.
3. All 750 – 1250 GPM pumps must pull a draft in 30 seconds or less.
4. A 1500 GPM pump must pull a draft in 45 seconds or less through a 20" section of hard suction hose with no more than 10" of lift. This time will be noted on the pump test form.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 603.05 Pump Testing

01/2024

Page 2 of 3

5. A portable monitor may be used to perform the pump test, but a stationary collector is preferred. Also, we recommend using a screw on pitot tip rather than a hand held one. This will give a more accurate reading and is much safer.
6. The pump will be put through 3 tests for a total of 40 minutes. Once the test is started, the pump should not be stopped except to change nozzle tips.
7. The first test is 100% of rated capacity and 150 psi for 20 minutes.
8. The second test is 70% of rated capacity at 200 psi for 10 minutes.
9. The third test is 50% of rated capacity at 250 psi for 10 minutes.
10. The pump does not need to pass the spurt test, or overload test (for information purposes only).
 - a) This test is 10% overload test and 100% of rated capacity.
 - b) The pump will be set to 165 psi.
 - c) This test will identify wear in the pump or a worn-out engine while performing the pump test.
11. Readings to the following will be noted on the pump test sheet every (5) minutes.
 - a) Time
 - b) Gauge pressure
 - c) Pitot pressure
 - d) Vacuum reading (off handheld gauge)
 - e) RPM
 - f) Oil pressure
 - g) Water temperature
12. Stop test if:
 - a) Engine overheats
 - b) Loss of oil pressure
13. Water Governor
 - a) The water governor or pressure relief valve will be tested 3 times throughout the pump test without the pressure changing +/- 30psi from flow to no flow.
 - b) Set up and operate the water governor or pressure relief valve according to manufacturer's directions.
 - c) Any one discharge valve being closed will not be closed faster than 5 seconds to prevent water spikes.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 603.05 Pump Testing

01/2024

Page 3 of 3

14. After 100% Test Completed
 - a) FIRST WATER GOVERNOR TEST.
Test the water governor, or relief valve at 150 psi.
 - b) SECOND WATER GOVERNOR TEST
 - (1) Test re-open all discharge that were required at 100% rated capacity.
 - (2) Drop pressure to 90 psi and test governor/relief at this pressure.
 - c) THIRD WATER GOVERNOR TEST
The third will be performed after the 50% rated capacity test at 250 psi.
15. To obtain the proper nozzle size and pitot pressure, use the reference guide. It is rated with the western flow kit.
16. If another brand of flow kit is used:
 - a) The nozzle will be the same
 - b) The GPM may differ slightly
 - c) Check the manufacturer flow chart to be sure
17. The pump sheet should be
 - a) Filled out completely
 - b) Kept in the Department files for ISO inspections.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 603.07 Ladder Testing

1/2024

Page 1 of 6

Ground Ladder Maintenance/Repair/Testing

I PURPOSE

The purpose of this procedure is to provide monthly check standards for routine maintenance and procedures for each check standard, along with annual testing procedures.

II POLICY

To comply with Cal-OSHA and NFPA, ground ladders are required to be inspected monthly to ensure the ladder is safe and ready to use. If discrepancies are noted, only certified personnel should repair ground ladders. Ground ladders also must be tested annually as described in this Operating Procedure. This Operating Procedure will serve as a guideline to assist station personnel in knowing how to inspect the ground ladders, what maintenance is required and how the testing will be performed. A certified, trained person, recognized by the department to do such testing, will perform the annual testing.

III PROCEDURE

Ladders – Care and Maintenance (NFPA 1932)

A. After Use

1. Cleaning Ground Ladders
 - a) Clean water and a dry cloth are all that is needed in most cases. Water and mild soap may be used to remove grease and dirt.
2. Inspecting Ground Ladders
 - a) Visually, to see if ladder has been damaged.
 - b) If subjected to heat, check heat sensor labels inside of rails. (Sensors will turn black)

B. Inspection of ground ladders – Monthly

1. Taken off apparatus and clean (any car wax is a suitable surface restorer)
2. Visual Inspection
 - a) A visual inspection shall include, but not be limited to, the following:
 - (1) Check heat sensor labels on metal ladders for a change indicating heat exposure.
 - (2) Electrical hazards warning label (Outside of beam)
 - (3) Ladder positioning label (Outside of beam)
 - (4) Length of ladder label (Butt of ladder)
 - (5) All rungs, for snugness, tightness, dents, and wear spots
 - (6) All bolts and rivets for tightness

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 603.07 Ladder Testing

1/2024

Page 2 of 6

- (7) Welds, for any cracks or apparent defects
- (8) Beams and rungs, for cracks, splintering, breaks, gouges, checks, wavy conditions, or deformation.
- (9) Butt spurs, for excessive wear or other defects
- (10) Halyards, for fraying or kinking
- (11) Roof hooks for sharpness and proper operation
- (12) Rungs, for punctures, wavy conditions, worn serrations, or deformation.
- (13) Surface corrosion
- (14) Ladder slide areas, for galling or absence of wax, if required by the manufacturer
- (15) Proper operation of the pawl assemblies
- (16) Wire rope on 3- and 4- section ladders for snugness when the ladder is in the bedded position, to ensure proper synchronization of upper sections during operation

Any signs of damage or defect during a visual inspection shall be cause to remove the ground ladder for service until it has been repaired for fire service use or until it is destroyed. Scratches and dents shall not be cause to fail a ladder if it masses the appropriate load test.

3. Lubrication

- a) Wax all moving parts of ladder (wherever surfaces rub together)
- b) Candle wax – this wax coats and works into the pores of the ladder material and does not easily wash away with frequent washing the engine.
- c) Testing Requirements – NFPA 1931 and 1932
 - (1) Personnel involved in service testing shall be completely trained in the service testing procedures and equipment. Personnel shall be fully cognizant at all times of the possibility of sudden and dramatic failure of the ground ladder undergoing service testing and shall take all personal safety precautions possible to protect themselves.
 - (a) Department personnel that are assigned as coordinating repairs and testing but be certified by the ladder manufacturer to do such repairs and testing.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 603.07 Ladder Testing

1/2024

Page 3 of 6

Personnel assisting with the repair and testing must work under direct supervision of the certified person.

(b) If repairs or testing are contracted out, the ladder manufacturer must certify the contract vendor.

(2) All ground ladders shall be service tested on the following schedule:

(a) Before the ladder is placed in service for the first time

(b) At least annually

(c) At any time, the ladder is suspected of being unsafe.

(d) After the ladder has been subjected to overloading

(e) After the ladder has been subjected to impact loading or unusual conditions of use

(f) After heat exposure

(g) After any repairs have been completed, unless the only repair was replacing the halyard

4. Documents

The person performing all repairs and testing will complete the approved work order of all repairs completed to the ladder. The work order will need to include all tests with the test results of each ladder.

a) The work order will include:

(1) Ladder inventory number

(2) Manufacturers name, serial number and model number

(3) All parts used

(4) All repairs completed

(5) Date ladder put into service

(6) Date of test/repair

(7) Type of ladder

(8) Length

(9) Heat sensor label check – Must have

(10) Horizontal test – Pass/Fail

(11) Hardware Test – Pass/Fail

(12) Horizontal Load Test

b) Record Keeping

All monthly maintenance and inspections of the ground ladders shall be performed as outlined in the Operating Procedure. The

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 603.07 Ladder Testing

1/2024

Page 4 of 6

maintenance and inspections shall be listed in the Vehicle Maintenance Logbook.

- c) Station
 - (1) A copy of all repairs and testing will be kept at the station in a separate file marked “Ladder Repairs and Testing”.
- d) Repair/Tester
 - (1) The personnel implementing the repairs and testing will keep a copy in a file marked “Ladder Repairs and Testing”.
- e) Vehicle Services
 - (1) Vehicle services shall keep a master file of all repairs and testing of all ladders being repaired and tested marked the same. The Repair/Tester personnel will be responsible to forward the documentation to Vehicle Services.
- f) Ladder Marking
 - (1) Each ground ladder will receive an inventory number for tracking. The number will be marked with a paint marker on both outer rails at the foot of the ladder. This will allow the inventory number to be viewed while mounted on the apparatus.
 - (2) New ladders
 - (a) All ladders must be marked with the appropriate inventory number before being placed in service.
 - (3) Used Ladders
 - (a) As repairs and/or testing are performed, each ladder shall be checked for inventory numbers. If the inventory number is missing or needs to be remarked, the repair/testing personnel shall ensure the ladder is marked with the proper inventory number before the ladder is placed back in service.
- g) Annual Testing
 - (1) Each ladder is to be tested annually as outlined in this directive.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6
Guideline: 603.07 Ladder Testing

1/2024

Page 5 of 6

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6
Guideline: 603.07 Ladder Testing

1/2024

Page 6 of 6

Station: _____

Date: _____ (Work Completed)

Inventory #: _____

Date: _____ (Ladder put into service)

Make: _____ Model: _____

Type: _____ Length: _____ Serial #: _____

Heat sensor check (Must have) Y N (Circle)

Horizontal Test: PASS FAIL

Hard ward Test : PASS FAIL

Horizontal Test: PASS FAIL

The listed ladder has been repaired and tested and is in good condition to return to service.

Signature: _____

****If ladder does not pass test, refer to Equipment/Repair order form***

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 604.02 Annual Hose Testing

1/2024

Page 1 of 3

I. PURPOSE

The purpose of this procedure is to provide a standard for care and maintenance of fire hose in accordance to NFPA 1962.

II. POLICY

Care and maintenance of the fire hose shall be in accordance with the most current edition of the NFPA 1962. This policy shall include department specific tasks for care, maintenance, and record keeping of the hose. The Department shall not use the recommended testing pressures when conducting the annual test. Pressure testing shall be performed as listed in this directive.

III. PROCEDURE

A) General Use/Operations

- 1) Hose shall not be in hose clamps for extended periods of time unless absolutely necessary.
- 2) Cribbing should be used as chaffing blocks and crossovers whenever possible.
- 3) Take care when taking hose aloft, over fences, etc. should be exercised, and use a hose roller whenever possible (Doesn't make sense)
- 4) All hoses shall be re-tested before being put back into service. If for any reason the hose is suspected of having:
 - (a) Excessive wear
 - (b) Abusive Handling
 - (c) Exposure to chemicals
 - (d) Exposure to gasses

B) After Use

- 1) Hose shall be cleaned of all foreign matter.
- 2) Clean water (under pressure) and brushing is all that is needed in most instances.
- 3) When the outer jacket has been in contact with hydrocarbons, chemicals and/or the like, use of mild detergent or soap may be necessary, followed by rinsing with clean water.
- 4) Any hose used to discharge any type of foam solution or gel shall be flushed with fresh water immediately after use.
- 5) Use of oil or grease on threads is prohibited.
- 6) Silicone or graphite may be used on threads.
- 7) Current hose is constructed of synthetic material which is resistant to mold and mildew, it is best, when allowable, to dry hose prior to rolling or reloading.

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 604.02 Annual Hose Testing

1/2024

Page 2 of 3

C) Testing

- 1) All new hoses should be tested within 90 days of arrival to the station or facility. All hoses shall be tested annually thereafter with testing to be completed by a specified date.
- 2) Prior to testing, the hose shall be marked along the edge of the female coupling using a permanent marker to check for expansion after testing is complete.
- 3) Hose test procedures are as follows:
 - (a) Hose lengths should not exceed 300ft in length.
 - (b) Double jacketed 1.5", 1.75", 2.5", and 4" diameter hose shall be tested at 250 psi for 5 minutes?
 - (c) Single jacketed 1.5" wildland hose tested at 200 psi for 5 minutes.
- 4) After testing, hose shall be marked with the year it was tested.

D) Hose Marking

- 1) All double jacket hoses will be marked and numbered utilizing our proper numbering system.
- 2) If the hose is already marked with an inventory number, that hose will keep that number for the remainder of the life of that specific hose.

E) Hose Repair

- 1) Hoses that do not pass the hose test will be placed out of service.
- 2) Equipment/Repair form shall be filled out with the following information:
 - (a) Station number and shift requesting repair
 - (b) Hose I.D. number (Inventory number)
 - (c) Size of hose and length
 - (d) Description of the problem
 - (e) Place an "X" over the problem area and mark with a red "Out of Service" tag
- 3) Damaged hoses must be cleaned prior to being submitted for repair

F) Documentation

- 1) The assigned company officer will complete the Annual Hose Testing Log Sheet and forward to the Battalion Chief to be properly inventoried. Hose testing records must be kept for 3 years at the station level and 10 years at the management level. Old records may be destroyed after the last retention year has been met.

G) Responsibility

- 1) It is the responsibility of the company officer to ensure care, maintenance, and testing and record keeping is completed as scheduled.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 604.02 Annual Hose Testing

1/2024

Page 3 of 3

- 2) It is the responsibility of the company officer to track hose left on scene and forward that information to the assigned Battalion Chief. It is the responsibility of the Battalion Chief to ensure the proper documents and approvals have been provided and plan for the delivery of a replacement hose.

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 603.08 NFPA 1851 - Protective Clothing Inspection Program

1/2024

Page 1 of 4

It is the guideline of the Calimesa Fire Department to provide its members with protective clothing and equipment to safeguard them from injury when involved in Fire Department activity. The protective clothing and equipment shall be appropriate for the various activities and services the Fire Department members may provide.

Effective January 2024, The City of Calimesa Fire Department shall follow the guidelines set forth and consistent with the requirements of NFPA 1851. The Departments Inventory Control Manager/Coordinator, Safety Officer, Disease Infection Control Officer, shall coordinate efforts to implement required decontamination, inspection, and RMS documentation. The Department Facilities and Grounds Manager shall oversee the use, maintenance, and training regarding the utilization of fixed on-site decontamination equipment such as PPE extractors and dryers.

This inspection is intended to assure that all personnel are provided with a complete set of protective clothing and equipment, maintained in safe and functional condition. Along with the inspection the company will fill out the Protective Clothing Inspection Form. (Form #402.15)

Protective clothing inspections will use the following inspection criteria to evaluate the condition of protective clothing. Each item will be rated in at least one of the five categories:

- Satisfactory
- Clean
- Repair
- Replace
- Missing Item

The company officers are responsible for the management of protective clothing and equipment inspections and adherence to requirements in their designated shift.

The company officer shall verify the proper fit of turnout coats and pants while the clothing is actually being worn by the firefighter when conducting the inspection. Protective hoods shall be inspected with SCBA facepiece in place and hood on to verify proper fit and coverage of all facial and neck skin surfaces.

Each member of the Fire Department is responsible for inspecting his/her protective clothing daily, as well as for the cleaning, care and maintenance of all issued protective equipment. The individual

- c. Helmet that is warped or bubbled from exposure to heat.
- d. Helmet that has been exposed to mist or fumes which are known to weaken polycarbonates.

NOTE: All items constructed from thermoplastics are susceptible to ultraviolet and chemical degradation. When the helmet loses its surface gloss and the surface begins to flake away, this chemical degradation has occurred. During inspections, helmets will be checked for these conditions and the shell will be replaced immediately if they are evident.

PROTECTIVE HOOD

- 1. Cleaning:
 - a. Use warm water and any mild detergent.
- 2. Replace:
 - a. Hoods that have holes or tears in them.
 - b. Hoods that are not Fire Department approved.
 - c. Hoods stretched out of shape and/or do not provide coverage of all face or neck skin surfaces.
 - d. Hoods that have burn discoloration.

PERSONAL IDENTIFICATION NAME TAGS

The personal identification nametag will be checked. Obtain or replace missing or damaged nametags. Five tags per firefighter are required.

GLOVES

- 1. Cleaning:
 - a. Use warm water and mild detergent.
- 2. Replace:
 - a. Stiff or rigid gloves.
 - b. Stitching worn or rotten.
 - c. Glove insulation is worn through.
 - d. Leather split.
 - e. Gloves with holes or tears in them.
 - f. Gloves that do not fit properly.
 - g. Gloves that are not Fire Department approved.

TURNOUT COAT & PANTS

- 1. Cleaning:
 - a. Liners and shell can be washed with mild detergent.
 - b. Heavily soiled spots can be removed with general spot cleaners.
- 2. Repairs:

- a. All repairs requiring stitching must be made with Nomex thread by a vender.
 - b. Rivets pulled loose from fabric and from the objects they secure.
 - c. Suspenders, snaps, and leather eyes that are broken or elongated.
 - d. Stitching missing.
 - e. Holes or rips in shell of garment.
 - f. Frayed or worn collars.
 - g. Ripped liners.
 - h. Reflective stripes that are burned cracked, melted or torn.
 - i. Wristlets that are torn or stretched.
3. Replace:
- a. Coats and pants on which the stitching is damaged beyond repair.
 - b. Coats and pants on which the fabric is worn through.
 - c. Coats and pants soiled to the point they cannot be cleaned, or saturated with oil, tar, etc.
 - d. Coats with charring or evidence of other fire damage.
 - e. Improper fitting coats - i.e. sleeves too short.

BOOTS

Inspect the rubber boots that are part of the turnout pants.

Replace:

1. Boots that are severely cracked.
2. Boots with any holes in them.
3. Improper fitting boots.
4. Obvious excessive tread wear.

FLASHLIGHT

Each firefighter's flashlight shall be checked for operation. Flashlights that do not work will be replaced or repa

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 603.09 Bi- Annual Hot Stick Calibration

1/2024

Page 1 of 1

SCOPE

The purpose of this policy is to establish a system of oversight to regularly inspect, repair, replace life safety monitoring/detection equipment assigned to its members, and to set standards for the maintenance of these items to include annual service, routine repairs or replacement of components as deemed necessary to ensure compliance with the required annual inspection guidelines.

The Department Apparatus/ Equipment Inventory Manager shall oversee the use, training, maintenance, and documentation via the appropriate records management system for any required repair, service, or replacement of components.

Additionally, the Apparatus/Equipment Manager shall coordinate all mandated calibration requirements as stipulated by the manufacturer, NFPA, or OSHA guidelines. (NFPA 1926.957)

The Apparatus/Equipment Inventory Officer shall ensure all required maintenance, repair and or training documentation is entered into the appropriate records management system and communicated to the Department Safety Officer, and Fire Chief.

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 603.10 Four Gas Monitor Calibration

1/2024

Page 1 of 1

SCOPE

The purpose of this policy is to establish a system of oversight to regularly inspect, repair, replace life safety monitoring/detection equipment assigned to its members, and to set standards for the maintenance of these items to include annual service, routine repairs or replacement of components as deemed necessary to ensure compliance with the required daily, monthly and annual inspection/calibration guidelines for the use of Four (4) Gas-Monitors.

The Department Apparatus/ Equipment Inventory Manager shall oversee the use, training, maintenance, and documentation via the appropriate records management system for any required repair, service, or replacement of components.

Additionally, the Apparatus/Equipment Manager shall coordinate all mandated calibration requirements as stipulated by the manufacturer, NFPA, or OSHA guidelines. (NFPA 12, OSHA 1910.120)

The Apparatus/Equipment Inventory Officer shall ensure all required maintenance, repair and or training documentation is entered into the appropriate records management system and communicated to the Department Safety Officer, and Fire Chief.

- Daily Function Test – Bump Test: Document RMS
- Fresh Air Calibration before & after use (Monthly Calibration) Document RMS
- Annual Inspection Calibration – Document RMS

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 603.11 Extrication Equipment Inspection - Power

1/2024

Page 1 of 1

SCOPE

The purpose of this policy is to establish a system of oversight to regularly inspect, repair, replace life safety monitoring/detection equipment assigned to its members, and to set standards for the maintenance of these items to include annual service, routine repairs or replacement of components as deemed necessary to ensure compliance with the required daily, monthly and annual inspection/calibration guidelines for the use of Four (4) Gas-Monitors.

The Department Apparatus/ Equipment Inventory Manager shall oversee the use, training, maintenance, and documentation via the appropriate records management system for any required repair, service, or replacement of components.

Additionally, the Apparatus/Equipment Manager shall coordinate all mandated calibration requirements as stipulated by the manufacturer, NFPA, or OSHA guidelines. (NFPA 12, OSHA 1910.120)

The Apparatus/Equipment Inventory Officer shall ensure all required maintenance, repair and or training documentation is entered into the appropriate records management system and communicated to the Department Safety Officer, and Fire Chief.

- Daily Function Test – Bump Test: Document RMS
- Fresh Air Calibration before & after use (Monthly Calibration) Document RMS
- Annual Inspection Calibration – Document RMS

Standard Operating Policies – Standard Operating Guidelines
Concise Table of Content – Volume 6
Apparatus Operations – 604.00

- **604.00 – Apparatus Operations – Volume 6**

- 604.01 Apparatus Program Manager
- 604.02 Apparatus Operations
- 604.03 Vehicle Operation
- 604.04 Code 3 Driving
- 604.05 Mandatory seatbelt guideline
- 604.06 Backing Hand Signals
- 604.07 Apparatus Placement
- 604.08 Unattended Apparatus
- 604.09 Apparatus Inspections

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 604.01 Apparatus Program Manager

1/2024

Page 1 of 1

SCOPE

The purpose of the Apparatus Program Manager is to establish a system of oversight to regularly inspect, repair, replace, train and maintain the various types and classification of all vehicle/automotive “rolling stock,” inventory and all closely related equipment, and or programs assigned to its members, and to set standards for the maintenance and records keeping of these items.

The Apparatus Program Manager shall be assigned as an ancillary duty to a Battalion Chief or Fire Captain. The program manager may designate “coordinators” as needed, to designate authority to complete maintenance task and records management needs, however the Manager shall be responsible for all compliance mandates.

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 604.01 Apparatus Program Manager

1/2024

Page 1 of 1

SCOPE

The purpose of the Apparatus Program Manager is to establish a system of oversight to regularly inspect, repair, replace, train and maintain the various types and classification of all vehicle/automotive “rolling stock,” inventory and all closely related equipment, and or programs assigned to its members, and to set standards for the maintenance and records keeping of these items.

The Apparatus Program Manager shall be assigned as an ancillary duty to a Battalion Chief or Fire Captain. The program manager may designate “coordinators” as needed, to designate authority to complete maintenance task and records management needs, however the Manager shall be responsible for all compliance mandates.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6
Guideline: 604.02 Apparatus Operations

1/2024

Page 1 of 1

The Apparatus Operations Guideline is to provide procedure for safe apparatus operations in conjunction with the California Vehicle Code.

STANDARD

1. Drivers shall exercise prudent and reasonable caution while operating Fire Department apparatus during routine and emergency operations.
2. Captains operating the apparatus will do a full walk around before the apparatus is moved.
3. Personnel shall wear full protective clothing, intercom headsets without helmets when responding to all fire incidents, traffic accidents and hazardous material incidents.
4. All vehicle occupants shall wear seat belts.
5. Drivers shall not exceed speeds commensurate with good safety practices due to weather, traffic, street or other conditions.
6. Drivers shall have their vehicles under control at all times and be prepared to stop.
7. Drivers shall be highly sensitive to the hazards and exercise extreme caution negotiating intersections during emergency response.
8. Apparatus shall not be driven against opposing traffic unless traffic is controlled.
9. Drivers shall exercise extreme caution when committing vehicles off pavement. Do not attempt to extricate stuck vehicles under their own power.
10. Drivers are to avoid utilizing private driveways unless it is the most prudent option to mitigate the situation.
11. Drivers involved in an accident shall adhere to the Vehicle Accident Reporting Policy (Policy# 204.03).
12. Drivers backing apparatus shall utilize a guide person positioned at the rear of the apparatus to facilitate backing directions. If the driver loses sight of the guide person, he shall stop the apparatus until visual contact is reestablished.
13. Personnel will be held directly responsible for misuse, negligent, or unsafe operations of any apparatus/equipment.

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 604.03 Vehicle Operations

1/2024

Page 1 of 1

The purpose of the Vehicle Operations Guideline is to provide procedure for safe vehicle operations in conjunction with the California Vehicle Code.

STANDARD

1. Drivers shall exercise prudent and reasonable caution while operating Fire Department vehicles during routine and emergency operations.
2. The assigned driver of apparatus or staff vehicles shall be responsible for the vehicle's operational readiness, inventory and maintenance.
3. Personnel shall wear full protective clothing, intercom headsets without helmets when responding to all fire incidents, traffic accidents and hazardous material incidents.
4. All vehicle occupants shall wear seat belts.
5. Drivers shall not exceed speeds commensurate with good safety practices due to weather, traffic, street or other conditions.
6. Drivers shall have their vehicles under control at all times and be prepared to stop.
7. Drivers shall be highly sensitive to the hazards and exercise extreme caution negotiating intersections during emergency response.
8. Apparatus shall not be driven against opposing traffic unless traffic is controlled.
9. Drivers shall exercise extreme caution when committing vehicles off pavement. Do not attempt to extricate stuck vehicles under their own power.
10. Drivers are to avoid utilizing private driveways unless it is the most prudent option to mitigate the situation.
11. Drivers involved in an accident shall adhere to the Traffic Accident Policy. (# 204.03)
12. Drivers backing apparatus shall utilize a guide person positioned at the rear of the apparatus to facilitate backing directions. If the driver loses sight of the guide person, he shall stop the apparatus until visual contact is reestablished.
13. Personnel will be held directly responsible for misuse, negligent, or unsafe operations of any apparatus/equipment.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 604.04 Code 3 Driving

1/2024

Page 1 of 5

To identify that all drivers and operators of fire department vehicles shall drive in a deliberate and responsible manner and shall adhere to the principle of the Basic Speed Law with due regard for the safety of all persons and property.

Drivers are to pay constant attention to visibility, vehicle stability and control, weather, road conditions and hazards as well as traffic volume and congestion when determining vehicle speed.

GENERAL GUIDELINES

Drivers of fire department vehicles bear the ultimate responsibility for the proper operation of a department vehicle. Each driver shall drive with due regard for the safety of all persons using the highway. Each driver must follow the California Vehicle Code when operating a department vehicle except as authorized when driving Code 3.

All individuals are required to wear seat belts and/or shoulder harnesses at all times when driving or riding in fire department vehicles. Drivers are responsible for the proper seating and fastening of the passengers prior to moving the vehicle.

BASIC SPEED LAW

Section 22350 of the California Vehicle Code states: “No person shall drive a vehicle upon a highway at a speed greater than is reasonable or prudent having due regard for weather, visibility, the traffic on, and the surface and width of, the highway, and in no event at a speed which endangers the safety of persons or property.”

AUTHORIZATION TO OPERATE CODE 3

Section 21055 of the California Vehicle Code exempts the driver of an authorized emergency vehicle from specific sections of the vehicle code (see exemption) while responding to or operating at the scene of an emergency call provided the driver sounds a siren as may be reasonably necessary and the vehicle displays a lighted red lamp visible from the front as a warning to other drivers and pedestrians. However, *Section 21056* goes on to state that *Section 21055* does not relieve the driver of a vehicle from the duty to drive with due regard for the safety of all persons using the highway, nor protect him from the consequences of an arbitrary exercise of the privileges granted in that section.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 604.04 Code 3 Driving

1/2024

Page 2 of 5

CODE 3 DEFINITION

Department policy defines Code 3 driving as the operation of an authorized emergency vehicle in response to an emergency call or while actively engaged in an emergency call, but not returning from an emergency call, when such emergency requires an expeditious response. Only those personnel who are properly trained and licensed and whose duties necessitate driving Code 3 may do so.

CODE 3 DRIVER RESPONSIBILITIES

Drivers of fire department emergency vehicles bear the ultimate responsibility for the proper operation of a department vehicle. Each driver shall drive with due regard for the safety of all persons using the highway.

1. Road position: When responding Code 3, the fire department emergency vehicle should normally be driven with the flow of traffic in the lane of traffic closest to the center of the roadway.
2. Maximum speed: When responding Code 3, fire department vehicles may, based on the principle of the Basic Speed Law and *Section 21055 of the California Vehicle Code*, exceed the speed limit as conditions allow. [This will be based upon visibility, vehicle stability and control, weather, road conditions and hazards as well as traffic volume and congestion when determining vehicle speed.] Under less than favorable conditions the posted speed limit is the absolute maximum permissible.
3. Use of warning devices: The use of warning lights, sirens and/or other traffic warning devices does not automatically give the right-of-way to the emergency unit. These devices simply request the right-of-way from other drivers based upon their awareness of the emergency units. When responding Code 3, the driver shall use installed warning devices as directed in this guideline. This includes:
 - a. Activation of all installed warning lights.
 - b. Continuous sounding of a siren, as may be reasonably necessary, in the “wail” or “yelp” mode. The “hi-lo” should not be used. Drivers may limit the use of the siren when responding through residential areas during normal sleeping hours.
 - c. Intermittent use of an air horn, may supplement, but not act in lieu of the siren.
4. Driving through Intersections: When approaching an intersection, the driver should reduce the speed of an emergency vehicle so as to allow the vehicle to be brought to a complete stop, if necessary, based on the position and actions of cross and opposing vehicle and pedestrian traffic. Come to a complete stop at red lights and stop signs. Prior to movement through the intersection, the driver of the emergency vehicle should visually account for the vehicles in each of the lanes of the cross and opposing traffic. A driver shall not respond through an intersection without first visually confirming it is safe

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 604.04 Code 3 Driving

1/2024

Page 3 of 5

to do so. The driver should not rely on the presence of a green traffic light as a signal that it is safe to proceed through an intersection.

5. Passing other responding emergency vehicles: A driver may pass other responding emergency vehicles only when radio contact is made and the action is coordinated.
6. Travel against on-coming traffic: Fire department vehicles traveling Code 3 should avoid traveling against on-coming traffic. If there is no reasonable way to proceed with the traffic flow, travel against on-coming traffic is acceptable with a direct visual accounting of the opposing traffic by the driver and at a reduced speed when it is safe to do so or when emergency personnel control the traffic lane.
7. Passing on the right: Drivers of fire department emergency vehicles responding Code 3 should give vehicular traffic an opportunity to yield to the right-of-way request and move to the right of the roadway. If a vehicle slows in the path of the emergency vehicle during an emergency response, passing on the right is acceptable when it has been reasonably established that the civilian traffic will not properly yield to a right-of-way request and it is safe to do so.
8. Response on freeways: The use of a freeway may be necessary during an emergency response. Drivers should adhere to the following when traveling on the freeways:
9. When using the freeway strictly for access to a destination and the traffic is moving well, travel without lights and siren.
10. When responding to an incident on the freeway, or, when traffic has slowed, use the red warning light ensemble and the siren at a reduced speed to safely navigate the traffic congestion.

RIGHT FRONT SEAT PASSENGER

Fire department personnel riding in the right front seat when responding Code 3 should provide visual support to the driver and report any hazards.

OFFICER/DRIVER DISCRETION

An officer may modify the response code at any time, if in her/his best judgment a Code 3 response might unduly jeopardize the safety of all persons and property. In the absence of an officer, the driver may exercise the same discretion and modify the response.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 604.04 Code 3 Driving

1/2024

Page 4 of 5

All City of Calimesa employees are required to use seat belts at all times when operating a City vehicle equipped with seat belts. Anyone riding as a passenger/attendant in a City vehicle is also required to use seat belts; i.e., engine, utility, staff vehicle, etc. The Company Officer/driver of the vehicle will confirm that all personnel and riders are on-board, properly attired, with seat belts on, before the vehicle is permitted to move.

1. All personnel shall ride only in regular seats provided with seat belts. Riding on tailboards or other exposed positions is not permitted on any vehicle at any time.
2. During an emergency response, fire vehicles should avoid passing other emergency vehicles. If passing is necessary, permission must be obtained through radio communications, using the communications order model.

The unique hazards of driving on or adjacent to the fire ground requires the driver to use extreme caution and to be alert and prepared to react to the unexpected.

1. Drivers must consider the dangers their moving vehicle poses to fire ground personnel and spectators who may be preoccupied with the emergency, and may inadvertently step in front of or behind a moving vehicle.
2. When stopped at the scene of an incident, vehicles should be placed to protect personnel who may be working in the street and warning lights shall be used to make approaching traffic aware of the incident. At night, vehicle mounted floodlights and any other lighting available shall be used to illuminate the scene. All personnel working in or near traffic lanes shall wear high visibility vests.
3. If it is not necessary to park vehicles in or near traffic lanes, the vehicle should be pulled off the road to parking lots, curbs, etc., whenever possible.
4. The officer in charge or driver of the vehicle is responsible for the safety of all vehicle operations and managing compliance of this procedure.

EMERGENCY RESPONSE POLICY

Calimesa Fire Department vehicles shall be operated in a manner that provides for the safety of all persons and property. Safe arrival shall always have priority over unnecessary speed and reckless driving en route to an emergency incident.

PROMPT, SAFE RESPONSE SHALL BE ATTAINED BY:

1. Leaving the station in a standard manner:
 - a. Quickly mounting apparatus
 - b. All personnel on board, seated and belts on
 - c. Station doors fully open
2. Driving defensively and professionally at reasonable speeds.
3. Knowing where you are going.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 604.04 Code 3 Driving

1/2024

Page 5 of 5

4. Using warning devices to move around traffic and to request the right-of-way in a safe and predictable manner.

FAST RESPONSE SHALL NOT BE ATTAINED BY:

1. Leaving quarters before crew has mounted safely and before apparatus doors are fully open.
2. Driving too fast for conditions.
3. Driving recklessly or without regard for safety.
4. Taking unnecessary chances with negative right-of-way intersections.
5. Intimidating or scaring other drivers.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6
Guideline: 604.05 Mandatory Seatbelts

1/2024

Page 1 of 1

The purpose of the Mandatory Seatbelts Guideline is to ensure the safety of all employees and to prevent injury or death in a traffic accident. **EVERYONE GOES HOME!**

The driver of any Calimesa Fire Department vehicle or apparatus shall be directly responsible for the safe operation of the vehicle. When the driver is under the direct supervision of an officer or acting officer, that officer or acting officer shall also assume responsibility for the actions of the driver.

Drivers shall not move fire department vehicles or apparatus until all persons are seated and secured with seat belts in approved riding positions.

All persons riding in fire department vehicles or apparatus shall be seated and secured by seat belts or safety harnesses at any time the vehicle is in motion. Riding on tailboards, side steps, running boards, or in any other exposed positions, or standing while riding shall be specifically prohibited.

Department members are exempt from wearing seat belts while actively performing emergency medical care while the vehicle is in motion, where requirements to be seated and restrained with seat belts would jeopardize patient care. The driver shall take extraordinary precautions in recognition of the additional danger that exists while driving with unrestrained member(s). All other persons in the vehicle shall be seated and restrained with seat belts in approved riding positions while the vehicle is in motion.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 604.06 Standard Signals for Backing of Fire Department Apparatus

1/2024

Page 1 of 2

VEHICLE BACKING AND SIGNALS

Backing of Fire Department vehicles should be avoided whenever possible. Where backing is unavoidable spotters shall be used. In addition, spotters shall be used when vehicles must negotiate forward turns with restrictive side clearances and where height clearances are uncertain.

Under circumstances where the vehicle is manned by only the driver, that vehicle driver shall attempt to utilize any available fire department personnel to act as spotters. Where no personnel are available to assist, the vehicle driver shall get out of the vehicle and make a complete 360-degree survey of the area around the vehicle to determine if any obstructions are present.

Where engine are backed, all crew members will dismount the apparatus and act as spotters. Spotters should be located at as many corners as possible with at least one spotter at the left rear corner of the apparatus. Where only a single spotter is available, the spotter should be located off the left rear corner, and will act as the primary spotter.

Spotters are not permitted to ride tailboard positions while backing fire apparatus.

Spotters will discuss the backing plan with the Company Officer before proceeding. The communication/warning process will be agreed upon prior to backing. Both door windows (driver and front passenger) will be in the down position to allow for maximum communication/hearing between spotters and the Company Officer. Fire radio volumes will be turned down.

The vehicle shall not be backed until all spotters are in position and communicate their approval to start the backing. Spotters will remain visible to the engineer/driver. Anytime the driver loses sight of the primary spotter, the vehicle shall be stopped immediately until the spotter is visible, and the communication to continue backing is processed.

When vehicles must be backed where other vehicles traffic exists, the vehicle's emergency lights (if equipped with such lights) shall be operating and orange safety vests shall be worn by all spotters.

The company officer is responsible for compliance with this procedure and the safe backing of the apparatus.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6

Guideline: 604.06 Standard Signals for Backing of Fire Department Apparatus

1/2024

Page 2 of 2

SIGNALS

STRAIGHT BACK: One hand above the head with palm toward face, waving back. Other hand at your side. (Left or right hand optional)

TURN: Both arms pointing the same direction with index fingers extended. (Driver will advise the spotter which way the turn will be made. The spotter then assists the driver in backing apparatus. The driver's intentions must be verbally communicated to the spotter).

STOP: Both arms crossed with hands in fist. Be sure to yell the stop order loud enough that the engineer/driver can hear the warning.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6
Guideline: 604.07 Apparatus Placement

1/2024

Page 1 of 2

Apparatus function should regulate placement. Poor apparatus placement can reverse this rule limiting the options or eliminating functions we can assign to a unit.

Fire fighters operate with a natural inclination to drive apparatus as close to the fire as possible. This often results in positioning of apparatus that is both dysfunctional and dangerous. The placement of all apparatus on the fire ground should reflect the following:

- Standard operational procedure for first arriving companies.
- Tactical objectives and priorities.
- Staging procedure.
- A direct order from Command.
- A conscious decision on the part of the Company officer based on existing or predictable conditions.

Effective apparatus placement must begin with the arrival of the first unit. The placement of the initial arriving engine should be based upon initial size-up and general conditions upon arrival. The first arriving company should place themselves to maximum advantage and go to work; later arriving units should be placed in a manner that builds on the initial plan and allows for expansion of the operation.

Avoid "belly to butt" placement on the fire ground. Do not drive all fire apparatus directly to the fire. Later arriving companies should stage a minimum of one block short of the immediate fire area, and remain uncommitted until ordered into action by Command. Company officers should select staged positions with a maximum of tactical options.

Command must maintain an awareness of site access that provides tactical options and that the immediate fire area can quickly become congested with apparatus. The officer must regard apparatus on the fire ground in two categories:

- Apparatus that is working
- Apparatus that is parked

Park out of the way. Apparatus that is not working should be left in the Staging Area or parked where it will not compromise access.

Maintain an access lane down the center of streets wherever possible.

Think of fire apparatus as an expensive exposure: position working apparatus in a manner that considers the extent and location of the fire and a pessimistic evaluation of fire spread and building failure. Anticipate the heat which may be released with structural collapse. Forecast where the fire is going and how it will affect exposure of apparatus. Apparatus should generally be positioned at least 30 ft. away from involved buildings, even with nothing showing.

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 604.07 Apparatus Placement

1/2024

Page 2 of 2

Greater distances are indicated in many situations.

Beware of putting fire apparatus in places where it cannot be repositioned easily and quickly; particularly operating positions with only one way in and out; i.e., yards, alleys, driveways, etc.

Beware of overhead power lines when positioning apparatus. Do not park where lines may fall.

If apparatus does become endangered operate hose lines between it and the fire while you reposition it. When you do move it move it to a position that is safe. It is dysfunctional to move apparatus several times throughout the progress of a fire.

Take maximum advantage of good operating positions and "build" the capability of units assigned to these effective positions. Initial arriving pumpers should be placed in "key" positions. These positions should offer maximum fire attack access to the fire area and be supplied with large diameter pumped supply lines as quickly as possible. Subsequent arriving companies can operate the hose lines from this apparatus.

Key tactical positions should be identified and engines placed in those locations with a strong water supply. The water supply should be at least one pumped line from an engine on a hydrant.

Take full advantage of hydrants close to the fire before laying additional supply lines to distant hydrants. Secondary hydrants should be used to obtain additional supply if the demand exceeds the capability of the closest hydrants.

Take advantage of the equipment on apparatus already in the fire area instead of bringing in more apparatus. Connect extra lines to pumpers which already have a good supply line instead of making "daisy chain" supply line connections.

Do not hook up to hydrants so close to the fire building that structural failure or fire extension will jeopardize the apparatus.

Fire hose soon limits the general access as the fire ground operation gets older. Command and Sectors must direct apparatus to important positions as early as possible. Lines should be laid with attention to the access problems they present. Try to lay lines on the same side of street as the hydrant and cross over near the fire.

Command vehicles should be positioned at a location that will allow maximum visibility of the fire building and surrounding area and the general effect of the companies operating on the fire. Command vehicle position should be easy and logical to find and should not restrict the movement of other apparatus.

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6
Guideline: 604.08 Unattended Apparatus

1/2024

Page 1 of 1

The Unattended Apparatus Guideline is to establish procedure when department apparatus can be left unattended.

STANDARD

1. One (1) department personnel will stay with the apparatus at all times when conducting non- department related business activities that include:
 - a. Trips to the grocery store are permitted. Trips are limited to one trip per day and are to occur in conjunction with fire department related activities.
 - b. Trips to restaurants and food establishments are permitted by a reserve using the utility pick up, but limited to “take out only” when out of local jurisdiction. Personnel are allowed to eat at the establishments within local jurisdiction.
2. Department apparatus may be left unattended during strike team or campaign incidents for food and rehabilitation.
3. Department apparatus can be left unattended during the following activities:
 - a. Life Safety Inspections, Code Enforcement Assignments and Public Education Activities
 - b. Training Activities
 - c. Emergency Incidents
4. Department staff vehicles that are operated by a single individual can be left unattended at any time.
5. Department apparatus and staff vehicle operators will obey all vehicle codes with regards to parking their apparatus/vehicle. Drivers will try to place their vehicles in a place/ position that will not hinder or disturb the public’s access or the place of business. Exception: Emergency Incidents.
6. The operator of the vehicle shall do a 360-degree visual check (golden circle) of the apparatus prior to moving the apparatus.
7. Personnel assigned to the apparatus will be responsible for the equipment that is assigned to the apparatus

CALIMESA FIRE DEPARTMENT
GUIDELINE MANUAL
VOLUME 6
Guideline: 604.09 Apparatus Inspections

12/2023

Page 1 of 1

TBD

Standard Operating Policies – Standard Operating Guidelines

Concise Table of Content – Volume 6

Intern Reserve & Explorer Program – 605.00

Table of content to be determined

CALIMESA FIRE DEPARTMENT

GUIDELINE MANUAL

VOLUME 6

Guideline: 605.00 Intern Reserve & Explorer Program

12/2023

Page 1 of 1

TBD

This is a place holder to be determined and held for later more detailed program development.

Standard Operating Policies – Standard Operating Guidelines
Concise Table of Content – Volume 6
Training – 606.00

- **606.00 – Training – Volume 6**
 - 606.00 Preface
 - 606.01 Training
 - 606.02 Manipulative Skills
 - 606.03 Position Task Book
 - 606.04 Apparatus Operator Certification
 - 606.05 Apparatus Certification Task Book
 - 606.06 Training Records
 - 606.07 Training Requirements
 - 606.08 Testing Requirements
 - 606.09 Fit Testing Guidelines

CALIMESA FIRE DEPARTMENT

POLICY MANUAL

VOLUME 6

Policy: 606.01 Training Policy

12/2023

Page 1 of 3

PURPOSE AND SCOPE

It is the policy of this department to administer a training program that will provide for the professional growth and continued development of its members. By doing so, the Department will ensure its members possess the knowledge and skills necessary to provide a professional level of service that meets the needs of the community.

POLICY

The Department seeks to provide ongoing training and encourages all members to participate in advanced training and formal education on a continual basis. Training is provided within the confines of funding, the requirements of a given assignment, staffing levels and legal mandates.

Whenever possible, the Department will use courses certified by the California Office of the State Fire Marshal (OSFM), the California Fire Service Training and Education System (CFSTES), the U.S. Department of Homeland Security or other accredited entities.

OBJECTIVES

The objectives of the training program are to:

- (a) Enhance the level of emergency services to the public.
- (b) Increase the technical expertise and overall effectiveness of department members.
- (c) Provide for continued professional development of department members.
- (d) Reduce risk and enhance safety.

RESPONSIBILITIES

The training department will be overseen by the Fire Chief and will consist of one training Battalion Chief and one training Fire Captain.

Training Battalion Chief

- (a) Administer department policies and procedures for the management of instructional resources, staff, facilities, records, and reports.
- (b) Administer a training record system, (Vector Solutions and or Image Trend) so that the information meets all agency, ISO and legal requirements and can be readily accessed.

CALIMESA FIRE DEPARTMENT

POLICY MANUAL

VOLUME 6

Policy: 606.01 Training Policy

12/2023

Page 2 of 3

- (c) Develop forms and appropriate reports for documentation of training activities for the department and individual staff members.
- (d) Select instructional staff that assist with meeting department policies and instructional goals.
- (e) Evaluate findings and conclusions; Make recommendations that are unbiased, support and reflect the department goals, policies, and procedures.
- (f) Will participate as the department's liaison to the Riverside County and San Bernardino County Training Officers Groups with required attendance or participation in monthly meetings.
- (g) Will work with the ALS Manager with assisting and implementing all BLS and ALS mandated computer base or in person live training.
- (h) Will be responsible for overseeing the implementation of positional task books for rank.
- (i) Will be responsible for overseeing the implementation of equipment task books as it relates to the rolling stock of the department.

Training Captain

- (a) Create lesson plans to include learning objectives, a lesson outline, course materials, instructional aids, and evaluation plan to ensure job performance requirements for the topic are achieved.
- (b) Modify existing lesson plans to include learning objectives, a lesson outline, course materials, instructional aids, and evaluation plan to ensure job performance requirements for the topic are achieved.
- (c) Conduct classes using a lesson plan that includes multiple teaching methods and techniques to achieve lesson objectives.
- (d) Obtain and assemble all lesson plans, course materials, resources, and equipment needed to deliver the lesson.
- (e) Will participate as the department's liaison to the Riverside County and San Bernardino County Training Officers Groups with required attendance or participation in monthly meetings.
- (f) Manage the Reserve Firefighter recruitment, retention and hiring practices and procedures.
- (g) Will be responsible for the implementation of equipment task books as it relates to the rolling stock of the department.

CALIMESA FIRE DEPARTMENT

POLICY MANUAL

VOLUME 6

Policy: 606.01 Training Policy

12/2023

Page 3 of 3

TRAINING PLAN

A master training plan will be developed and maintained by the Training Chief. It is the responsibility of the Training Chief to maintain, review and update the master training plan on an annual basis, ensuring that all mandated training is achieved. All training records will be maintained in Vector Solutions or Image Trend web-based program.

TRAINING NEEDS ASSESSMENT

The Training Officer will conduct an annual training needs assessment. Command staff will review the needs assessment. Upon approval by the Fire Chief, the needs assessment will form the basis of the training plan for the following year.

TRAINING CALENDAR

The Training Calendar is available in Outlook and will detail the approved scheduled training events daily for each shift. It is the responsibility of each member to view this calendar on a regular basis to prepare for department-approved training sessions.

CALIMESA FIRE DEPARTMENT
POLICY MANUAL
VOLUME 6
Policy: 606.02 Manipulative Skills Basic

12/2023

Page 1 of 1

PURPOSE AND SCOPE

This guideline has been established to provide personnel with a reference to manipulative skills and techniques.

STANDARD

To maintain consistency among fire department personnel performing manipulative skills, the Training Office will maintain a Manipulative Skills Manual current built into the training manual.

Manipulative skills will be referenced through the Training Manual and/or the IFSTA Essentials Edition 5 or 6 training books.

Manipulative skills that are identified as techniques specific to the Calimesa Fire Department will be referenced through the Training Manual.

CALIMESA FIRE DEPARTMENT

POLICY MANUAL

VOLUME 6

Policy: 606.03 Position Task Books Firefighter Engineer Captain Battalion Chief

1/2024

Page 1 of 1

PURPOSE AND SCOPE

This guideline has been developed to assist with employee development in meeting the department standards for probationary Firefighters, Engineers, Captains, and Battalion Chiefs. In completing the positions task book the employee has shown the ability to operate in their position.

STANDARD

Task Books have been created primarily as an employee development tool for evaluating performance using approved standards. The Task Book provides a guideline for the members of the Calimesa Fire Department to develop the knowledge, skills, and abilities required to perform the job specific functions required within the Calimesa Fire Department. The Task Book lists the required tasks in a format that allows department members to be evaluated against performance-based standards and written guidelines.

CALIMESA FIRE DEPARTMENT



PROBATIONARY ENGINEER TASK BOOK

The material in this task book defines the performance expected of the position for which it is developed. This task book is approved for use as an employee development guidebook and a post-promotional probationary assessment.

TASK BOOK ASSIGNED TO:

NAME/RANK/TITLE

TASK BOOK INITIATED BY:

TRAINING CAPTAIN:

DATE TASK BOOK INITIATED:

VERIFICATION OF COMPLETED TASK BOOK
FOR THE POSITION OF

ENGINEER

FINAL EVALUATOR'S VERIFICATION

I verify that all tasks have been performed and are complete with signatures. I also verify that

(Print Employee's Name)

Has performed as a trainee and should therefore be considered for certification in this position.

EVALUATOR'S SIGNATURE AND DATE

EVALUATOR'S PRINTED NAME AND TITLE

AGENCY CERTIFICATION:

I certify that the above individual has met all requirements for qualification in this position and
that such qualification has been issued.

TRAINING CHIEF SIGNATURE AND DATE

TRAINING CHIEF PRINTED NAME

CALIMESA FIRE DEPARTMENT EMPLOYEE DEVELOPMENT PROGRAM

I. PERFORMANCE BASED SYSTEM

The Calimesa Fire Department Employee Development Program is a “performance based” system. This system is one in which the primary criteria for qualification is individual performance as observed by an evaluator using approved standards. The Employee Development Program utilizes Position Task Books as the primary tool for observing and evaluating performance. They contain the “approved standards” in the form of tasks, which have been established by industry standards.

Position Task Books have been developed for designated positions within the Calimesa Fire Department. An Engineer Position Task Book lists the performance requirements (tasks) for the specific position in a format that allows a probationary Engineer to be evaluated against written guidelines.

IMPORTANT NOTE: Position task books are designed with a specific focus on a particular position, and therefore contain a narrower set of skills and knowledge than may be necessary to be successful in that position. As a result, each position task book includes a *presumption* that the probationary Engineer has the requisite knowledge of the position subordinate to the task book being initiated. For example, the individual who initiates an Engineer Position Task Book must have the knowledge, skills, and abilities contained in the Firefighter Position Task Book to successfully complete the Engineer Position Tasks.

II. USE OF THE POSITION TASK BOOK

The position task book will be used during completion of the employee’s probationary period (the post-promotion process) to verify the employee’s performance meets the requirements of the position for which the individual is being promoted.

III. TIME FRAME FOR COMPLETING THE POSITION TASK BOOK

Completion of the position task book is required prior to the end of the probation period. Final determination of the position task book completion time frame lies with the Training Chief.

IV. RESPONSIBILITIES

NOTE: The list below contains a summary of the responsibilities for the various participants in the Career Development Program. For complete details, refer to the Career Development Guide.

A. The Department

- 1) Establish and implement the Career Development Program.
- 2) Maintain the program to meet current Department needs.

B. The Training Division

Issue Position Task Books to document task performance

Explain to the employee the purposes and processes of the Position Task Book as well as the employees' responsibilities.

Confirm Position Task Book completion.

Determine certification per Department requirements.

Conduct a closeout interview with the employee and the evaluator to ensure that documentation is proper and complete.

Issue proof of certification

C. The Evaluator (Captain, Engineer)

Be qualified and proficient in the position being evaluated.

Meet with the individual and determine experience, current qualifications, and desired objectives and goals.

Review tasks with the individual

Explain to the individual the evaluation procedures that will be utilized, and which objectives may be attained.

Identify tasks to be performed during the evaluation process.

Initialize and date the tasks completed and evaluated.

Complete the evaluation record found at the end of each Position Task Book

Sign the verification statement inside the front cover of the Position Task Book when all tasks have been completed and initialed.

D. The Individual (Probationary Engineer)

Review and understand the instructions in the Position Task Book

Identify desired personal objectives and goals.

Satisfactorily complete all tasks for an assigned position

Assure the evaluation record is complete.

Notify the Training Division when the Position Task Book is completed.

Maintain a copy of the completed Position Task Book in the individuals training file.

Track all training by category and timeframe and record completed training into Target Solutions. Also enter training for individuals associated with each individual task or category.

V. PREREQUISITE RECOMMENDATIONS

The Engineer Position Task Book requires the foundational knowledge, skills, and abilities of the following position task books: Firefighter.

Training Hours Documentation for Target Solutions Engineer Position Task Book

<u>Categories</u>	<u>Time</u>	<u>Other Personnel Associated</u>
General	_____	_____
Administration	_____	_____
Department Specific	_____	_____
Communications	_____	_____
Emergency Planning	_____	_____
Driving	_____	_____
Apparatus	_____	_____
Aerial Apparatus	_____	_____
Apparatus Maintenance	_____	_____
Pumps and Pump Theory	_____	_____
Apparatus Operations	_____	_____
Special Apparatus	_____	_____
Fire Protection Systems	_____	_____
Hydraulics	_____	_____

QUALIFICATION RECORD

POSITION: ENGINEER

POSITION PERFORMANCE TASK	CODE	PROBATIONARY EMPLOYEE OR TRAINEE Initial & date upon completion of task	EVALUATOR Initial & date upon completion of task
---------------------------	------	--	--

GENERAL

1. Demonstrates an understanding of the CMSFD Career Development Program task book. • Purpose • Use of Career Development Guide • Performance based system • Important terms • Task book use • Task book issuance • Prerequisite recommendations • Task book design • Comments and recommendations Ref.: 2, 3	O D		
2. Demonstrates an understanding of the responsibilities of the following person(s) regarding the Employee Development Program: • Department • Training Division • Evaluator • Trainee	O D		
3. Demonstrates an understanding of the Engineer Position Task Book • Headings/Sub-headings • Code(s) column • Trainee column • Evaluator column • Time frames for completion • Initials and signatures • Verification of qualifications	O D		

* CODE: O =task can be completed in any situation (classroom, simulation, daily job, etc.)
 I = task must be performed on an incident (fire, rescue, vehicle accident wildland fire, etc.)
 D = Can be completed by discussion
 M P = Completion must include manipulative performance
 R = task is required to be completed prior to promotional testing process

QUALIFICATION RECORD

POSITION: ENGINEER

POSITION PERFORMANCE TASK	CODE	PROBATIONARY EMPLOYEE OR TRAINEE Initial & date upon completion of task	EVALUATOR Initial & date upon completion of task
---------------------------	------	--	--

ADMINISTRATION

4. Demonstrates an understanding of the job description for Fire Engineer • Job Summary • Characteristics • Essential functions • Minimum qualifications • Physical requirements • License • Certification • Health exposure	O D		
5. Demonstrates an understanding of the required Driver's Licenses/Certificates • Class C w/ FF Endorsement • Endorsements • Notification process • Medical evaluation • Filing of license/medical examination certification	O D DR		
6. Explains the vehicle accident reporting process • Scope • Forms • Definitions • Policy • Notifications • Documentation filing	O D		

* CODE: O =task can be completed in any situation (classroom, simulation, daily job, etc.)
 I = task must be performed on an incident (fire, rescue, vehicle accident wildland fire, etc.)
 D = Can be completed by discussion
 M P = Completion must include manipulative performance
 R = task is required to be completed prior to promotional testing process

QUALIFICATION RECORD

POSITION: ENGINEER

POSITION PERFORMANCE TASK	CODE	PROBATIONARY EMPLOYEE OR TRAINEE Initial & date upon completion of task	EVALUATOR Initial & date upon completion of task
---------------------------	------	--	--

DEPARTMENT SPECIFIC

7. Explains the various fuel types used by CMSFD and fueling locations. - Fuel types - Fueling while traveling (Cal Card) - Minimum levels	O D		
8. Demonstrates an understanding of the use of map books, including. - District map books - Thomas Brothers - Wall maps - GPS Units - Hospital locations	O MP		

COMMUNICATIONS

9. Demonstrates a working knowledge of the radio communication systems used by the Department. - Mobile radios - Portable radios - Clear text - Repairs - Battery management - Headsets	O MP		
---	-----------------	--	--

* CODE: O =task can be completed in any situation (classroom, simulation, daily job, etc.)
 I = task must be performed on an incident (fire, rescue, vehicle accident wildland fire, etc.)
 D = Can be completed by discussion
 M P = Completion must include manipulative performance
 R = task is required to be completed prior to promotional testing process

QUALIFICATION RECORD

POSITION: ENGINEER

POSITION PERFORMANCE TASK	CODE	PROBATIONARY EMPLOYEE OR TRAINEE Initial & date upon completion of task	EVALUATOR Initial & date upon completion of task
10. Demonstrates a working knowledge of Mobile Data Computers (MDC's) - Codes - Receiving messages - Sending messages - Interpreting alarm notifications Ref.: 8	O MP		

EMERGENCY PLANNING

11. Explains the procedures for multi-casualty incident operations as it pertains to Engineer - Definitions - Responsibilities - Assignments - ICS - Safety	O D		
12. Explains the procedures for wildland fire fighting operations as it pertains to Engineer - Definitions - Responsibilities - Assignments - ICS - Safety	O D		

* CODE: O =task can be completed in any situation (classroom, simulation, daily job, etc.)
 I = task must be performed on an incident (fire, rescue, vehicle accident wildland fire, etc.)
 D = Can be completed by discussion
 M P = Completion must include manipulative performance
 R = task is required to be completed prior to promotional testing process

QUALIFICATION RECORD

POSITION: ENGINEER

POSITION PERFORMANCE TASK	CODE	PROBATIONARY EMPLOYEE OR TRAINEE Initial & date upon completion of task	EVALUATOR Initial & date upon completion of task
13. Explains the procedure for hazardous materials incident as it pertains to Engineer. • Definitions • Responsibilities • Assignments • ICS • Safety	O D		

DRIVING

14. Demonstrates an understanding of "Driver Safety." • Vehicle control and Right-of-Way • Basic procedures • Seat belt use • Wheel chocks	O MP		
15. Demonstrates an ability to position emergency apparatus in the most advantageous locations at emergency scenes. • Fire attack • Truck operations • Structural protection • Wildland fires • Automobile accidents • Automobile fires • Hazardous materials incidents • Sprinklered building responses.	O MP		

* CODE: O =task can be completed in any situation (classroom, simulation, daily job, etc.)
 I = task must be performed on an incident (fire, rescue, vehicle accident wildland fire, etc.)
 D = Can be completed by discussion
 M P = Completion must include manipulative performance
 R = task is required to be completed prior to promotional testing process

QUALIFICATION RECORD

POSITION: ENGINEER

POSITION PERFORMANCE TASK	CODE	PROBATIONARY EMPLOYEE OR TRAINEE Initial & date upon completion of task	EVALUATOR Initial & date upon completion of task
16. Demonstrates an understanding of the following elements of emergency driving. • Warning devices • Intersections • Overtaking apparatus • Response speeds	O MP		
17. Demonstrates an ability to drive emergency vehicles in non-emergency situations. • Right-of-Way • Proper lane travel	MP		
18. Demonstrates an understanding of the safety aspects of driving emergency apparatus in various types of weather conditions. • Rain • Snow • Sleet • Icy Roads • Fog • Nighttime	O MP		

* CODE: O =task can be completed in any situation (classroom, simulation, daily job, etc.)
I = task must be performed on an incident (fire, rescue, vehicle accident wildland fire, etc.)
D = Can be completed by discussion
M P = Completion must include manipulative performance
R = task is required to be completed prior to promotional testing process

QUALIFICATION RECORD

POSITION: ENGINEER

POSITION PERFORMANCE TASK	CODE	PROBATIONARY EMPLOYEE OR TRAINEE Initial & date upon completion of task	EVALUATOR Initial & date upon completion of task
19. Demonstrate the concepts of off-road driving. - Angles of approach and departure - Surface conditions - Proper gears - Proper speeds - Side hill	MP		
20. Demonstrates an understanding of the following defensive driving concepts. - Accident avoidance - Braking distances - Reaction time - Visual lead time - Following distances	O		
21. Demonstrates an understanding of federal, state, and local laws and statutes governing the operation of emergency vehicles. - California Vehicle Code - Dept. of Transportation - NFPA 1002 Driver/Operator Professional Qualifications	O D		

* CODE: O =task can be completed in any situation (classroom, simulation, daily job, etc.)
 I = task must be performed on an incident (fire, rescue, vehicle accident wildland fire, etc.)
 D = Can be completed by discussion
 M P = Completion must include manipulative performance
 R = task is required to be completed prior to promotional testing process

QUALIFICATION RECORD

POSITION: ENGINEER

POSITION PERFORMANCE TASK	CODE	PROBATIONARY EMPLOYEE OR TRAINEE Initial & date upon completion of task	EVALUATOR Initial & date upon completion of task
22. Demonstrates an ability to research and apply vehicle code rules/regulations governing the operation of emergency vehicles. • Vehicle licensing • Driver's license • Rules of the road • Accidents and accident reporting • Size, weight, and load • Safety regulations • Transport of hazardous materials • Transport of inhalation hazards • Transport of radioactive materials • Transport of flammable and combustible liquids	O D		

APPARATUS

23. Demonstrates an understanding of the various types of emergency vehicles used in the department, including Type 1 and 3 engines, truck 1, and water tender 1 • Specifications • Inventory • Fuel • Use/function • Staffing • Capacities • Safety considerations • Special considerations	O D		
--	----------------	--	--

* CODE: O =task can be completed in any situation (classroom, simulation, daily job, etc.)
 I = task must be performed on an incident (fire, rescue, vehicle accident wildland fire, etc.)
 D = Can be completed by discussion
 M P = Completion must include manipulative performance
 R = task is required to be completed prior to promotional testing process

QUALIFICATION RECORD

POSITION: ENGINEER

POSITION PERFORMANCE TASK	CODE	PROBATIONARY EMPLOYEE OR TRAINEE Initial & date upon completion of task	EVALUATOR Initial & date upon completion of task
24. Demonstrates an understanding of gasoline and diesel engines. • Ignition system • Shut down procedures. • Emergency shut off	O D		
25. Demonstrates an understanding of the readiness requirements for emergency apparatus. • In-service • Out-of-service • Inspections • Reserve apparatus	O D		
26. Type 1 Engine • DMV Pre-trip inspection (include cab tilt) • All gauges in the cab • Code 3 warning systems • Emergency lighting • Brake systems • Main pump • Booster pump • Generator and/or adjunct Equipment (Maintenance & Use) • Fluid checks and maintenance procedures • Foam operations, Class "A" and Class "B" (include master stream) • Changeover/Tank to hydrant • Hookup both front and side suction <i>continued next page...</i>	O MP		

* CODE: O =task can be completed in any situation (classroom, simulation, daily job, etc.)
 I = task must be performed on an incident (fire, rescue, vehicle accident wildland fire, etc.)
 D = Can be completed by discussion
 M P = Completion must include manipulative performance
 R = task is required to be completed prior to promotional testing process

QUALIFICATION RECORD

POSITION: ENGINEER

POSITION PERFORMANCE TASK	CODE	PROBATIONARY EMPLOYEE OR TRAINEE Initial & date upon completion of task	EVALUATOR Initial & date upon completion of task
• Portable monitor operation • Engineers' role in a progressive hose lay. • Master stream operation • Pressure relief valve and pressure governor operations • Pump & Roll and stationery • Pump panel gauges and controls • Identify all discharges/suctions. • Monthly inspection			
27. Type 3 Engine • DMV Pre-trip inspection (include cab tilt) • All gauges in the cab • Code 3 warning systems • Emergency lighting • Brake systems • Main pump • Generator and/or adjunct equipment (Maintenance & Use) • Fluid checks and maintenance Procedures • Gear selection • Pressure relief valve and pressure governor operations • Pump & Roll and stationery • Pump panel gauges and controls • Identify all discharges/suctions • Monthly inspection	O MP		

* CODE: O =task can be completed in any situation (classroom, simulation, daily job, etc.)
 I = task must be performed on an incident (fire, rescue, vehicle accident wildland fire, etc.)
 D = Can be completed by discussion
 M P = Completion must include manipulative performance
 R = task is required to be completed prior to promotional testing process

QUALIFICATION RECORD

POSITION: ENGINEER

POSITION PERFORMANCE TASK	CODE	PROBATIONARY EMPLOYEE OR TRAINEE Initial & date upon completion of task	EVALUATOR Initial & date upon completion of task
<u>AERIAL APPARATUS</u>			
32. Truck 1 • DMV Pre-trip inspection (include cab tilt) • All gauges in the cab • Code 3 warning systems • Emergency lighting • Brake systems • Main pump • Generator and/or adjunct equipment (Maintenance & Use) • Fluid checks and maintenance procedures • Aerial water supply vs. pump supply • Outrigger controls • Limitations and overrides • Outrigger placement and spotting • All controls on the turntable & aerial tip • Ladder load capabilities • Waterway system • Pinning waterway • Tip placement • All controls used during power interruption. • Pressure relief valve • Pump panel gauges and controls • Identify all discharges/suctions. • Monthly inspection	O MP		

* CODE: O =task can be completed in any situation (classroom, simulation, daily job, etc.)
 I = task must be performed on an incident (fire, rescue, vehicle accident wildland fire, etc.)
 D = Can be completed by discussion
 M P = Completion must include manipulative performance
 R = task is required to be completed prior to promotional testing process

QUALIFICATION RECORD

POSITION: ENGINEER

POSITION PERFORMANCE TASK	CODE	PROBATIONARY EMPLOYEE OR TRAINEE Initial & date upon completion of task	EVALUATOR Initial & date upon completion of task
33. Water Tender - DMV pre-trip inspection (include cab tilt) - All gauges in the cab - Code 3 warning systems - Emergency lighting - Brake systems - Main pump - Equipment (Maintenance & Use) - Fluid checks and maintenance procedures - Waterway system - Snap tank operations. - Floating Porta Pump operations - Pressure relief valve - Pump panel gauges and controls - Identify all discharges/suctions. - Monthly inspection	O MP		

APPARATUS MAINTENANCE

34. Demonstrates an ability to perform apparatus preventive maintenance inspections. - Accessing computer files - Performing the inspection - Daily checks - Weekly checks - Notification of repairs needed.	O		
---	---	--	--

* CODE: O =task can be completed in any situation (classroom, simulation, daily job, etc.)
 I = task must be performed on an incident (fire, rescue, vehicle accident wildland fire, etc.)
 D = Can be completed by discussion
 M P = Completion must include manipulative performance
 R = task is required to be completed prior to promotional testing process

QUALIFICATION RECORD

POSITION: ENGINEER

POSITION PERFORMANCE TASK	CODE	PROBATIONARY EMPLOYEE OR TRAINEE Initial & date upon completion of task	EVALUATOR Initial & date upon completion of task
35. Demonstrates an understanding of obtaining a repair or replacement of apparatus - Scheduled services - Station level repairs - Mobile repairs - Emergency repairs - Emergency/off-hours towing. - Flat tire service - BC/Dispatch notification - On-call mechanic - Inventory - Repairs - Apparatus status in On Scene	O D		

PUMPS AND PUMP THEORY

36. Demonstrates an understanding of various types of fire service pumps - Centrifugal - Single stage - Multi-stage - Midship - PTO - Positive displacement - Rotary gear - Rotary vane	O D		

* CODE: O =task can be completed in any situation (classroom, simulation, daily job, etc.)
 I = task must be performed on an incident (fire, rescue, vehicle accident wildland fire, etc.)
 D = Can be completed by discussion
 M P = Completion must include manipulative performance
 R = task is required to be completed prior to promotional testing process

QUALIFICATION RECORD

POSITION: ENGINEER

POSITION PERFORMANCE TASK	CODE	PROBATIONARY EMPLOYEE OR TRAINEE Initial & date upon completion of task	EVALUATOR Initial & date upon completion of task
37. Demonstrates a working knowledge of pressure relief valve & pressure governor • Theory of operation • Settings and controls • Activation • Options for use • Troubleshooting • Cleaning strainers	O MP		
38. Demonstrates an ability to maintain/analyze and troubleshoot pumping conditions and operations • Monitor gauges. • Pressure settings • RPM's • Operating from apparatus tank • Operating from hydrant • Operating from a draft • Operating in relay • Foam operations	O MP		

APPARATUS OPERATIONS

39. Demonstrates an ability to set up and complete pumping operations using the following tools/equipment • Handline • Standpipe systems • Sprinkler systems • Master stream appliances • Foam eductor	O MP		
--	---------	--	--

* CODE: O =task can be completed in any situation (classroom, simulation, daily job, etc.)
 I = task must be performed on an incident (fire, rescue, vehicle accident wildland fire, etc.)
 D = Can be completed by discussion
 M P = Completion must include manipulative performance
 R = task is required to be completed prior to promotional testing process

QUALIFICATION RECORD

POSITION: ENGINEER

POSITION PERFORMANCE TASK	CODE	PROBATIONARY EMPLOYEE OR TRAINEE Initial & date upon completion of task	EVALUATOR Initial & date upon completion of task
40. Demonstrates an ability to evaluate pumping requirements • Water supply limitations • Pressure limitations • Required pressures	O MP		
41. Demonstrates an understanding of various water sources used for fire service operations • Dynamic sources • Static sources • Hydrant systems (types)	O D		
42. Demonstrates an understanding of relay pumping operations • Relay apparatus and equipment • Operational considerations • Types of relay pumping operations • Maximum distance relay method • Constant pressure relay method • Putting a relay into operation • Operating the relay • Shutting down the relay	O MP		

* CODE: O =task can be completed in any situation (classroom, simulation, daily job, etc.)
 I = task must be performed on an incident (fire, rescue, vehicle accident wildland fire, etc.)
 D = Can be completed by discussion
 M P = Completion must include manipulative performance
 R = task is required to be completed prior to promotional testing process

QUALIFICATION RECORD

POSITION: ENGINEER

POSITION PERFORMANCE TASK	CODE	PROBATIONARY EMPLOYEE OR TRAINEE Initial & date upon completion of task	EVALUATOR Initial & date upon completion of task
43. Demonstrates an understanding of water shuttle operations • Apparatus • Setting up a water shuttle • Dump sites • Fill locations • Selecting the travel route • Make necessary notifications regarding fire flow based on turnaround times. • Positioning apparatus • Dump site operations • Shutting down the dump site	O		
44. Demonstrates an understanding of foam practices • Principles of foam • Foam concentrates • Portable foam application devices • Foam application techniques	O		
45. Demonstrates an understanding of the various hose loads and applications • Types • Pre-connect. • Supply lines • High rise packs • Front bumper line	O D		

* CODE: O =task can be completed in any situation (classroom, simulation, daily job, etc.)
I = task must be performed on an incident (fire, rescue, vehicle accident wildland fire, etc.)
D = Can be completed by discussion
M P = Completion must include manipulative performance
R = task is required to be completed prior to promotional testing process

QUALIFICATION RECORD

POSITION: ENGINEER

POSITION PERFORMANCE TASK	CODE	PROBATIONARY EMPLOYEE OR TRAINEE Initial & date upon completion of task	EVALUATOR Initial & date upon completion of task
46. Demonstrates a knowledge of hose testing • Purpose • Frequency • Tools/equipment • Pressures • Failure replacement	O MP		

SPECIAL APPARATUS

47. Water Tender • DMV pre-trip inspection (include cab tilt) • All gauges in the cab • Code 3 warning systems • Emergency lighting • Brake systems • Main pump • Generator and/or adjunct equipment (Maintenance & Use) • Fluid checks and maintenance procedures • Foam operations • Portable pumps • Water tank • Pump panel gauges and controls • Identify all discharges/suctions. • Monthly inspection	O MP		

* CODE: O =task can be completed in any situation (classroom, simulation, daily job, etc.)
 I = task must be performed on an incident (fire, rescue, vehicle accident wildland fire, etc.)
 D = Can be completed by discussion
 M P = Completion must include manipulative performance
 R = task is required to be completed prior to promotional testing process

QUALIFICATION RECORD

POSITION: ENGINEER

POSITION PERFORMANCE TASK	CODE	PROBATIONARY EMPLOYEE OR TRAINEE Initial & date upon completion of task	EVALUATOR Initial & date upon completion of task
48. Breathing Fill Station • Air compressor gauges • Air compressor • Fill SCBA bottle • Operate fill station in a contaminated air environment (closed loop system) • Lighting system • Rehab duties • Vehicle placement on scene • Monthly inspection	O MP		
49. USAR • DMV pre-trip inspection (include cab tilt) • All gauges in the cab • Code 3 warning systems • Emergency lighting • Brake systems • Generator and/or adjunct equipment (Maintenance & Use) • Fluid checks and maintenance procedures • Stationary power supply (PTO) • Lighting system • Air compressor	O MP		

* CODE: O =task can be completed in any situation (classroom, simulation, daily job, etc.)
 I = task must be performed on an incident (fire, rescue, vehicle accident wildland fire, etc.)
 D = Can be completed by discussion
 M P = Completion must include manipulative performance
 R = task is required to be completed prior to promotional testing process