Pseudo Classes and Elements

Designing for consistent appearance

Pseudo-Classes

شبه کلاسها برای انتخاب عناصر بر اساس حالتها یا موقعیتهای ساختاری استفاده میشوند

- Elements that are dynamically populated or dependent on tree structure
- You have seen this before…

```
a:hover{  }
```

Types of Pseudo-Classes

- Link
  - :link, :visited
- User Action
  - :hover, :active, :focus
- Forms (interfaces)
  - :enabled, :checked, :disabled

Types of Pseudo-Classes

- **Structural/Positional**
  - :first-child, :last-child, :nth-child(), :only-child
  - :first-of-type, :last-of-type, :only-of-type

```
li:first-child{   }
li:nth-child(4){   }
p:empty{   }
img:only-of-type{   }
p:last-of-type{   }
```

Pseudo-Elements

- These elements aren't part of the DOM
- Can be used to style specific (unique) parts of the page

شبه المانها برای انتخاب و استایل دهی بخشهای خاص از یک عنصر استفاده میشوند.
این بخشها میتوانند شامل محتوای قبل یا بعد از عنصر، یا بخشهای خاصی از متن باشند

Types of Pseudo-Elements

- Textual
  - :first-letter, :first-line
- Positional/Generated
  - :before, :after
- Fragments
  - ::selection

Review

- Pseudo-elements and classes are just one more way to add style to your page
- I haven't covered every combination so make sure to do some investigation on your own

Acknowledgements/Contributions

These slides are Copyright 2015- Colleen van Lent as part of http://www.intro-webdesign.com/ and made available under a Creative Commons Attribution Non-Commercial 4.0 License. Please maintain this last slide in all copies of the document to comply with the attribution requirements of the license. If you make a change, feel free to add your name and organization to the list of contributors on this page as you republish the materials.

Initial Development: Colleen van Lent , University of Michigan School of Information

