

**CMPS 130**  
**Computational Models**  
**Spring 2016**  
**Midterm Exam 1**

**Solutions**

1. (20 Points) Let  $S$  be a set. Prove that no function  $f : S \rightarrow 2^S$  is onto. (Recall that  $2^S$  denotes the power set of  $S$ , i.e. the set of all subsets of  $S$ .)

**Proof:**

Assume  $f : S \rightarrow 2^S$  is onto. Define  $A \subseteq S$  by  $A = \{ x \in S \mid x \notin f(x) \}$ . Since  $f$  is supposedly onto, there exists  $y \in S$  such that  $f(y) = A$ . Either  $y \in A$  or  $y \in S - A$ . If  $y \in A$  then  $y \in f(y)$ , so by the definition of  $A$  we have  $y \notin A$ , a contradiction. On the other hand if  $y \notin A$  then  $y \notin f(y)$  so again by definition of  $A$  we have  $y \in A$ , another contradiction. These contradictions show that our assumption was false, and therefore no such function  $f$  can exist. ///

2. (20 Points) Let  $\Sigma$  be a finite alphabet and let  $M = (Q, \Sigma, q_0, A, \delta)$  be a finite state automaton. Write down the following recursive definitions.

- a. (5 Points)  $\Sigma^*$  the set of all strings over  $\Sigma$ .

**Definition:**

- (1)  $\lambda \in \Sigma^*$
- (2) If  $x \in \Sigma^*$  and  $\sigma \in \Sigma$ , then  $x\sigma \in \Sigma^*$ .

- b. (5 Points)  $r : \Sigma^* \rightarrow \Sigma^*$  the reversal function.

**Definition:**

- (1)  $r(\lambda) = \lambda$
- (2) If  $x \in \Sigma^*$  and  $\sigma \in \Sigma$ , then  $r(x\sigma) = \sigma r(x)$

- c. (5 Points)  $\delta^* : Q \times \Sigma^* \rightarrow Q$  the extended transition function.

**Definition:**

- (1) If  $q \in Q$ , then  $\delta^*(q, \lambda) = q$
- (2) If  $x \in \Sigma^*$ ,  $\sigma \in \Sigma$  and  $q \in Q$ , then  $\delta^*(q, x\sigma) = \delta(\delta^*(q, x), \sigma)$

- d. (5 Points)  $\mathcal{F} \subseteq 2^{\Sigma^*}$  the set of all finite languages over  $\Sigma$ .

**Definition:**

- (1)  $\emptyset, \{\lambda\}, \{\sigma\} \in \mathcal{F}$  (for any  $\sigma \in \Sigma$ )
- (2) If  $L_1, L_2 \in \mathcal{F}$ , then  $L_1 \cup L_2 \in \mathcal{F}$
- (3) If  $L_1, L_2 \in \mathcal{F}$ , then  $L_1 L_2 \in \mathcal{F}$

3. (20 Points) Let  $\Sigma$  be a finite alphabet,  $M = (Q, \Sigma, q_0, A, \delta)$  be a finite state automaton, and let  $p \in Q$ . Prove that for all strings  $x, y \in \Sigma^*$ :  $\delta^*(p, xy) = \delta^*(\delta^*(p, x), y)$ . Hint: write this as

$$\forall y \quad \boxed{\forall x \quad \delta^*(p, xy) = \delta^*(\delta^*(p, x), y)}$$

and proceed by structural induction on  $y$ . To do this let  $P(y)$  be the boxed statement and prove: I.  $P(\lambda)$  is true, and II. if  $P(y)$  holds, then so does  $P(y\sigma)$  for any  $\sigma \in \Sigma$ .

**Proof:**

I. Show  $P(\lambda)$ :

$$\begin{aligned} \delta^*(p, x\lambda) &= \delta^*(p, x) && \text{(since } x = x\lambda \text{)} \\ &= \delta^*(\delta^*(p, x), \lambda) && \text{(by (1) in the recursive definition of } \delta^* \text{)} \end{aligned}$$



II. Show  $P(y) \Rightarrow P(y\sigma)$ :

Assume  $P(y)$  holds for some  $y \in \Sigma^*$ , i.e. assume:  $\forall x \quad \delta^*(p, xy) = \delta^*(\delta^*(p, x), y)$ . We must show that  $P(y\sigma)$  holds for any  $\sigma \in \Sigma$ , i.e. show:  $\forall x \quad \delta^*(p, x(y\sigma)) = \delta^*(\delta^*(p, x), y\sigma)$ . We have

$$\begin{aligned} \delta^*(p, x(y\sigma)) &= \delta^*(p, (xy)\sigma) && \text{(by the associative law)} \\ &= \delta(\delta^*(p, xy), \sigma) && \text{(by (2) in the recursive definition of } \delta^* \text{)} \\ &= \delta(\delta^*(\delta^*(p, x), y), \sigma) && \text{(by the induction hypothesis)} \\ &= \delta^*(\delta^*(p, x), y\sigma) && \text{(by (2) in the recursive definition of } \delta^* \text{)} \end{aligned}$$


Therefore  $P(y)$  holds for all  $y \in \Sigma^*$ , i.e.  $\delta^*(p, xy) = \delta^*(\delta^*(p, x), y)$  for all  $x, y \in \Sigma^*$ . ///

4. (20 Points) Let  $L_1$  and  $L_2$  be the languages over  $\{a, b\}$  accepted by the FAs  $M_1$  and  $M_2$  pictured below, respectively.

 $M_1:$  $M_2:$ 

Use the product construction to draw an FA accepting the language  $L_1 - L_2$ . Give simple verbal descriptions of the languages  $L_1$ ,  $L_2$  and  $L_1 - L_2$ . (No justification is necessary for either the drawing or the descriptions.)

**Solution:**



$$L_1 = \{ \text{strings containing } aa \}$$

$$L_2 = \{ \text{strings containing } bb \}$$

$$L_1 - L_2 = \{\text{strings containing } aa \text{ but not containing } bb\}$$

5. (20 Points) Let  $L_1$  and  $L_2$  be languages over a finite alphabet  $\Sigma$ .

a. (10 Points) Prove that  $(L_1 \cap L_2)^* \subseteq L_1^* \cap L_2^*$ .

**Proof:**

Let  $x \in (L_1 \cap L_2)^*$ . Then  $x \in (L_1 \cap L_2)^n$  for some  $n \geq 0$ . Thus  $x = x_1 x_2 \dots x_n$  for some  $x_i \in L_1 \cap L_2$  ( $1 \leq i \leq n$ ). But then both  $x_i \in L_1$  and  $x_i \in L_2$  ( $1 \leq i \leq n$ ). Therefore both  $x \in L_1^n$  and  $x \in L_2^n$ , hence  $x \in L_1^*$  and  $x \in L_2^*$ . Therefore  $x \in L_1^* \cap L_2^*$ , whence  $(L_1 \cap L_2)^* \subseteq L_1^* \cap L_2^*$ . ///

b. (10 Points) Give an example of specific  $\Sigma$ ,  $L_1$  and  $L_2$  for which  $(L_1 \cap L_2)^* \neq L_1^* \cap L_2^*$ .

**Example:**

Let  $\Sigma = \{a, b\}$ ,  $L_1 = \{a, ba\}$  and  $L_2 = \{ab, a\}$ . Then  $aba \in L_1^2 \subseteq L_1^*$  and  $aba \in L_2^2 \subseteq L_2^*$ , whence  $aba \in L_1^* \cap L_2^*$ . But  $L_1 \cap L_2 = \{a\}$  so that  $(L_1 \cap L_2)^* = \{a^n \mid n \geq 0\}$ . Thus  $aba \notin (L_1 \cap L_2)^*$  showing that  $(L_1 \cap L_2)^* \neq L_1^* \cap L_2^*$ . ///

Note: there are many other possible examples illustrating  $(L_1 \cap L_2)^* \neq L_1^* \cap L_2^*$ .