[Practice](#) [Compete](#) [Jobs](#) [Rank](#) [Leaderboard](#)

[Dashboard](#) > [Algorithms](#) > [Strings](#) > [Pangrams](#)

Badge Progress ★ ★ Points: 746.00 Rank: 39553

Pangrams

by Bidhan

[Problem](#) [Submissions](#) [Leaderboard](#) [Discussions](#) [Editorial](#) [Topics](#)

Roy wanted to increase his typing speed for programming contests. So, his friend advised him to type the sentence "The quick brown fox jumps over the lazy dog" repeatedly, because it is a *pangram*. (Pangrams are sentences constructed by using every letter of the alphabet at least once.)

After typing the sentence several times, Roy became bored with it. So he started to look for other pangrams.

Given a sentence *s*, tell Roy if it is a pangram or not.

Input Format

Input consists of a string *s*.

Constraints

Length of *s* can be at most 10^3 ($1 \leq |s| \leq 10^3$) and it may contain spaces, lower case and upper case letters. Lower-case and upper-case instances of a letter are considered the same.

Output Format

Output a line containing *pangram* if *s* is a pangram, otherwise output *not pangram*.

Sample Input

Input #1

```
We promptly judged antique ivory buckles for the next prize
```

Input #2

```
We promptly judged antique ivory buckles for the prize
```

Sample Output

Output #1

```
pangram
```



Output #2



```
not pangram
```

Explanation

In the first test case, the answer is *pangram* because the sentence contains all the letters of the English alphabet.

[f](#) [t](#) [in](#)
Submissions: 90557
Max Score: 20
Difficulty: Easy
Rate This Challenge:
☆☆☆☆☆
Need Help?
[String Basics](#)
[Alphabets](#)
[Set](#)
[More](#)

Current Buffer (saved locally, editable)  

C++  

```
1 #include <cmath>
2 #include <cstdio>
3 #include <vector>
4 #include <iostream>
5 #include <algorithm>
6 using namespace std;
7
8
9 int main() {
10     /* Enter your code here. Read input from STDIN. Print output to STDOUT */
11     int chars[26] = { 0 };
12     string st;
13
14     getline(cin, st);
15
16     for (int i = 0; i < st.size(); i++) {
17         if (isalpha(st[i])) {
18             chars[tolower(st[i]) - 'a']++;
19         }
20     }
21
22     for (int i = 0; i < sizeof(chars) / sizeof(int); i++) {
23         if (chars[i] == 0) {
24             cout << "not pangram" << "\n";
25             return 0;
26         }
27     }
28
29     cout << "pangram" << "\n";
30
31     return 0;
32 }
33
```

Line: 1 Col: 1

 Upload Code as File ☐ Test against custom input

Run Code

Submit Code

Copyright © 2017 HackerRank. All Rights Reserved

Join us on IRC at [#hackerrank](#) on freenode for hugs or bugs.

[Contest Calendar](#) | [Interview Prep](#) | [Blog](#) | [Scoring](#) | [Environment](#) | [FAQ](#) | [About Us](#) | [Support](#) | [Careers](#) | [Terms Of Service](#) | [Privacy Policy](#) | [Request a Feature](#)