

Short-Range Communication Protocols

Protocol	Range & Frequency	Use Cases	Pros	Cons
Wi-Fi	Up to 100m; 2.4 GHz & 5 GHz	Smart homes, industrial IoT, multimedia streaming	High data rate, widely available	Limited range, high power consumption
Bluetooth	Up to 100m (Class 1); 2.4 GHz	Wearables, sensors, smart devices	Energy-efficient (BLE), widely supported	Limited range and data rate
Zigbee	Up to 100m; 2.4 GHz	Mesh networking, home automation, smart lighting, industrial IoT	Low power, supports large networks	Lower data rate than Wi-Fi
Z-Wave	Up to 100m; sub-GHz (e.g., 908.42 MHz in U.S.)	Smart home automation (security, lighting, HVAC)	Low power, strong mesh networking	Proprietary, fewer devices than Zigbee

Long-Range Communication Protocols

Protocol	Range & Frequency	Use Cases	Pros	Cons
LPWAN	10–40 km; varies by tech/region	Smart cities, agriculture, logistics, remote monitoring	Low power, very long range	Limited data rates, high latency


LoRaWAN	Up to 15 km; unlicensed sub-GHz (868 MHz EU, 915 MHz US)	IoT sensors, environmental monitoring, asset tracking	Low power, long-range, bidirectional communication	Lower data rate than cellular
NB-IoT	Several km; licensed LTE cellular bands	Smart meters, asset tracking, industrial IoT, smart parking	Excellent indoor coverage, low power, secure	Needs carrier support, slightly higher cost
Sigfox	10 km urban, 50 km rural; sub-GHz ISM (868/915 MHz)	Asset tracking, smart agriculture, logistics, environmental monitoring	Ultra-low power, cost- effective, global availability	Very limited data rate, not suitable for real-time apps

Department of Computer Science and Engineering

Daffodil International University

MQTT

MQTT, or Message Queuing Telemetry Transport, is a lightweight, publish-subscribe messaging protocol designed for resource-constrained devices and low-bandwidth networks




Department of Computer Science and Engineering

Daffodil International University

HTTP

HTTP (Hypertext Transfer Protocol) is a widely used application-layer protocol for communication between devices and servers, particularly through RESTful APIs.




Department of Computer Science and Engineering

Daffodil International University

WebSocket

A WebSocket is a communication protocol that enables persistent, two-way (full-duplex) communication channels over a single TCP connection.




Department of Computer Science and Engineering

Daffodil International University

COAP

COAP, or Constrained Application Protocol, is a lightweight web transfer protocol designed for constrained devices and networks within the Internet of Things (IoT).




Department of Computer Science and Engineering

Daffodil International University

DDS

DDS (Data Distribution Service) is a protocol for IoT that enables interoperability between connected machines, enterprise systems, and mobile devices.




Department of Computer Science and Engineering

Daffodil International University

AMQP

The Advanced Message Queuing Protocol (AMQP) is an open standard application layer protocol used for reliable and secure message exchange between devices and applications.




Department of Computer Science and Engineering

Daffodil International University

XMPP

XMPP, or Extensible Messaging and Presence Protocol, is an open, XML-based protocol used in IoT for real-time communication and data exchange.



Protocol	When to Use	Typical Applications	Key Features
MQTT	Resource-constrained devices; low bandwidth, high-latency networks; publish/subscribe messaging	Device data collection, telemetry, smart sensors, centralized “hub and spoke” IoT systems	Lightweight, minimal header, QoS levels, efficient for many-to-one communication
HTTP	RESTful APIs; web interactions; client-server communication; when interoperability with standard web services is needed	Web applications, REST APIs for sensors/devices, device-to-server	Widely supported, stateless, human-readable, not optimized for low-power or real-time IoT
WebSocket	Persistent two-way client-server communication; real-time updates; streaming and interactive apps	Real-time dashboards, streaming, chat, gaming, IoT needing instant updates	Full-duplex, low latency, efficient for bi-directional real-time data
CoAP	Very constrained low-power devices and networks; RESTful control for sensors/actuators; multicast; UDP-based	Remote control/monitoring, smart agriculture, building automation, environmental monitoring	Lightweight, RESTful, multicast support, efficient for M2M (machine-to-machine)
DDS	High-performance, real-time device-to-device networks with complex data models; peer-to-peer and many-to-many	Industrial automation, robotics, autonomous vehicles, real-time control	Peer-to-peer, real-time, dynamic discovery, extensive QoS

AMQP	Enterprise scenarios needing high reliability, security, and message delivery guarantees; queue-based messaging	Financial services, enterprise integration, cloud/server backends	Robust messaging, built-in ack/persistence, granular security
XMPP	Open, extensible, XML-based real-time communication and messaging; presence/instant messaging	Instant messaging, real-time data exchange, decentralized IoT, federated device networks	Human-readable, extensible, decentralized architecture, suitable for interoperable messaging

IoT Protocol and Network Technology Mapping: When and How to Use

Network Technology	Protocol(s) Used	Typical Use Case / Scenario	Reason to Use This Pairing
Wi-Fi	MQTT, HTTP, WebSocket	High-speed data transfer in smart homes, industrial IoT, multimedia streaming, real-time dashboards	Wi-Fi offers high bandwidth and range; MQTT for lightweight messaging, HTTP for REST APIs, WebSocket for real-time bidirectional streaming
Bluetooth (BLE or Classic)	MQTT, CoAP, HTTP	Short-range sensor networks, wearables, smart	Bluetooth enables energy-efficient local communication; MQTT or CoAP used over gateway to bridge

		devices communicating locally before cloud upload	to cloud; HTTP sometimes for device configuration
LoRaWAN / LPWAN	MQTT, CoAP	Long-range, low-power IoT applications like smart agriculture, asset tracking, environmental monitoring	LoRaWAN offers long-range and low power; MQTT or CoAP used to deliver data from gateway to server/cloud efficiently
Cellular (NB-IoT, LTE)	MQTT, HTTP, CoAP	Wide-area IoT deployments needing mobility or deep indoor penetration, smart meters, parking systems	Cellular networks carry data over licensed bands; MQTT and CoAP offer lightweight messaging; HTTP for cloud APIs
Zigbee / Z-Wave	MQTT (via gateway), CoAP	Mesh networks for home automation, smart lighting, sensor clusters	Zigbee / Z-Wave manage low-power mesh at device level; gateways translate to MQTT or CoAP for cloud communication
Ethernet / Wired	MQTT, HTTP, AMQP, DDS	Industrial automation, factory floor, reliable high-speed connectivity	Wired networks provide stable, high-speed links; AMQP or DDS provide enterprise reliability and QoS; MQTT for lightweight messaging

Multicast (UDP networks)	CoAP	Group communication for constrained devices needing simultaneous control / updates	CoAP supports UDP multicast efficiently for constrained deployments
---	------	---	---