

Functional Programming

GADT: Generalized Algebraic Data Type

Dr. Gabriel Radanne

Albert-Ludwigs-Universität Freiburg, Germany

WS 2022/23

Interpreters, again

Language definition

```
1 data Term = I Integer  
2           | Add Term Term  
3           deriving (Eq, Show)
```

Interpreters, again

Evaluation

```
1 eval :: Term -> Integer
2 eval (I n) = n
3 eval (Add t u) = eval t + eval u
```

A language with multiple types

Language definition

```
1 data Term = I Integer  
2           | B Bool  
3           | Add Term Term  
4           | EqI Term Term  
5           deriving (Eq, Show)
```

A language with multiple types

Evaluation

```
1 type Value = Int Integer | Bool Bool
2           deriving Show
3
4 eval :: Term -> Value
5 eval (I n) = Int n
6 eval (B b) = Bool b
7 eval (Add t t') = case (eval t, eval t') of
8                   (Int i, Int i2) -> Int (i + i2)
9 eval (Eq1 t t') = case (eval t, eval t') of
10                  (Int i, Int i2) -> Bool (i == i2)
11                  (Bool i, Bool i2) -> Bool (i == i2)
```

Issues with the interpreter

- The interpreter can fail because of type mismatch.
- We need to deal with failures manually (for instance by making the interpreter monadic).
- The more values we have in the language, the more complicated it becomes.
- The Haskell type system does not help us.

Issues with the interpreter

- The interpreter can fail because of type mismatch.
- We need to deal with failures manually (for instance by making the interpreter monadic).
- The more values we have in the language, the more complicated it becomes.
- The Haskell type system does not help us.

Issues with the interpreter

- The interpreter can fail because of type mismatch.
- We need to deal with failures manually (for instance by making the interpreter monadic).
- The more values we have in the language, the more complicated it becomes.
- The Haskell type system does not help us.

Issues with the interpreter

- The interpreter can fail because of type mismatch.
- We need to deal with failures manually (for instance by making the interpreter monadic).
- The more values we have in the language, the more complicated it becomes.
- The Haskell type system does not help us.

GADTs to the rescue!

Algebraic Data Type

```
1 data Maybe a =  
2   Nothing  
3   | Just a
```

GADTs to the rescue!

Generalized Algebraic Data Type

```
1 {-# LANGUAGE GADTs #-}  
2  
3 data Maybe a where  
4   Nothing :: Maybe a  
5   Just    :: a -> Maybe a
```

- Now we also specify the return type of the data constructors!
- We cannot change the type constructor **Maybe**, but its arguments may vary

GADTs to the rescue!

Generalized Algebraic Data Type

```
1 {-# LANGUAGE GADTs #-}  
2  
3 data Maybe a where  
4   Nothing :: Maybe a  
5   Just    :: a -> Maybe a
```

- Now we also specify the return type of the data constructors!
- We cannot change the type constructor **Maybe**, but its arguments may vary

Language definition without GADTs

```
1 data Term =  
2   I Integer  
3   | B Bool  
4   | Add Term Term  
5   | Eql Term Term
```

Language definition with GADT syntax

```
1 data Term where  
2   I :: Integer -> Term  
3   B :: Bool -> Term  
4   Add :: Term -> Term -> Term  
5   Eql :: Term -> Term -> Term
```

Language definition with GADTs

```
1 data Term a where  
2   I :: Integer -> Term Integer  
3   B :: Bool -> Term Bool  
4   Add :: Term (?) -> Term (?) -> Term (?)  
5   Eql :: Term (?) -> Term (?) -> Term (?)
```

Language definition with GADTs

```
1 data Term a where
2   I :: Integer -> Term Integer
3   B :: Bool -> Term Bool
4   Add :: Term Integer -> Term Integer -> Term Integer
5   Eql :: Term (?) -> Term (?) -> Term (?)
```


Language definition with GADTs

```
1 data Term a where
2   I :: Integer -> Term Integer
3   B :: Bool -> Term Bool
4   Add :: Term Integer -> Term Integer -> Term Integer
5   Eq1 :: (Eq x) => Term x -> Term x -> Term Bool
```

- Read the last line as “there exists some type x such that x is an instance of **Eq** and the two arguments have the **same** type x .”

Evaluation for GADTs

```
1 eval :: Term a -> a  -- This type annotation is mandatory
2 eval (I i) = i
3 eval (B b) = b
4 eval (Add t t') = eval t + eval t'
5 eval (Eq1 t t') = eval t == eval t'
```

- This kind of interpreter is called “tag-less”, because it does not require type tags like the data constructors `Int` and `Bool`.
- Pattern matching specializes the type `a` according to the return type of the constructor.
- The corresponding right hand side is checked against this specialization of type `a`.

Evaluation for GADTs

```
1 eval :: Term a -> a  -- This type annotation is mandatory
2 eval (I i) = i
3 eval (B b) = b
4 eval (Add t t') = eval t + eval t'
5 eval (Eq1 t t') = eval t == eval t'
```

- This kind of interpreter is called “tag-less”, because it does not require type tags like the data constructors `Int` and `Bool`.
- Pattern matching specializes the type `a` according to the return type of the constructor.
- The corresponding right hand side is checked against this specialization of type `a`.

Evaluation for GADTs

```
1 eval :: Term a -> a  -- This type annotation is mandatory
2 eval (I i) = i
3 eval (B b) = b
4 eval (Add t t') = eval t + eval t'
5 eval (Eq1 t t') = eval t == eval t'
```

- This kind of interpreter is called “tag-less”, because it does not require type tags like the data constructors `Int` and `Bool`.
- Pattern matching specializes the type `a` according to the return type of the constructor.
- The corresponding right hand side is checked against this specialization of type `a`.

Evaluation for GADTs

```
1 eval :: Term a -> a  -- This type annotation is mandatory
2 eval (I i) = i
3 eval (B b) = b
4 eval (Add t t') = eval t + eval t'
5 eval (Eq1 t t') = eval t == eval t'
```

- This kind of interpreter is called “tag-less”, because it does not require type tags like the data constructors `Int` and `Bool`.
- Pattern matching specializes the type `a` according to the return type of the constructor.
- The corresponding right hand side is checked against this specialization of type `a`.

Evaluation for GADTs

```
1 eval :: Term a -> a  -- This type annotation is mandatory
2 eval (I i) = i
3 eval (B b) = b
4 eval (Add t t') = eval t + eval t'
5 eval (Eq1 t t') = eval t == eval t'
```

- This kind of interpreter is called “tag-less”, because it does not require type tags like the data constructors `Int` and `Bool`.
- Pattern matching specializes the type `a` according to the return type of the constructor.
- The corresponding right hand side is checked against this specialization of type `a`.

Evaluation for GADTs

```
1 eval :: Term a -> a  -- This type annotation is mandatory
2 eval (I i) = i
3 eval (B b) = b
4 eval (Add t t') = eval t + eval t'
5 eval (Eq1 t t') = eval t == eval t'
```

- This kind of interpreter is called “tag-less”, because it does not require type tags like the data constructors **Int** and **Bool**.
- Pattern matching specializes the type `a` according to the return type of the constructor.
- The corresponding right hand side is checked against this specialization of type `a`.

Evaluation for GADTs

```
1 eval :: Term a -> a  -- This type annotation is mandatory
2 eval (I i) = i
3 eval (B b) = b
4 eval (Add t t') = eval t + eval t'
5 eval (Eq1 t t') = eval t == eval t'
```

- This kind of interpreter is called “tag-less”, because it does not require type tags like the data constructors **Int** and **Bool**.
- Pattern matching specializes the type *a* according to the return type of the constructor.
- The corresponding right hand side is checked against this specialization of type *a*.

Evaluation for GADTs

```
1 eval :: Term a -> a  -- This type annotation is mandatory
2 eval (I i) = i
3 eval (B b) = b
4 eval (Add t t') = eval t + eval t'
5 eval (Eq1 t t') = eval t == eval t'
```

- This kind of interpreter is called “tag-less”, because it does not require type tags like the data constructors **Int** and **Bool**.
- Pattern matching specializes the type `a` according to the return type of the constructor.
- The corresponding right hand side is checked against this specialization of type `a`.

What about functions?

We want to add functions to our language.

First try

```
1 data FExp a where
2   Var :: FExp a
3   Lam :: FExp b -> FExp (a -> b)
4   App :: FExp (a -> b) -> FExp a -> FExp b
```

This doesn't work: not enough type information for variables and lambdas.

What about functions?

We want to add functions to our language.

First try

```
1 data FExp a where  
2   Var :: FExp a  
3   Lam :: FExp b -> FExp (a -> b)  
4   App :: FExp (a -> b) -> FExp a -> FExp b
```

This doesn't work: not enough type information for variables and lambdas.

What about functions?

We want to add functions to our language.

First try

```
1 data FExp a where  
2   Var :: FExp a  
3   Lam :: FExp b -> FExp (a -> b)  
4   App :: FExp (a -> b) -> FExp a -> FExp b
```

This doesn't work: not enough type information for variables and lambdas.

Existential Types

In the definition of `App`, `a` is present in the argument types, but not in the result. Such a type variable stands for an *existential type*:

For each use of `App` there is some type `a` so that the types of the subterms work out.

```
1 App :: FExp (a -> b) -> FExp a -> FExp b
```

Demo!

Existential Types

In the definition of `App`, `a` is present in the argument types, but not in the result. Such a type variable stands for an *existential type*:

For each use of `App` there is some type `a` so that the types of the subterms work out.

```
1 App :: FExp (a -> b) -> FExp a -> FExp b
```

Demo!

Back to functions!

Type definition

```
1 data FExp e a where  
2   App :: FExp e (a -> b) -> FExp e a -> FExp e b  
3   Lam :: FExp (a, e) b -> FExp e (a -> b)  
4   Var :: Nat e a -> FExp e a  
5  
6 data Nat e a where  
7   Zero :: Nat (a, b) a  
8   Succ :: Nat e a -> Nat (b, e) a
```

Demo!

Back to functions!

Type definition

```
1 data FExp e a where  
2   App :: FExp e (a -> b) -> FExp e a -> FExp e b  
3   Lam :: FExp (a, e) b -> FExp e (a -> b)  
4   Var :: Nat e a -> FExp e a  
5  
6 data Nat e a where  
7   Zero :: Nat (a, b) a  
8   Succ :: Nat e a -> Nat (b, e) a
```

Demo!

Back to functions!

Type definition

```
1 data FExp e a where  
2   App :: FExp e (a -> b) -> FExp e a -> FExp e b  
3   Lam :: FExp (a, e) b -> FExp e (a -> b)  
4   Var :: Nat e a -> FExp e a  
5  
6 data Nat e a where  
7   Zero :: Nat (a, b) a  
8   Succ :: Nat e a -> Nat (b, e) a
```

Demo!

Back to functions!

Type definition

```
1 data FExp e a where  
2   App :: FExp e (a -> b) -> FExp e a -> FExp e b  
3   Lam :: FExp (a, e) b -> FExp e (a -> b)  
4   Var :: Nat e a -> FExp e a  
5  
6 data Nat e a where  
7   Zero :: Nat (a, b) a  
8   Succ :: Nat e a -> Nat (b, e) a
```

Demo!

Origin of GADTs

- Comparatively recent extension to Haskell's type system.
Invented by 3 different groups:
 - ▶ Augustsson & Petersson (1994): Silly Type Families
 - ▶ Cheney & Hinze (2003): First-Class Phantom Types.
 - ▶ Xi, Chen & Chen (2003): Guarded Recursive Datatype Constructors.
- Type *checking* is decidable.
- Type *inference* is undecidable.
- Pattern matching is more complicated.

Origin of GADTs

- Comparatively recent extension to Haskell's type system.
Invented by 3 different groups:
 - ▶ Augustsson & Petersson (1994): Silly Type Families
 - ▶ Cheney & Hinze (2003): First-Class Phantom Types.
 - ▶ Xi, Chen & Chen (2003): Guarded Recursive Datatype Constructors.
- Type *checking* is decidable.
- Type *inference* is undecidable.
- Pattern matching is more complicated.

Origin of GADTs

- Comparatively recent extension to Haskell's type system.
Invented by 3 different groups:
 - ▶ Augustsson & Petersson (1994): Silly Type Families
 - ▶ Cheney & Hinze (2003): First-Class Phantom Types.
 - ▶ Xi, Chen & Chen (2003): Guarded Recursive Datatype Constructors.
- Type *checking* is decidable.
- Type *inference* is undecidable.
- Pattern matching is more complicated.

Origin of GADTs

- Comparatively recent extension to Haskell's type system.
Invented by 3 different groups:
 - ▶ Augustsson & Petersson (1994): Silly Type Families
 - ▶ Cheney & Hinze (2003): First-Class Phantom Types.
 - ▶ Xi, Chen & Chen (2003): Guarded Recursive Datatype Constructors.
- Type *checking* is decidable.
- Type *inference* is undecidable.
- Pattern matching is more complicated.

Wrapping up

- GADTs can express extra properties in types:



- We leverage Haskell's type system.
- GADTs do not solve *all* the problems. For example, you can try to write a function of type

```
1 parse :: String -> Expr a
```

GADTs can be combined with other Haskell features such as type classes and type families.

- GADTs become very complex when the domain grows!

Wrapping up

- GADTs can express extra properties in types:



- We leverage Haskell's type system.
- GADTs do not solve *all* the problems. For example, you can try to write a function of type

```
1 parse :: String -> Expr a
```

GADTs can be combined with other Haskell features such as type classes and type families.

- GADTs become very complex when the domain grows!

Wrapping up

- GADTs can express extra properties in types:
 - ▶
- We leverage Haskell's type system.
- GADTs do not solve *all* the problems. For example, you can try to write a function of type
1 `parse :: String -> Expr a`
GADTs can be combined with other Haskell features such as type classes and type families.
- GADTs become very complex when the domain grows!

Wrapping up

- GADTs can express extra properties in types:
 - ▶
 - We leverage Haskell's type system.
 - GADTs do not solve *all* the problems. For example, you can try to write a function of type
- ```
1 parse :: String -> Expr a
```

GADTs can be combined with other Haskell features such as type classes and type families.

- GADTs become very complex when the domain grows!

# Wrapping up

- GADTs can express extra properties in types:
    - ▶
  - We leverage Haskell's type system.
  - GADTs do not solve *all* the problems. For example, you can try to write a function of type
- ```
1 parse :: String -> Expr a
```

GADTs can be combined with other Haskell features such as type classes and type families.

- GADTs become very complex when the domain grows!

Wrapping up

- GADTs can express extra properties in types:
 - ▶
- We leverage Haskell's type system.
- GADTs do not solve *all* the problems. For example, you can try to write a function of type
1 `parse :: String -> Expr a`
GADTs can be combined with other Haskell features such as type classes and type families.
- GADTs become very complex when the domain grows!