

Exercise 2.5: Create a Simple Deployment

Creating a pod does not take advantage of orchestration abilities of Kubernetes. We will now create a Deployment which gives us scalability, reliability, and updates.

1. Now run a containerized webserver **nginx**. Use **kubectl create** to create a simple, single replica deployment running the nginx web server. It will create a single pod as we did previously but with new controllers to ensure it runs as well as other features.

```
student@cp:~$ kubectl create deployment firstpod --image=nginx
```

```
deployment.apps/firstpod created
```

2. Verify the new deployment exists and the desired number of pods matches the current number. Using a comma, you can request two resource types at once. The **Tab** key can be helpful. Type enough of the word to be unique and press the **Tab** key, it should complete the word. The deployment should show a number 1 for each value, such that the desired number of pods matches the up-to-date and running number. The pod should show zero restarts.

```
student@cp:~$ kubectl get deployment,pod
```

NAME	READY	UP-TO-DATE	AVAILABLE	AGE
deployment.apps/firstpod	1/1	1	1	2m42s

NAME	READY	STATUS	RESTARTS	AGE
pod/firstpod-7d88d7b6cf-lrsbk	1/1	Running	0	2m42s

3. View the details of the deployment, then the pod. Work through the output slowly. Knowing what a healthy deployment and looks like can be helpful when troubleshooting issues. Again the **Tab** key can be helpful when using long auto-generated object names. You should be able to type firstpod**Tab** and the name will complete when viewing the pod.

```
student@cp:~$ kubectl describe deployment firstpod
```

```
Name:                firstpod
Namespace:           default
CreationTimestamp:    Tue, 21 Sep 2021 16:36:29 +0000
Labels:               app=firstpod
Annotations:          deployment.kubernetes.io/revision=1
Selector:             app=firstpod
Replicas:             1 desired | 1 updated | 1 total | 1 available....
StrategyType:         RollingUpdate
MinReadySeconds:      0
<output_omitted>
```

```
student@cp:~$ kubectl describe pod firstpod-6bb4574d94-rqk76
```

```
Name:                firstpod-6bb4574d94-rqk76
Namespace:           default
Priority:             0
PriorityClassName:    <none>
Node:                cp/10.128.0.2
Start Time:          Tue, 21 Sep 2021 16:36:29 +0000
Labels:               pod-template-hash=2660130850
                     app=firstpod
```

```

Annotations:    cni.projectcalico.org/podIP: 192.168.200.65/32
Status:         Running
IP:             192.168.200.65
Controlled By:  ReplicaSet/firstpod-6bb4574d94

<output_omitted>

```

4. Note that the resources are in the default namespace. Get a list of available namespaces.

```
student@cp:~$ kubectl get namespaces
```

NAME	STATUS	AGE
default	Active	20m
kube-node-lease	Active	20m
kube-public	Active	20m
kube-system	Active	20m

5. There are four default namespaces. Look at the pods in the kube-system namespace.

```
student@cp:~$ kubectl get pod -n kube-system
```

NAME	READY	STATUS	RESTARTS	AGE
calico-node-5ftrr	2/2	Running	0	24m
calico-node-f7zrw	2/2	Running	0	21m
coredns-fb8b8dcf-cmkds	1/1	Running	0	24m
coredns-fb8b8dcf-grltk	1/1	Running	0	24m
etcd-v141-r24p	1/1	Running	0	23m

<output_omitted>

6. Now look at the pods in a namespace that does not exist. Note you do not receive an error.

```
student@cp:~$ kubectl get pod -n fakenamespace
```

No resources found in fakenamespaces namespace.

7. You can also view resources in all namespaces at once. Use the `--all-namespaces` options to select objects in all namespaces at once.

```
student@cp:~$ kubectl get pod --all-namespaces
```

NAMESPACE	NAME	READY	STATUS	RESTARTS	AGE
default	firstpod-69cfdfd8d9-kj6ql	1/1	Running	0	44m
kube-system	calico-node-5ftrr	2/2	Running	0	92m
kube-system	calico-node-f7zrw	2/2	Running	0	89m
kube-system	coredns-fb8b8dcf-cmkds	1/1	Running	0	92m

<output_omitted>

8. View several resources at once. Note that most resources have a short name such as `rs` for `ReplicaSet`, `po` for `Pod`, `svc` for `Service`, and `ep` for `endpoint`. Note the endpoint still exists after we deleted the pod.

```
student@cp:~$ kubectl get deploy,rs,po,svc,ep
```

NAME	READY	UP-TO-DATE	AVAILABLE	AGE
deployment.apps/firstpod	1/1	1	1	4m

NAME	DESIRED	CURRENT	READY....
replicaset.apps/firstpod-6bb4574d94-rqk76	1	1	1

NAME	READY	STATUS	RESTARTS	AGE
------	-------	--------	----------	-----

```
pod/firstpod-6bb4574d94-rqk76 1/1    Running    0          4m
```

NAME	TYPE	CLUSTER-IP	EXTERNAL-IP	PORT(S)	AGE
service/basicservice	NodePort	10.108.147.76	<none>	80:31601/TCP	21m
service/kubernetes	ClusterIP	10.96.0.1	<none>	443/TCP	21m

NAME	ENDPOINTS	AGE
endpoints/basicservice	<none>	21m
endpoints/kubernetes	10.128.0.3:6443	21m

9. Delete the ReplicaSet and view the resources again. Note that the age on the ReplicaSet and the pod it controls is now less than a minute of age. The deployment operator started a new ReplicaSet operator when we deleted the existing one. The new ReplicaSet started another pod when the desired spec did not match the current status.

```
student@cp:~$ kubectl delete rs firstpod-6bb4574d94-rqk76
```

```
replicaset.apps "firstpod-6bb4574d94-rqk76" deleted
```

```
student@cp:~$ kubectl get deployment,rs,po,svc,ep
```

```
NAME                                READY  UP-TO-DATE  AVAILABLE  AGE
deployment.apps/firstpod  1/1    1            1           7m
```


NAME	DESIRED	CURRENT....
replicaset.apps/firstpod-6bb4574d94-rqk76	1	1

NAME	READY	STATUS	RESTARTS	AGE
pod/firstpod-7d99ffc75-p9hbw	1/1	Running	0	12s

NAME	TYPE	CLUSTER-IP	EXTERNAL-IP	PORT(S)	AGE
service/kubernetes	ClusterIP	10.96.0.1	<none>	443/TCP	24m

NAME	ENDPOINTS	AGE
endpoints/kubernetes	10.128.0.2:6443	80m
endpoints/basicservice	<none>	21m

10. This time delete the top-level controller. After about 30 seconds for everything to shut down you should only see the cluster service and endpoint remain for the cluster and the service we created.

```
student@cp:~$ kubectl delete deployment firstpod
```

```
deployment.apps "firstpod" deleted
```

```
student@cp:~$ kubectl get deployment,rs,po,svc,ep
```

NAME	TYPE	CLUSTER-IP	EXTERNAL-IP	PORT(S)	AGE
service/basicservice	NodePort	10.108.147.76	<none>	80:31601/TCP	35m
kubernetes	ClusterIP	10.96.0.1	<none>	443/TCP	24m

NAME	ENDPOINTS	AGE
endpoints/basicservice	<none>	21m
kubernetes	10.128.0.3:6443	24m

11. As we won't need it for a while, delete the basicservice service as well.

```
student@cp:~$ kubectl delete svc basicservice
```

```
service "basicservice" deleted
```