

## Linear scale



1000 Ohm-m



10



## Clay

**Sand**

Gravel / rock

15 Ohm-m  
pos: 0.7%

40 Ohm-m  
pos: 2.0%

500 Ohm-m  
pos: 25.0%

2000 Ohm-m  
pos: 100.0%

## Logarithmic scale



2

200

5



## Clay

## Sand

Gravel / rock

15 Ohm-m  
pos: 46.9%

40 Ohm-m  
pos: 57.5%

500 Ohm-m  
pos: 84.9%

2000 Ohm-m  
pos: 100.0%

## Comparison table

| Material      | rho (Ohm-m) | log10(rho) | Pos — linear | Color                                                                             | Pos — log | Color                                                                               |
|---------------|-------------|------------|--------------|-----------------------------------------------------------------------------------|-----------|-------------------------------------------------------------------------------------|
| Saltwater     | 0.2         | -0.70      | 0.0%         |  | 0.0%      |  |
| Clay          | 15          | 1.18       | 0.7%         |  | 46.9%     |  |
| Peat          | 40          | 1.60       | 2.0%         |  | 57.5%     |  |
| Sand          | 500         | 2.70       | 25.0%        |  | 84.9%     |  |
| Gravel / rock | 2000        | 3.30       | 100.0%       |  | 100.0%    |  |