

Recent research achievements

Boris Zolotov, МКН СПбГУ

Advanced Mathematics

Friday, December 20



Part 1

Sublinear Explicit Incremental Voronoi Diagrams

Voronoi Diagram: basics

Voronoi diagram of $S = \{s_1, \dots, s_N\}$: subdivision of the Euclidean plane, for each q inside the *cell* of s_i



$$\text{dist}(q, s_i) < \text{dist}(q, s_j), \quad j \neq i.$$



Voronoi Diagram: basics

Voronoi diagram of $S = \{s_1, \dots, s_N\}$: subdivision of the Euclidean plane, for each q inside the *cell* of s_i



$$\text{dist}(q, s_i) < \text{dist}(q, s_j), \quad j \neq i.$$



Voronoi Diagram: basics

Voronoi diagram of $S = \{s_1, \dots, s_N\}$: subdivision of the Euclidean plane, for each q inside the *cell* of s_i

$$\text{dist}(q, s_i) < \text{dist}(q, s_j), \quad j \neq i.$$



Dynamic VD: setting

Incremental Voronoi Diagram

Maintain initially empty Voronoi diagram under insertion of new sites

There is a linear-time solution, no faster solutions possible: there may be $O(N)$ changes per insertion.

Dynamic VD: setting

Incremental Voronoi Diagram

Maintain initially empty Voronoi diagram under insertion of new sites

There is a linear-time solution, no faster solutions possible: there may be $O(N)$ changes per insertion.

Incremental Combinatorial Voronoi Diagram

Maintain the graph of initially empty Voronoi diagram under insertion of new sites

There is a naive linear-time algorithm. Can we find a faster solution?

Dynamic VD: combinatorial changes

Theorem (Allen et al. 2017)


The number of cells with combinatorial changes is $O(N^{\frac{1}{2}})$ amortized, there are a constant number of combinatorial changes per cell, cells with changes are connected.

Dynamic VD: combinatorial changes


Theorem (Allen et al. 2017)

The number of cells with combinatorial changes is $O(N^{\frac{1}{2}})$ amortized, there are a constant number of combinatorial changes per cell, cells with changes are connected.


When we are inserting new site s_N , the graph of the VD undergoes operation called *flarb*.



(a) Graph before flarb



(b) Graph after flarb




(c) Flarb on a VD

Identifying changes

Theorem: Let g be a cell adjacent to f .
Cell g needs to undergo changes \iff
circle of either of its vertices that are
paws of f encloses s_N .


Allen et al. 2017



Identifying changes

Theorem: Let g be a cell adjacent to f .
Cell g needs to undergo changes \iff
circle of either of its vertices that are
paws of f encloses s_N .

Allen et al. 2017



Dynamic circle reporting structure (Chan 2010; Allen et al. 2017)

Returns all k circles enclosing given point in $\tilde{O}(k)$. Addition and deletion of a circle in $\tilde{O}(1)$.

Description of data structure

Definition


A cell is *big* if it has size at least $N^{\frac{1}{4}}$. Otherwise it is *small*.

Description of data structure

Definition

A cell is *big* if it has size at least $N^{\frac{1}{4}}$. Otherwise it is *small*.

- (1) Graph of VD in a form of adjacency list,
- (2) *Dynamic nearest neighbor* structure for sites,
- (3) Graph of big cells stored as adjacency list,
- (4) For each big cell:
 - linked list of DCRs,
 - binary search tree of vertices in circular order.



Handling insertion

Initialize queue; look at cells one-by-one, on each step add to it unprocessed cells with changes, then implement changes.

Handling insertion

Initialize queue; look at cells one-by-one, on each step add to it unprocessed cells with changes, then implement changes.

- Small cell: look at each paw to find neighboring cells needing changes, add them to the queue.
- Big cell: ask DCRs to return Voronoi circles that enclose s_N , add corresponding cells to the queue.

Handling insertion

Initialize queue; look at cells one-by-one, on each step add to it unprocessed cells with changes, then implement changes.

- Small cell: look at each paw to find neighboring cells needing changes, add them to the queue.
- Big cell: ask DCRs to return Voronoi circles that enclose s_N , add corresponding cells to the queue.

$$\text{Time complexity: } \tilde{O} \left(sN^{\frac{1}{4}} + \sum_{i=1}^{|B|} \left(\left\lceil \frac{|b_i|}{N^{\frac{1}{4}}} \right\rceil + \ell_i \right) + N^{\frac{3}{4}} + sN^{\frac{1}{4}} \right).$$

Handling insertion

Initialize queue; look at cells one-by-one, on each step add to it unprocessed cells with changes, then implement changes.

- Small cell: look at each paw to find neighboring cells needing changes, add them to the queue.
- Big cell: ask DCRs to return Voronoi circles that enclose s_N , add corresponding cells to the queue.

$$\text{Time complexity: } \tilde{O} \left(sN^{\frac{1}{4}} + \sum_{i=1}^{|B|} \left(\left\lceil \frac{|b_i|}{N^{\frac{1}{4}}} \right\rceil + \ell_i \right) + N^{\frac{3}{4}} + sN^{\frac{1}{4}} \right).$$

This is $\tilde{O}(N^{\frac{3}{4}})$ amortized.

Ongoing research:

Optimal-Time Incremental Voronoi Diagrams

- Allen, S. R., Barba, L., Iacono, J., and Langerman, S. (2017). Incremental voronoi diagrams. *Discrete & Computational Geometry*, 58(4):822–848.
- Chan, T. M. (2010). A dynamic data structure for 3-d convex hulls and 2-d nearest neighbor queries. *J. ACM*, 57(3):16:1–16:15.