LX6/7 (Liverpool) BLOCK DIAGRAM

PCB STACK UP
6L Dis.

LAYER 1 : TOP
LAYER 2 : SGND
LAYER 3 : IN1(High)
LAYER 4 : IN2(Low)
LAYER 5 : SVCC
LAYER 6 : BOT





HOLE



NB5

PROJECT : LX6_LX7
Quanta Computer Inc.

Size	Document Number	Rev
Custom	Clock Gen(9LRS3197)/HOLES	1A

Date: Tuesday, February 02, 2010 | Sheet 2 of 44



AUBURNDALE/CLARKSFIELD PROCESSOR (DDR3)



PROJECT : LX6_LX7 Quanta Computer Inc.		
NB5	Size: Custom	Document Number: PROCESSER 2/4(DDR) Rev: 1A
	Date: Tuesday, February 02, 2010	Sheet 4 of 44



	DIS	SG/UMA
Rc	NA	470
Rd	NA	0 ohm
Re	NA	0 ohm
Rf	NA	NA

	DIS	SG/UMA
Ra	0 ohm	NA
Rb	NA	STUFF

PROJECT : LX6_LX7
Quanta Computer Inc.
NB5
PROCESSER 3/4(POWER)
Rev 1A
Tuesday, February 02, 2010
Sheet 5 of 44

AUBURNDALE/CLARKSFIELD PROCESSOR (GND)



AUBURNDALE/CLARKSFIELD PROCESSOR(RESERVED, CFG)



	UMA	SG/DIS
R90	NA	NA
R77	NA	3.01K
R79	NA	NA
R87	NA	NA

	1	0
CFG4 (Display Port Presence)	Disabled; No Physical Display Port attached to Embedded Diplay Port	Enabled; An external Display port device is connected to the Embedded Display port
CFG0 (PCI-Epress Configuration Select)	Single PEG	Bifurcation enabled
CFG3 (PCI-Epress Static Lane Reversal)	Normal Operation	Lane Numbers Reversed 15 -> 0 , 14 -> 1

```
CFG[ 1:0 ] - PCI_Epress Configuration Select
* 11= 1 x 16 PEG
* 10= 2 x 8 PEG
```

The Clarkfield processor's PCI Express interface may not meet PCI Express 2.0 jitter specifications. Intel recommends placing a 3.01K +/- 5% pull down resistor to VSS on CFG[7] pin for both rPGA and BGA components. This pull down resistor should be removed when this issue is fixed.

NB5

PROJECT : LX6_LX7
Quanta Computer Inc.

Size	Document Number	Rev
Custom	PROCESSER 4/4 (GND)	1A

Date: Tuesday, February 02, 2010 Sheet 6 of 44

INTVRMEN - Integrated SUS 1.1V VRM Enable
High - Enable Internal VRs

IBEX PEAK-M (HDA,JTAG,SATA)



UMA CRT,LVDS&HDMI signals

IBEX PEAK-M (LVDS,DDI)



UMA HDMI signals

For AUDIO



RTC

1mA



4M byte SPI ROM

PV change short pad



Socket: DG008000031
MXIC AKE39FP0Z00
WINBOND AKE391P0N00

NB5	PROJECT : LX6_LX7 Quanta Computer Inc.	
Size: Custom	Document Number: PCH 1/5 (SATA,HDA,LPC)	Rev: 1A
Date: Tuesday, February 02, 2010	Sheet 7 of 44	

IBEX PEAK-M (GND)



IBEX PEAK-M (PCI-E,SMBUS,CLK)









IBEX PEAK-M (PCI,USB,NVRAM)



IBEX PEAK-M (DMI,FDI,GPIO)



Left_USB
E-Sata
Fingerprint
Touchscreen
Webcam

Right_USB 17"/SATA LED
Right_USB 15"/SATA LED
WLAN
Right_USB 15"
Card Reaer
Blue tooth

FOR SG ONLY

DGPU_SELECT#	R515	0_4	REQ2#		
EDID_SELECT#	R532	0_4	REQ3#		
PWM_SELECT#	R202	0_4	PCI_GNT2#		
DGPU_PWR_EN	R163	0_4	SATA2GP	SATA2GP	10
DGPU_PWROK	R204	0_4	TACH0	TACH0	10
DGPU_HOLD_RST#	R461	0_4	SATA4GP	SATA4GP	10

2,7,8,11,36,37,43 +1.05V
2,3,7,8,10,11,12,13,21,22,23,24,25,26,27,28,29,30,31,32,33,34,37,40,41 +3V
3,8,10,11,41 +3VS5

PROJECT : LX6_LX7
Quanta Computer Inc.
NB5
Size: Custom | Document Number: PCH 3/5 (PCI,ONFI,USB,DMI) | Rev: 1A
Date: Tuesday, February 02, 2010 | Sheet 9 of 44









BOARD ID SETTING

Board ID	ID5	ID4	ID3	ID2	ID1	ID0
TBD	RD5 (0)	RD4 (0)	RD3 (0)	RD2 (0)	RD1 (0)	RU0 (1)
TBD	RD5 (0)	RD4 (0)	RD3 (0)	RD2 (0)	RU1 (1)	RD0 (0)
TBD	RD5 (0)	RD4 (0)	RD3 (0)	RD2 (0)	RU1 (1)	RU0 (1)
TBD	RD5 (0)	RD4 (0)	RD3 (0)	RU2 (1)	RD1 (0)	RD0 (0)
TBD	RD5 (0)	RD4 (0)	RD3 (0)	RU2 (1)	RD1 (0)	RU0 (1)
TBD	RD5 (0)	RD4 (0)	RD3 (0)	RU2 (1)	RU1 (1)	RD0 (0)
TBD	RD5 (0)	RD4 (0)	RD3 (0)	RU2 (1)	RU1 (1)	RU0 (1)

Board ID	ID0	ID1	ID2	ID3	ID4	ID5
LX6	0	1				
LX7	1	0				
Discrete			0	0		
UMA			0	1		
SG			1	0		
LX7_No Subwoofer	1	1				



NB5

PROJECT : LX6_LX7
Quanta Computer Inc.

Size: Custom | Document Number: PCH 4/5 (GPIO & Strap) | Rev: 1A
Date: Tuesday, February 02, 2010 | Sheet 10 of 44



	DIS	SG/UMA
Ra	0 ohm	NA
Rb	NA	0 ohm
Rc	0 ohm	NA
Rd	NA	0 ohm

PROJECT :	LX6_LX7
	Quanta Computer Inc.
Size: Custom	Document Number: PCH 5/5 (POWER)
Rev: 1A	
Date: Tuesday, February 02, 2010	Sheet 11 of 44

NB5





PROJECT :	LX6_LX7
	Quanta Computer Inc.
Size	Custom
Document Number	DDR3 DIMM-1
Rev	1A
Date:	Tuesday, February 02, 2010
Sheet	13 of 44







SI Del R43,R38,C57







	For PARK	For Madison
MEM_CALRNP0		stuff
MEM_CALRNP1	stuff	
MEM_CALRNP2		stuff

DDR3/GDDR3 Memory Stuff Option

	GDDR5	GDDR3	DDR3
+1.5V_VGA	1.5V	1.8V/1.5V	1.5V
Ra	40.2R	40.2R	40.2R
Rb	100R	100R	100R

Designator		For Mannhatton
Ra		10K
Rb		51R
Rc		DNI
Ca		68pF

PROJECT : LX6_LX7
Quanta Computer Inc.
NB5
Size: Custom | Document Number: ATI M97-M2 (MEM I/F) 2/5 | Rev: 1A
Date: Tuesday, February 02, 2010 | Sheet 15 of 44



GPIO15	GPIO20	+VGACORE
Low	Low	1.05V
Low	High	0.95V
High	Low	0.9V
High	High	0.9V

GPIO6	+VDDCI
High	1.07V
Low	1.12V

MEM_ID[3:0]	Vendor	Type	Vendor P/N
0000	Hinyx	64*16-800MHZ	H5TQ1G63BFR-12C
0001	Samsung	64*16-800MHZ	K4W1G1646E-HC12
0010	Samsung	64*16-900MHZ	K4W1G1646E-HC11
0011			Reserved
0100			Reserved
0101			Reserved
0110			Reserved
0111			Reserved
1000			Reserved
1001			Reserved
1010			Reserved
1011			Reserved
1100			Reserved
1101			Reserved
1110			Reserved
1111			Reserved

NB5

PROJECT : LX6_LX7
Quanta Computer Inc.

Size: Custom | Document Number: ATI M97-M2 (DISPLAY) 3/5 | Rev: 1A

Date: Tuesday, February 02, 2010 | Sheet 16 of 44





Memory Aperture size fix 256M

GPIO9 BIOSROM		GPIO13 ROMIDCFG2	GPIO12 ROMIDCFG1	GPIO11 ROMIDCFG0
0	128M	0	0	0
0	256M	0	0	1
0	64M	0	1	0
0	32M	0	1	1
0	512M	1	0	0
0	1G	1	0	1
0	2G	1	1	0
0	4G	1	1	1

It is a shared pin strap with CONFIG[2:0] if BIOS_ROM_EN is set to 0.

CONFIGURATION STRAPS

ALLOW FOR PULLUP PADS FOR THESE STRAPS AND IF THESE GPIOS ARE USED, THEY MUST NOT CONFLICT DURING RESET

RECOMMENDED SETTINGS
0= DO NOT INSTALL RESISTOR
1 = INSTALL 10K RESISTOR
X = DESIGN DEPENDANT
NA = NOT APPLICABLE

STRAPS	PIN	DESCRIPTION OF DEFAULT SETTINGS	
TX_PWRS_ENB	GPIO0	**Transmitter Power Savings Enable** 0: 50% Tx output swing for mobile mode 1: full Tx output swing (Default setting for Desktop)	1
TX_DEEMPH_EN	GPIO1	**PCI Express Transmitter De-emphasis Enable** 0: Tx de-emphasis disabled for mobile mode 1: Tx de-emphasis enabled (Default setting for Desktop)	1
BIF_GEN2_EN_A	GPIO2	0 = Advertises the PCI-E device as 2.5 GT/s capable at power-on. 1 = Advertises the PCI-E device as 5.0 GT/s capable at power-on. 5.0 GT/s capability will be controlled by software.	0
RSVD BIF_VGA_DIS RSVD	GPIO8 GPIO9 GPIO21	VGA ENABLED	0 0 0
BIOS_ROM_EN	GPIO_22_ROMCSB	ENABLE EXTERNAL BIOS ROM	0
ROMIDCFG(2:0)	GPIO[13:11]	SERIAL ROM TYPE OR MEMORY APERTURE SIZE SELECT	0 0 1
VIP_DEVICE_STRAP_ENA	V2SYNC	IGNORE VIP DEVICE STRAPS	0
RSVD AUD[1] AUD[0]	GENERICC HSYNC VSYNC	AUD[1] AUD[0] 0 0 No audio function 0 1 Audio for DisplayPort and HDMI if dongle is detected 1 0 Audio for DisplayPort only 1 1 Audio for both DisplayPort and HDMI	0 0 11

AMD RESERVED CONFIGURATION STRAPS

ALLOW FOR PULLUP PADS FOR THESE STRAPS AND IF THESE GPIOS ARE USED, THEY MUST NOT CONFLICT DURING RESET

H2SYNC GENERICC

PULLUP PADS ARE NOT REQUIRED FOR THESE STRAPS BUT IF THESE GPIOS ARE USED, THEY MUST NOT CONFLICT DURING RESET

GPIO21_BB_EN



15,16,18,31,34,39 +3V_VGA

PROJECT : LX6_LX7
Quanta Computer Inc.

NB5

Size	Document Number	Rev
Custom	ATI M97(GND&Str&Ther)4/5	1A

Date: Tuesday, February 02, 2010 Sheet 17 of 44



CHANNEL A: 256MB/512MB DDR3



CHANNEL B: 256MB/512MB DDR3



LVDS Channel Switch



SEL	FUNCTION
LOW	DGPU (AN to B1)
HIGH	IGPU (AN to B2)

DPST Control



PV del in BOM

SEL	FUNCTION(COM)
LOW	IN_B0 to A
HIGH	IN_B1 to A



LCDVcc control



FOR UMA ONLY

OPTION SIGNAL FROM NB to LVDS for UMA

OPTION Back Light SIGNAL FROM NB to LVDS for UMA

OPTION SIGNAL FROM NB to LVDS for UMA

FOR 17"UMA ONLY





FOR UMA/SG



FOR DIS ONLY

OPTION SIGNAL FROM NB to CRT for DIS



OPTION SIGNAL FROM NB to CRT for DIS

FOR UMA ONLY

OPTION SIGNAL FROM NB to CRT for UMA



OPTION SIGNAL FROM NB to CRT for UMA



SEL	FUNCTION(COM)
LOW	IN_B1 to A
HIGH	IN_B2 to A

LVDS/CRT DDC Switch



VGA SWITCH



PV EMI request

FOR DIS ONLY

OPTION SIGNAL FROM NB to LVDS for DIS



OPTION Back Light SIGNAL FROM NB to LVDS for DIS





OPTION SIGNAL FROM NB to LVDS for DIS

FOR 17"DIS ONLY





NB5

PROJECT : LX6_LX7
Quanta Computer Inc.

Size	Document Number	Rev
Custom	LCD CONN/LID function	1A
Date: Tuesday, February 02, 2010	Sheet 22 of 44	







PROJECT :	LX6_LX7
	Quanta Computer Inc.
Size: Custom	Document Number: RTS5159 & CR SOCKET
Rev:	1A
Date:	Tuesday, February 02, 2010
Sheet	24 of 44



Line out



MIC

Accelerometer Sensor

SGT-LIS302DLTR interrupt pin default is low / active Hi , BIOS need to programming 22h to change status from active Hi to low



Pin 12: Low 38hex

Pin 12: unconnected/floating 3Ahex

NB5	PROJECT : LX6_LX7 Quanta Computer Inc.	
Size: Custom	Document Number: Audio Jack/Accelerometer	Rev: 1A
Date: Tuesday, February 02, 2010	Sheet 26 of 44	

EQ FOR SUBWOOFER



Sub-Woofer power



PV Del R574,R241,R240

GAIN1	GAIN0	dB
0	0	12
0	1	18
1	0	23.6
1	1	36

+3V 2,3,7,8,9,10,11,12,13,21,22,23,24,25,26,28,29,30,31,32,33,34,37,40,41
+4.75VAVDD 25
+VIN 22,35,36,37,39,40,41,42,43

PROJECT : LX6_LX7
Quanta Computer Inc.
NB5
Size: Custom | Document Number: SUBWOOFER (EQ & AMP.) | Rev: 1A
Date: Tuesday, February 02, 2010 | Sheet 27 of 44

BLUETOOTH



RIGHT SIDE USBX2 for 17"



RIGHT SIDE USB for 15"



USB fingerprint CON

1. USBP2-
2. USBP2+
3. +3V
4. +5V
5. SYSTEM GND
6. SYSTEM GND



E-SATA



LEFT USB PORT



Touch screen for 15"



NB5

PROJECT : LX6_LX7
Quanta Computer Inc.

Size	Document Number	Rev
Custom	BT/WC/FT/Touchscreen	1A

Date: Tuesday, February 02, 2010 | Sheet 28 of 44

T : Stuffed for RTL8111DL(10/100/1000)

for RTL8111DL use close Pin 44,45

SI del R452

Remove R3571,R3573

R3571 and R3573 are used in RTL8111DL , remove R3573 if switching regulator is enable , Remove R3571 external power is used.

SI del R130

Close to PIN 1

AL08111DB00 RTL8111DL-GR

RTL8111DL-VB-GR

if ISOLATEB pin pull-low,the LAN chip will not drive it's PCI-E outputs (excluding PCIE_WAKE# pin)

NS892405

NS892402:GIGABIT

>60mil

Power trace Layout 寬度> 60mil

>60mil

L23
RTL8111DL (Gaga lan) use 4.7uH power choke A>600mA tolerance ±15%

Close to 8111DL DVDD12 pins-- 19

Close to 8111DL DVDD12 pins-- 10, 13, 30, 36, 39.

RJ45

FOR EMI

Link

PROJECT : LX6_LX7
Quanta Computer Inc.

NB5

Size: Custom | Document Number: 8103E/RJ45 | Rev: 1A

Date: Tuesday, February 02, 2010 | Sheet 29 of 44

SATA HDD CONNECTOR



SATA_2 CONNECTOR FOR 17.3"



SATA CD-ROM



SI Add



+3V 2,3,7,8,9,10,11,12,13,21,22,23,24,25,26,27,28,29,31,32,33,34,37,40,41
+5V 11,21,22,23,25,26,28,31,33,34,41
+12VALW 22,34,39,41

NB5

PROJECT : LX6_LX7
Quanta Computer Inc.

Size	Document Number	Rev
Custom	ODD/HDD/ANT	1A

Date: Tuesday, February 02, 2010 Sheet 30 of 44

For UMA HDMI function

for UMA

SI EMI Request

MV Del R181,R182

U14

POWER

*PS8101

CONTROL

GND

EQUALIZATION SETTING
PC1:PC0=0:0 8dB
PC1:PC0=0:1 4dB Recommanded
PC1:PC0=1:0 12dB
PC1:PC0=1:1 0dB

SCLZ/SDAZ Low-level input/output Voltage
CFG1:CFG0=0:0 VIL:<0.4V VOL:0.6V (Default)
CGF1:CGF0=0:1 VIL:<0.36V VOL:0.55V
CGF1:CGF0=1:0 VIL:<0.44V VOL:0.65V
CGF1:CGF0=1:1 VIL:<0.36V VOL:0.6V

Signals		PDT	CHR	PIM
PC1	Ra	NC	4.7K	NC
HDMI_CFG0	Rb	NC	NC	NC
HDMI_CFG1	Rc	4.7K	NC	NC
REXT	Rd	499	1.2K	4.7K
PC1	Re	NC	NC	4.7K
HDMI_OE#	Rf	NC	4.7K	NC
PC0	Rg	4.7K	4.7K	4.7K

Vendor:PDT P/N:AL008101000
Vendor:CHR P/N:AL007318002
Vendor:PIM P/N:ALP411LS004

U14
for UMA

for Dis/SG

PV EMI Request

Close to HDMI(CN21) Connector

MV EMI Request

SI Del Q29,R378,R413,R415

MV Change

MV Del R670,R669

PV Change to short pad

PV Del R374,R368,R378 BOM

for UMA/DIS/SG

for UMA

Close to HDMI(CN21) Connector

for SG/DIS

Close to HDMI(CN21) Connector

DFHD19MR021

PROJECT : LX6_LX7
Quanta Computer Inc.

NB5

KB/POWER CONN

Date: Tuesday, February 02, 2010 Sheet 31 of 44



Mini PCI-E Card 1
WLAN



CPU FAN



POWER BOTTON CONNECT



1. +3VPCU(LIDSWITCH PWR)
2. +3VPCU(LIDSWITCH PWR)
3. LIDSWITCH
4. NBSWON1#
5. PWRLED#
6. GND

NB5	PROJECT : LX6_LX7 Quanta Computer Inc.	
Size: Custom	Document Number: MINI PCIE CONN/FAN	Rev: 1A
Date: Tuesday, February 02, 2010	Sheet 33 of 44	

KEYBOARD PULL-UP

RP30 10P8R-8.2K
RP35 10P8R-8.2K
+3VPCU
R355 8.25K/F_4
R356 8.25K/F_4

clear ABS 758 resin for key cap.
7 LEDs for 15.4" (total LED current 140mA)
11 LEDs for 17" (Total LED current 220mA)

SI Add
PV Change BOM
R521 1K/F_4
R389 *200/F_6
WIRELESS_ON_R
32 WIRELESS_ON#
Q46 PDTC144EU

PV Change BOM
R565 1K/F_4
R392 *200/F_6
WIRELESS_OFF_R
32 WIRELESS_OFF#
Q47 PDTC144EU

KB CONN
MV Add
25 MUTE_LED#
32 CAPSLED#
32 KEYLED_CN
R403 200_4
R408 200_4
R675 1K/F_4
R674 100K/F_4
C247 .1U/10V_4
CN8

KB backlight for 15"

+12VALW
R102 100K/F_4
R99 1M_4
Q7 AO3404
Q6 2N7002E
C813 0.01U/16V_4
C621 .1U/10V_4
C620 .1U/10V_4
32 KB_LED_EN
+5V_LED_KBLIGHT
140 mA
CN6 DFFC04FR042 88513-0401-4p-l
KB LIGHT CONN
4.LEDVCC
3. LEDVCC
2. GND
1. GND

LED1 Wireless Enable White 27
LED2 Wireless Disable Amber 28
LED3 Mute Amber 29
LED4 Caps White 30
VCC VCC 31 32

FOR DIS ONLY

PLTRST# R551 *0_4 PEGX_RST#

FOR SG ONLY

U35 MC74VHC1G08DFT2G
3,9,29,32,33 PLTRST#
9 DGPU_HOLD_RST#
R484 330/F_4
DGPU_HIN_RST#
PEGX_RST# 14
C706 .1U/10V_4
R468 100K/F_4
Q38 *MMBT3904-7-F

+1.0V_VGA R440 *4.7K_4 DGPU_POK2 Q33 *MMBT3904-7-F C677 *1000P/50V_4
+1.8V_VGA R456 *4.7K_4 DGPU_POK4 Q36 *MMBT3904-7-F C705 *1000P/50V_4
+1.5V_VGA R442 4.7K_4 DGPU_POK3 Q35 *MMBT3904-7-F C697 *1000P/50V_4
DGPU_PGOK-1
R443 *0_4/S short/0402
+3V R437 4.7K_4 C664 *1000P/50V_4
+3V_VGA R445 4.7K_4 Q34 MMBT3904-7-F R444 100K/F_4
DGPU_PWROK 9,32,39,40

+3V 2,3,7,8,9,10,11,12,13,21,22,23,24,25,26,27,28,29,30,31,32,33,37,40,41
+5V 11,21,22,23,25,26,28,30,31,33,41
+3VPCU 7,22,28,32,33,35,36,39,41,42,43
+3V_VGA 15,16,17,18,21,39
+12VALW 22,30,39,41
+1.0V_VGA 14,16,18,40
+1.5V_VGA 15,18,19,20,39
+1.8V_VGA 14,16,18,39

NB5
PROJECT : LX6_LX7
Quanta Computer Inc.
Size Custom | Document Number KB | Rev 1A
Date Tuesday, February 02, 2010 | Sheet 34 of 44

DC/DC +3V_ALW/+5V_ALW/+5V_ALW2 /+15V_ALW





+1.8V	5,10,11,21,41	
+VIN	22,27,35,37,39,40,41,42,43	
+1.05V	2,7,8,9,11,37,43	
+3VPCU	7,22,28,32,33,34,35,39,41,42,43	
+5VPCU	28,32,35,37,38,39,40,41,42,43	

NB5

PROJECT : LX6_LX7
Quanta Computer Inc.

Size	Document Number	Rev
Custom	+1.05V/+1.8V (RT8204C)	1A

Date: Tuesday, February 02, 2010 | Sheet 36 of 44

	DIS (Clarksfild)	SG/UMA (Arburndle)
不上件		PQ45 PQ46 PQ43 PQ44
PR14	1.91k(OCP=63A) (CS21912FB13)	1.69k(OCP=55A) (CS21692FB01)
PR34	4.7k (CS24702FB10)	4.87k (CS24872FB07)



	SG	DIS	UMA
PR156 PR26 PR29 PQ8	Stuff	Stuff	no Stuff
PR157	40.2K (CS34022FB15)	40.2K (CS34022FB15)	38.3K (CS33832FB08)

	Clarksfild	Arraindle
PU10	VT358 (AL000358U00)	VT357 (AL000357U00)
PR160	40.2K (CS34022FB15)	36K (CS33602FB15)
PR158	5.76K (CS25762FB01)	6.49K (CS26492FB23)



PROJECT : LX6_LX7
Quanta Computer Inc.

NB5

Size	Document Number	Rev
Custom	+1.05V_VTT (VT358)	1A

Date: Tuesday, February 02, 2010 Sheet 38 of 44

VGA Core



+1.5V +/- 5%
Countinue current:6A
Peak current:12A
OCP minimum 15A



SG & Discrete Only

+1.0V +/- 5%
Countinue current:1.7A
Peak current:3A







+3V 2,3,7,8,9,10,11,12,13,21,22,23,24,25,26,27,28,29,30,31,32,33,34,37,41
+VIN 22,27,35,36,37,39,41,42,43
+5VPCU 28,32,35,36,37,38,39,41,42,43
+1.5VSUS 5,12,13,39,41
+1.0V_VGA 14,16,18,34
+0.75V_DDR_VTT 12,13,41

NB5

PROJECT : LX6_LX7
Quanta Computer Inc.

Size	Document Number	Rev
Custom	DDR3 (RT8207)	1A

Date: Tuesday, February 02, 2010 Sheet 40 of 44









Switchable GPIOs	Descriptions
PCH_GPIO52	DGPU_SELECT#
PCH_GPIO16	DGPU_HOLD_RST#
PCH_GPIO36	DGPU_PWR_EN#
PCH_GPIO17	DGPU_PWR_OK
PCH_GPIO54	EDID_ELECT#
PCH_GPIO37	DGPU_PRSNT#

NB5

PROJECT : LX6_LX7
Quanta Computer Inc.

Size: Custom | Document Number: Switch Blockdiagram | Rev: 1A

Date: Tuesday, February 02, 2010 | Sheet 44 of 44