


Working with Spatial Data. Network Analysis

Reading, exploring and analyzing,
feature extraction

Yordan Darakchiev

Technical Trainer

iordan93@gmail.com





sli.do

#DataScience

Table of Contents

- Geospatial data
 - Reading and exploring
 - Projections
 - Visualization
 - Scatter plots
 - Choropleth maps
- Network analysis
 - Graphs, types of graphs
 - Shortest path between nodes
 - Centrality
 - Communities

Geospatial Data

Exploring, analyzing
and visualizing

Geospatial Data

- Data that has a geographic component to it
 - Most commonly: coordinates (latitude, longitude)
 - Sometimes: country, city, ZIP code, address
 - Not necessarily on Earth ([Google Mars](#))
- Sources
 - Satellite images
 - GPS data
 - Geotagging (e.g., photos at Facebook)
 - Manual entry, etc.
- Working with spatial data isn't trivial...
 - E.g., we need geometry on a sphere to calculate distances
 - ... but we have libraries that make our lives easier

Reading and Exploring Geospatial Data

- In some cases, we have convenient datasets
- In other cases, it's in specific formats
 - GeoJSON, Shapefile, KML, etc.
 - Some libraries (like geopandas) can read these automatically
- Data cleaning
 - Non-spatial columns: proceed as usual
 - Tidy up the data, impute or remove missing values, explore outliers, normalize columns, etc.
 - Spatial columns: fixing or changing coordinates is easier when you visualize them
- Exploratory data analysis
 - Most commonly: look for clusters and other patterns
 - Also: compare attributes across different regions
 - E.g., income by country

Example: Earthquake Data

- Dataset: earthquakes.csv, [info](#)

- Read the dataset, look at missing values
- Leave only columns you're interested in

```
["Date", "Time", "Latitude", "Longitude", "Magnitude", "Depth"]
```

- Explore the dataset

- Examples: how is the magnitude distributed? When and where did the most powerful earthquakes happen? What are the recent ones?

- Perform additional data cleaning, exploration and visualization of the non-spatial columns

- Fix dates (remove invalid date format, convert to datetime)

```
dt_info = earthquake_data.Date + " " + earthquake_data.Time
earthquake_data = earthquake_data.drop(
    index = dt_info[dt_info.str.len() > 20].index)
earthquake_data["DateTime"] = pd.to_datetime(
    earthquake_data.Date + " " + earthquake_data.Time)
```

Plotting Data on a Map

- To plot data, we'll use the geopandas package

```
conda install -c conda-forge geopandas  
conda install -c conda-forge geodatasets
```

```
import geopandas as gpd
```

- Setting up and displaying a world map

```
land = gpd.read_file(geodatasets.data.naturalearth.land.url)  
  
land.plot(figsize = (20, 10), color = "coral", facecolor = "aqua")  
plt.gca().set_facecolor("aqua")  
plt.show()
```

- Projections ([docs](#), [EPSG](#))
 - Different ways to show a sphere in a 2D plane
 - **Every projection has distortions**

Plotting Data on a Map (2)


- Data (features)
 - Use as common pandas columns (Series)
- Selection, projection, grouping, etc.
 - Work as expected
- Geometry
 - Points, lines, polygons
 - [Quick guide](#)
 - Contains useful info and methods, such as area, bounds, centroids and distances
 - Allows for **very** easy plotting
- Using / changing projections
 - `dataframe.to_crs(name)`
 - Commonly used with EPSG (4326 by default)



Adding Data on Volcanoes

- Dataset: `volcanoes.csv`, [info](#)
- Read the data and convert to x, y coordinates
- Plot just after the earthquakes
 - And before the "map decorations"

```
volcano_data = pd.read_csv(...)
geometry = [Point(xy) for xy in zip(
    volcano_data.Longitude, volcano_data.Latitude)
]
volcano_data = gpd.GeoDataFrame(volcano_data,
    geometry = geometry, crs = "EPSG:4326")
land.plot(figsize = (20, 10), color = "coral")
plt.gca().set_facecolor("aqua")
earthquake_data.plot(ax = plt.gca(),
    c = "r", markersize = 2)
volcano_data.plot(...)
plt.show()
```



Drawing a Choropleth Map

- Like a heatmap
 - Shows different countries (or US states) in different colors according to a scale
- Dataset: `ufo_sightings_scrubbed.csv`, [info](#)
 - Clean the data (careful with "longitude")
 - Narrow down the data to US

```
ufos = pd.read_csv("ufo_sightings_scrubbed.csv", low_memory = False)
ufos = ufos[["datetime", "country", "state", "latitude", "longitude "]]
ufos.columns = ["datetime", "country", "state", "latitude", "longitude"]

ufos = ufos[ufos.country == "us"]
```

- Use the shape files from `States_shapefile`

Drawing a Choropleth Map (2)

- Read the shape file
- Read the state names from `state_names.csv`
 - Use them to add the full names to the UFOs dataset

```
states = gpd.read_file("States_shapefile.shp")
state_names = pd.read_csv("states.csv")
state_names.abbreviation = state_names.abbreviation.str.lower()
state_names_dict = {state.abbreviation: state["name"]
    for index, state in state_names.iterrows()}

ufos.state.replace(state_names_dict, inplace = True)
```

- Get the number of sightings per state

```
num_sightings_by_state = ufos.groupby("state").size()
num_sightings_by_state.state = num_sightings_by_state.state.str.upper()
```

Drawing a Choropleth Map (3)

- Combine the two datasets


```
states = states.merge(num_sightings_by_state,  
    left_on = "State_Name", right_on = "state")  
states.plot(column = 0, legend = True, cmap = "Greens", figsize = (8, 5))
```

- Add text annotations

```
states["centers"] = states.geometry.apply(lambda x: x.centroid.coords[0])  
for idx, row in states.iterrows():  
    plt.annotate(text = row["State_Code"], xy = row["centers"])  
plt.show()
```

- * Other ideas

- Remove Alaska / show it separately
- Use a transformation (e.g. sqrt)



Analyzing Maps

- There are many algorithms used to model spatial data
 - Most commonly, we look for density patterns and clusters of points
 - Common algorithms are
 - [KDE](#) – Kernel Density Estimation
 - [kMeans](#) Clustering
 - [Hierarchical](#) Clustering
 - [kNN](#) – k Nearest Neighbors
 - This course doesn't deal with modelling, so we won't get into more detail
 - But feel free to explore the algorithms as you wish
 - You can see details on these on machine learning-related articles
- We can also represent the map as a network
 - E.g., road maps, railway maps, or other "sets of connected dots"




Network Analysis

Working with graphs

Networks = Graphs

- A graph is a geometrical object consisting of objects which are related by some attribute

- **Nodes** (vertices, points) – describe objects
- **Edges** (arcs, lines) – connect nodes




- Types of graphs


- Directed / undirected

- In a directed graph, there is only one way to travel between the nodes

Undirected Graph




Directed Graph




- Weighted / unweighted



- A weighted graph contains some quantity ("weight", usually ≥ 0) over each of its edges



Graphs


■ Types of graphs (cont'd)

- Cyclic / acyclic
 - When you travel along a cyclic graph, you will visit one node more than once
 - These types are independent
 - i.e. a graph can be “acyclic directed unweighted graph”
- 
- ```
graph LR; A((A)) -- red --> B((B)); B -- red --> D((D)); D -- red --> A; D -- black --> C((C));
```




- Special cases

- **Tree** – each node has at most one "parent"



- **DAG** – directed acyclic graph



# Representing Graphs

- We can use the library networkx
  - Installed by default with Anaconda
- Create a simple weighted undirected graph

```
import networkx as nx
g = nx.Graph()
g.add_edge("a", "b", weight = 0.1)
g.add_edge("b", "c", weight = 1.5)
g.add_edge("a", "c", weight = 1.0)
g.add_edge("c", "d", weight = 2.2)
```

- Display the graph

```
nx.draw(g, with_labels = True)
plt.show()
```

# Finding a Shortest Path

- Advanced graph display
  - Show the weights at each edge
  - Make the edge width proportional to its weight

```
pos = nx.spring_layout(g)
weights = nx.get_edge_attributes(g, "weight")
nx.draw(g, pos, with_labels = True)

nx.draw_networkx_edge_labels(g, pos,
 edge_labels = weights)
nx.draw_networkx_edges(g, pos,
 width = [v * 2 for v in weights.values()])
plt.show()
```

- Shortest paths

```
print(nx.shortest_path(g, "b", "d"),
 nx.shortest_path_length(g, "b", "d"))
print(nx.shortest_path(g, "b", "d", weight = "weight"),
 nx.shortest_path_length(g, "b", "d", weight = "weight"))
```

# Creating Directed Graphs

- Directed graph (digraph)
  - Simply change the definition of g
  - Now each edge is directed
  - The visualization will include arrows
    - They point at the direction of each connection


```
g = nx.DiGraph()
g.add_edge("a", "b", weight = 0.1)
g.add_edge("b", "c", weight = 1.5)
g.add_edge("a", "c", weight = 1.0)
g.add_edge("c", "d", weight = 2.2)
```

```
print(nx.shortest_path(g, "b", "d")) # ['b', 'c', 'd']
print(nx.shortest_path(g, "d", "b")) # Error: No path between d and b.
```

# Example: Social Circles

- Dataset: facebook.zip, [info](#)
  - Format: first\_user\_id second\_user\_id
    - I.e. edge list
- Read the graph
  - Extremely simple

```
facebook_graph = nx.read_edgelist("facebook_combined.txt")
print(len(facebook_graph.nodes)) # 4039
print(len(facebook_graph.edges)) # 88234
```




# Calculating Important Nodes

- Measure: **centrality**
  - Different types of centrality, according to different formulas
    - E.g. "betweenness centrality"
    - Measures how important a node is
- To exemplify, let's use a smaller graph

```
karate_graph = nx.karate_club_graph()
centrality = nx.betweenness centrality(karate_graph)
Returns a dictionary
```

- Ten most important nodes in the Facebook graph
  - Look similar to cluster centroids




# Finding Communities

- Measure: **cliques**

- Most commonly used algorithm: Girvan – Newman
  - Uses **edge betweenness** as the measure

```
from networkx.algorithms import community
nx.draw(karate_graph, with_labels = True)
communities_generator = community.girvan_newman(karate_graph)
for i in range(1, 4):
 communities = next(communities_generator)
 print("level " + str(i), communities)
```

- We can find communities in the Facebook graph
  - Look similar to different clusters



# Summary

- Geospatial data
  - Reading and exploring
  - Projections
  - Visualization
    - Scatter plots
    - Choropleth maps
- Network analysis
  - Graphs, types of graphs
  - Shortest path between nodes
  - Centrality
  - Communities



The image features a white background with two blue decorative bars at the top and bottom. The top bar is a solid blue strip. The bottom bar consists of a thin dark blue line above a wider, lighter blue strip. The word "Questions?" is centered in a blue, sans-serif font.

Questions?