R Reference Card for Data Mining

Yanchang Zhao, RDataMining.com, November 3, 2015

- See the latest version at http://www.RDataMining.com
- The package names are in parentheses.
- Recommended packages and functions are shown in bold.
- Click a package in this PDF file to find it on CRAN.

Association Rules and Sequential Patterns

Functions

apriori() mine associations with APRIORI algorithm – a level-wise, breadth-first algorithm which counts transactions to find frequent itemsets (arules)

eclat () mine frequent itemsets with the Eclat algorithm, which employs equivalence classes, depth-first search and set intersection instead of counting (arules)

cspade() mine frequent sequential patterns with the cSPADE algorithm (arulesSequences)

seqefsub() search for frequent subsequences (TraMineR)

Packages

arules mine frequent itemsets, maximal frequent itemsets, closed frequent itemsets and association rules. It includes two algorithms, Apriori and Eclat.

arules Viz visualizing association rules

arulesSequences add-on for arules to handle and mine frequent sequences TraMineR mining, describing and visualizing sequences of states or events

Classification & Prediction

Decision Trees

ctree () conditional inference trees, recursive partitioning for continuous, censored, ordered, nominal and multivariate response variables in a conditional inference framework (party)

rpart () recursive partitioning and regression trees (rpart)

mob () model-based recursive partitioning, yielding a tree with fitted models associated with each terminal node (party)

Random Forest

cforest () random forest and bagging ensemble (party)

randomForest() random forest(randomForest)

importance() variable importance (randomForest)

varimp() variable importance (party)

Neural Networks

nnet () fit single-hidden-layer neural network (nnet)

neuralnet training of neural networks (neuralnet)

Support Vector Machine (SVM)

svm() train a support vector machine for regression, classification or densityestimation (e1071)

ksvm() support vector machines (kernlab)

Bayes Classifiers

naiveBayes () naive Bayes classifier (e1071)

Performance Evaluation

performance () provide various measures for evaluating performance of prediction and classification models (*ROCR*)

PRcurve () precision-recall curves (*DMwR*)

CRchart () cumulative recall charts (DMwR)

roc() build a ROC curve (pROC)

auc () compute the area under the ROC curve (pROC)

ROC () draw a ROC curve (DiagnosisMed)

Packages

party recursive partitioning

rpart recursive partitioning and regression trees

randomForest classification and regression based on a forest of trees using random inputs

ROCR visualize the performance of scoring classifiers

caret classification and regression models

r1071 functions for latent class analysis, short time Fourier transform, fuzzy clustering, support vector machines, shortest path computation, bagged clustering, naive Bayes classifier, ...

rpartOrdinal ordinal classification trees, deriving a classification tree when the response to be predicted is ordinal

rpart.plot plots rpart models

pROC display and analyze ROC curves

nnet feed-forward neural networks and multinomial log-linear models

RSNNS neural networks in R using the Stuttgart Neural Network Simulator (SNNS)

neuralnet training of neural networks using backpropagation, resilient backpropagation with or without weight backtracking

Regression

Functions

lm() linear regression

qlm() generalized linear regression

qbm () generalized boosted regression models (gbm)

predict () predict with models

residuals () residuals, the difference between observed values and fitted values

nls() non-linear regression

gls () fit a linear model using generalized least squares (nlme)

gnls () fit a nonlinear model using generalized least squares (nlme)

Packages

nlme linear and nonlinear mixed effects models *gbm* generalized boosted regression models

Clustering

Partitioning based Clustering

partition the data into k groups first and then try to improve the quality of clustering by moving objects from one group to another

kmeans () perform k-means clustering on a data matrix

kmeansruns () call kmeans for the k-means clustering method and includes estimation of the number of clusters and finding an optimal solution from several starting points (*fpc*)

pam () the Partitioning Around Medoids (PAM) clustering method (cluster)

pamk () the Partitioning Around Medoids (PAM) clustering method with estimation of number of clusters (fpc)

kmeansCBI() interface function for kmeans (fpc)

clara() Clustering Large Applications (cluster)

fanny (x, k, ...) compute a fuzzy clustering of the data into k clusters (cluster)

kcca() k-centroids clustering (flexclust)

ccfkms () clustering with Conjugate Convex Functions (cba)

apcluster() affinity propagation clustering for a given similarity matrix (apcluster)

apclusterK() affinity propagation clustering to get K clusters (apcluster)

cclust () Convex Clustering, incl. k-means and two other clustering algorithms (cclust)

KMeansSparseCluster() sparse k-means clustering (sparcl)

tclust(x,k,alpha,...) trimmed k-means with which a proportion alpha of observations may be trimmed (*tclust*)

Hierarchical Clustering

a hierarchical decomposition of data in either bottom-up (agglomerative) or topdown (divisive) way

hclust () hierarchical cluster analysis on a set of dissimilarities

birch() the BIRCH algorithm that clusters very large data with a CF-tree (birch)
pvclust() hierarchical clustering with p-values via multi-scale bootstrap resampling (pvclust)

agnes () agglomerative hierarchical clustering (cluster)

diana() divisive hierarchical clustering (*cluster*)

mona () divisive hierarchical clustering of a dataset with binary variables only (cluster)

rockCluster() cluster a data matrix using the Rock algorithm (cba)

proximus () cluster the rows of a logical matrix using the Proximus algorithm (cha)

isopam() Isopam clustering algorithm (isopam)

flashClust() optimal hierarchical clustering (flashClust)

fastcluster() fast hierarchical clustering (fastcluster)

cutreeDynamic(), cutreeHybrid() detection of clusters in hierarchical clustering dendrograms (dynamicTreeCut)

HierarchicalSparseCluster() hierarchical sparse clustering (sparcl)

Model based Clustering

Mclust() model-based clustering (mclust)

HDDC() a model-based method for high dimensional data clustering (HDclassif)

fixmahal () Mahalanobis Fixed Point Clustering (fpc)

fixreg() Regression Fixed Point Clustering (fpc)

mergenormals () clustering by merging Gaussian mixture components (fpc)

Density based Clustering

generate clusters by connecting dense regions

dbscan (data, eps, MinPts, ...) generate a density based clustering of arbitrary shapes, with neighborhood radius set as eps and density threshold as MinPts (fpc)

pdfCluster() clustering via kernel density estimation (pdfCluster)

Other Clustering Techniques

mixer() random graph clustering (mixer)

nncluster() fast clustering with restarted minimum spanning tree (nnclust) orclus() ORCLUS subspace clustering (orclus)



Plotting Clustering Solutions

plotcluster() visualisation of a clustering or grouping in data (*fpc*) bannerplot() a horizontal barplot visualizing a hierarchical clustering (*cluster*)

Cluster Validation

 $\verb|silhouette|()|$ compute or extract silhouette information (cluster)

cluster.stats() compute several cluster validity statistics from a clustering and a dissimilarity matrix (fpc)

clValid() calculate validation measures for a given set of clustering algorithms and number of clusters (clValid)

clustIndex() calculate the values of several clustering indexes, which can be independently used to determine the number of clusters existing in a data set (cclust)

NbClust () provide 30 indices for cluster validation and determining the number of clusters (NbClust)

Packages

cluster cluster analysis

fpc various methods for clustering and cluster validation

mclust model-based clustering and normal mixture modeling

birch clustering very large datasets using the BIRCH algorithm

pvclust hierarchical clustering with p-values

apcluster Affinity Propagation Clustering

cclust Convex Clustering methods, including k-means algorithm, On-line Update algorithm and Neural Gas algorithm and calculation of indexes for finding the number of clusters in a data set

cba Clustering for Business Analytics, including clustering techniques such as Proximus and Rock

bclust Bayesian clustering using spike-and-slab hierarchical model, suitable for clustering high-dimensional data

biclust algorithms to find bi-clusters in two-dimensional data

clue cluster ensembles

clues clustering method based on local shrinking

clValid validation of clustering results

clv cluster validation techniques, contains popular internal and external cluster validation methods for outputs produced by package cluster

bayesclust tests/searches for significant clusters in genetic data

clustsig significant cluster analysis, tests to see which (if any) clusters are statistically different

clusterSim search for optimal clustering procedure for a data set

clusterGeneration random cluster generation

gcExplorer graphical cluster explorer

hybridHclust hybrid hierarchical clustering via mutual clusters

Modalclust hierarchical modal Clustering

iCluster integrative clustering of multiple genomic data types

EMCC evolutionary Monte Carlo (EMC) methods for clustering

rEMM extensible Markov Model (EMM) for data stream clustering

Outlier Detection

Functions

boxplot.stats()\$out list data points lying beyond the extremes of the
 whiskers

lof() a parallel implementation of the LOF algorithm (*Rlof*)

Packages

Rlof a parallel implementation of the LOF algorithm extremevalues detect extreme values in one-dimensional data mvoutlier multivariate outlier detection based on robust methods outliers some tests commonly used for identifying outliers

Time Series Analysis

Construction & Plot

ts() create time-series objects

plot.ts() plot time-series objects

smoothts() time series smoothing (ast)

sfilter() remove seasonal fluctuation using moving average (ast)

Decomposition

decomp () time series decomposition by square-root filter (timsac)

decompose () classical seasonal decomposition by moving averages stl() seasonal decomposition of time series by loess

tsr() time series decomposition (ast)

ardec() time series autoregressive decomposition (ArDec)

Forecasting

arima () fit an ARIMA model to a univariate time series predict.Arima () forecast from models fitted by arima

auto.arima() fit best ARIMA model to univariate time series (forecast)

forecast.stl(), forecast.ets(), forecast.Arima()

forecast time series using stl, ets and arima models (forecast)

Correlation and Covariance

acf () autocovariance or autocorrelation of a time series

ccf () cross-correlation or cross-covariance of two univariate series

Packages

forecast displaying and analysing univariate time series forecasts

hts analysing and forecasting hierarchical and grouped time series TSclust time series clustering utilities

dtw Dynamic Time Warping (DTW)

timsac time series analysis and control program

ast time series analysis

ArDec time series autoregressive-based decomposition

dse tools for multivariate, linear, time-invariant, time series models

Text Mining

Text Cleaning and Preparation

Corpus () build a corpus, which is a collection of text documents (tm)

tm_map() transform text documents, e.g., stemming, stopword removal (tm)

tm_filter() filtering out documents (tm)

TermDocumentMatrix(), **DocumentTermMatrix()** construct a term-document matrix or a document-term matrix (tm)

Dictionary () construct a dictionary from a character vector or a termdocument matrix (tm)

stemDocument () stem words in a text document (tm)

stemCompletion() complete stemmed words (tm)

SnowballStemmer() Snowball word stemmers (Snowball)

stopwords (language) return stopwords in different languages (tm)

removeNumbers(), removePunctuation(), removeWords() remove numbers, punctuation marks, or a set of words from a text document (tm) removeSparseTerms() remove sparse terms from a term-document matrix (tm)

Frequent Terms and Association

findAssocs () find associations in a term-document matrix (tm)

findFreqTerms () find frequent terms in a term-document matrix (tm)

 $\textbf{termFreq()} \ \ \text{generate a term frequency vector from a text document } (\textit{tm})$

Topic Modelling

LDA () fit a LDA (latent Dirichlet allocation) model (*topicmodels*)

CTM() fit a CTM (correlated topics model) model (topicmodels)

terms () extract the most likely terms for each topic (topicmodels)

topics () extract the most likely topics for each document (topicmodels)

Sentiment Analysis

polarity () polarity score (sentiment analysis) (qdap)

Text Categorization

textcat() n-gram based text categorization (textcat)

Text Visualizatoin

wordcloud() plot a word cloud (wordcloud)

comparison.cloud() plot a cloud comparing the frequencies of words across documents (wordcloud)

commonality.cloud() plot a cloud of words shared across documents
 (wordcloud)

Packages

tm a framework for text mining applications

topicmodels fit topic models with LDA and CTM

wordcloud various word clouds

lda fit topic models with LDA

wordnet an interface to the WordNet

RTextTools automatic text classification via supervised learning

qdap transcript analysis, text mining and natural language processing

sentiment 140 sentiment text analysis using free sentiment 140 service

tm.plugin.dc a plug-in for package tm to support distributed text mining

tm.plugin.mail a plug-in for package tm to handle mail

textir a suite of tools for inference about text documents and associated sentiment tau utilities for text analysis

textcat n-gram based text categorization

Rwordseg Chinese word segmentation using Ansj

Social Network Analysis and Graph Mining

Functions

graph(), graph.edgelist(), graph.adjacency(),

graph.incidence() create graph objects respectively from edges, an edge list, an adjacency matrix and an incidence matrix (*igraph*)

plot(), tkplot(), rglplot() static, interactive and 3D plotting of graphs (igraph)

gplot(), gplot3d() plot graphs (sna)

vcount(), ecount() number of vertices/edges (igraph)

V(), **E()** vertex/edge sequence of igraph (*igraph*)

is.directed() whether the graph is directed (igraph)

are.connected() check whether two nodes are connected (igraph)

degree(), betweenness(), closeness(), transitivity() various centrality scores (igraph, sna)

add.edges(), add.vertices(), delete.edges(), delete.vertices()
 add and delete edges and vertices (igraph)

neighborhood() neighborhood of graph vertices (igraph, sna)



get.adjlist() adjacency lists for edges or vertices (igraph) nei(), adj(), from(), to() vertex/edge sequence indexing (igraph)

cliques(), largest.cliques(), maximal.cliques(), clique.number() find cliques, ie. complete subgraphs (*igraph*)

clusters(), no.clusters() maximal connected components of a graph and the number of them (*igraph*)

fastgreedy.community(), spinglass.community() community detection (igraph)

cohesive.blocks() calculate cohesive blocks (igraph)

induced.subgraph() create a subgraph of a graph(igraph)

\$->\$, \$<-\$, \$--\$ edge sequence indexing (*igraph*)

get.edgelist() return an edge list in a two-column matrix (igraph)

read.graph(), write.graph() read and writ graphs from and to files of various formats (igraph)

Packages

igraph network analysis and visualization

sna social network analysis

d3Network, networkD3 creating D3 JavaScript network, tree, dendrogram, and Sankey graphs from R

RNeo4j interact with a Neo4j database through R

statnet a set of tools for the representation, visualization, analysis and simulation of network data

egonet ego-centric measures in social network analysis

snort social network-analysis on relational tables

network tools to create and modify network objects

bipartite visualising bipartite networks and calculating some (ecological) indices blockmodelinggeneralized and classical blockmodeling of valued networks diagram visualising simple graphs (networks), plotting flow diagrams NetCluster clustering for networks

NetData network data for McFarland's SNA R labs

NetIndices estimating network indices, including trophic structure of foodwebs

NetworkAnalysis statistical inference on populations of weighted or unweighted networks

tnet analysis of weighted, two-mode, and longitudinal networks

Spatial Data Analysis

Functions

geocode () geocodes a location using Google Maps (ggmap)

plotGoogleMaps () create a plot of spatial data on Google Maps (plot-GoogleMaps)

qmap () quick map plot (ggmap)

get_map() queries the Google Maps, OpenStreetMap, or Stamen Maps server for a map at a certain location (ggmap)

gvisGeoChart(), gvisGeoMap(), gvisIntensityMap(), qvisMap() Google geo charts and maps (googleVis)

GetMap() download a static map from the Google server (*RgoogleMaps*) ColorMap() plot levels of a variable in a colour-coded map (*RgoogleMaps*)

PlotOnStaticMap() overlay plot on background image of map tile (RgoogleMaps)

TextOnStaticMap() plot text on map (*RgoogleMaps*)

Packages

plotGoogleMaps plot spatial data as HTML map mushup over Google Maps RgoogleMaps overlay on Google map tiles in R

ggmap Spatial visualization with Google Maps and OpenStreetMap plotKML visualization of spatial and spatio-temporal objects in Google Earth SGCS Spatial Graph based Clustering Summaries for spatial point patterns spdep spatial dependence: weighting schemes, statistics and models

Statistics

Summarization

summary () summarize data

describe() concise statistical description of data (*Hmisc*)

boxplot.stats() box plot statistics

Analysis of Variance

aov () fit an analysis of variance model

anova () compute analysis of variance (or deviance) tables for one or more fitted model objects

Statistical Tests

chisq.test() chi-squared contingency table tests and goodness-of-fit tests

ks.test() Kolmogorov-Smirnov tests

t.test() student's t-test

prop.test() test of equal or given proportions

binom.test() exact binomial test

Mixed Effects Models

lme () fit a linear mixed-effects model (nlme)

nlme() fit a nonlinear mixed-effects model (nlme)

Principal Components and Factor Analysis

princomp() principal components analysis

prcomp() principal components analysis

Other Functions

var(), cov(), cor() variance, covariance, and correlation

density() compute kernel density estimates

cmdscale() Multidimensional Scaling (MDS)

Packages

nlme linear and nonlinear mixed effects models

Graphics

Functions

plot () generic function for plotting

barplot(), pie(), hist() bar chart, pie chart and histogram

boxplot () box-and-whisker plot

stripchart () one dimensional scatter plot

dotchart () Cleveland dot plot

ggnorm(), ggplot(), ggline() QQ (quantile-quantile) plot

coplot () conditioning plot

splom() conditional scatter plot matrices (lattice)

pairs () a matrix of scatterplots

cpairs () enhanced scatterplot matrix (gclus)

parcoord() parallel coordinate plot (MASS)

cparcoord() enhanced parallel coordinate plot (gclus)

parallelplot() parallel coordinates plot (lattice)

densityplot() kernel density plot (lattice)

contour(), filled.contour() contour plot

levelplot(), contourplot() level plots and contour plots (lattice)

smoothScatter() scatterplots with smoothed densities color representation; capable of visualizing large datasets

```
sunflowerplot () a sunflower scatter plot
assocplot() association plot
mosaicplot() mosaic plot
matplot () plot the columns of one matrix against the columns of another
fourfoldplot () a fourfold display of a 2 \times 2 \times k contingency table
persp() perspective plots of surfaces over the x?y plane
cloud(), wireframe() 3d scatter plots and surfaces (lattice)
interaction.plot() two-way interaction plot
iplot(), ihist(), ibar(), ipcp() interactive scatter plot, histogram, bar
      plot, and parallel coordinates plot (iplots)
pdf(), postscript(), win.metafile(), jpeq(), bmp(),
      png(), tiff() save graphs into files of various formats
gvisAnnotatedTimeLine(), gvisAreaChart(),
      gvisBarChart(), gvisBubbleChart(),
      gvisCandlestickChart(), gvisColumnChart(),
      gvisComboChart(), gvisGauge(), gvisGeoChart(),
      gvisGeoMap(), gvisIntensityMap(),
      gvisLineChart(), gvisMap(), gvisMerge(),
      gvisMotionChart(), gvisOrgChart(),
      qvisPieChart(), qvisScatterChart(),
      gvisSteppedAreaChart(), gvisTable(),
      qvisTreeMap() various interactive charts produced with the Google
      Visualisation API (googleVis)
```

gvisMerge() merge two googleVis charts into one (googleVis)

Packages

ggplot2 an implementation of the Grammar of Graphics

ggvis interactive grammar of graphics

googleVis an interface between R and the Google Visualisation API to create interactive charts

d3Network, networkD3 creating D3 JavaScript network, tree, dendrogram, and Sankey graphs from R

rCharts interactive javascript visualizations from R

lattice a powerful high-level data visualization system, with an emphasis on multivariate data

vcd visualizing categorical data

iplots interactive graphics

Data Manipulation

Functions

transform() transform a data frame

scale () scaling and centering of matrix-like objects

t () matrix transpose

aperm() array transpose

sample() sampling

table(), tabulate(), xtabs() cross tabulation

stack(), unstack() stacking vectors

split(), unsplit() divide data into groups and reassemble

reshape () reshape a data frame between "wide" and "long" format

merge () merge two data frames; similar to database join operations

aggregate () compute summary statistics of data subsets

by () apply a function to a data frame split by factors

melt(), cast() melt and then cast data into the reshaped or aggregated form you want (reshape)

complete.cases() find complete cases, i.e., cases without missing values



na.fail, na.omit, na.exclude, na.pass handle missing values **Packages**

reshape flexibly restructure and aggregate data using melt and cast **reshape2** flexibly reshape data: a reboot of the **reshape** package

tidyr easily tidy data with spread and gather functions; an evolution of reshape2 data.table extension of data.frame for fast indexing, ordered joins, assignment, and grouping and list columns

gdata various tools for data manipulation

dplyr a fast, consistent tool for working with data frame like objects

Data Access

Functions

save (), load () save and load R data objects read.csv(), write.csv() import from and export to .CSV files read.table(), write.table(), scan(), write() read and write data

read.xlsx(), write.xlsx() read and write Excel files (xlsx) read.fwf() read fixed width format files

write.matrix() write a matrix or data frame (MASS)

readLines(), writeLines() read/write text lines from/to a connection, such as a text file

sqlQuery () submit an SQL query to an ODBC database (RODBC)

sqlFetch() read a table from an ODBC database (RODBC)

sqlSave(), sqlUpdate() write or update a table in an ODBC database (RODBC)

sqlColumns() enquire about the column structure of tables (*RODBC*)

sqlTables() list tables on an ODBC connection (RODBC)

odbcConnect(), odbcClose(), odbcCloseAll() open/close connections to ODBC databases (RODBC)

dbSendQuery execute an SQL statement on a given database connection (DBI) dbConnect(), dbDisconnect() create/close a connection to a DBMS (DBI)

Packages

RODBC ODBC database access

foreign read and write data in other formats, such as Minitab, S, SAS, SPSS, Stata, Systat, ...

sqldf perform SQL selects on R data frames

DBI a database interface (DBI) between R and relational DBMS

RMySQL interface to the MySQL database

RJDBC access to databases through the JDBC interface

RSQLite SQLite interface for R

ROracle Oracle database interface (DBI) driver

RpgSOL DBI/RJDBC interface to PostgreSQL database

RODM interface to Oracle Data Mining

xlsx read, write, format Excel 2007 and Excel 97/2000/XP/2003 files

xlsReadWrite read and write Excel files

WriteXLS create Excel 2003 (XLS) files from data frames

SPARQL Use SPARQL to pose SELECT or UPDATE queries to an end-point

Web Data Access

Functions

download.file() download a file from the Internet xmlParse(), htmlParse() parse an XML or HTML file (XML) userTimeline(), homeTimeline(), mentions(),

retweetsOfMe() retrieve various timelines within the Twitter universe (twitteR)

searchTwitter() a search of Twitter based on a supplied search string (twit-

getUser(), lookupUsers() get information of Twitter users (twitteR) getFollowers(), getFollowerIDs(), getFriends(),

getFriendIDs () get a list of followers/friends or their IDs of a Twitter user (twitteR)

twListToDF() convert twitteR lists to data frames (twitteR)

Packages

twitteR an interface to the Twitter web API

RCurl general network (HTTP/FTP/...) client interface for R

XML reading and creating XML and HTML documents

httr tools for working with URLs and HTTP; a simplified wrapper built on top of RCurl

MapReduce, Hadoop and Spark

mapreduce () define and execute a MapReduce job (rmr2)

keyval () create a key-value object (rmr2)

from.dfs(), to.dfs() read/write R objects from/to file system (rmr2) hb.get(), hb.scan(), hb.get.data.frame() read HBase tables (rhbase) hb.insert(), hb.insert.data.frame() write to HBase tables (rhbase) hb.delete() delete from HBase tables (rhbase)

Packages

*rmr*2 perform data analysis with R via MapReduce on a Hadoop cluster

rhdfs connect to the Hadoop Distributed File System (HDFS)

rhbase connect to the NoSOL HBase database

Rhipe R and Hadoop Integrated Processing Environment

SparkR a light-weight frontend to use Apache Spark from R

RHive distributed computing via HIVE query

Segue Parallel R in the cloud using Amazon's Elastic Map Reduce (EMR) engine

HadoopStreaming Utilities for using R scripts in Hadoop streaming hive distributed computing via the MapReduce paradigm

rHadoopClient Hadoop client interface for R

Large Data

Functions

as.ffdf() coerce a dataframe to an ffdf(ff)

read.table.ffdf(), read.csv.ffdf() read data from a flat file to an ffdf

write.table.ffdf(), write.csv.ffdf() write an ffdf object to a flat file

ffdfappend () append a dataframe or an ffdf to an existing ffdf (ff)

big.matrix() create a standard big.matrix, which is constrained to available RAM (bigmemory)

read.big.matrix() create a big.matrix by reading from an ASCII file (big-

write.big.matrix() write a big.matrix to a file (bigmemory)

filebacked.big.matrix() create a file-backed big.matrix, which may exceed available RAM by using hard drive space (bigmemory)

mwhich() expanded "which"-like functionality (bigmemory)

Packages

ff memory-efficient storage of large data on disk and fast access functions ffbase basic statistical functions for package ff

filehash a simple key-value database for handling large data

g.data create and maintain delayed-data packages

BufferedMatrix a matrix data storage object held in temporary files

biglm regression for data too large to fit in memory

bigmemory manage massive matrices with shared memory and memory-mapped

biganalytics extend the bigmemory package with various analytics

bigtabulate table-, tapply-, and split-like functionality for matrix and big.matrix objects

Parallel Computing

Functions

sfInit(), **sfStop()** initialize and stop the cluster (*snowfall*) sfLapply(), sfSapply(), sfApply() parallel versions of lapply(), sapply(), apply() (snowfall)

foreach(...) %dopar% looping in parallel (foreach)

registerDoSEQ(), registerDoSNOW(), registerDoMC() register respectively the sequential, SNOW and multicore parallel backend with the foreach package (foreach, doSNOW, doMC)

Packages

snowfall usability wrapper around snow for easier development of parallel R

snow simple parallel computing in R

multicore parallel processing of R code on machines with multiple cores or

snowFT extension of snow supporting fault tolerant and reproducible applications, and easy-to-use parallel programming

Rmpi interface (Wrapper) to MPI (Message-Passing Interface)

rpvm R interface to PVM (Parallel Virtual Machine)

nws provide coordination and parallel execution facilities

foreach foreach looping construct for R

doMC foreach parallel adaptor for the multicore package

doSNOW foreach parallel adaptor for the snow package

doMPI foreach parallel adaptor for the Rmpi package

doParallel foreach parallel adaptor for the multicore package

doRNG generic reproducible parallel backend for foreach Loops

GridR execute functions on remote hosts, clusters or grids fork R functions for handling multiple processes

Interface to Weka

Package **RWeka** is an R interface to Weka, and enables to use the following Weka functions in R.

Association rules:

Apriori(), Tertius()

Regression and classification:

LinearRegression(), Logistic(), SMO()

Lazy classifiers:

IBk(), LBR()

AdaBoostM1(), Bagging(), LogitBoost(), MultiBoostAB(), Stacking(), CostSensitiveClassifier()



Rule classifiers:

JRip(), M5Rules(), OneR(), PART()

Regression and classification trees:

J48(), LMT(), M5P(), DecisionStump()

Clustering:

Cobweb(), FarthestFirst(), SimpleKMeans(), XMeans(),
DBScan()

Filters:

Normalize(), Discretize()

Word stemmers:

IteratedLovinsStemmer(), LovinsStemmer()

Tokenizers:

AlphabeticTokenizer(), NGramTokenizer(), WordTokenizer()

Interface to Other Programming Languages

Functions

- . jcall () call a Java method (rJava)
- . jnew () create a new Java object (rJava)
- . jinit () initialize the Java Virtual Machine (JVM) (rJava)
- . jaddClassPath () adds directories or JAR files to the class path (rJava)

Packages

rJava low-level R to Java interface

rPython call Python from R

Generating Documents and Reports

Functions

Sweave () mixing text and R/S code for automatic report generation xtable() export tables to LaTeX or HTML (xtable)

Packages

knitr a general-purpose package for dynamic report generation in R xtable export tables to LaTeX or HTML

R2HTML making HTML reports

R2PPT generating Microsoft PowerPoint presentations

Building GUIs and Web Applications

shiny web application framework for R

svDialogs dialog boxes

gWidgets a toolkit-independent API for building interactive GUIs

R Editors/GUIs

RStudio a free integrated development environment (IDE) for R

Tinn-R a free GUI for R language and environment

rattle graphical user interface for data mining in R

Rpad workbook-style, web-based interface to R

RPMG graphical user interface (GUI) for interactive R analysis sessions

Red-R An open source visual programming GUI interface for R

R AnalyticFlow a software which enables data analysis by drawing analysis flowcharts

latticist a graphical user interface for exploratory visualisation

Other R Reference Cards

R Reference Card, by Tom Short

 $\label{lem:http://rpad.googlecode.com/svn-history/r76/Rpad_homepage/R-refcard.pdf or } $$ Preferred and $$ Preferred are $$ $$ Preferred are $$ Preferred are$

http://cran.r-project.org/doc/contrib/Short-refcard.pdf

R Reference Card, by Jonathan Baron

http://cran.r-project.org/doc/contrib/refcard.pdf

R Functions for Regression Analysis, by Vito Ricci

http://cran.r-project.org/doc/contrib/Ricci-refcard-regression.
pdf

R Functions for Time Series Analysis, by Vito Ricci

http://cran.r-project.org/doc/contrib/Ricci-refcard-ts.pdf

RDataMining Books

R and Data Mining: Examples and Case Studies

introduces into using R for data mining with examples and case studies.

http://www.rdatamining.com/books/rdm

Data Mining Applications with R

presents 15 real-world applications on data mining with R.

http://www.rdatamining.com/books/dmar

RDataMining Website, Group, Twitter & Package

RDataMining Website

http://www.rdatamining.com

http://www2.rdatamining.com

RDataMining Group on LinkedIn (16,000+ members)

http://group.rdatamining.com or

https://www.linkedin.com/grps/RDataMining-4066593

RDataMining on Twitter (2,300+ followers)

@RDataMining

RDataMining Project on R-Forge

http://www.rdatamining.com/package

http://package.rdatamining.com

Comments & Feedback

If you have any comments, or would like to suggest any relevant R packages/functions, please feel free to email me <yanchang@rdatamining.com>. Thanks

If you have any questions on using R for data mining, please post them to the RDataMining Group on LinkedIn at http://group.rdatamining.com.

