


Multi-Layer Perceptron

Dr. Ratna Babu Chinnam
Industrial & Systems Engineering
Wayne State University

Multi-Layer Perceptron

- Consists of ***input layer***, 1 or more ***hidden layers***, and ***output layer***




"Fully connected" typically implies that nodes in adjacent layers (not across layers) are fully connected!

Architectural Graph of an MLP Network with Two Hidden Layers

- MLP networks are ***feed-forward networks*** (FFNs)
 - Signal propagates forward, layer-by-layer
- ***Trained in a supervised fashion*** using ***error back-propagation algorithm*** or its variants (based on error-correction rule)

Multi-Layer Perceptron


- ***Back-propagation learning*** consists of ***two passes***:
 - *Forward Pass*: Input signal propagates forward
 - *Backward Pass*: Error signal back-propagates
- **Three distinctive characteristics**:
 1. Neuron has a ***differentiable nonlinear activation function***
 2. Network contains 1 or more ***hidden layers***
 3. Network exhibits a high degree of ***connectivity***
- Development of ***back-propagation algorithm*** represents a landmark in that it provides a ***computationally efficient*** method for ***implementing the error-correction rule***



Back-Propagation: Notation

- Indices i , j , and k refer to different neurons in consecutive layers
- $\xi(n)$ denotes "instantaneous" sum of error squares at iteration n
- $y_j(n)$ and $d_j(n)$ denote actual and desired responses, at output neuron j
- $e_j(n)$ denotes neuron j error for iteration n : $e_j(n) = (d_j(n) - y_j(n))$
- $w_{ji}(n)$ denotes weight connecting neuron i to neuron j at iteration n
- $v_j(n)$ denotes activation potential of neuron j at iteration n
- $\varphi_j(\cdot)$ denotes activation function associated with neuron j
- b_j denotes bias for neuron j ; represented by $w_{j0} = b_j$ and input ± 1
- η denotes learning rate parameter
- m_l denotes number of nodes in layer l of network; $l = 0, 1, \dots, L$, where L denotes number of hidden and output layers in network
- N denotes total number of patterns in training set

Back-Propagation: Notation



Signal-flow Graph Highlighting the Details of Neuron k Connected to Neuron j

Back-Propagation: Algorithm

- **Errors:** *Instantaneous* and *averaged* sum of squared errors for network

$$\xi(n) = \frac{1}{2} \sum_j e_j(n)^2 \quad \xi_{av} = \frac{1}{N} \sum_{n=1}^N \xi(n)$$

- **Objective:** Adjust free parameters of network to minimize ξ_{av}
- Let us adjust weights pattern-by-pattern (i.e., "pattern mode" learning)
 - Average of individual weight changes over training set estimate change from directly minimizing ξ_{av} (i.e., "batch mode" learning)

- **Back-Propagation Algorithm:** Employs steepest-descent

$$\Delta w_{ji}(n) \propto \partial \xi(n) / \partial w_{ji}(n)$$

- **Per *delta* rule:**

$$\begin{aligned} \Delta w_{ji}(n) &= -\eta \frac{\partial \xi(n)}{\partial w_{ji}(n)} \\ &= \eta \left[-\frac{\partial \xi(n)}{\partial v_j(n)} \right] \frac{\partial v_j(n)}{\partial w_{ji}(n)} \quad (\text{by chain rule}) \\ &= \eta \delta_j(n) y_i(n) \end{aligned}$$

where $\delta_j(n)$ denotes **local gradient** of neuron j

Back-Propagation: Algorithm

Case I: Neuron j is an Output Node

- According to the chain rule:

$$\frac{\partial \xi(n)}{\partial w_{ji}(n)} = \frac{\partial \xi(n)}{\partial e_j(n)} \frac{\partial e_j(n)}{\partial y_j(n)} \frac{\partial y_j(n)}{\partial v_j(n)} \frac{\partial v_j(n)}{\partial w_{ji}(n)}$$

- From our notation:

$$\frac{\partial \xi(n)}{\partial e_j(n)} = e_j(n) \quad \frac{\partial e_j(n)}{\partial y_j(n)} = -1 \quad \frac{\partial y_j(n)}{\partial v_j(n)} = \varphi'_j(v_j(n)) \quad \frac{\partial v_j(n)}{\partial w_{ji}(n)} = y_i(n)$$

- For current case where neuron j is an output node:

$$\begin{aligned} \delta_j(n) &= - \frac{\partial \xi(n)}{\partial e_j(n)} \frac{\partial e_j(n)}{\partial y_j(n)} \frac{\partial y_j(n)}{\partial v_j(n)} \\ &= e_j(n) \varphi'_j(v_j(n)) \end{aligned}$$

Back-Propagation: Algorithm

Case II: Neuron j is a Hidden Node

- No specified desired response for neuron (hidden node)
 - Error to be determined in terms of errors of neurons to which it is connected

- Local gradient $\delta_j(n)$ for hidden neuron j is:


$$\delta_j(n) = -\frac{\partial \xi(n)}{\partial y_j(n)} \frac{\partial y_j(n)}{\partial v_j(n)} = -\frac{\partial \xi(n)}{\partial y_j(n)} \varphi'_j(v_j(n))$$

- Instantaneous error: $\xi(n) = \frac{1}{2} \sum_k e_k(n)^2$

- Local gradient $\delta_j(n)$ for hidden neuron j can be rewritten as:

$$\begin{aligned} \delta_j(n) &= -\varphi'_j(v_j(n)) \cdot \sum_k \left[e_k(n) \frac{\partial e_k(n)}{\partial y_j(n)} \right] = -\varphi'_j(v_j(n)) \cdot \sum_k \left[e_k(n) \frac{\partial e_k(n)}{\partial v_k(n)} \frac{\partial v_k(n)}{\partial y_j(n)} \right] \\ &= -\varphi'_j(v_j(n)) \cdot \sum_k \left[e_k(n) \frac{\partial e_k(n)}{\partial y_k(n)} \frac{\partial y_k(n)}{\partial v_k(n)} \frac{\partial v_k(n)}{\partial y_j(n)} \right] = -\varphi'_j(v_j(n)) \cdot \sum_k \left[e_k(n) (-1) \varphi'_k(v_k(n)) \frac{\partial v_k(n)}{\partial y_j(n)} \right] \\ &= \varphi'_j(v_j(n)) \cdot \sum_k \left[e_k(n) \varphi'_k(v_k(n)) \frac{\partial \sum_j w_{kj}(n) y_j(n)}{\partial y_j(n)} \right] = \varphi'_j(v_j(n)) \cdot \sum_k [\delta_k(n) w_{kj}(n)] \end{aligned}$$

- $\delta_j(n)$ can be shown to be valid for any neuron in any hidden layer



Activation Function

- Local gradient requires derivative of activation function ($\varphi'(\cdot)$)
- **Logistic Function:**

$$\varphi_j(v_j(n)) = \frac{a}{1 + \exp(-bv_j(n))} \quad (a, b) > 0 \quad -\infty < v_j(n) < +\infty$$
$$\varphi'_j(v_j(n)) = \frac{ab \exp(-bv_j(n))}{[1 + \exp(-bv_j(n))]^2} = \frac{b}{a} \varphi_j(v_j(n)) [a - \varphi_j(v_j(n))]$$

- **Hyperbolic Tangent Function:**

$$\begin{aligned} \varphi_j(v_j(n)) &= a \cdot \tanh(bv_j(n)) \quad (a, b) > 0 \quad -\infty < v_j(n) < +\infty \\ &= a \cdot \frac{1 - \exp(-bv_j(n))}{1 + \exp(-bv_j(n))} \\ \varphi'_j(v_j(n)) &= ab \cdot \operatorname{sech}^2(bv_j(n)) \\ &= ab(1 - \tanh^2(bv_j(n))) = \frac{b}{a} [a + \varphi_j(v_j(n))] [a - \varphi_j(v_j(n))] \end{aligned}$$

Activation Function

- **Softmax Function:**

$$p_j = \text{softmax}(\mathbf{y} = [y_1, \dots, y_K]) = \frac{e^{y_j}}{\sum_{k=1}^K e^{y_k}}$$

$$\frac{\partial p_j(n)}{\partial y_i(n)} = \begin{cases} p_j(1 - p_i) & \text{if } j = i \\ -p_j \cdot p_i & \text{if } j \neq i \end{cases}$$

See Full Derivation Here: [Link](#)

- **ReLu Functions:**

Rectifier:


$$\varphi_j(v_j(n)) = \max(0, v_j(n))$$

$$\varphi'_j(v_j(n)) = \begin{cases} 1 & \text{if } v_j(n) > 0 \\ 0 & \text{if } v_j(n) \leq 0 \end{cases}$$


Softplus:

$$\varphi_j(v_j(n)) = \log(1 + e^{v_j(n)})$$

$$\varphi'_j(v_j(n)) = \frac{e^{v_j(n)}}{1 + e^{v_j(n)}}$$



Signal-flow Summary of Back-propagation Algorithm



Representation: Top Part→Forward Pass. Bottom Part→Backward Pass.

Rate of Learning: “Momentum” and $\eta(n)$

- Back-propagation algorithm provides an “approximation” to steepest descent during pattern-mode learning: **Stochastic Gradient Descent**

- **Rate of Learning:**

- Small η : Smooth trajectory attained at the cost of a slower rate of learning
 - Large η : Faster learning but there is a danger network may become unstable

- **Momentum:** One can increase rate of learning while avoiding instability:

$$\begin{aligned}\Delta w_{ji}(n) &= \alpha \Delta w_{ji}(n-1) + \eta \delta_j(n) y_i(n) \quad 0 \leq |\alpha| < 1 \\ &= \eta \sum_{t=0}^n \alpha^{n-t} \delta_j(t) y_i(t)\end{aligned}$$

- Current adjustment represents sum of an exponentially weighted time series
- Tends to *accelerate descent* in steady downhill directions and has a *stabilizing effect* in directions that oscillate in sign
- **Learning Rate:** Can be adapted as well: $\eta(n)$ Ideas?

Sequential (Pattern) & Batch Modes of Training

- **Sequential Mode:** Adjusts network parameters for each example

$$\Delta w_{ji}(n) = \eta \delta_j(n) y_i(n)$$

- Search in the weight space tends to be *stochastic* avoiding limit cycles
- Order of presentation of training examples has to be randomized
- Reduced memory storage
- Increased potential for avoiding local minima

- **Batch Mode:** Adjusts network parameters after presenting all examples

- Local gradients have to be calculated after presentation of each example

$$\Delta w_{ji} = \frac{\eta}{N} \sum_{n=1}^N \delta_j(n) y_i(n)$$

- Easier to establish theoretical conditions for algorithm convergence

- **Note:** Computed $\delta_j(n)$ and $y_i(n)$ tend to differ for the two modes of training since the weights are updated at different frequencies

Useful Criteria for “Stopping” Network Training

- **Epochs:** Predetermined number of “epochs”
 - Epoch: A single presentation of ALL training patterns to network
- **Computation Time:** Predetermined processor computation time
- **Learning Error:** Acceptable minimum learning error
- **Learning Rate:** Acceptable minimum learning rate
- **Generalization:**
 - Acceptable generalization performance
 - Apparent peak (actually, a “valley” in error plot) in generalization performance

“Heuristics” for Improving Back-propagation Algorithm

- ***Sequential versus batch update.*** Sequential update leads to stochastic gradient search and can be more effective in practice
- ***Mini-batches provide a better balance*** between accuracy and computational efficiency
- ***Nature of activation function.*** Antisymmetric functions generally help (i.e., $\varphi(-v) = -\varphi(v)$).
- ***Target values.*** Linear output neurons might be safer for regression.
- ***Normalization of inputs and outputs.*** Is crucial.
- ***Weight initialization.*** Synaptic weights should be initialized uniformly with mean zero and variance equal to the reciprocal of the number of synaptic connections of a neuron.
- ***Learning rate parameters.*** All neurons should learn at the same rate. Since the last layers have usually larger local gradients, their learning rate parameters should be smaller.
- ***A priori information.*** Utilize this knowledge to achieve invariance properties, symmetries, etc.

“Heuristics” for Improving Back-propagation Algorithm

Batch Normalization for Hidden Layers

- Stochastic/mini-batch gradient is effective, but requires tuning of hyper-parameters
 - Learning rate, network initialization
- Training is complicated for each layer is affected by parameters of preceding layers
 - Small changes to network parameters amplify as network becomes deeper
- **Covariate shift:** Change in distributions of layers’ inputs presents a problem
 - Layers need to continuously adapt to new distributions over the course of training
 - Batch to batch variation
 - Learnt “black” cats and now learning “white” cats
 - **Batch normalization helps overcome covariate shift** for hidden layers
- If γ and β parameters are calculated from the mini-batch, the noise introduced also has a **slight regularization effect**

For Any Given Hidden Layer

Input: Values of x over a mini-batch: $\mathcal{B} = \{x_1 \dots x_m\}$;

Parameters to be learned: γ, β

Output: $\{y_i = \text{BN}_{\gamma, \beta}(x_i)\}$

$\frac{\partial \ell}{\partial \hat{x}_i} = \frac{\partial \ell}{\partial y_i} \cdot \gamma$ **Gradients for Back-Propagation**

$$\frac{\partial \ell}{\partial \sigma_{\mathcal{B}}^2} = \sum_{i=1}^m \frac{\partial \ell}{\partial \hat{x}_i} \cdot (x_i - \mu_{\mathcal{B}}) \cdot \frac{-1}{2} (\sigma_{\mathcal{B}}^2 + \epsilon)^{-3/2}$$

$$\frac{\partial \ell}{\partial \mu_{\mathcal{B}}} = \left(\sum_{i=1}^m \frac{\partial \ell}{\partial \hat{x}_i} \cdot \frac{-1}{\sqrt{\sigma_{\mathcal{B}}^2 + \epsilon}} \right) + \frac{\partial \ell}{\partial \sigma_{\mathcal{B}}^2} \cdot \frac{\sum_{i=1}^m -2(x_i - \mu_{\mathcal{B}})}{m}$$

$$\frac{\partial \ell}{\partial x_i} = \frac{\partial \ell}{\partial \hat{x}_i} \cdot \frac{1}{\sqrt{\sigma_{\mathcal{B}}^2 + \epsilon}} + \frac{\partial \ell}{\partial \sigma_{\mathcal{B}}^2} \cdot \frac{2(x_i - \mu_{\mathcal{B}})}{m} + \frac{\partial \ell}{\partial \mu_{\mathcal{B}}} \cdot \frac{1}{m}$$

$$\frac{\partial \ell}{\partial \gamma} = \sum_{i=1}^m \frac{\partial \ell}{\partial y_i} \cdot \hat{x}_i$$

$$\frac{\partial \ell}{\partial \beta} = \sum_{i=1}^m \frac{\partial \ell}{\partial y_i}$$

Batch Normalization: Accelerating Deep Network Training by
Reducing Internal Covariate Shift

Source: [Link](#)


Sergey Ioffe Christian Szegedy
Google Inc., sioffe@google.com Google Inc., szegedy@google.com

Batch Normalization in TensorFlow: [Link](#)


Why Batch Norm Works: [Link](#)

Achieving “Generalization” with MLP

- Network is said to *generalize* well when the mapping is correct for test data
 - Assumption: Test data are drawn from the same process/population
- Curve-fitting Example: Equivalent to good interpolation
- *Overtraining* or *overfitting* can result if network starts “memorizing” training data
- Can be viewed from different perspectives:
 - Architecture is fixed, what should be the size of the training data?
 - VC dimension provides the theoretical basis
 - Training data set is fixed, what is the best architecture for the network?
 - More common approach





Mapping with good generalization



Mapping with poor generalization

Achieving Generalization through “Cross-Validation”

- “Training” can be seen as making the network “learn enough” to generalize
- **Cross-Validation:** A standard tool from statistics is valuable
 - Dataset is partitioned into **training** (N patterns) and **test** sets (M patterns)
 - Training set is further partitioned into two disjoint subsets:
 - **Estimation** subset to “learn” the model (with $(1 - r)N$ patterns, where $0 < r < 1$)
 - **Validation** subset to “validate” the model (with rN patterns)
 - Possible for model to overfit validation subset. Measure performance on test set.
 - As target function becomes complex relative to N , choice of r^* becomes important and should decrease in value (Kearns, 1996)
- **Early Stopping:** A method of training using cross-validation
 - Periodically stop network training process and test network
 - Permanently stop training if an increase is noted in validation error over successive evaluations.
 - Effectiveness decreases if $N \gg W$



Variants of Cross-Validation

- For relatively small training data sets, two variants of cross-validation that offer more promise include:
- ***Multifold Method***
 - Involves dividing training set into K subsets, $K > 1$
 - Model is trained on all subsets except for one, and validation error is measured by testing it on the subset left out
 - Procedure is repeated for a total of K trials, each time using a different subset for validation
 - Model performance is assessed by averaging squared error under validation over all trials of the experiment
 - Increases computational burden
- ***Leave-one-out Method***
 - When data set is severely small, one can use extreme form of multifold cross-validation where K equals N




Illustration of the Hold-Out Method of Cross-Validation

Implementing Cross-Validation: Heuristic Guidelines

- **Large Sample Size (data points \gggg model parameters): No need for cross-validation**
 - Optimize network configuration and model parameters using full dataset
 - Occam's Razor Principle is still relevant (seek smaller models over complex models)
- **Decent Sample Size (data points \gg model parameters): Simple Cross-Validation** (partition dataset into *training, validation, and test* sets)
 - Optimize network configuration using best validation error as criteria
 - Evaluate errors on test set to ensure that they are comparable to errors seen under cross-validation
- **Small Sample Size (data points $>$ model parameters): Implement Multifold Method**
 - Optimize network configuration using best pooled validation error as criteria
 - Aggregate errors over "all" validation trials of the experiment
 - Retrain network using **entire training and validation sets** and rely on early-stopping to stop training once training error reaches the training error corresponding to best validation error
- **Very Small Sample Size (data points $<$ model parameters): Leave-one-out Method**
 - Optimize network configuration using best pooled validation error as criteria
 - Retrain network using **entire dataset** and rely on early-stopping to stop the training once the error reaches the training error corresponding to best validation error
- **Sampling for Data Partition:** Seek stratified (classification) sets with full coverage
 - To the extent possible, all datasets should have cases from all classes (classification) and/or cover the full range of the input space (regression)

Complexity-Regularization: Network Pruning/Growing

- **Idea:** A network with minimum/optimal size is less likely to learn the idiosyncrasies or noise in the training data (offering good generalization)
- **Two Approaches:** *Network Growing & Network Pruning*
 - Aim to tackle the bias-variance dilemma
- **Complexity-Regularization:** Minimize risk $R(\mathbf{w}) = \xi_S(\mathbf{w}) + \lambda \xi_C(\mathbf{w})$
 - $\xi_C(\mathbf{w})$ denotes complexity penalty and depends on the network (model) alone
 - $\xi_S(\mathbf{w})$ denotes the standard performance measure (such as MSE) and depends on network (model) and input data
 - λ denotes complexity regularization parameter ($0 \leq \lambda \leq \infty$)
- **K^{th} -Order Smoothing Requirement:** $\xi_C(\mathbf{w}, k) = \frac{1}{2} \int \left\| \frac{\partial^k}{\partial \mathbf{x}^k} F(\mathbf{x}, \mathbf{w}) \right\|^2 \mu(\mathbf{x}) d\mathbf{x}$
 - $F(\mathbf{x}, \mathbf{w})$ is input-output mapping performed by the model
 - $\mu(\mathbf{x})$ is some weighting function determining region of input space over which function $F(\mathbf{x}, \mathbf{w})$ is required to be smooth
 - Larger the k , smoother (i.e., less complex) the function $F(\mathbf{x}, \mathbf{w})$
- **Weight Decay Method:** $\xi_C(\mathbf{w}) = \|\mathbf{w}\|^2$
- **Weight Elimination Method:** $\xi_C(\mathbf{w}) = \sum_{\forall i} \frac{(w_i/w_0)^2}{1+(w_i/w_0)^2}$ (w_0 is a parameter)

Hyper-Parameter Tuning

- **Need to optimize network structure and learning parameters**


- Number of hidden layers
- Nodes per layer
- Transfer function/parameters
- Learning rate/decay
- Regularization parameters
- Others ...

- **Joint optimization is necessary**

- Total Enumeration (Grid Search): Can be expensive
- Random Search: Little more practical
- [Bayesian Optimization](#): Smart exploration & exploitation



- **Example Packages:**

- Matlab: bayesopt | [Link](#)
- Python: [skopt](#) | [Link](#) | [Example](#); bayesopt | [Example](#)
- Keras: Talos | [Link](#)
- Google Cloud: Bayesian Optimization | [Link](#)





Neural Network Playground: Website

- Daniel Smilkov and Shan Carter created a [neural network playground](#) (using TensorFlow) to demystify MLP networks



Neural Network Playground: Classification Experiments

#	Data	Features	Hidden Layers & Nodes	Activation & Learning Rate	Regularization Type & Rate	OBSERVATIONS: Accuracy/Loss (Train/Test), Convergence Rate, Robustness, Others
1		X_1, X_2	2: 4, 2	Tanh, 0.03	None	
2				ReLU, 0.03		
3				Tanh, 0.03	L2, 0.01	
4					L1, 0.01	
5		$+X_1^2, X_2^2, X_1X_2$			None	
6					L2, 0.01	
7		X_1, X_2	2: 4, 2	Tanh, 0.03	None	
8			2: 8, 4			
9			3: 8, 4, 2			
10		$+ \sin(X_1), \sin(X_2)$	2: 4, 2			
11		X_1, X_2	5: 6,5,4,3,2			Batch Size: 30
12			3: 8, 5, 3			

Other Settings: Ratio of Training to Test Data=50%, Noise=0, Batch Size=10



Epoch
000,520

Learning rate

0.03

Activation

Tanh

Regularization

None

Regularization rate

0.01

Problem type

Classification

DATA

Which dataset do you want to use?



Ratio of training to test data: 50%


Noise: 0

Batch size: 10

REGENERATE

FEATURES

Which properties do you want to feed in?



+ - 2 HIDDEN LAYERS

+ -

4 neurons

+ -

2 neurons


This is the output from one neuron. Hover to see it larger.

The outputs are mixed with varying weights, shown by the thickness of the lines.


OUTPUT

Test loss 0.000

Training loss 0.000



Colors shows data, neuron and weight values.



☐ Show test data

☐ Discretize output

Observations!!!

Classification Experiment #1



Epoch
000,340

Learning rate
0.03

Activation
ReLU

Regularization
None

Regularization rate
0.01

Problem type
Classification

DATA


Which dataset do you want to use?




Ratio of training to test data: 50%



Noise: 0



Batch size: 10



REGENERATE

FEATURES

Which properties do you want to feed in?



2 HIDDEN LAYERS



4 neurons



2 neurons




The outputs are mixed with varying weights, shown by the thickness of the lines.


This is the output from one neuron. Hover to see it larger.

OUTPUT

Test loss 0.000
Training loss 0.000



Colors shows data, neuron and weight values.



☐ Show test data

☐ Discretize output

Observations!!!

Classification Experiment #2



Epoch
000,322

Learning rate
0.03

Activation
Tanh


Regularization
L2

Regularization rate
0.01

Problem type
Classification

DATA

Which dataset do you want to use?



Ratio of training to test data: 50%

Noise: 0

Batch size: 10

REGENERATE

FEATURES


Which properties do you want to feed in?




2 HIDDEN LAYERS



4 neurons




2 neurons



OUTPUT

Test loss 0.003
Training loss 0.004



Colors shows data, neuron and weight values.

☐ Show test data ☐ Discretize output

Observations!!!

Classification Experiment #3



Epoch
002,020

Learning rate

0.03

Activation

Tanh

Regularization

L1

Regularization rate

0.01

Problem type

Classification

DATA

Which dataset do you want to use?



Ratio of training to test data: 50%



Noise: 0



Batch size: 10



REGENERATE

FEATURES

Which properties do you want to feed in?

X_1

X_2

X_1^2

X_2^2

X_1X_2

$\sin(X_1)$

$\sin(X_2)$

2 HIDDEN LAYERS

+ -

4 neurons

+ -

2 neurons


The outputs are mixed with varying weights, shown by the thickness of the lines.

This is the output from one neuron. Hover to see it larger.


OUTPUT

Test loss 0.003

Training loss 0.004



Colors shows data, neuron and weight values.



☐ Show test data

☐ Discretize output

Observations!!!

Classification Experiment #4



Epoch
000,318

Learning rate
0.03

Activation
Tanh

Regularization
None

Regularization rate
0.01

Problem type
Classification

DATA

Which dataset do you want to use?



Ratio of training to test data: 50%


Noise: 0

Batch size: 10

REGENERATE

FEATURES

Which properties do you want to feed in?




2 HIDDEN LAYERS



4 neurons




2 neurons




OUTPUT

Test loss 0.000
Training loss 0.000



Colors shows data, neuron and weight values.



☐ Show test data

☐ Discretize output

Observations!!!

Classification Experiment #5



Epoch
000,320

Learning rate
0.03

Activation
Tanh

Regularization
L1

Regularization rate
0.01

Problem type
Classification

DATA

Which dataset do you want to use?



Ratio of training to test data: 50%

Noise: 0

Batch size: 10

REGENERATE

FEATURES

Which properties do you want to feed in?

X_1
 X_2
 X_1^2
 X_2^2
 X_1X_2

$\sin(X_1)$
 $\sin(X_2)$

+ - 2 HIDDEN LAYERS

+ -
4 neurons


+ -
2 neurons

The outputs are mixed with varying weights, shown by the thickness of the lines.


This is the output from one neuron. Hover to see it larger.

OUTPUT

Test loss 0.004
Training loss 0.004



Colors shows data, neuron and weight values.



☐ Show test data

☐ Discretize output

Observations!!!

Classification Experiment #6



Epoch
002,019

Learning rate
0.03

Activation
Tanh

Regularization
None

Regularization rate
0.01

Problem type
Classification

DATA

Which dataset do you want to use?



Ratio of training to test data: 50%

Noise: 0

Batch size: 10

REGENERATE

FEATURES

Which properties do you want to feed in?

- ☒ X_1
- ☒ X_2
- ☐ X_1^2
- ☐ X_2^2
- ☐ X_1X_2
- ☐ $\sin(X_1)$
- ☐ $\sin(X_2)$

+ - 2 HIDDEN LAYERS

+ -
4 neurons


+ -
2 neurons

This is the output from one neuron. Hover to see it larger.


The outputs are mixed with varying weights, shown by the thickness of the lines.

OUTPUT

Test loss 0.446
Training loss 0.267



Colors shows data, neuron and weight values.





☐ Show test data

☐ Discretize output

Observations!!!

Classification Experiment #7





Classification Experiment #9



Epoch
002,929

Learning rate

0.03

Activation

Tanh

Regularization

None

Regularization rate

0.01

Problem type

Classification

DATA

Which dataset do you want to use?



Ratio of training to test data: 50%

Noise: 0

Batch size: 10

REGENERATE

FEATURES

Which properties do you want to feed in?

X_1

X_2

X_1^2

X_2^2

X_1X_2

$\sin(X_1)$

$\sin(X_2)$


+ - 2 HIDDEN LAYERS

+ -

4 neurons

+ -



2 neurons




OUTPUT

Test loss 0.173

Training loss 0.001



Colors shows data, neuron and weight values.




☐ Show test data


☐ Discretize output

Observations!!!

Classification Experiment #10



Classification Experiment #11



Observations!!!

Classification Experiment #12