

Reviewer Response Status — IEEE Access 33821

Generated 2026-09-08

Contents

All comments in one table
Reference numbers

12 comments, one-shot resubmission. One row per comment: what was asked, what changed, and what is still open. Manuscript sources: paper-access.tex (A) and paper-build.tex (B), kept in sync. Work line: main.

All comments in one table

Comment	Asked	Done	Remaining
R1-1 single collection, 31 images	Only 31 images from a single collection, with no proof the method works on other drawing styles or at larger scale.	Results labeled as within-collection only, with data origins disclosed; no broad claims; future expansion described as future work.	Owner read-through
R1-2 complex parts	Which complex devices are really handled: pin modeling for non-trivial parts, and switches currently exported as plain resistors.	New capability table separating tested connectivity, estimated pins, and illustrative export; switch behavior stated exactly as the code does it.	Owner read-through

Comment	Asked	Done	Remaining
R1-3 hand-set thresholds	Fixed scale-relative thresholds set by hand, including the alpha the reviewer names; no adaptive learning; behavior at size extremes unknown.	All values stated plainly (alpha 0.35, multipliers, clamps); untested extremes admitted.	Nothing
R1-4 no values, can't simulate	No component values are read, so the output cannot simulate despite SPICE-format claims.	Scope stated in abstract, intro, and conclusion; retitled; export labeled illustrative throughout.	Nothing
R1-5 small circuits only	Narrow coverage of 3 to 14 supported parts with median 7; dense buses and multilayer crossings untested.	Limits stated; true distribution printed in the caption; nothing claimed beyond it.	Nothing
R1-6 memristor citations	Cite two suggested papers (memristor neural circuit with classical conditioning; memristive decision-making for navigation) in the SPICE-simulation sections.	Both checked and cited in Related Work with full references.	Template check
R2-1 statistics, roadmap	Statistical treatment of the results plus a research roadmap; historical timing data missing.	Sampling and checking process described; roadmap added; missing timing honestly noted.	Owner read-through
R2-2 VLM comparison	Whether the VLM comparison is fair (it receives annotated boxes) and how cost is framed.	Labeled as a diagnostic with identical inputs; no equivalence or cost claims.	Nothing
R2-3 title overclaims	Title promises simulation-ready SPICE output the method does not produce.	Retitled everywhere, including running heads and the pipeline diagram.	PDF rebuild

Comment	Asked	Done	Remaining
R2-4 crossing wires	Whether crossings get merged into junctions, including detector misses, and what that costs netlist correctness.	Measured tradeoff reported in full (27/4/0 goes to 19/0/8); detector-miss part honestly marked unmeasured.	Nothing possible
R2-5 ablations	Module ablations judged severely insufficient as evidence for each part's contribution.	Real table as observed, ties presented without spin; missing tests disclosed.	Nothing provable
R2-6 single-scalar limit	Discussion point on the limits of single-scalar evaluation.	Kept as-is; no change needed.	Nothing

Shared language everywhere: a non-finding is not equivalence; no blanket guarantees; pair scores do not certify pin layouts; lab-condition results do not prove real-world dominance.

Reference numbers

Join 0.890 (418/37/66) on all 31; perfect-wire 0.88983 (420/40/64). Wire ledger: 0.9755 = 10°/18px config, 0.9726 = 12°/8px production. Otsu 0.789. VLM 0.923, 21/31 exact. Reach sweep macro 0.895–0.903. Numeric gate: 192/192 stored comparisons pass.