

Score-Based Calibration of Scientific Surrogate Models

Nora I. Alvarez

Department of Applied Mathematics, University of Colorado Boulder
`n.alvarez@colorado.edu`

Henrik S. Holm

Niels Bohr Institute, University of Copenhagen
`hholm@nbi.ku.dk`

January 1, 1970

Abstract

Surrogate models accelerate scientific simulation but are often miscalibrated out of distribution. We present a compact score-based calibration procedure that post-hoc adjusts a pretrained emulator using a small labeled holdout set. The method estimates a monotone transport map on residual scores and yields prediction intervals with near-nominal coverage on three benchmark PDE families. The preprint is written as a standard one-column article suitable for arXiv.

Preprint. Comments welcome.

1 Introduction

High-fidelity solvers remain expensive for inverse problems and uncertainty quantification. Learned surrogates reduce wall-clock cost, yet their residual distributions drift when the operating regime changes [1, 2]. Calibration—rather than full retraining—is often sufficient when the emulator already captures the dominant solution manifold.

This note describes a lightweight post-hoc procedure. Let f_θ be a frozen surrogate and $s(x, y)$ a residual score. We fit a monotone map T on a calibration split so that $T \circ s$ is approximately uniform under the target measure, then invert T to form intervals.

2 Method

Given pairs $\{(x_i, y_i)\}_{i=1}^n$ from the calibration split, define

$$s_i = s(x_i, y_i) = \|y_i - f_\theta(x_i)\|_2. \quad (1)$$

Let $\hat{F}$ be the empirical distribution function of $\{s_i\}$. For a desired miscoverage α , the interval at a query x is

$$[f_\theta(x) - \hat{F}^{-1}(1 - \alpha), f_\theta(x) + \hat{F}^{-1}(1 - \alpha)] \quad (2)$$

in the scalar case, and an analogous Mahalanobis ball in the vector case. When a held-out score sequence is available we replace $\hat{F}$ by an isotonic regression against ranks, which reduces finite-sample jitter.

Proposition 2.1. *If the calibration scores are exchangeable with the test score, the resulting intervals have coverage at least $1 - \alpha$ up to a $1/(n + 1)$ discretization term.*

Table 1: Empirical coverage (target 90%) and mean interval width.

System	Base cov.	Cal. cov.	Base width	Cal. width
Burgers	0.71	0.91	0.42	0.55
Darcy	0.64	0.89	0.31	0.48
Reaction–diffusion	0.77	0.92	0.28	0.36

3 Experiments

We evaluate on Burgers, Darcy flow, and a reaction–diffusion system. Table 1 reports interval coverage and width relative to an uncalibrated residual baseline.

4 Related Work

Physics-informed networks and neural operators provide differentiable surrogates for continuum models [1, 2, 3]. Conformal prediction supplies finite-sample coverage under exchangeability [4]. The present note uses residual scores as the interface between the two: the emulator stays frozen, and only a one-dimensional monotone map is fit.

5 Discussion

Calibration cannot repair a surrogate that misses a bifurcation. In that regime we recommend detecting score inflation and falling back to the numerical solver. When the holdout set is smaller than about fifty points the isotonic map becomes noisy; a parametric Gamma tail is then preferable. The construction adds no trainable weights to f_θ and remains a standard one-column preprint.

6 Conclusion

Score-based calibration is a cheap insurance policy for scientific emulators. The method requires only a labeled holdout set and produces intervals that track the target coverage on the studied PDE families. Code and a reproducibility checklist accompany the arXiv deposit.

References

- [1] M. Raissi, P. Perdikaris, and G. E. Karniadakis, “Physics-informed neural networks,” *J. Comput. Phys.*, vol. 378, pp. 686–707, 2019.
- [2] G. E. Karniadakis et al., “Physics-informed machine learning,” *Nat. Rev. Phys.*, vol. 3, pp. 422–440, 2021.
- [3] Z. Li et al., “Fourier neural operator for parametric partial differential equations,” in *Proc. ICLR*, 2021.
- [4] V. Vovk, A. Gammerman, and G. Shafer, *Algorithmic Learning in a Random World*. Springer, 2005.