

S.T.I.T.C.H.: Simulating The Interactions of Thousands of Clusters in Hyperspace

Stéphane

*MCfA — Malaga Center for Astrophysics**

July 21, 2026

Abstract

We present S.T.I.T.C.H., a novel hyper-dimensional N -body integration framework designed to simulate massive stellar clusters in spaces ranging from 1D to 100D. The primary motivation of this project is to study gravitational objects in high-dimensional space, providing deep theoretical insights into how spatial dimensionality fundamentally governs the formation, stability, and structural evolution of these celestial bodies. By mathematically generalizing Gauss’s Law to higher-dimensional topologies, we preserve strict physical realism across arbitrary coordinate limits. Our integrations leverage high-performance Vulkan compute shaders (WGPU via Rust) and tensor-accelerated architectures (ROCm via PyTorch) to compute dense $O(N^2)$ pairwise forces, eliminating traditional performance bottlenecks. Furthermore, we investigate collisional dynamics by injecting hyper-massive rogue objects into perfectly virialized Salpeter-mass clusters, validating our integration stability in localized hyper-spatial disturbances. All phase spaces are durably logged to a PostgreSQL database for comprehensive topological analysis.

1 Introduction to N -Dimensional Gravity

Traditional Newtonian gravity in 3-dimensional space dictates that the gravitational force between two masses follows an inverse-square relationship with distance. This arises naturally from Gauss’s Law for gravity, wherein the gravitational flux spreads uniformly across the surface area of a bounding sphere, which is proportional to $4\pi R^2$.

To simulate cluster interactions in N -dimensional space, this mathematical constraint must be generalized. By observing and simulating gravitational objects across these varying dimensionalities, we can isolate how the geometry of space itself dictates macroscopic properties such as cluster morphology, stability thresholds, and structural organization. The surface area of an N -dimensional hypersphere scales proportionally to R^{N-1} . Therefore, to maintain a consistent physical framework, the gravitational force magnitude between two bodies separated by distance R in N -dimensions must decay as:

$$F(R) \propto \frac{1}{R^{N-1}} \quad (1)$$

Consequently, the physical behaviors in S.T.I.T.C.H. vary drastically based on dimensionality:

- **1D:** Force is constant ($F \propto 1/R^0$), resulting in unbounded linear oscillatory mechanics.
- **2D:** Force decays logarithmically with potential ($F \propto 1/R^1$), modelling idealized planar accretion discs.

*Disclaimer: The MCfA is a purely fictional research institute, established solely for illustrative purposes under the "Newtonian Agreement".

- **3D:** Standard Newtonian gravity ($F \propto 1/R^2$).
- **4D+:** Extreme short-range decay ($F \propto 1/R^3 \dots 1/R^{99}$), where gravitational influence falls off rapidly, mimicking the behavior of microscopic particle physics at macroscopic scales.

2 Numerical Implementation & Architecture

S.T.I.T.C.H. is powered by a dual-engine architecture targeting both generalized computing and AI-tensor acceleration.

2.1 GPU Compute Engine (Rust/WGPU)

For stable, long-running integrations, we utilize Rust combined with the WGPU ecosystem targeting the Vulkan backend. The equations of motion are solved utilizing the Velocity Verlet symplectic integrator, defined as:

$$\vec{x}(t + \Delta t) = \vec{x}(t) + \vec{v}(t)\Delta t + \frac{1}{2}\vec{a}(t)\Delta t^2 \quad (2)$$

$$\vec{v}(t + \Delta t) = \vec{v}(t) + \frac{1}{2} [\vec{a}(t) + \vec{a}(t + \Delta t)] \Delta t \quad (3)$$

To prevent catastrophic computational singularities (division by zero during near-field interactions), a softening parameter ϵ is introduced into the generalized force calculation:

$$F_{ij} = \frac{Gm_i m_j}{(R_{ij}^2 + \epsilon^2)^{(N-1)/2}} \quad (4)$$

2.2 TDR Mitigation Strategy

Due to the massive $O(N^2)$ workload required for gravity passes, traditional bulk GPU submissions trigger Driver Timeout Detection and Recovery (TDR) crashes. S.T.I.T.C.H. successfully circumvents this via granular, per-pass command submissions inside the compute loop, yielding stable execution for millions of time-steps.

3 Cluster Initialization & Collisional Dynamics

3.1 Virial Equilibrium

The simulations spawn 10,000 particles following a King Model spatial distribution, with masses sampled from a Salpeter Initial Mass Function (IMF). Before integration begins, the cluster undergoes a scaling sequence to guarantee strict virial equilibrium. According to the Virial Theorem, a stable self-gravitating system must satisfy:

$$2T + V = 0 \implies Q = \frac{T}{|V|} = 0.5 \quad (5)$$

Where T is the total kinetic energy and V is the potential energy. S.T.I.T.C.H. iteratively scales the generated velocity vectors to achieve exactly $Q = 0.5$.

3.2 Rogue Object Injections

To test the resilience of our perfectly virialized clusters, we introduced collisional simulation forks (`rust_nbody_2D_incoming` and `3D_incoming`). A rogue supermassive object of $300 M_{\odot}$ is injected at a distance of 200 pc, traveling directly toward the cluster core at 200 km/s. Initial accelerations are dynamically recalculated to subject the cluster to the rogue object’s gravitational pull at $t = 0$, providing an excellent environment to study cluster disruption, ejection events, and evaporation rates.

4 Analytics & Database Framework

A core feature of the S.T.I.T.C.H. framework is its native PostgreSQL integration. As opposed to writing unwieldy binary files, the engines commit all physical parameters—snapshot IDs, physical time (Myr), positions, and velocities—directly into the local `hypercluster` relational database. This allows our Julia and Python analysis suites to effortlessly query phase spaces, track escaping stars across the R_{80} boundary, and model dynamic surface densities via SQL queries.

5 Conclusion

S.T.I.T.C.H. bridges the gap between hyper-dimensional mathematics and high-performance GPU computing. By coupling robust symplectic integrators with strict topological physical laws, the MCfA has created a sandbox capable of unravelling the deepest mysteries of N -body systems across arbitrary spatial manifolds.

Acknowledgments

The numerical framework, architectural code generation, and mathematical typesetting of the S.T.I.T.C.H. project were heavily assisted by Google Gemini.