

Midas_V2 — Afternoon Session (Combined Report)

(2025-09-16 PM, v0.3.19-WIP)

Executive Summary

- Objective: make the catalyst flow simple and reliable using **A-priority + B-fill** (TopN=3), without touching keys.
- Baseline B (2025-08-05): **10 trades → TP=4, SL=6, Win% 40.0**.
- Catalyst B (2025-08-05, TopN=3): **picked MD → 1 trade → TP=1, Win% 100.0**.
- Key changes:
 - **SAFE wrappers** added; subprocesses now set **PYTHONPATH=./src**.
 - `topgappers.py` default **min_gap=10%** (was 5%) for Cameron simplicity.
 - **Catalyst picker** hardened: **A-priority + B-fill**, robust CSV parsing (case-insensitive headers, BOM/delimiter auto-detect) and **news fallback** (uses per-symbol `max(best_score)`).

What We Did (in order, with exact commands)

1) Baseline day — Scenario B (2025-08-05)

```
python scripts/run_day_simple_SAFE.py --date 2025-08-05 --scenario B
python scripts/summarize_results.py --date 2025-08-05
```

Observed: header `min_gap=10.0%`; universe=36 symbols; results at `out/20250805/B/results_2025-08-05.csv`; **B: TP=4 SL=6 Win%=40.0**.

2) Catalyst day — Scenario B (2025-08-05) — A-priority + B-fill, TopN=3

```
python scripts/run_day_catalyst_SAFE.py --date 2025-08-05 --scenario B --topn 3
--min-grade 2 --allow-b-fill
python scripts/summarize_results.py --date 2025-08-05
```

Observed: `catalyst_scores_...` malformed (header parsed as `['MD']`), but news audit existed; picker debug:

```
``[PICKER] scores_headers=['MD'] rows_in_scores=0 news_symbols=1 min_grade=2
allow_b_fill=True -> picked=['MD']``
```

Universe: `data/universe_catalyst_2025-08-05.txt` contained **MD**; minutes fetched; **B: TP=1 SL=0 Win%=100.0**.

Catalyst Selection — Process & Policy

Process

1. Build topgappers (`topgappers.py`) → `data/samples/universe_sample.txt` (price 1–20, **gap ≥10%**).
2. Enrich catalysts (`enrich_universe_catalyst.py --in ... --out ...`) →
 - `out/catalyst/catalyst_scores.csv` (symbol scores),
 - `out/catalyst/catalyst_news.csv` (news audit).
3. Picker (SAFE): read **scores**; if empty/zero, **promote** via news audit `max(best_score)`;

4. **A**priority + **B**fill: take A's (score ≥ 2) first; B's (score =1) only if `--allow-b-fill`;
5. Safety net: if still empty but rows exist, pick top few by score; write universe + audit; run and summarize.

Defaults now

- TopN = 3; **A**priority; **B**fill allowed; confirms on (EMA + VWAP + MACD); later we can add an **opening RVOL gate** (≥ 1.5).

Catalyst CSVs — What's Inside

A `catalyst_scores.csv` (symbol scores, primary)

- Columns (case-insensitive): `symbol`/`ticker`, `score`/`catalyst_score`, optional `grade` (derived: A if ≥ 2 ; B if =1; else 0).
- Today's issue: parsed header as `['MD']` → 0 usable rows; picker's robust reader + news fallback handled it.

B `catalyst_news.csv` (news audit, fallback + debugging)

- Columns (case-insensitive): `symbol`/`ticker`, `best_score` (or `score`), `count`, `title`, `published`.
- Note: `count` $\neq$ `score`; we rely on `best_score` for fallback.

Problems & Fixes

- 1) `midas_v2.cli` not found → **Fix:** SAFE wrappers set `PYTHONPATH=./src` for subprocesses.
- 2) `--in/--out` and `--universe` args missing → **Fix:** wrapper now passes required arguments.
- 3) Scanner too loose (5%) → **Fix:** default `min_gap=10%`.
- 4) Early empty pick bug despite **B**fill → **Fix:** corrected **A**priority + **B**fill; added safety net.
- 5) Malformed symbol scores CSV → **Fix:** robust CSV reader + **news fallback** to avoid dropping catalysts.
- 6) YMAB confusion → news shows `count=3` but `best_score=0`, so not A/B; correctly excluded. MD had `best_score=1` (**B**grade) and was picked.

Files Written (Aug 05)

- `data\samples\universe_sample.txt` (36 symbols, 10% gap)
- `out\20250805\B\results_2025-08-05.csv` (baseline)
- `out\20250805\catalyst\catalyst_scores_2025-08-05.csv` (malformed in this run)
- `out\20250805\catalyst\catalyst_news_2025-08-05.csv` (news audit; MD `best_score=1`, YMAB `best_score=0`)
- `out\20250805\catalyst\catalyst_universe_2025-08-05.csv` (audit)
- `data\universe_catalyst_2025-08-05.txt` (final TopN universe)

Results (Aug 05)

- **Baseline B:** `TP=4`, `SL=6` → Win% 40.0
- **Catalyst B (TopN=3):** **MD picked** → `TP=1`, `SL=0` → Win% 100.0

Next Steps (one step at a time)

1) Aug 06 baseline then catalyst (Top N=3) and compare:

```
python scripts/run_day_simple_SAFE.py --date 2025-08-06 --scenario B; python
scripts/summarize_results.py --date 2025-08-06
python scripts/run_day_catalyst_SAFE.py --date 2025-08-06 --scenario B --topn 3
--min-grade 2 --allow-b-fill; python scripts/summarize_results.py --date 2025-08-06
```

2) If catalyst wins again, keep **Top N=3**; later add opening **RVOL gate ≥ 1.5 **.

Commit Snippet (PowerShell)

```
git add .\scripts\run_day_simple_SAFE.py .\scripts\run_day_catalyst_SAFE.py
.\scripts\topgappers.py
git commit -m "PM: SAFE wrappers + PYTHONPATH; catalyst picker robust CSV + news
fallback; min_gap=10%; Aug-05 catalyst B: MD TP=1"
```