

Hybrid Router (A–E) — Deferred

Date: 2025-09-07

Status: Deferred (post-tuning)

Version context: v0.3.7-cleanup

Rationale

We will postpone introducing a Scenario Router (hybrid of A–E) until we finish tuning and validating the individual scenarios. Early hybridization could mask weaknesses in B/D/E and make debugging harder.

Prerequisites Before Hybridization

- Clean repo checkpoint at **v0.3.7-cleanup**
- Re-establish **Scenario B** as a stable baseline (Aug + Sep)
- Validate **Scenario D_strict** across Aug + Sep (target ~60–63% WR)
- Trial **Scenario E_dip** with guardrails (EMA/VWAP confirm, rise_bars ≥ 2 , gate 10–15)
- Add **opening RVOL gate** (first 10–15m vs prior day) and **universe hygiene** (exclude ADRs/China, low float junk) across all scenarios
- Confirm risk model (TP 2.0%, SL 2.5–3.0%, daily max loss cap)
- Compare August vs September to check regime sensitivity

When We're Ready

- Implement a **router** with precedence (example: $E \rightarrow D \rightarrow B$), one position per symbol.
- Emit merged CSV: `out/YYYYMMDD/ROUTER/merged\_YYYY-MM-DD.csv` and a summary TXT.
- Keep per-scenario outputs for auditability.

Notes

- Hybridization historically improved **stability** and **profit** once scenarios were tuned.
- We'll document router design and commands in a separate guide when activated.