

ACM-ICPC TEAM REFERENCE DOCUMENT

Vilnius University (Šimoliūnaitė, Strakšys, Strimaitis)

Contents

1 General	1
1.1 C++ Template	1
1.2 Python Template	1
1.3 Compilation	1
1.4 Automatic Test	1
1.5 Ternary Search	1
1.6 Big Integer	2
2 Data Structures	4
2.1 Disjoin Set Union	4
2.2 Fenwick Tree Point Update And Range Query	4
2.3 Fenwick Tree Range Update And Point Query	4
2.4 Fenwick Tree Range Update And Range Query	4
2.5 Fenwick 2D	4
2.6 Segment Tree	5
2.7 Segment Tree With Lazy Propagation	5
2.8 Treap	5
2.9 Implicit Treap	6
2.10 Trie	6
3 Graphs	7
3.1 Dfs With Timestamps	7
3.2 Lowest Common Ancestor	7
3.3 Strongly Connected Components	7
3.4 Bellman Ford Algorithm	7
3.5 Bipartite Graph	8
3.6 Finding Articulation Points	8
3.7 Finding Bridges	9
3.8 Max Flow With Ford Fulkerson	9
3.9 Max Flow With Dinic	9
3.10 Max Flow With Dinic 2	10
3.11 Min Cut	10
3.12 Number Of Paths Of Fixed Length	11
3.13 Shortest Paths Of Fixed Length	11
4 Geometry	11
4.1 2d Vector	11
4.2 Line	11
4.3 Convex Hull Gift Wrapping	11
4.4 Convex Hull With Graham's Scan	11
4.5 Circle Line Intersection	12
4.6 Circle Circle Intersection	12
4.7 Common Tangents To Two Circles	12
4.8 Number Of Lattice Points On Segment	12
4.9 Pick's Theorem	12

5 Math	12
5.1 Linear Sieve	12
5.2 Extended Euclidean Algorithm	13
5.3 Chinese Remainder Theorem	13
5.4 Euler Totient Function	13
5.5 Factorization With Sieve	13
5.6 Modular Inverse	13
5.7 Simpson Integration	13
5.8 Burnside's Lemma	14
5.9 FFT	14
5.10 FFT With Modulo	14
5.11 Big Integer Multiplication With FFT	15
5.12 Formulas	15
6 Strings	15
6.1 Hashing	15
6.2 Prefix Function	16
6.3 Prefix Function Automaton	16
6.4 KMP	16
6.5 Aho Corasick Automaton	16
6.6 Suffix Array	17

1 General

1.1 C++ Template

```
#include <bits/stdc++.h>
#include <ext/pb_ds/assoc_container.hpp> // gp_hash_table
<int, int> == hash map
#include <ext/pb_ds/tree_policy.hpp>
using namespace std;
using namespace __gnu_pbds;
typedef long long ll;
typedef unsigned long long ull;
typedef long double ld;
typedef pair<int, int> pii;
typedef pair<ll, ll> pll;
typedef pair<double, double> pdd;
template <typename T> using min_heap = priority_queue<T,
vector<T>, greater<T>>;
template <typename T> using max_heap = priority_queue<T,
vector<T>, less<T>>;
template <typename T> using ordered_set = tree<T,
null_type, less<T>, rb_tree_tag,
tree_order_statistics_node_update>;
template <typename K, typename V> using hashmap =
gp_hash_table<K, V>;

template<typename A, typename B> ostream& operator<<(<
ostream& out, pair<A, B> p) { out << "(" << p.first
<< ", " << p.second << ")"; return out;}
template<typename T> ostream& operator<<(<ostream& out,
vector<T> v) { out << "["; for(auto& x : v) out << x
<< ", "; out << "]" ; return out;}
template<typename T> ostream& operator<<(<ostream& out,
set<T> v) { out << "{"; for(auto& x : v) out << x <<
", "; out << "}"; return out;}
template<typename K, typename V> ostream& operator<<(<
ostream& out, map<K, V> m) { out << "{"; for(auto& e
: m) out << e.first << " " << e.second << ", "; out
<< "}"; return out;}
template<typename K, typename V> ostream& operator<<(<
ostream& out, hashmap<K, V> m) { out << "{"; for(
auto& e : m) out << e.first << " " << e.second <<
", "; out << "}"; return out;} }
```

```

#define FAST_IO ios_base::sync_with_stdio(false); cin.tie(
    NULL)
#define TESTS(t) int NUMBER_OF_TESTS; cin >>
    NUMBER_OF_TESTS; for(int t = 1; t <=
    NUMBER_OF_TESTS; t++)
#define FOR(i, begin, end) for (int i = (begin) - ((begin) > (
    end)); i != (end) - ((begin) > (end)); i += 1 - 2 * ((begin)
    > (end)))
#define sgn(a) ((a) > eps ? 1 : ((a) < -eps ? -1 : 0))
#define precise(x) fixed << setprecision(x)
#define debug(x) cerr << ">" << #x << " = " << x <<
    endl;
#define pb push_back
#define rnd(a, b) (uniform_int_distribution<int>((a), (b))(rng
    ))
#define LOCAL
#define cerr if(0)cout
#define endl "\n"
#define if
mt19937 rng(chrono::steady_clock::now().time_since_epoch().
    count());
clock_t __clock__;
void startTime() {__clock__ = clock();}
void timeit(string msg) {cerr << ">" << msg << ": " <<
    precise(6) << ld(clock()-__clock__)/
    CLOCKS_PER_SEC << endl;}
const ld PI = asin(1) * 2;
const ld eps = 1e-14;
const int oo = 2e9;
const ll OO = 2e18;
const ll MOD = 1000000007;
const int MAXN = 1000000;

int main() {
    FAST_IO;
    startTime();

    timeit("Finished");
    return 0;
}

```

1.2 Python Template

```

import sys
import re
from math import ceil, log, sqrt, floor

__local_run__ = False
if __local_run__:
    sys.stdin = open('input.txt', 'r')
    sys.stdout = open('output.txt', 'w')

def main():
    a = int(input())
    b = int(input())
    print(a*b)

main()

```

1.3 Compilation

```

# Simple compile
g++ -DLOCAL -O2 -o main.exe -std=c++17 -Wall -Wno-unused
    -result -Wshadow main.cpp
# Debug
g++ -DLOCAL -std=c++17 -Wshadow -Wall -o main.exe main.
    cpp -fsanitize=address -fsanitize=undefined -fuse-ld=gold
    -D_GLIBCXX_DEBUG -g

```

1.4 Automatic Test

```

# Linux Bash
# gen, main and stupid have to be compiled beforehand
for((i=1;;++i)); do
    echo $i;

```

```

./gen $i > genIn;
diff <./main < genIn < ./stupid < genIn || break;
done

```

```

# Windows CMD
@echo off
FOR /L %%I IN (1,1,2147483647) DO (
    echo %%I
    gen.exe %%I > genIn
    main.exe < genIn > mainOut
    stupid.exe < genIn > stupidOut
    FC mainOut stupidOut || goto :eof
)

```

1.5 Ternary Search

```

double ternary_search(double l, double r) {
    while (r - l > eps) {
        double m1 = l + (r - l) / 3;
        double m2 = r - (r - l) / 3;
        double f1 = f(m1);
        double f2 = f(m2);
        if (f1 < f2)
            l = m1;
        else
            r = m2;
    }
    return f(l); //return the maximum of f(x) in [l, r]
}

```

1.6 Big Integer

```

const int base = 1000000000;
const int base_digits = 9;
struct bigint {
    vector<int> a;
    int sign;
    int size() {
        if (a.empty()) return 0;
        int ans = (a.size() - 1) * base_digits;
        int ca = a.back();
        while (ca) ans++, ca /= 10;
        return ans;
    }
    bigint operator^(const bigint &v) {
        bigint ans = 1, x = *this, y = v;
        while (!y.isZero()) {
            if (y % 2) ans *= x;
            x *= x, y /= 2;
        }
        return ans;
    }
    string to_string() {
        stringstream ss;
        ss << *this;
        string s;
        ss >> s;
        return s;
    }
    int sumof() {
        string s = to_string();
        int ans = 0;
        for (auto c : s) ans += c - '0';
        return ans;
    }
    bigint() : sign(1) {}
    bigint(long long v) {
        *this = v;
    }
    bigint(const string &s) {
        read(s);
    }
    void operator=(const bigint &v) {
        sign = v.sign;
        a = v.a;
    }
    void operator=(long long v) {
        sign = 1;
        a.clear();
        if (v < 0)

```

```

    sign = -1, v = -v;
    for (; v > 0; v = v / base)
        a.push_back(v % base);
}
bigint operator+(const bigint &v) const {
    if (sign == v.sign) {
        bigint res = v;
        for (int i = 0, carry = 0; i < (int)max(a.size(), v.a.size()) || carry; ++i) {
            if (i == (int)res.a.size()) res.a.push_back(0);
            res.a[i] += carry + (i < (int)a.size() ? a[i] : 0);
            carry = res.a[i] >= base;
            if (carry) res.a[i] -= base;
        }
        return res;
    }
    return *this - (-v);
}
bigint operator-(const bigint &v) const {
    if (sign == v.sign) {
        if (abs() >= v.abs()) {
            bigint res = *this;
            for (int i = 0, carry = 0; i < (int)v.a.size() || carry; ++i) {
                res.a[i] -= carry + (i < (int)v.a.size() ? v.a[i] : 0);
                carry = res.a[i] < 0;
                if (carry) res.a[i] += base;
            }
            res.trim();
            return res;
        }
        return -(v - *this);
    }
    return *this + (-v);
}
void operator*=(int v) {
    if (v < 0) sign = -sign, v = -v;
    for (int i = 0, carry = 0; i < (int)a.size() || carry; ++i) {
        if (i == (int)a.size()) a.push_back(0);
        long long cur = a[i] * (long long)v + carry;
        carry = (int)(cur / base);
        a[i] = (int)(cur % base);
    }
    trim();
}
bigint operator*(int v) const {
    bigint res = *this;
    res *= v;
    return res;
}
void operator*=(long long v) {
    if (v < 0) sign = -sign, v = -v;
    for (int i = 0, carry = 0; i < (int)a.size() || carry; ++i) {
        if (i == (int)a.size()) a.push_back(0);
        long long cur = a[i] * (long long)v + carry;
        carry = (int)(cur / base);
        a[i] = (int)(cur % base);
    }
    trim();
}
bigint operator*(long long v) const {
    bigint res = *this;
    res *= v;
    return res;
}
friend pair<bigint, bigint> divmod(const bigint &a1, const
    bigint &b1) {
    int norm = base / (b1.a.back() + 1);
    bigint a = a1.abs() * norm;
    bigint b = b1.abs() * norm;
    bigint q, r;
    q.a.resize(a.a.size());
    for (int i = a.a.size() - 1; i >= 0; i--) {
        r *= base;
        r += a.a[i];
        int s1 = r.a.size() <= b.a.size() ? 0 : r.a[b.a.size()];
        int s2 = r.a.size() <= b.a.size() - 1 ? 0 : r.a[b.a.size() - 1];
        int d = ((long long)base * s1 + s2) / b.a.back();
        r -= b * d;
        while (r < 0) r += b, --d;
        q.a[i] = d;
    }
    q.sign = a1.sign * b1.sign;
    r.sign = a1.sign;
    q.trim();
    r.trim();
}

```

```

    return make_pair(q, r / norm);
}
bigint operator/(const bigint &v) const {
    return divmod(*this, v).first;
}
bigint operator%(const bigint &v) const {
    return divmod(*this, v).second;
}
void operator/=(int v) {
    if (v < 0) sign = -sign, v = -v;
    for (int i = (int)a.size() - 1, rem = 0; i >= 0; --i) {
        long long cur = a[i] + rem * (long long)base;
        a[i] = (int)(cur / v);
        rem = (int)(cur % v);
    }
    trim();
}
bigint operator/(int v) const {
    bigint res = *this;
    res /= v;
    return res;
}
int operator%(int v) const {
    if (v < 0) v = -v;
    int m = 0;
    for (int i = a.size() - 1; i >= 0; --i)
        m = (a[i] + m * (long long)base) % v;
    return m * sign;
}
void operator+=(const bigint &v) {
    *this = *this + v;
}
void operator-=(const bigint &v) {
    *this = *this - v;
}
void operator*=(const bigint &v) {
    *this = *this * v;
}
void operator/=(const bigint &v) {
    *this = *this / v;
}
bool operator<(const bigint &v) const {
    if (sign != v.sign) return sign < v.sign;
    if (a.size() != v.a.size())
        return a.size() * sign < v.a.size() * v.sign;
    for (int i = a.size() - 1; i >= 0; i--)
        if (a[i] != v.a[i])
            return a[i] * sign < v.a[i] * v.sign;
    return false;
}
bool operator>(const bigint &v) const {
    return v < *this;
}
bool operator<=(const bigint &v) const {
    return !(v < *this);
}
bool operator>=(const bigint &v) const {
    return !(*this < v);
}
bool operator==(const bigint &v) const {
    return !(*this < v) && !(v < *this);
}
bool operator!=(const bigint &v) const {
    return *this < v || v < *this;
}
void trim() {
    while (!a.empty() && !a.back()) a.pop_back();
    if (a.empty()) sign = 1;
}
bool isZero() const {
    return a.empty() || (a.size() == 1 && !a[0]);
}
bigint operator-() const {
    bigint res = *this;
    res.sign = -sign;
    return res;
}
bigint abs() const {
    bigint res = *this;
    res.sign = res.sign;
    return res;
}
long long longValue() const {
    long long res = 0;
    for (int i = a.size() - 1; i >= 0; i--) res = res * base + a[i];
    return res * sign;
}
}

```

```

friend bigint gcd(const bigint &a, const bigint &b) {
    return b.isZero() ? a : gcd(b, a % b);
}
friend bigint lcm(const bigint &a, const bigint &b) {
    return a / gcd(a, b) * b;
}
void read(const string &s) {
    sign = 1;
    a.clear();
    int pos = 0;
    while (pos < (int)s.size() && (s[pos] == '-' || s[pos] ==
        '+')) {
        if (s[pos] == '-') sign = -sign;
        ++pos;
    }
    for (int i = s.size() - 1; i >= pos; i -= base_digits) {
        int x = 0;
        for (int j = max(pos, i - base_digits + 1); j <= i; j
            ++
            )
            x = x * 10 + s[j] - '0';
        a.push_back(x);
    }
    trim();
}
friend istream &operator>>(istream &stream, bigint &v) {
    string s;
    stream >> s;
    v.read(s);
    return stream;
}
friend ostream &operator<<(ostream &stream, const bigint
    &v) {
    if (v.sign == -1) stream << '-';
    stream << (v.a.empty() ? 0 : v.a.back());
    for (int i = (int)v.a.size() - 2; i >= 0; --i)
        stream << setw(base_digits) << setfill('0') << v.a[i]
            ];
    return stream;
}
static vector<int> convert_base(const vector<int> &a, int
    old_digits, int new_digits) {
    vector<long long> p(max(old_digits, new_digits) + 1);
    p[0] = 1;
    for (int i = 1; i < (int)p.size(); i++)
        p[i] = p[i - 1] * 10;
    vector<int> res;
    long long cur = 0;
    int cur_digits = 0;
    for (int i = 0; i < (int)a.size(); i++) {
        cur += a[i] * p[cur_digits];
        cur_digits += old_digits;
        while (cur_digits >= new_digits) {
            res.push_back((int)(cur % p[new_digits]));
            cur /= p[new_digits];
            cur_digits -= new_digits;
        }
    }
    res.push_back((int)cur);
    while (!res.empty() && !res.back()) res.pop_back();
    return res;
}
typedef vector<long long> vll;
static vll karatsubaMultiply(const vll &a, const vll &b) {
    int n = a.size();
    vll res(n + n);
    if (n <= 32) {
        for (int i = 0; i < n; i++)
            for (int j = 0; j < n; j++)
                res[i + j] += a[i] * b[j];
        return res;
    }
    int k = n >> 1;
    vll a1(a.begin(), a.begin() + k);
    vll a2(a.begin() + k, a.end());
    vll b1(b.begin(), b.begin() + k);
    vll b2(b.begin() + k, b.end());

    vll a1b1 = karatsubaMultiply(a1, b1);
    vll a2b2 = karatsubaMultiply(a2, b2);

    for (int i = 0; i < k; i++) a2[i] += a1[i];
    for (int i = 0; i < k; i++) b2[i] += b1[i];

    vll r = karatsubaMultiply(a2, b2);
    for (int i = 0; i < (int)a1b1.size(); i++) r[i] -= a1b1[i];
    for (int i = 0; i < (int)a2b2.size(); i++) r[i] -= a2b2[i];

    for (int i = 0; i < (int)r.size(); i++) res[i + k] += r[i];

```

```

        for (int i = 0; i < (int)a1b1.size(); i++) res[i] += a1b1[i]
            ];
        for (int i = 0; i < (int)a2b2.size(); i++) res[i + n] +=
            a2b2[i];
        return res;
    }
    bigint operator*(const bigint &v) const {
        vector<int> a6 = convert_base(this->a, base_digits, 6);
        vector<int> b6 = convert_base(v.a, base_digits, 6);
        vll x(a6.begin(), a6.end());
        vll y(b6.begin(), b6.end());
        while (x.size() < y.size()) x.push_back(0);
        while (y.size() < x.size()) y.push_back(0);
        while (x.size() & (x.size() - 1)) x.push_back(0), y.
            push_back(0);
        vll c = karatsubaMultiply(x, y);
        bigint res;
        res.sign = sign * v.sign;
        for (int i = 0, carry = 0; i < (int)c.size(); i++) {
            long long cur = c[i] + carry;
            res.a.push_back((int)(cur % 1000000));
            carry = (int)(cur / 1000000);
        }
        res.a = convert_base(res.a, 6, base_digits);
        res.trim();
        return res;
    }
};

```

2 Data Structures

2.1 Disjoin Set Union

```

struct DSU {
    vector<int> par;
    vector<int> sz;

    DSU(int n) {
        FOR(i, 0, n) {
            par.pb(i);
            sz.pb(1);
        }
    }

    int find(int a) {
        return par[a] = par[a] == a ? a : find(par[a]);
    }

    bool same(int a, int b) {
        return find(a) == find(b);
    }

    void unite(int a, int b) {
        a = find(a);
        b = find(b);
        if (sz[a] > sz[b]) swap(a, b);
        sz[b] += sz[a];
        par[a] = b;
    }
};

```

2.2 Fenwick Tree Point Update And Range Query

```

struct Fenwick {
    vector<ll> tree;
    int n;
    Fenwick() {}
    Fenwick(int __n) {
        n = __n;
        tree = vector<ll>(n+1, 0);
    }
    void add(int i, ll val) { // arr[i] += val
        for (; i <= n; i += i&(-i)) tree[i] += val;
    }
    ll get(int i) { // arr[i]
        return sum(i, i);
    }
};

```

```

    }
    ll sum(int i) { // arr[1]+...+arr[i]
        ll ans = 0;
        for(; i > 0; i -= i&(-i)) ans += tree[i];
        return ans;
    }
    ll sum(int l, int r) { // arr[l]+...+arr[r]
        return sum(r) - sum(l-1);
    }
};

```

2.3 Fenwick Tree Range Update And Point Query

```

struct Fenwick {
    vector<ll> tree;
    vector<ll> arr;
    int n;
    Fenwick(vector<ll> _arr) {
        n = _arr.size();
        arr = _arr;
        tree = vector<ll>(n+2, 0);
    }
    void add(int i, ll val) { // arr[i] += val
        for(; i <= n; i += i&(-i)) tree[i] += val;
    }
    void add(int l, int r, ll val) { // arr[l..r] += val
        add(l, val);
        add(r+1, -val);
    }
    ll get(int i) { // arr[i]
        ll sum = arr[i-1]; // zero based
        for(; i > 0; i -= i&(-i)) sum += tree[i];
        return sum; // zero based
    }
};

```

2.4 Fenwick Tree Range Update And Range Query

```

struct RangedFenwick {
    Fenwick F1, F2; // support range query and point update
    RangedFenwick(int _n) {
        F1 = Fenwick(_n+1);
        F2 = Fenwick(_n+1);
    }
    void add(int l, int r, ll v) { // arr[l..r] += v
        F1.add(l, v);
        F1.add(r+1, -v);
        F2.add(l, v*(l-1));
        F2.add(r+1, -v*r);
    }
    ll sum(int i) { // arr[1..i]
        return F1.sum(i)*i-F2.sum(i);
    }
    ll sum(int l, int r) { // arr[l..r]
        return sum(r)-sum(l-1);
    }
};

```

2.5 Fenwick 2D

```

struct Fenwick2D {
    vector<vector<ll>> bit;
    int n, m;
    Fenwick2D(int _n, int _m) {
        n = _n; m = _m;
        bit = vector<vector<ll>>(n+1, vector<ll>(m+1, 0));
    }
    ll sum(int x, int y) {
        ll ret = 0;
        for (int i = x; i > 0; i -= i & (-i))
            for (int j = y; j > 0; j -= j & (-j))
                ret += bit[i][j];
    }
};

```

```

        return ret;
    }
    ll sum(int x1, int y1, int x2, int y2) {
        return sum(x2, y2) - sum(x2, y1-1) - sum(x1-1, y2) +
            sum(x1-1, y1-1);
    }
    void add(int x, int y, ll delta) {
        for (int i = x; i <= n; i += i & (-i))
            for (int j = y; j <= m; j += j & (-j))
                bit[i][j] += delta;
    }
};

```

2.6 Segment Tree

```

struct SegmentTree {
    int n;
    vector<ll> t;
    const ll IDENTITY = 0; // OO for min, -OO for max, ...
    ll f(ll a, ll b) {
        return a+b;
    }
    SegmentTree(int _n) {
        n = _n; t = vector<ll>(4*n, IDENTITY);
    }
    SegmentTree(vector<ll>& arr) {
        n = arr.size(); t = vector<ll>(4*n, IDENTITY);
        build(arr, 1, 0, n-1);
    }
    void build(vector<ll>& arr, int v, int tl, int tr) {
        if(tl == tr) { t[v] = arr[tl]; }
        else {
            int tm = (tl+tr)/2;
            build(arr, 2*v, tl, tm);
            build(arr, 2*v+1, tm+1, tr);
            t[v] = f(t[2*v], t[2*v+1]);
        }
    }
    // sum(1, 0, n-1, l, r)
    ll sum(int v, int tl, int tr, int l, int r) {
        if(l > r) return IDENTITY;
        if(l == tl && r == tr) return t[v];
        int tm = (tl+tr)/2;
        return f(sum(2*v, tl, tm, l, min(r, tm)), sum(2*v+1, tm
            +1, tr, max(l, tm+1), r));
    }
    // update(1, 0, n-1, i, v)
    void update(int v, int tl, int tr, int pos, ll newVal) {
        if(tl == tr) { t[v] = newVal; }
        else {
            int tm = (tl+tr)/2;
            if(pos <= tm) update(2*v, tl, tm, pos, newVal);
            else update(2*v+1, tm+1, tr, pos, newVal);
            t[v] = f(t[2*v], t[2*v+1]);
        }
    }
};

```

2.7 Segment Tree With Lazy Propagation

```

// Add to segment, get maximum of segment
struct LazySegTree {
    int n;
    vector<ll> t, lazy;
    LazySegTree(int _n) {
        n = _n; t = vector<ll>(4*n, 0); lazy = vector<ll>(4*n,
            0);
    }
    LazySegTree(vector<ll>& arr) {
        n = _n; t = vector<ll>(4*n, 0); lazy = vector<ll>(4*n,
            0);
        build(arr, 1, 0, n-1); // same as in simple SegmentTree
    }
    void push(int v) {
        t[v*2] += lazy[v];
        lazy[v*2] += lazy[v];
        t[v*2+1] += lazy[v];
        lazy[v*2+1] += lazy[v];
    }
};

```

```

    lazy[v] = 0;
}
void update(int v, int tl, int tr, int l, int r, ll addend) {
    if (l > r)
        return;
    if (l == tl && tr == r) {
        t[v] += addend;
        lazy[v] += addend;
    } else {
        push(v);
        int tm = (tl + tr) / 2;
        update(v*2, tl, tm, l, min(r, tm), addend);
        update(v*2+1, tm+1, tr, max(l, tm+1), r, addend);
        t[v] = max(t[v*2], t[v*2+1]);
    }
}

int query(int v, int tl, int tr, int l, int r) {
    if (l > r)
        return -OO;
    if (tl == tr)
        return t[v];
    push(v);
    int tm = (tl + tr) / 2;
    return max(query(v*2, tl, tm, l, min(r, tm)),
               query(v*2+1, tm+1, tr, max(l, tm+1), r));
}
};

```

2.8 Treap

```

namespace Treap {
    struct Node {
        Node *l, *r;
        ll key, prio, size;
        Node() {}
        Node(ll key) : key(key), l(nullptr), r(nullptr), size(1) {
            prio = rand() ^ (rand() << 15);
        }
    };

    typedef Node* NodePtr;

    int sz(NodePtr n) {
        return n ? n->size : 0;
    }

    void recalc(NodePtr n) {
        if (!n) return;
        n->size = sz(n->l) + 1 + sz(n->r); // add more
            operations here as needed
    }

    void split(NodePtr tree, ll key, NodePtr& l, NodePtr& r) {
        if (!tree) {
            l = r = nullptr;
        }
        else if (key < tree->key) {
            split(tree->l, key, l, tree->l);
            r = tree;
        }
        else {
            split(tree->r, key, tree->r, r);
            l = tree;
        }
        recalc(tree);
    }

    void merge(NodePtr& tree, NodePtr l, NodePtr r) {
        if (!l || !r) {
            tree = l ? l : r;
        }
        else if (l->prio > r->prio) {
            merge(l->r, l->r, r);
            tree = l;
        }
        else {
            merge(r->l, l, r->l);
            tree = r;
        }
        recalc(tree);
    }

    void insert(NodePtr& tree, NodePtr node) {

```

```

        if (!tree) {
            tree = node;
        }
        else if (node->prio > tree->prio) {
            split(tree, node->key, node->l, node->r);
            tree = node;
        }
        else {
            insert(node->key < tree->key ? tree->l : tree->r,
                  node);
        }
        recalc(tree);
    }

    void erase(NodePtr tree, ll key) {
        if (!tree) return;
        if (tree->key == key) {
            merge(tree, tree->l, tree->r);
        }
        else {
            erase(key < tree->key ? tree->l : tree->r, key);
        }
        recalc(tree);
    }

    void print(NodePtr t, bool newline = true) {
        if (!t) return;
        print(t->l, false);
        cout << t->key << " ";
        print(t->r, false);
        if (newline) cout << endl;
    }
}

```

2.9 Implicit Treap

```

template <typename T>
struct Node {
    Node* l, *r;
    ll prio, size, sum;
    T val;
    bool rev;
    Node() {}
    Node(T _val) : l(nullptr), r(nullptr), val(_val), size(1), sum(
        _val), rev(false) {
        prio = rand() ^ (rand() << 15);
    }
};

template <typename T>
struct ImplicitTreap {
    typedef Node<T>* NodePtr;
    int sz(NodePtr n) {
        return n ? n->size : 0;
    }
    ll getSum(NodePtr n) {
        return n ? n->sum : 0;
    }

    void push(NodePtr n) {
        if (n && n->rev) {
            n->rev = false;
            swap(n->l, n->r);
            if (n->l) n->l->rev ^= 1;
            if (n->r) n->r->rev ^= 1;
        }
    }

    void recalc(NodePtr n) {
        if (!n) return;
        n->size = sz(n->l) + 1 + sz(n->r);
        n->sum = getSum(n->l) + n->val + getSum(n->r);
    }

    void split(NodePtr tree, ll key, NodePtr& l, NodePtr& r) {
        push(tree);
        if (!tree) {
            l = r = nullptr;
        }
        else if (key <= sz(tree->l)) {
            split(tree->l, key, l, tree->l);
            r = tree;
        }
        else {
            split(tree->r, key-sz(tree->l)-1, tree->r, r);

```

```

        l = tree;
    }
    recalc(tree);
}

void merge(NodePtr& tree, NodePtr l, NodePtr r) {
    push(l); push(r);
    if (!l || !r) {
        tree = l ? l : r;
    }
    else if (l->prio > r->prio) {
        merge(l->r, l->r, r);
        tree = l;
    }
    else {
        merge(r->l, l, r->l);
        tree = r;
    }
    recalc(tree);
}

void insert(NodePtr& tree, T val, int pos) {
    if (!tree) {
        tree = new Node<T>(val);
        return;
    }
    NodePtr L, R;
    split(tree, pos, L, R);
    merge(L, L, new Node<T>(val));
    merge(tree, L, R);
    recalc(tree);
}

void reverse(NodePtr tree, int l, int r) {
    NodePtr t1, t2, t3;
    split(tree, l, t1, t2);
    split(t2, r - l + 1, t2, t3);
    if (t2->rev = true;
    merge(t2, t1, t2);
    merge(tree, t2, t3);
}

void print(NodePtr t, bool newline = true) {
    push(t);
    if (!t) return;
    print(t->l, false);
    cout << t->val << " ";
    print(t->r, false);
    if (newline) cout << endl;
}

NodePtr fromArray(vector<T> v) {
    NodePtr t = nullptr;
    FOR(i, 0, (int)v.size()) {
        insert(t, v[i], i);
    }
    return t;
}

ll calcSum(NodePtr t, int l, int r) {
    NodePtr L, R;
    split(t, l, L, R);
    NodePtr good;
    split(R, r - l + 1, good, L);
    return getSum(good);
}

};
/* Usage: ImplicitTreap<int> t;
Node<int> tree = t.fromArray(someVector); t.reverse(tree, l, r);
*/

```

2.10 Trie

```

struct Trie {
    const int ALPHA = 26;
    const char BASE = 'a';
    vector<vector<int>>> nextNode;
    vector<int> mark;
    int nodeCount;
    Trie() {
        nextNode = vector<vector<int>>>(MAXN, vector<int>(
            ALPHA, -1));
        mark = vector<int>(MAXN, -1);
    }
}

```

```

        nodeCount = 1;
    }
    void insert(const string& s, int id) {
        int curr = 0;
        FOR(i, 0, (int)s.length()) {
            int c = s[i] - BASE;
            if (nextNode[curr][c] == -1) {
                nextNode[curr][c] = nodeCount++;
            }
            curr = nextNode[curr][c];
        }
        mark[curr] = id;
    }

    bool exists(const string& s) {
        int curr = 0;
        FOR(i, 0, (int)s.length()) {
            int c = s[i] - BASE;
            if (nextNode[curr][c] == -1) return false;
            curr = nextNode[curr][c];
        }
        return mark[curr] != -1;
    }
};

```

3 Graphs

3.1 Dfs With Timestamps

```

vector<vector<int>>> adj;
vector<int> tIn, tOut, color;
int dfs_timer = 0;

```

```

void dfs(int v) {
    tIn[v] = dfs_timer++;
    color[v] = 1;
    for (int u : adj[v])
        if (color[u] == 0)
            dfs(u);
    color[v] = 2;
    tOut[v] = dfs_timer++;
}

```

3.2 Lowest Common Ancestor

```

int n, l; // l == logN (usually about ~20)
vector<vector<int>>> adj;

```

```

int timer;
vector<int> tin, tout;
vector<vector<int>>> up;

```

```

void dfs(int v, int p)
{
    tin[v] = ++timer;
    up[v][0] = p;
    // wUp[v][0] = weight[v][u]; // <- path weight sum to 2^i-th
    // ancestor
    for (int i = 1; i <= l; ++i)
        up[v][i] = up[up[v][i-1]][i-1];
        // wUp[v][i] = wUp[v][i-1] + wUp[up[v][i-1]][i-1];

    for (int u : adj[v]) {
        if (u != p)
            dfs(u, v);
    }

    tout[v] = ++timer;
}

```

```

bool isAncestor(int u, int v)
{
    return tin[u] <= tin[v] && tout[v] <= tout[u];
}

```

```

int lca(int u, int v)
{
    if (isAncestor(u, v))

```

```

        return u;
    if (isAncestor(v, u))
        return v;
    for (int i = l; i >= 0; --i) {
        if (!isAncestor(up[u][i], v))
            u = up[u][i];
    }
    return up[u][0];
}

void preprocess(int root) {
    tin.resize(n);
    tout.resize(n);
    timer = 0;
    l = ceil(log2(n));
    up.assign(n, vector<int>(l + 1));
    dfs(root, root);
}

```

3.3 Strongly Connected Components

```

vector < vector<int> > g, gr; // adjList and reversed adjList
vector<bool> used;
vector<int> order, component;

void dfs1 (int v) {
    used[v] = true;
    for (size_t i=0; i<g[v].size(); ++i)
        if (!used[ g[v][i] ])
            dfs1 (g[v][i]);
    order.push_back (v);
}

void dfs2 (int v) {
    used[v] = true;
    component.push_back (v);
    for (size_t i=0; i<gr[v].size(); ++i)
        if (!used[ gr[v][i] ])
            dfs2 (gr[v][i]);
}

int main() {
    int n;
    // read n
    for (;;) {
        int a, b;
        // read edge a -> b
        g[a].push_back (b);
        gr[b].push_back (a);
    }

    used.assign (n, false);
    for (int i=0; i<n; ++i)
        if (!used[i])
            dfs1 (i);
    used.assign (n, false);
    for (int i=0; i<n; ++i) {
        int v = order[n-1-i];
        if (!used[v]) {
            dfs2 (v);
            // do something with the found component
            component.clear(); // components are generated in
                               topological order
        }
    }
}

```

3.4 Bellman Ford Algorithm

```

struct Edge
{
    int a, b, cost;
};

int n, m, v; // v - starting vertex
vector<Edge> e;

/* Finds SSSP with negative edge weights.
 * Possible optimization: check if anything changed in a
 * relaxation step. If not - you can break early.

```

```

 * To find a negative cycle: perform one more relaxation step. If
 * anything changes - a negative cycle exists.
 */
void solve() {
    vector<int> d (n, oo);
    d[v] = 0;
    for (int i=0; i<n-1; ++i)
        for (int j=0; j<m; ++j)
            if (d[e[j].a] < oo)
                d[e[j].b] = min (d[e[j].b], d[e[j].a] + e[j].cost);
    // display d, for example, on the screen
}

```

3.5 Bipartite Graph

```

class BipartiteGraph {
private:
    vector<int> _left, _right;
    vector<vector<int>>> _adjList;
    vector<int> _matchR, _matchL;
    vector<bool> _used;

    bool _kuhn(int v) {
        if (_used[v]) return false;
        _used[v] = true;
        FOR(i, 0, (int)_adjList[v].size()) {
            int to = _adjList[v][i] - _left.size();
            if (_matchR[to] == -1 || _kuhn(_matchR[to])) {
                _matchR[to] = v;
                _matchL[v] = to;
                return true;
            }
        }
        return false;
    }

    void _addReverseEdges() {
        FOR(i, 0, (int)_right.size()) {
            if (_matchR[i] != -1) {
                _adjList[_left.size() + i].pb(_matchR[i]);
            }
        }
    }

    void _dfs(int p) {
        if (_used[p]) return;
        _used[p] = true;
        for (auto x : _adjList[p]) {
            _dfs(x);
        }
    }

    vector<pii> _buildMM() {
        vector<pair<int, int>> res;
        FOR(i, 0, (int)_right.size()) {
            if (_matchR[i] != -1) {
                res.push_back(make_pair(_matchR[i], i));
            }
        }
        return res;
    }

public:
    void addLeft(int x) {
        _left.pb(x);
        _adjList.pb({});
        _matchL.pb(-1);
        _used.pb(false);
    }

    void addRight(int x) {
        _right.pb(x);
        _adjList.pb({});
        _matchR.pb(-1);
        _used.pb(false);
    }

    void addForwardEdge(int l, int r) {
        _adjList[l].pb(r + _left.size());
    }

    void addMatchEdge(int l, int r) {
        if (l != -1) _matchL[l] = r;
        if (r != -1) _matchR[r] = l;
    }

    // Maximum Matching
    vector<pii> mm() {
        _matchR = vector<int>(_right.size(), -1);
        _matchL = vector<int>(_left.size(), -1);
    }
}

```



```

// ^ these two can be deleted if performing MM on
// already partially matched graph
_used = vector<bool>(_left.size() + _right.size(), false);

bool path_found;
do {
    fill(_used.begin(), _used.end(), false);
    path_found = false;
    FOR(i, 0, (int)_left.size()) {
        if (_matchL[i] < 0 && !_used[i]) {
            path_found |= _kuhn(i);
        }
    }
} while (path_found);

return _buildMM();
}

// Minimum Edge Cover
// Algo: Find MM, add unmatched vertices greedily.
vector<pii> mec() {
    auto ans = mm();
    FOR(i, 0, (int)_left.size()) {
        if (_matchL[i] != -1) {
            for (auto x : _adjList[i]) {
                int ridx = x - _left.size();
                if (_matchR[ridx] == -1) {
                    ans.pb({ i, ridx });
                    _matchR[ridx] = i;
                }
            }
        }
    }
    FOR(i, 0, (int)_left.size()) {
        if (_matchL[i] == -1 && (int)_adjList[i].size() > 0) {
            int ridx = _adjList[i][0] - _left.size();
            _matchL[i] = ridx;
            ans.pb({ i, ridx });
        }
    }
    return ans;
}

// Minimum Vertex Cover
// Algo: Find MM. Run DFS from unmatched vertices from
// the left part.
// MVC is composed of unvisited LEFT and visited RIGHT
// vertices.
pair<vector<int>, vector<int>> mvc(bool runMM = true)
{
    if (runMM) mm();
    _addReverseEdges();
    fill(_used.begin(), _used.end(), false);
    FOR(i, 0, (int)_left.size()) {
        if (_matchL[i] == -1) {
            _dfs(i);
        }
    }
    vector<int> left, right;
    FOR(i, 0, (int)_left.size()) {
        if (!_used[i]) left.pb(i);
    }
    FOR(i, 0, (int)_right.size()) {
        if (_used[i + (int)_left.size()]) right.pb(i);
    }
    return { left, right };
}

// Maximal Independant Vertex Set
// Algo: Find complement of MVC.
pair<vector<int>, vector<int>> mivs(bool runMM = true)
{
    auto m = mvc(runMM);
    vector<bool> containsL(_left.size(), false), containsR(
        _right.size(), false);
    for (auto x : m.first) containsL[x] = true;
    for (auto x : m.second) containsR[x] = true;
    vector<int> left, right;
    FOR(i, 0, (int)_left.size()) {
        if (!containsL[i]) left.pb(i);
    }
    FOR(i, 0, (int)_right.size()) {
        if (!containsR[i]) right.pb(i);
    }
    return { left, right };
}

```

```

}
};

```

3.6 Finding Articulation Points

```

int n; // number of nodes
vector<vector<int>>> adj; // adjacency list of graph

vector<bool> visited;
vector<int> tin, fup;
int timer;

void processCutpoint(int v) {
    // problem-specific logic goes here
    // it can be called multiple times for the same v
}

void dfs(int v, int p = -1) {
    visited[v] = true;
    tin[v] = fup[v] = timer++;
    int children=0;
    for (int to : adj[v]) {
        if (to == p) continue;
        if (visited[to]) {
            fup[v] = min(fup[v], tin[to]);
        } else {
            dfs(to, v);
            fup[v] = min(fup[v], fup[to]);
            if (fup[to] >= tin[v] && p != -1)
                processCutpoint(v);
            ++children;
        }
    }
    if (p == -1 && children > 1)
        processCutpoint(v);
}

void findCutpoints() {
    timer = 0;
    visited.assign(n, false);
    tin.assign(n, -1);
    fup.assign(n, -1);
    for (int i = 0; i < n; ++i) {
        if (!visited[i])
            dfs(i);
    }
}

```

3.7 Finding Bridges

```

int n; // number of nodes
vector<vector<int>>> adj; // adjacency list of graph

vector<bool> visited;
vector<int> tin, fup;
int timer;

void processBridge(int u, int v) {
    // do something with the found bridge
}

void dfs(int v, int p = -1) {
    visited[v] = true;
    tin[v] = fup[v] = timer++;
    for (int to : adj[v]) {
        if (to == p) continue;
        if (visited[to]) {
            fup[v] = min(fup[v], tin[to]);
        } else {
            dfs(to, v);
            fup[v] = min(fup[v], fup[to]);
            if (fup[to] > tin[v])
                processBridge(v, to);
        }
    }
}

// Doesn't work with multiple edges
// But multiple edges are never bridges, so it's easy to check

```

```

void findBridges() {
    timer = 0;
    visited.assign(n, false);
    tin.assign(n, -1);
    fup.assign(n, -1);
    bridges.clear();
    FOR(i, 0, n) {
        if (!visited[i])
            dfs(i);
    }
}

```

3.8 Max Flow With Ford Fulkerson

```

struct Edge {
    int to, next;
    ll f, c;
    int idx, dir;
    int from;
};

int n, m;
vector<Edge> edges;
vector<int> first;

void addEdge(int a, int b, ll c, int i, int dir) {
    edges.pb({ b, first[a], 0, c, i, dir, a });
    edges.pb({ a, first[b], 0, 0, i, dir, b });
    first[a] = edges.size() - 2;
    first[b] = edges.size() - 1;
}

void init() {
    cin >> n >> m;
    edges.reserve(4 * m);
    first = vector<int>(n, -1);
    FOR(i, 0, m) {
        int a, b, c;
        cin >> a >> b >> c;
        a--; b--;
        addEdge(a, b, c, i, 1);
        addEdge(b, a, c, i, -1);
    }
}

int cur_time = 0;
vector<int> timestamp;

ll dfs(int v, ll flow = OO) {
    if (v == n - 1) return flow;
    timestamp[v] = cur_time;
    for (int e = first[v]; e != -1; e = edges[e].next) {
        if (edges[e].f < edges[e].c && timestamp[edges[e].to] !=
            cur_time) {
            int pushed = dfs(edges[e].to, min(flow, edges[e].c -
                edges[e].f));
            if (pushed > 0) {
                edges[e].f += pushed;
                edges[e ^ 1].f -= pushed;
                return pushed;
            }
        }
    }
    return 0;
}

ll maxFlow() {
    cur_time = 0;
    timestamp = vector<int>(n, 0);
    ll f = 0, add;
    while (true) {
        cur_time++;
        add = dfs(0);
        if (add > 0) {
            f += add;
        }
        else {
            break;
        }
    }
    return f;
}

```

3.9 Max Flow With Dinic

```

struct Edge {
    int f, c;
    int to;
    pii revIdx;
    int dir;
    int idx;
};

int n, m;
vector<Edge> adjList[MAX_N];
int level[MAX_N];

void addEdge(int a, int b, int c, int i, int dir) {
    int idx = adjList[a].size();
    int revIdx = adjList[b].size();
    adjList[a].pb({ 0, c, b, {b, revIdx}, dir, i });
    adjList[b].pb({ 0, 0, a, {a, idx}, dir, i });
}

bool bfs(int s, int t) {
    FOR(i, 0, n) level[i] = -1;
    level[s] = 0;
    queue<int> Q;
    Q.push(s);
    while (!Q.empty()) {
        auto t = Q.front(); Q.pop();
        for (auto x : adjList[t]) {
            if (level[x.to] < 0 && x.f < x.c) {
                level[x.to] = level[t] + 1;
                Q.push(x.to);
            }
        }
    }
    return level[t] >= 0;
}

int send(int u, int f, int t, vector<int>& edgeIdx) {
    if (u == t) return f;
    for (; edgeIdx[u] < adjList[u].size(); edgeIdx[u]++) {
        auto& e = adjList[u][edgeIdx[u]];
        if (level[e.to] == level[u] + 1 && e.f < e.c) {
            int curr_flow = min(f, e.c - e.f);
            int next_flow = send(e.to, curr_flow, t, edgeIdx);
            if (next_flow > 0) {
                e.f += next_flow;
                adjList[e.revIdx.first][e.revIdx.second].f -=
                    next_flow;
                return next_flow;
            }
        }
    }
    return 0;
}

int maxFlow(int s, int t) {
    int f = 0;
    while (bfs(s, t)) {
        vector<int> edgeIdx(n, 0);
        while (int extra = send(s, oo, t, edgeIdx)) {
            f += extra;
        }
    }
    return f;
}

void init() {
    cin >> n >> m;
    FOR(i, 0, m) {
        int a, b, c;
        cin >> a >> b >> c;
        a--; b--;
        addEdge(a, b, c, i, 1);
        addEdge(b, a, c, i, -1);
    }
}

```

3.10 Max Flow With Dinic 2

```

struct FlowEdge {
    int v, u;
    long long cap, flow = 0;
};

```

```

FlowEdge(int v, int u, long long cap) : v(v), u(u), cap(cap)
{}
};

struct Dinic {
    const long long flow_inf = 1e18;
    vector<FlowEdge> edges;
    vector<vector<int>>> adj;
    int n, m = 0;
    int s, t;
    vector<int> level, ptr;
    queue<int> q;

    Dinic(int n, int s, int t) : n(n), s(s), t(t) {
        adj.resize(n);
        level.resize(n);
        ptr.resize(n);
    }

    void add_edge(int v, int u, long long cap) {
        edges.push_back(FlowEdge(v, u, cap));
        edges.push_back(FlowEdge(u, v, 0));
        adj[v].push_back(m);
        adj[u].push_back(m + 1);
        m += 2;
    }

    bool bfs() {
        while (!q.empty()) {
            int v = q.front();
            q.pop();
            for (int id : adj[v]) {
                if (edges[id].cap - edges[id].flow < 1)
                    continue;
                if (level[edges[id].u] != -1)
                    continue;
                level[edges[id].u] = level[v] + 1;
                q.push(edges[id].u);
            }
        }
        return level[t] != -1;
    }

    long long dfs(int v, long long pushed) {
        if (pushed == 0)
            return 0;
        if (v == t)
            return pushed;
        for (int& cid = ptr[v]; cid < (int)adj[v].size(); cid++) {
            int id = adj[v][cid];
            int u = edges[id].u;
            if (level[v] + 1 != level[u] || edges[id].cap - edges[id].flow < 1)
                continue;
            long long tr = dfs(u, min(pushed, edges[id].cap - edges[id].flow));
            if (tr == 0)
                continue;
            edges[id].flow += tr;
            edges[id ^ 1].flow -= tr;
            return tr;
        }
        return 0;
    }

    long long flow() {
        long long f = 0;
        while (true) {
            fill(level.begin(), level.end(), -1);
            level[s] = 0;
            q.push(s);
            if (!bfs())
                break;
            fill(ptr.begin(), ptr.end(), 0);
            while (long long pushed = dfs(s, flow_inf)) {
                f += pushed;
            }
        }
        return f;
    }
};

```

3.11 Min Cut

```

init();
ll f = maxFlow(); // Ford-Fulkerson
cur_time++;
dfs(0);
set<int> cc;
for (auto e : edges) {
    if (timestamp[e.from] == cur_time && timestamp[e.to] !=
        cur_time) {
        cc.insert(e.idx);
    }
}
// (# of edges in min-cut, capacity of cut)
// [indices of edges forming the cut]
cout << cc.size() << " " << f << endl;
for (auto x : cc) cout << x + 1 << " ";

```

3.12 Number Of Paths Of Fixed Length

Let G be the adjacency matrix of a graph. Then $C_k = G^k$ gives a matrix, in which the value $C_k[i][j]$ gives the number of paths between i and j of length k .

3.13 Shortest Paths Of Fixed Length

Define $A \odot B = C \iff C_{ij} = \min_{p=1..n} (A_{ip} + B_{pj})$. Let G be the adjacency matrix of a graph. Also, let $L_k = G \odot \dots \odot G = G^{\odot k}$. Then the value $L_k[i][j]$ denotes the length of the shortest path between i and j which consists of exactly k edges.

4 Geometry

4.1 2d Vector

```

template <typename T>
struct Vec {
    T x, y;
    Vec(): x(0), y(0) {}
    Vec(T _x, T _y): x(_x), y(_y) {}
    Vec operator+(const Vec& b) {
        return Vec<T>(x+b.x, y+b.y);
    }
    Vec operator-(const Vec& b) {
        return Vec<T>(x-b.x, y-b.y);
    }
    Vec operator*(T c) {
        return Vec(x*c, y*c);
    }
    T operator*(const Vec& b) {
        return x*b.x + y*b.y;
    }
    T operator^(const Vec& b) {
        return x*b.y - y*b.x;
    }
    bool operator<(const Vec& other) const {
        if (x == other.x) return y < other.y;
        return x < other.x;
    }
    bool operator==(const Vec& other) const {
        return x==other.x && y==other.y;
    }
    bool operator!=(const Vec& other) const {
        return !(*this == other);
    }
    friend ostream& operator<<(ostream& out, const Vec& v) {
        return out << "(" << v.x << ", " << v.y << ")";
    }
    friend istream& operator>>(istream& in, Vec<T>& v) {
        return in >> v.x >> v.y;
    }
    T norm() { // squared length
        return (*this)*(*this);
    }
};

```

```

ld len() {
    return sqrt(norm());
}
ld angle(const Vec& other) { // angle between this and
    other vector
    return acosl((*this)*other/len()/other.len());
}
Vec perp() {
    return Vec(-y, x);
}
};
/* Cross product of 3d vectors: (ay*bz-az*by, az*bx-ax*bz, ax*
    by-ay*bx)
*/

```

4.2 Line

```

template <typename T>
struct Line { // expressed as two vectors
    Vec<T> start, dir;
    Line() {}
    Line(Vec<T> a, Vec<T> b): start(a), dir(b-a) {}

    Vec<ld> intersect(Line l) {
        ld t = ld((l.start-start)^l.dir)/(dir^l.dir);
        // For segment-segment intersection this should be in
        // range [0, 1]
        Vec<ld> res(start.x, start.y);
        Vec<ld> dirlld(dir.x, dir.y);
        return res + dirlld*t;
    }
};

```

4.3 Convex Hull Gift Wrapping

```

vector<Vec<int>> buildConvexHull(vector<Vec<int>>& pts)
{
    int n = pts.size();
    sort(pts.begin(), pts.end());
    auto currP = pts[0]; // choose some extreme point to be on
    the hull

    vector<Vec<int>> hull;
    set<Vec<int>> used;
    hull.pb(pts[0]);
    used.insert(pts[0]);
    while(true) {
        auto candidate = pts[0]; // choose some point to be a
        candidate

        auto currDir = candidate-currP;
        vector<Vec<int>> toUpdate;
        FOR(i, 0, n) {
            if(currP == pts[i]) continue;
            // currently we have currP->candidate
            // we need to find point to the left of this
            auto possibleNext = pts[i];
            auto nextDir = possibleNext - currP;
            auto cross = currDir ^ nextDir;
            if(candidate == currP || cross > 0) {
                candidate = possibleNext;
                currDir = nextDir;
            } else if(cross == 0 && nextDir.norm() > currDir.
                norm()) {
                candidate = possibleNext;
                currDir = nextDir;
            }
        }
        if(used.find(candidate) != used.end()) break;
        hull.pb(candidate);
        used.insert(candidate);
        currP = candidate;
    }
    return hull;
}

```

4.4 Convex Hull With Graham's Scan

```

// Takes in >= 3 points
// Returns convex hull in clockwise order
// Ignores points on the border
vector<Vec<int>> buildConvexHull(vector<Vec<int>> pts) {
    if(pts.size() <= 3) return pts;
    sort(pts.begin(), pts.end());
    stack<Vec<int>> hull;
    hull.push(pts[0]);
    auto p = pts[0];
    sort(pts.begin()+1, pts.end(), [&](Vec<int> a, Vec<int> b)
        -> bool {
        // p->a->b is a ccw turn
        int turn = sgn((a-p)^(b-a));
        //if(turn == 0) return (a-p).norm() > (b-p).norm();
        // ^ among collinear points, take the farthest one
        return turn == 1;
    });
    hull.push(pts[1]);
    FOR(i, 2, (int)pts.size()) {
        auto c = pts[i];
        if(c == hull.top()) continue;
        while(true) {
            auto a = hull.top(); hull.pop();
            auto b = hull.top();
            auto ba = a-b;
            auto ac = c-a;
            if((ba^ac) > 0) {
                hull.push(a);
                break;
            } else if((ba^ac) == 0) {
                if(ba^ac < 0) c = a;
                // ^ c is between b and a, so it shouldn't be
                // added to the hull
                break;
            }
        }
        hull.push(c);
    }
    vector<Vec<int>> hullPts;
    while(!hull.empty()) {
        hullPts.pb(hull.top());
        hull.pop();
    }
    return hullPts;
}

```

4.5 Circle Line Intersection

```

double r, a, b, c; // ax+by+c=0, radius is at (0, 0)
// If the center is not at (0, 0), fix the constant c to translate
// everything so that center is at (0, 0)
double x0 = -a*c/(a*a+b*b), y0 = -b*c/(a*a+b*b);
if (c*c > r*r*(a*a+b*b)+eps)
    puts ("no_points");
else if (abs (c*c - r*r*(a*a+b*b)) < eps) {
    puts ("1_point");
    cout << x0 << ' ' << y0 << '\n';
}
else {
    double d = r*r - c*c/(a*a+b*b);
    double mult = sqrt (d / (a*a+b*b));
    double ax, ay, bx, by;
    ax = x0 + b * mult;
    bx = x0 - b * mult;
    ay = y0 - a * mult;
    by = y0 + a * mult;
    puts ("2_points");
    cout << ax << ' ' << ay << '\n' << bx << ' ' << by
        << '\n';
}
}

```

4.6 Circle Circle Intersection

Let's say that the first circle is centered at (0,0) (if it's not, we can move the origin to the center of the first circle and adjust the coordinates), and the

second one is at (x_2, y_2) . Then, let's construct a line $Ax + By + C = 0$, where $A = -2x_2, B = -2y_2, C = x_2^2 + y_2^2 + r_1^2 - r_2^2$. Finding the intersection between this line and the first circle will give us the answer. The only tricky case: if both circles are centered at the same point. We handle this case separately.

4.7 Common Tangents To Two Circles

```
struct pt {
    double x, y;

    pt operator- (pt p) {
        pt res = { x-p.x, y-p.y };
        return res;
    }
};

struct circle : pt {
    double r;
};

struct line {
    double a, b, c;
};

void tangents (pt c, double r1, double r2, vector<line> & ans) {
    double r = r2 - r1;
    double z = sqrt(c.x) + sqrt(c.y);
    double d = z - sqrt(r);
    if (d < -eps) return;
    d = sqrt(abs(d));
    line l;
    l.a = (c.x * r + c.y * d) / z;
    l.b = (c.y * r - c.x * d) / z;
    l.c = r1;
    ans.push_back(l);
}

vector<line> tangents (circle a, circle b) {
    vector<line> ans;
    for (int i=-1; i<=1; i+=2)
        for (int j=-1; j<=1; j+=2)
            tangents (b-a, a.r*i, b.r*j, ans);
    for (size_t i=0; i<ans.size(); ++i)
        ans[i].c -= ans[i].a * a.x + ans[i].b * a.y;
    return ans;
}
```

4.8 Number Of Lattice Points On Segment

Let's say we have a line segment from (x_1, y_1) to (x_2, y_2) . Then, the number of lattice points on this segment is given by

$$\gcd(x_2 - x_1, y_2 - y_1) + 1.$$

4.9 Pick's Theorem

We are given a lattice polygon with non-zero area. Let's denote its area by S , the number of points with integer coordinates lying strictly inside the polygon by I and the number of points lying on the sides of the polygon by B . Then:

$$S = I + \frac{B}{2} - 1.$$

5 Math

5.1 Linear Sieve

```
ll minDiv[MAXN+1];
vector<ll> primes;

void sieve(ll n){
    FOR(k, 2, n+1){
        minDiv[k] = k;
    }
    FOR(k, 2, n+1) {
        if(minDiv[k] == k) {
            primes.pb(k);
        }
        for(auto p : primes) {
            if(p > minDiv[k]) break;
            if(p*k > n) break;
            minDiv[p*k] = p;
        }
    }
}
```

5.2 Extended Euclidean Algorithm

```
// ax+by=gcd(a,b)
void solveEq(ll a, ll b, ll& x, ll& y, ll& g) {
    if(b==0) {
        x = 1;
        y = 0;
        g = a;
        return;
    }
    ll xx, yy;
    solveEq(b, a%b, xx, yy, g);
    x = yy;
    y = xx-yy*(a/b);
}

// ax+by=c
bool solveEq(ll a, ll b, ll c, ll& x, ll& y, ll& g) {
    solveEq(a, b, x, y, g);
    if(c%g != 0) return false;
    x *= c/g; y *= c/g;
    return true;
}

// Finds a solution (x, y) so that x >= 0 and x is minimal
bool solveEqNonNegX(ll a, ll b, ll c, ll& x, ll& y, ll& g) {
    if(!solveEq(a, b, c, x, y, g)) return false;
    ll k = x*g/b;
    x = x - k*b/g;
    y = y + k*a/g;
    if(x < 0) {
        x += b/g;
        y -= a/g;
    }
    return true;
}
```

All other solutions can be found like this:

$$x' = x - k\frac{b}{g}, y' = y + k\frac{a}{g}, k \in \mathbb{Z}$$

5.3 Chinese Remainder Theorem

Let's say we have some numbers m_i , which are all mutually coprime. Also, let $M = \prod_i m_i$. Then the system of congruences

$$\begin{cases} x \equiv a_1 \pmod{m_1} \\ x \equiv a_2 \pmod{m_2} \\ \dots \\ x \equiv a_k \pmod{m_k} \end{cases}$$

is equivalent to $x \equiv A \pmod{M}$ and there exists a unique number A satisfying $0 \leq A \leq M$.

Solution for two: $x \equiv a_1 \pmod{m_1}, x \equiv a_2 \pmod{m_2}$. Let $x = a_1 + km_1$. Substituting into the second congruence: $km_1 \equiv a_2 - a_1 \pmod{m_2}$. Then, $k = (m_1)_{m_2}^{-1}(a_2 - a_1) \pmod{m_2}$. and we can easily find x . This can be extended to multiple equations by solving them one-by-one.

If the moduli are not coprime, solve the system $y \equiv 0 \pmod{\frac{m_1}{g}}, y \equiv \frac{a_2 - a_1}{g} \pmod{\frac{m_2}{g}}$ for y . Then let $x \equiv gy + a_1 \pmod{\frac{m_1 m_2}{g}}$.

5.4 Euler Totient Function

```
// Number of numbers x < n so that gcd(x, n) = 1
ll phi(ll n) {
    if(n == 1) return 1;
    auto f = factorize(n);
    ll res = n;
    for(auto p : f) {
        res = res - res/p.first;
    }
    return res;
}
```

5.5 Factorization With Sieve

```
// Use linear sieve to calculate minDiv
vector<pll> factorize(ll x) {
    vector<pll> res;
    ll prev = -1;
    ll cnt = 0;
    while(x != 1) {
        ll d = minDiv[x];
        if(d == prev) {
            cnt++;
        } else {
            if(prev != -1) res.pb({prev, cnt});
            prev = d;
            cnt = 1;
        }
        x /= d;
    }
    res.pb({prev, cnt});
    return res;
}
```

5.6 Modular Inverse

```
bool invWithEuclid(ll a, ll m, ll& aInv) {
    ll x, y, g;
    if(!solveEqNonNegX(a, m, 1, x, y, g)) return false;
    aInv = x;
    return true;
}
// Works only if m is prime
ll invFermat(ll a, ll m) {
    return pwr(a, m-2, m);
}
// Works only if gcd(a, m) = 1
ll invEuler(ll a, ll m) {
    return pwr(a, phi(m)-1, m);
}
```

5.7 Simpson Integration

```
const int N = 1000 * 1000; // number of steps (already
                             multiplied by 2)
```

```
double simpsonIntegration(double a, double b){
    double h = (b - a) / N;
    double s = f(a) + f(b); // a = x_0 and b = x_2n
    for (int i = 1; i <= N - 1; ++i) {
        double x = a + h * i;
        s += f(x) * ((i & 1) ? 4 : 2);
    }
    s *= h / 3;
    return s;
}
```

5.8 Burnside's Lemma

Let G be a finite group that acts on a set X . For each g in G let X^g denote the set of elements in X that are fixed by g . Burnside's lemma asserts the following formula for the number of orbits:

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|.$$

Example. Coloring a cube with three colors.

Let X be the set of 3^6 possible face color combinations. Let's count the sizes of the fixed sets for each of the 24 rotations:

- one 0-degree rotation which leaves all 3^6 elements of X unchanged
- six 90-degree face rotations, each of which leaves 3^3 elements of X unchanged
- three 180-degree face rotation, each of which leaves 3^4 elements of X unchanged
- eight 120-degree vertex rotations, each of which leaves 3^2 elements of X unchanged
- six 180-degree edge rotations, each of which leaves 3^3 elements of X unchanged

The average is then $\frac{1}{24}(3^6 + 6 \cdot 3^3 + 3 \cdot 3^4 + 8 \cdot 3^2 + 6 \cdot 3^3) = 57$. For n colors: $\frac{1}{24}(n^6 + 3n^4 + 12n^3 + 8n^2)$.

Example. Coloring a circular stripe of n cells with two colors.

X is the set of all colored striped (it has 2^n elements), G is the group of rotations (n elements - by 0 cells, by 1 cell, ..., by $(n-1)$ cells). Let's fix some K and find the number of stripes that are fixed by the rotation by K cells. If a stripe becomes itself after rotation by K cells, then its 1st cell must have the same color as its $(1+K \bmod n)$ -th cell, which is in turn the same as its $(1+2K \bmod n)$ -th cell, etc., until $mK \bmod n = 0$. This will happen when $m = n/\gcd(K, n)$. Therefore, we have $n/\gcd(K, n)$ cells that must all be of the same color. The same will happen when starting from the second cell and so on. Therefore, all cells are separated into $\gcd(K, n)$ groups, with each group being of one color, and that yields $2^{\gcd(K, n)}$ choices. That's why the answer to the original problem is $\frac{1}{n} \sum_{k=0}^{n-1} 2^{\gcd(k, n)}$.

5.9 FFT

```

namespace FFT {
    int n;
    vector<int> r;
    vector<complex<ld>> omega;
    int logN, pwrN;

    void initLogN() {
        logN = 0;
        pwrN = 1;
        while (pwrN < n) {
            pwrN *= 2;
            logN++;
        }
        n = pwrN;
    }

    void initOmega() {
        FOR(i, 0, pwrN) {
            omega[i] = { cos(2 * i*PI / n), sin(2 * i*PI / n) };
        }
    }

    void initR() {
        r[0] = 0;
        FOR(i, 1, pwrN) {
            r[i] = r[i / 2] / 2 + ((i & 1) << (logN - 1));
        }
    }

    void initArrays() {
        r.clear();
        r.resize(pwrN);
        omega.clear();
        omega.resize(pwrN);
    }

    void init(int n) {
        FFT::n = n;
        initLogN();
        initArrays();
        initOmega();
        initR();
    }

    void fft(complex<ld> a[], complex<ld> f[]) {
        FOR(i, 0, pwrN) {
            f[i] = a[r[i]];
        }
        for (ll k = 1; k < pwrN; k *= 2) {
            for (ll i = 0; i < pwrN; i += 2 * k) {
                for (ll j = 0; j < k; j++) {
                    auto z = omega[j*n / (2 * k)] * f[i + j + k];
                    f[i + j + k] = f[i + j] - z;
                    f[i + j] += z;
                }
            }
        }
    }
}

```

5.10 FFT With Modulo

```

bool isGenerator(ll g) {
    if (pwr(g, M - 1) != 1) return false;
    for (ll i = 2; i*i <= M - 1; i++) {
        if ((M - 1) % i == 0) {
            ll q = i;
            if (isPrime(q)) {
                ll p = (M - 1) / q;
                ll pp = pwr(g, p);
                if (pp == 1) return false;
            }
        }
        q = (M - 1) / i;
        if (isPrime(q)) {
            ll p = (M - 1) / q;
            ll pp = pwr(g, p);
            if (pp == 1) return false;
        }
    }
}

```

```

        return true;
    }
}

namespace FFT {
    ll n;
    vector<ll> r;
    vector<ll> omega;
    ll logN, pwrN;

    void initLogN() {
        logN = 0;
        pwrN = 1;
        while (pwrN < n) {
            pwrN *= 2;
            logN++;
        }
        n = pwrN;
    }

    void initOmega() {
        ll g = 2;
        while (!isGenerator(g)) g++;
        ll G = 1;
        g = pwr(g, (M - 1) / pwrN);
        FOR(i, 0, pwrN) {
            omega[i] = G;
            G *= g;
            G %= M;
        }
    }

    void initR() {
        r[0] = 0;
        FOR(i, 1, pwrN) {
            r[i] = r[i / 2] / 2 + ((i & 1) << (logN - 1));
        }
    }

    void initArrays() {
        r.clear();
        r.resize(pwrN);
        omega.clear();
        omega.resize(pwrN);
    }

    void init(ll n) {
        FFT::n = n;
        initLogN();
        initArrays();
        initOmega();
        initR();
    }

    void fft(ll a[], ll f[]) {
        for (ll i = 0; i < pwrN; i++) {
            f[i] = a[r[i]];
        }
        for (ll k = 1; k < pwrN; k *= 2) {
            for (ll i = 0; i < pwrN; i += 2 * k) {
                for (ll j = 0; j < k; j++) {
                    auto z = omega[j*n / (2 * k)] * f[i + j + k] %
                        M;
                    f[i + j + k] = f[i + j] - z;
                    f[i + j] += z;
                    f[i + j + k] %= M;
                    if (f[i + j + k] < 0) f[i + j + k] += M;
                    f[i + j] %= M;
                }
            }
        }
    }
}

```

5.11 Big Integer Multiplication With FFT

```

complex<ld> a[MAX_N], b[MAX_N];
complex<ld> fa[MAX_N], fb[MAX_N], fc[MAX_N];
complex<ld> cc[MAX_N];

string mul(string as, string bs) {
    int sgn1 = 1;
    int sgn2 = 1;

```

```

if (as[0] == '-') {
    sgn1 = -1;
    as = as.substr(1);
}
if (bs[0] == '-') {
    sgn2 = -1;
    bs = bs.substr(1);
}
int n = as.length() + bs.length() + 1;
FFT::init(n);
FOR(i, 0, FFT::pwrN) {
    a[i] = b[i] = fa[i] = fb[i] = fc[i] = cc[i] = 0;
}
FOR(i, 0, as.size()) {
    a[i] = as[as.size() - 1 - i] - '0';
}
FOR(i, 0, bs.size()) {
    b[i] = bs[bs.size() - 1 - i] - '0';
}
FFT::fft(a, fa);
FFT::fft(b, fb);
FOR(i, 0, FFT::pwrN) {
    fc[i] = fa[i] * fb[i];
}
// turn [0,1,2,...,n-1] into [0, n-1, n-2, ..., 1]
FOR(i, 1, FFT::pwrN) {
    if (i < FFT::pwrN - i) {
        swap(fc[i], fc[FFT::pwrN - i]);
    }
}
FFT::fft(fc, cc);
ll carry = 0;
vector<int> v;
FOR(i, 0, FFT::pwrN) {
    int num = round(cc[i].real() / FFT::pwrN) + carry;
    v.pb(num % 10);
    carry = num / 10;
}
while (carry > 0) {
    v.pb(carry % 10);
    carry /= 10;
}
reverse(v.begin(), v.end());
bool start = false;
ostringstream ss;
bool allZero = true;
for (auto x : v) {
    if (x != 0) {
        allZero = false;
        break;
    }
}
if (sgn1*sgn2 < 0 && !allZero) ss << "-";
for (auto x : v) {
    if (x == 0 && !start) continue;
    start = true;
    ss << abs(x);
}
if (!start) ss << 0;
return ss.str();
}

```

5.12 Formulas

$$\begin{aligned}
\sum_{i=1}^n i &= \frac{n(n+1)}{2}; & \sum_{i=1}^n i^2 &= \frac{n(2n+1)(n+1)}{6}; \\
\sum_{i=1}^n i^3 &= \frac{n^2(n+1)^2}{4}; & \sum_{i=1}^n i^4 &= \frac{n(n+1)(2n+1)(3n^2+3n-1)}{30}; \\
\sum_{i=a}^b c^i &= \frac{c^{b+1}-c^a}{c-1}, c \neq 1; & \sum_{i=1}^n a_1 + (i-1)d &= \frac{n(a_1+a_n)}{2}; \\
\sum_{i=1}^n a_1 r^{i-1} &= \frac{a_1(1-r^n)}{1-r}, r \neq 1; \\
\sum_{i=1}^{\infty} ar^{i-1} &= \frac{a}{1-r}, |r| \leq 1.
\end{aligned}$$

6 Strings

6.1 Hashing

```

struct HashedString {
    const ll A1 = 9999999929, B1 = 1000000009, A2 =
        10000000087, B2 = 10000000097;

```

```

vector<ll> A1pwrs, A2pwrs;
vector<pll> prefixHash;
HashedString(const string& _s) {
    init(_s);
    calcHashes(_s);
}
void init(const string& s) {
    ll a1 = 1;
    ll a2 = 1;
    FOR(i, 0, (int)s.length()+1) {
        A1pwrs.pb(a1);
        A2pwrs.pb(a2);
        a1 = (a1*A1)%B1;
        a2 = (a2*A2)%B2;
    }
}
void calcHashes(const string& s) {
    pll h = {0, 0};
    prefixHash.pb(h);
    for(char c : s) {
        ll h1 = (prefixHash.back().first*A1 + c)%B1;
        ll h2 = (prefixHash.back().second*A2 + c)%B2;
        prefixHash.pb({h1, h2});
    }
}
pll getHash(int l, int r) {
    ll h1 = (prefixHash[r+1].first - prefixHash[l].first*A1pwrs[r+1-l]) % B1;
    ll h2 = (prefixHash[r+1].second - prefixHash[l].second*
        A2pwrs[r+1-l]) % B2;
    if(h1 < 0) h1 += B1;
    if(h2 < 0) h2 += B2;
    return {h1, h2};
}
};

```

6.2 Prefix Function

```

// pi[i] is the length of the longest proper prefix of the substring
// s[0..i] which is also a suffix
// of this substring
vector<int> prefixFunction(const string& s) {
    int n = (int)s.length();
    vector<int> pi(n);
    for (int i = 1; i < n; i++) {
        int j = pi[i-1];
        while (j > 0 && s[i] != s[j])
            j = pi[j-1];
        if (s[i] == s[j])
            j++;
        pi[i] = j;
    }
    return pi;
}

```

6.3 Prefix Function Automaton

```

// aut[oldPi][c] = newPi
vector<vector<int>>> computeAutomaton(string s) {
    const char BASE = 'a';
    s += "#";
    int n = s.size();
    vector<int> pi = prefixFunction(s);
    vector<vector<int>>> aut(n, vector<int>(26));
    for (int i = 0; i < n; i++) {
        for (int c = 0; c < 26; c++) {
            if (i > 0 && BASE + c != s[i])
                aut[i][c] = aut[pi[i-1]][c];
            else
                aut[i][c] = i + (BASE + c == s[i]);
        }
    }
    return aut;
}
vector<int> findOccurs(const string& s, const string& t) {
    auto aut = computeAutomaton(s);
    int curr = 0;
    vector<int> occurs;
    FOR(i, 0, (int)t.length()) {
        int c = t[i] - 'a';

```



```

    curr = aut[curr][c];
    if(curr == (int)s.length()) {
        occurs.pb(i-s.length()+1);
    }
}
return occurs;
}

```

6.4 KMP

```

// Knuth-Morris-Pratt algorithm
vector<int> findOccurrences(const string& s, const string& t) {
    int n = s.length();
    int m = t.length();
    string S = s + "#" + t;
    auto pi = prefixFunction(S);
    vector<int> ans;
    FOR(i, n+1, n+m+1) {
        if(pi[i] == n) {
            ans.pb(i-2*n);
        }
    }
    return ans;
}

```

6.5 Aho Corasick Automaton

```

// alphabet size
const int K = 70;

// the indices of each letter of the alphabet
int intVal[256];
void init() {
    int curr = 2;
    intVal[1] = 1;
    for(char c = '0'; c <= '9'; c++, curr++) intVal[(int)c] = curr;
    for(char c = 'A'; c <= 'Z'; c++, curr++) intVal[(int)c] = curr;
    for(char c = 'a'; c <= 'z'; c++, curr++) intVal[(int)c] = curr;
}

struct Vertex {
    int next[K];
    vector<int> marks;
    // ^ this can be changed to int mark = -1, if there will be
    // no duplicates
    int p = -1;
    char pch;
    int link = -1;
    // ^ exitLink points to the next node on the path of suffix
    // links which is marked
    int go[K];

    // ch has to be some small char
    Vertex(int _p=-1, char ch=(char)1) : p(_p), pch(ch) {
        fill(begin(next), end(next), -1);
        fill(begin(go), end(go), -1);
    }
};

vector<Vertex> t(1);

void addString(string const& s, int id) {
    int v = 0;
    for(char ch : s) {
        int c = intVal[(int)ch];
        if(t[v].next[c] == -1) {
            t[v].next[c] = t.size();
            t.emplace_back(v, ch);
        }
        v = t[v].next[c];
    }
    t[v].marks.pb(id);
}

int go(int v, char ch);

```

```

int getLink(int v) {
    if(t[v].link == -1) {
        if(v == 0 || t[v].p == 0)
            t[v].link = 0;
        else
            t[v].link = go(getLink(t[v].p), t[v].pch);
    }
    return t[v].link;
}

int getExitLink(int v) {
    if(t[v].exitLink != -1) return t[v].exitLink;
    int l = getLink(v);
    if(l == 0) return t[v].exitLink = 0;
    if(!t[l].marks.empty()) return t[v].exitLink = l;
    return t[v].exitLink = getExitLink(l);
}

int go(int v, char ch) {
    int c = intVal[(int)ch];
    if(t[v].go[c] == -1) {
        if(t[v].next[c] != -1)
            t[v].go[c] = t[v].next[c];
        else
            t[v].go[c] = v == 0 ? 0 : go(getLink(v), ch);
    }
    return t[v].go[c];
}

void walkUp(int v, vector<int>& matches) {
    if(v == 0) return;
    if(!t[v].marks.empty()) {
        for(auto m : t[v].marks) matches.pb(m);
    }
    walkUp(getExitLink(v), matches);
}

// returns the IDs of matched strings.
// Will contain duplicates if multiple matches of the same string
// are found.
vector<int> walk(const string& s) {
    vector<int> matches;
    int curr = 0;
    for(char c : s) {
        curr = go(curr, c);
        if(!t[curr].marks.empty()) {
            for(auto m : t[curr].marks) matches.pb(m);
        }
        walkUp(getExitLink(curr), matches);
    }
    return matches;
}

/* Usage:
 * addString(strs[i], i);
 * auto matches = walk(text);
 * .. do what you need with the matches - count, check if some
 *    id exists, etc ..
 * Some applications:
 * - Find all matches: just use the walk function
 * - Find lexicographically smallest string of a given length that
 *    doesn't match any of the given strings:
 *   For each node, check if it produces any matches (it either
 *   contains some marks or walkUp(v) returns some marks).
 *   Remove all nodes which produce at least one match. Do DFS
 *   in the remaining graph, since none of the remaining
 *   nodes
 *   will ever produce a match and so they're safe.
 * - Find shortest string containing all given strings:
 *   For each vertex store a mask that denotes the strings which
 *   match at this state. Start at (v = root, mask = 0),
 *   we need to reach a state (v, mask=2^n-1), where n is the
 *   number of strings in the set. Use BFS to transition
 *   between states
 *   and update the mask.
 */

```

6.6 Suffix Array

```

vector<int> sortCyclicShifts(string const& s) {
    int n = s.size();
    const int alphabet = 256; // we assume to use the whole
    ASCII range
    vector<int> p(n), c(n), cnt(max(alphabet, n), 0);
    for(int i = 0; i < n; i++)

```

```

    cnt[s[i]]++;
    for (int i = 1; i < alphabet; i++)
        cnt[i] += cnt[i-1];
    for (int i = 0; i < n; i++)
        p[--cnt[s[i]]] = i;
    c[p[0]] = 0;
    int classes = 1;
    for (int i = 1; i < n; i++) {
        if (s[p[i]] != s[p[i-1]])
            classes++;
        c[p[i]] = classes - 1;
    }
    vector<int> pn(n), cn(n);
    for (int h = 0; (1 << h) < n; ++h) {
        for (int i = 0; i < n; i++) {
            pn[i] = p[i] - (1 << h);
            if (pn[i] < 0)
                pn[i] += n;
        }
        fill(cnt.begin(), cnt.begin() + classes, 0);
        for (int i = 0; i < n; i++)
            cnt[c[pn[i]]]++;
        for (int i = 1; i < classes; i++)
            cnt[i] += cnt[i-1];
        for (int i = n-1; i >= 0; i--)
            p[--cnt[c[pn[i]]]] = pn[i];
        cn[p[0]] = 0;
        classes = 1;
        for (int i = 1; i < n; i++) {
            pair<int, int> cur = {c[p[i]], c[(p[i] + (1 << h)) % n]};
            pair<int, int> prev = {c[p[i-1]], c[(p[i-1] + (1 << h)) % n]};
            if (cur != prev)
                ++classes;
            cn[p[i]] = classes - 1;
        }
        c.swap(cn);
    }
    return p;
}

vector<int> constructSuffixArray(string s) {
    s += "$"; // <- this must be smaller than any character in
               s
    vector<int> sorted_shifts = sortCyclicShifts(s);
    sorted_shifts.erase(sorted_shifts.begin());
    return sorted_shifts;
}

```