TEAS Working Group   D. King
Internet-Draft   Old Dog Consulting
Intended status: Informational   J. Drake
Expires: 10 March 2023   Juniper Networks
                                                         H. Zheng
                                              Huawei Technologies
                                                        A. Farrel
                                                 Old Dog Consulting
                                                 6 September 2022

Applicability of Abstraction and Control of Traffic Engineered Networks
                      (ACTN) to Network Slicing
            draft-ietf-teas-applicability-actn-slicing-02

Abstract

   Network abstraction is a technique that can be applied to a network
   domain to obtain a view of potential connectivity across the network
   by utilizing a set of policies to select network resources.

   Network slicing is an approach to network operations that builds on
   the concept of network abstraction to provide programmability,
   flexibility, and modularity. It may use techniques such as Software
   Defined Networking (SDN) and Network Function Virtualization (NFV) to
   create multiple logical or virtual networks, each tailored for a set
   of services that share the same set of requirements.

   Abstraction and Control of Traffic Engineered Networks (ACTN) is
   described in RFC 8453. It defines an SDN-based architecture that
   relies on the concept of network and service abstraction to detach
   network and service control from the underlying data plane.

   This document outlines the applicability of ACTN to network slicing
   in a Traffic ~~Engineering~~ Engineered (TE) network that utilizes IETF
   ~~technology~~technologies.
   It also identifies the features of network slicing not currently
   within the scope of ACTN, and indicates where ACTN might be extended.

Status of This Memo

Copyright Notice

Table of Contents

1. Introduction

   The principles of network resource separation are not new. For
   years, the concepts of separated overlay and logical (virtual)
   networking have existed, allowing multiple services to be deployed
   over a single physical network comprised of single or multiple
   layers. However, several key ~~differences exist that~~aspects
differentiate
   overlay and virtual networking from network slicing.

   A network slice is a virtual (that is, logical) network with its own
   network topology and a set of network resources that are used to
   provide connectivity that conforms to ~~a~~specific Service Level_s_
   Agreement (SLA_s_) or set of Service Level Objectives (SLOs). The
   network resources used to realize a network slice belong to the
   network that is sliced. The resources may be assigned and dedicated

to an individual slice, or they may be shared with other slices
enabling different degrees of service guarantee and providing
different levels of isolation between the traffic in each slice.

[I-D.ietf-teas-ietf-network-slices] provides a definition for network
slicing in the context of IETF network technologies. In particular,
that document defines the term "IETF Network Slice" as the generic
network slice concept applied to a network that uses IETF
technologies. An IETF Network Slice could span multiple technologies
(such as IP, MPLS, or optical) and multiple administrative domains.
The logical network that is an IETF Network Slice may be kept
separate from other concurrent logical networks with independent
control and management: each can be created or modified on demand.
Since this document is focused entirely on IETF technologies, it uses
the term "network slice" as a more concise expression. Further
discussion on the topic of IETF Network Slices and details of how an
IETF Network Slice Sservice may be requested and realized as an IETF
Network Slice can be found in [I-D.ietf-teas-ietf-network-slices].

At one end of the spectrum, a virtual private wire or a ~~virtual~~Virtual
~~private~~Private ~~network~~Network (VPN) may be used to build a network
slice. In these
cases, the network slices do not require the service provider to
isolate network resources for the provision of the service - the
service is "virtual".

At the other end of the spectrum, there may be a detailed description
of a complex network service that will meet the needs of a set of
applications with connectivity and service function requirements that
may include compute resources, storage capabilities, and access to
content. Such a service may be requested dynamically (that is,
instantiated when an application needs it, and released when the
application no longer needs it), and modified as the needs of the
application change. An example of such a ~~This~~ type of service can be
provided using ~~is called an~~ enhanced VPN
~~and is~~ described ~~in more detail~~ in [I-D.ietf-teas-enhanced-vpn]. It
is often based on Traffic Engineering (TE) constructs in the underlay
network.

Abstraction and Control of TE Networks (ACTN) [RFC8453] is a
framework that ~~facilitates~~ is designed to facilitate the abstraction
of underlying network
resources to higher-layer applications and that allows network
operators to create and supply virtual networks for their customers
through the abstraction of the operators' network resources.

ACTN is a toolset capable of delivering network slice functionality.
This document outlines the application of ACTN and associated
enabling technologies to provide network slicing in a network that
utilizes IETF TE-based technologies. It describes how the ACTN
functional components can be used to support model-driven
partitioning of network resources into variable-sized bandwidth units
to
facilitate network sharing and virtualization. Furthermore, the use
of model-based interfaces to dynamically request the instantiation of
virtual networks can be extended to encompass requesting and
instantiation of specific service functions (which may be both
physical or virtual), and to partition network resources such as

compute resource, storage capability, and access to content.
Finally, this document highlights how the ACTN approach might be
extended to address the requirements of network slicing where the
underlying network is TE-capable.

1.1. Terminology

As far as is possible, tThis document re-uses terminology from
[I-D.ietf-teas-ietf-network-slices] and [I-D.ietf-teas-enhanced-vpn].

Service Provider: See "Provider" in
   [I-D.ietf-teas-ietf-network-slices].

Consumer: See [I-D.ietf-teas-ietf-network-slices].

Service Functions (SFs): Components that provide specific functions
   within a network. SFs are often combined in a specific sequence
   called a service function chain to deliver services [RFC7665].

Resource: Any feature including connectivity, bufferagebuffers,
compute,
   storage, and content delivery that forms part of or can be
   accessed through a network. Resources may be shared between
   users, applications, and clients, or they may be dedicated for use
   by a unique customer.

Infrastructure Resources: The hardware and software for hosting and
   connecting SFs. These resources may include computing hardware,
   storage capacity, network resources (e.g., links and switching/
   routing devices enabling network connectivity), and physical
   assets for radio access.

Service Level Agreement (SLA): See
   [I-D.ietf-teas-ietf-network-slices].

Service Level Expectation (SLE): See [I-D.ietf-teas-ietf-network-sli
   ces].

Service Level Objective (SLO): See
   [I-D.ietf-teas-ietf-network-slices].

IETF Network Slice Service: See [I-D.ietf-teas-ietf-network-slices].

2. Overview of Key Requirements for Network Slicing

According to [I-D.ietf-teas-ietf-network-slices] the customer
expresses requirements for a particular network slice by specifying
what is required rather than how the requirement is to be fulfilled.
That is, the customer's view of a network slice is an abstract one
expressed as a network slice service request.

The concept of network slicing is a key capability to serve a
customer with a wide variety of different service needs expressed as
SLOs/SLEs in terms of, e.g., —latency, reliability, capacity, and
service
function-specific capabilities.

This section outlines the key capabilities required to realize

network slicing in a TE-enabled IETF technology network.

2.1. Resource ~~Slicing~~Partitioning

   Network resources need to be allocated and dedicated for use by a
   specific network slice_service, or they may be shared among multiple
slice_services.
   This allows a flexible approach that can deliver a range of services
   by partitioning (that is, slicing) the available network resources to
   make them available to meet the customer's SLA.

2.2. Network Topology Customization and Virtualization

   Network virtualization enables the creation of multiple virtual
   networks that are operationally decoupled from the underlying
   physical network, and are run on top of it. Slicing enables the
   creation of virtual networks as customer services.

2.3. Service Isolation

   A customer may request, through their SLA, that changes to the other
   services delivered by the service provider do not have any negative
   impact on the delivery of the service. This quality is referred to
   as "isolation" (Section 7.1 of [I-D.ietf-teas-ietf-network-slices])
   ~~[I-D.ietf-teas-enhanced-vpn]~~.

   Delivery of such a service isolation may be achieved in the underlying
   network by various forms of resource partitioning ranging from
   dedicated allocation of resources for a specific slice, to sharing or
   resources with safeguards.

   Although multiple network slices may utilize resources from a single
   underlying network, isolation should be understood in terms of the
   following three categorizations.

   * Performance isolation requires that service delivery for one
      network slice does not adversely impact congestion or performance
      levels this perceived by the users of other slices.

   * Security isolation means that attacks or faults occurring in one
      slice do not impact on other slices. Moreover, the security
      functions supporting each slice must operate independently so that
      an attack or misconfiguration of security in one slice will not
      prevent proper security function in the other slices. Further,
      privacy concerns require that traffic from one slice is not
      delivered to an endpoint in another slice, and that it should not
      be possible to determine the nature or characteristics of a slice
      from any external point.

   * Management isolation means that each slice must be independently
      viewed, utilized, and managed as a separate network. Furthermore,
      it should be possible to prevent the operator of one slice from
      being able to control, view, or detect any aspect of any other
      network slice.

2.4. Control and Orchestration

   ~~Orchestration combines and coordinates multiple control methods to~~

provide a single mechanism to operate one or more networks to deliver services. An orchestrator is needed used to coordinate disparate processes and resources for creating, managing, and deploying the network slicing service in a network slicing environment. TwoThe following aspects of orchestration are requiredshould be considered:

* Multi-domain Orchestration: Managing connectivity to set up a network slice across multiple administrative domains.

* End-to-end Orchestration: Combining resources for an end-to-end service (e.g., underlay connectivity with firewalling, and guaranteed bandwidth with minimum delay).

3. Abstraction and Control of Traffic Engineered (TE) Networks (ACTN): Overview of Key Components

   ACTN is designed to facilitates end-to-end connectivity and provides virtual
   connectivity services (such as virtual links and virtual networks) to
   the user. The ACTN framework [RFC8453] introduces three functional
   components and two interfaces:

* Customer Network Controller (CNC)

* Multi-domain Service Coordinator (MDSC)

* Provisioning Network Controller (PNC)

* CNC-MDSC Interface (CMI)

* MDSC-PNC Interface (MPI)

   [RFC 8453] also highlights how:

* Abstraction of the underlying network resources is provided to higher-layer applications and customers.

* Virtualization is achieved by selecting resources according to criteria derived from the details and requirements of the customer, application, or service.

* Creation of a virtualized environment is performed to allow operators to view and control multi-domain networks as a single virtualized network.

* A network is presented to a customer as a single virtual network via open and programmable interfaces.

   The ACTN ACTN-managed infrastructure consists of traffic engineered
   network resources. The concept of traffic engineering is broad: it
   describes the planning and operation of networks using a method of
   reserving and partitioning of network resources in order to
   facilitate traffic delivery across a network (see
   [I-D.ietf-teas-rfc3272bis] for more details). In the context of
   ACTN, traffic engineering engineered network resources may include:

* Statistical packet bandwidth.

* Physical forwarding plane sources, such as wavelengths and time
       slots.

    * Forwarding and cross-connect capabilities.

    The An ACTN network is can be "sliced" with each customer being given
a
    different partial and abstracted topology view of the physical
    underlay network.

3.1. ACTN Virtual Network as a Network Slice

    To support multiple customers, each with its own view of and control
    of a virtual network constructed using a server network, a service
    provider needs to partition the network resources to create network
    slices assigned to each customer.

    An ACTN Virtual Network (VN) is a customer view of a slice of the
    ACTN-managed infrastructure. It is a network slice that is presented
    to the customer by the ACTN provider as a set of abstracted
    resources. See [I-D.ietf-teas-actn-vn-yang] for a detailed
    description of ACTN VNs and an overview of how various different
    types of YANG models model are applicable to the ACTN framework.

    Depending on the agreement between a customer and a provider, various
VN
    operations are possible:

    * Network Slice Creation: A VN could be pre-configured and created
       through static configuration or through dynamic request and
       negotiation between customers and service providers. The VN must
       meet the network slice requirements specified in the SLA to
       satisfy the customer's objectives.

    * Network Slice Operations: The VN may be modified and or deleted
based
       on direct customer requests. Also, the VN engineering can be
    adjusted by the operator to continuously ensure that the delivered
    service complies with the requested one. — The customer can further act
upon
       the VN to manage the their traffic flows across the network slice.

    * Network Slice View: The A VN topology is viewed from the customer's
       perspective. This may be the entire VN topology, or a collection
       of tunnels that are expressed as customer endpoints, access links,
       intra-domain paths and inter-domain links.

    [RFC8454] describes a set of functional primitives that support these
    different ACTN VN operations.

3.2. ACTN Virtual Network for and Scaling Network Slices

    Scaling considerations for network slicing are an important
    consideration. If the service provider must manage and maintain
    state in the core of the network for every network slice, then this
    will quickly limit the number of customer services that can be
    supported.

The importance of scalability for network slices is discussed in
[I-D.ietf-teas-enhanced-vpn] and further in
[I-D.dong-teas-enhanced-vpn-vtn-scalability]. That work notes the
importance of collecting network slices or their composite
connectivity constructs into groups that require similar treatment in
the network before realizing those groups in the network.

The same consideration applies to ACTN VNs. But fortunately, ACTN
VNs may be arranged hierarchically by recursing the MDSCs so that one
VN is realized over another VN. This allows the VNs presented to the
customer to be aggregated before they are instantiated in the
physical network.

3.3. Management Components for ACTN and Network Slicing

The ACTN management components (CNC, MDSC, and PNC) and interfaces
(CMI and MPI) are introduced in Section 3 and described in detail in
[RFC8453]. The management components for network slicing are
described in [I-D.ietf-teas-ietf-network-slices] and are known as the
customer orchestration system, the IETF Network Slice Controller
(NSC), and the network controller. The network slicing management
components are separated by the Network Slice Service Interface and
the Network Configuration Interface, modeling the architecture
described in [RFC8309].

The mapping between network slicing management components and ACTN
management components is presented visually in Figure 1 and provides
a reference for understanding the material in Sections 3.4 and
~~Section~~ 4.

```
        +-------------------------------------+
        |       Customer operation system     |   |    +-----+
        | (e.g., E2E network slice orchestrator,  | =====> | CNC |
        |   customer network management system) |   |    +-----+
        +-------------------------------------+   |       ^
                          A                       |       |
           IETF Network Slice |                   |       | CMI
             Service Interface |                   |       |
                          V                        |       v
        +-------------------------------------+   |    +------+
        |  IETF Network Slice Controller (NSC) | =====> | MDSC |
        +-------------------------------------+   |    +------+
                          A                       |       ^
              Network          |                  |       |
              Configuration |                     |       | MPI
              Interface        |                  |       |
                          V                        |       v
        +-------------------------------------+   |    +-----+
        |          Network Controllers         | =====> | PNC |
        +-------------------------------------+   |    +-----+
```

        Figure 1: Mapping Between IETF Network Slice and ACTN Management
                                Components

3.4. Examples of ACTN Delivering ~~Types of~~ Network Slice Services

The examples that follow build on the ACTN framework to provide
control, management, and orchestration for the network slice life-

cycle. These network slices utilize common physical infrastructure,
and meet specific service-level requirements.

Three examples are shown. Each uses ACTN to achieve a different
network slicing scenario. All three scenarios can be scaled up in
capacity or be subject to topology changes as well as changes in
customer requirements.

3.4.1. ACTN Used for Virtual Private Line

In the example shown in Figure 2, ACTN provides virtual connections
between multiple customer locations (sites accessed through Customer
Edge nodes - CEs). The service is requested by the customer (via
CNC-A) and delivered as a Virtual Private Line (VPL) service. The
benefits characteristics of this model include the following.

   * Automated: The service set-up and operation is managed by the
      network provider.

   * Virtual: The private line connectivity is provided from Site A to
      Site C (VPL1) and from Site B to Site C (VPL2) across the ACTN-
      managed physical network.

   * Agile: On-demand adjustments to the connectivity and bandwidth are
      available according to the customer's requests.

In terms of the network slicing concept defined in
[I-D.ietf-teas-ietf-network-slices], in this example the customer
requests a single network slice with two pairs of point-to-point
connectivity constructs between the service demarcation points CE1
and CE3, and CE2 and CE3 with each pair comprising one connectivity
construct in each direction.

```
                    (Customer VPL Request)
                             :
                          -------
                          | CNC-A |
     Boundary             -------
     Between  . . . . . . . .:. . . . . . . . . .
     Customer &                :
     Network Provider       ------
                          | MDSC |
                          ------
                             :
                           -----
                          | PNC |
      Site A              ( ----- )            Site B
      -----              (         )            -----
     | CE1 |========(  Physical )========| CE2 |
      -----\          ( Network )         /-----
           \          (_____)          /
            \              ||            /
             \             ||           /
         VPL1 \            ||          / VPL2
               \           ||         /
                \          ||        /
                 \         ||       /
                  \-------------/
```

<comment>Commenté [BMI7]: Why is this unique to this model?</comment>

<comment>Commenté [BMI8]: This is a side effect of using automation? No?</comment>

```
                    |      CE3      |
                     -------------
                        Site C

       Key:   ... ACTN control connectivity
              === Physical connectivity
              --- Logical connectivity
                  Figure 2: Virtual Private Line Model
```

3.4.2. ACTN Used for VPN Delivery Model

   In the example shown in Figure 3, ACTN provides VPN connectivity
   between two sites across three physical networks. The requirements
   for the VPN are expressed by the users of the two sites. The request
   is directed to the CNC, and the CNC interacts with the network
   provider's MDSC. The ~~benefits~~ man characteristics of this model
include are as follows.

   * Provides edge-to-edge VPN multi-access connectivity.

   * Most of the function is managed by the network provider, with some
      flexibility delegated to the customer-managed CNC.

   In terms of the network slicing concept defined in
   [I-D.ietf-teas-ietf-network-slices], in this example, the customer
   requests a single network slice with a pair of point-to-point
   connectivity constructs (one in each direction) between the service
   demarcation points at site A and site B. The customer is unaware
   that the service is delivered over multiple physical networks.

```
                     --------------   --------------
                     | Site-A Users | | Site-B Users |
                     --------------   --------------
                           :              :
                          -------------
                          |    CNC     |
          Boundary        -------------
          Between  . . . . . . . . . . . : . . . . . . . . . .
          Customer &                     :
          Network Provider               :
                     ---------------------------------
                     |             MDSC              |
                     ---------------------------------
                       :            :            :
                       :            :            :
                     -------      -------      -------
                     | PNC |      | PNC |      | PNC |
                     -------      -------      -------
                       :            :            :
                       :            :            :
           _____    ---------    ---------    ---------    _____
          <      >  (         )  (         )  (         )  <      >
          <Site A>==( Physical )==( Physical )==( Physical )==<Site B>
          <      >  ( Network )   ( Network )   ( Network )  <      >
          <      >  (         )   (         )   (         )  <      >
          <      >   -------       -------       -------     <      >
          <      >--------------------------------------------<     >
          <_____>                                          <_____>
```

```
      Key:   ... ACTN control connectivity
             === Physical connectivity
             --- Logical connectivity
```

   Figure 3: VPN Model

3.4.3. ACTN Used to Deliver a Virtual Customer Network

   In the example shown in Figure 4, ACTN provides a virtual network to
   the customer. This virtual network is managed by the customer. The
   figure shows two virtual networks (Network Slice 1 and Network Slice
   2) each created for a different customer under the care of a
   different CNC. There are two physical networks controlled by
   separate PNCs. Network Slice 2 is built using resources from just
   one physical network, while Network Slice 1 is constructed from
   resources from both physical networks.

   The ~~benefits~~ characteristics of this model include the following.

   * The MDSC provides the topology to the customer so that the
      customer can control their network slice to fit their needs.

   * Applications can interact with their assigned network slices
      directly. The customer may implement their own network control
      methods and traffic classification, mapping, prioritization, and
manage their own
      addressing schemes.

   * Customers may further slice their virtual networks so that this
      becomes a recursive model.

   * Service isolation can be provided through selection of physical
      networking resources through a combination of efforts of the MSDC
      and PNC.

   * The network slice may include nodes with specific capabilities.
      These can be delivered as Physical Network Functions (PNFs) or
      Virtual Network Functions (VNFs).

```
                                             _____
                    -------------           (           )
                   |    CNC      |---------------->(  Network  )
                    -------------           (  Slice 2  )
                     ^                       (_____)
                     |                        _____     ^
                     |   -------------       (           ) :
                     |  |    CNC      |------->(  Network  ) :
                     |   -------------       (  Slice 1  ) :
                     |       ^               (_____) :
                     |       |                ^      ^     :
      Boundary       |       |                :      :     :
      Between      .|. . . .|. . . . . . . . . : . .:. . : . . .
      Customer &     |       |                :      :     :
      Network        |       |                :      :     :
      Provider       v       v                :      :     :
                    -------------             :      :....:
                   |    MDSC     |            :          :
```

```
          -------------                      :          :
              ^                  ------^--       :
              |                 (          )     :
              v                 (  Physical )    :
          -------               ( Network )      :
         |  PNC  |<------------>(          )   ---^-----
          -------  |             -------     (          )
         |  PNC  |-                          (  Physical )
         |       |<------------------------>( Network )
          -------                            (          )
                                              -------
```

```
     Key: --- ACTN control connection
          ... Virtualization/abstraction through slicing
```

                    Figure 4: Network Slicing

4. YANG Models

4.1. Network Slice Service Mapping from TE to ACTN VN Models

   The ~~role of the~~ TE-service mapping model
   [I-D.ietf-teas-te-service-mapping-yang] ~~is to~~ creates a binding
   relationship across a Layer 3 Service Model (L3SM) [RFC8299], Layer 2
   Service Model (L2SM) [RFC8466], and TE Tunnel model
   [I-D.ietf-teas-yang-te], via the generic ACTN Virtual Network (VN)
   model [I-D.ietf-teas-actn-vn-yang].

   The ACTN VN model is a generic virtual network service model that
   allows customers to specify a VN that meets the customer's service
   objectives with various constraints on how the service is delivered.
   For example, a request for a network slice service may be mapped
   directly to a request for a VN.

   The TE-service mapping model [I-D.ietf-teas-te-service-mapping-yang]
   is used to bind the L3SM with TE-specific parameters. This binding
   facilitates seamless service operation and enables visibility of the
   underlay TE network. The TE-service model developed in that document
   can also be extended to support other services including L2SM, and
   the Layer 1 Connectivity Service Model (L1CSM)
   [I-D.ietf-ccamp-l1csm-yang] L1CSM network service models.

   Figure 5 shows the relationship between the YANG models discussed
above.

```
    ---------------     -----------
   |     L3SM      |<=========|               |            -----------
    --------------- augments |            |...........>|  ACTN VN  |
    ---------------          | Augmented | references  -----------
   |     L2SM      |<=========| Service   |
    --------------- augments | Model     |            -----------
    ---------------          |           |...........>|  TE-topo  |
   |     L1CSM     |<=========|           | references  -----------
    --------------- augments |           |
    ---------------          |           |            -----------
   | TE & Service  |-------->|            |...........>| TE-tunnel |
   | Mapping Types |  imports  ----------- references  -----------
    ---------------
```

Commenté [BMI12]: I would indicate that these constraints are similar those that might be included in a slice service request.

The intent is to make the mapping between a slice service request and ACTN/TE mapping more straightforward.

Figure 5: TE-Service Mapping

4.2. Interfaces and ~~Yang~~ YANG Models

Figure 6 shows the three ACTN components and two ACTN interfaces as
listed in Section 3. The figure also shows the Device Configuration
Interface between the PNC and the devices in the physical network.
That interface might be used to install state on every device in the
network, or might instruct a "head-end" node when a control plane is
used within the physical network. In the context of [RFC8309], the
Device Configuration Interface uses one or more device configuration
models.

~~The figure~~Figure 6 also shows the Network Slice Service Interface.
This
interface allows a customer to make requests for delivery of the
service, and it facilitates the customer modifying and monitoring the
service. In the context of [RFC8309], this is a customer service
interface and uses a service model.

When an ACTN system is used to manage the delivery of network slices,
a network slice resource model is needed. This model will be used
for instantiation, operation, and monitoring of network and function
resource slices. The YANG model defined in
[I-D.ietf-teas-ietf-network-slice-nbi-yang] provides a suitable basis
for requesting, controlling, and deletion, of network slices.

```
                     ----------
                    | Customer |
                     ----------
             .......:....... Network Slice Service Interface
                    :
              -------------
             |    CNC      |
              -------------
             .......:....... CMI
                    :
            ---------------
           |     MDSC      |
            ---------------
             .......:....... MPI
                    :
                -------
               | PNC  |
                -------
             .......:....... Device Configuration Interface
                    :
               ----------
              (          )
             (  Physical  )
              ( Network  )
               (_____)
```

Figure 6: The Yang Interfaces in Context

4.3. ACTN VN Telemetry

The ACTN VN KPI telemetry model
[I-D.ietf-teas-actn-pm-telemetry-autonomics] provides a way for a
customer to define performance monitoring relevant for ~~its~~ his/her
VN/network
slice via the NETCONF subscription mechanisms [RFC8639], [RFC8640],
or using the equivalent mechanisms in RESTCONF [RFC8641], [RFC8650].

Key characteristics of [I-D.ietf-teas-actn-pm-telemetry-autonomics]
include the following~~.~~:

* An ability to provide scalable VN-level telemetry aggregation
   based on a customer subscription model for key performance
   parameters defined by the customer.

* An ability to facilitate proactive re-optimization and
   reconfiguration of VNs/network slices based on autonomic network
   traffic engineering scaling configuration mechanisms.

5. IANA Considerations

   This document makes no requests for action by IANA.

6. Security Considerations

   Network slicing involves the control of network resources in order to
   meet the service requirements of customers. In some deployment
   models using ACTN, the customer may directly request modification in
   the behaviour of resources owned and operated by a service provider.
   Such changes could significantly affect the service provider's
   ability to provide services to other customers. Furthermore, the
   resources allocated for or consumed by a customer will typically be
   billable by the service provider.

   Therefore, it is crucial that the mechanisms used in any network
   slicing system allow for authentication of requests, security of
   those requests, and tracking of resource allocations.

   It should also be noted that while the partitioning or slicing of
   resources is virtual, as mentioned in Section 2.3 the customers
   expect and require that there is no risk of leakage of data from one
   slice to another, no transfer of knowledge of the structure or even
   existence of other slices. Further, in some service requests, there
   is an expectation that changes to one slice (under the control of one
   customer) should not have detrimental effects on the operation of
   other slices (whether under control of different or the same
   customers) even within limits allowed within the SLA. Thus, slices
   are assumed to be private and to provide the appearance of genuine
   physical connectivity.

   Some service providers may offer secure network slices as a service.
   Such services may claim to include edge-to-edge encryption for the
   customer's traffic. However, a customer should take full
   responsibility for the privacy and integrity of their traffic and
   should carefully consider using their own edge-to-edge encryption.

   ACTN operates using the NETCONF [RFC6241] or RESTCONF [RFC8040]
   protocols and assumes the security characteristics of those
   protocols. Deployment models for ACTN should fully explore the

authentication and other security aspects before networks start to
carry live traffic.

7. Acknowledgements

8. Contributors

The following people contributed text to this document.

     Young Lee
     Email: younglee.tx@gmail.com

     Mohamed Boucadair
     Email: mohamed.boucadair@orange.com

     Sergio Belotti
     Email: sergio.belotti@nokia.com

     Daniele Ceccarelli
     Email: daniele.ceccarelli@ericsson.com

9. Informative References

> **Commenté [BMI13]:** At least the ACTN RFC and the IETF Slice Framework should be listed as normative.

[I-D.dong-teas-enhanced-vpn-vtn-scalability]
          Dong, J., Li, Z., Gong, L., Yang, G., Guichard, J. N.,
          Mishra, G., and F. Qin, "Scalability Considerations for
          Enhanced VPN (VPN+)", Work in Progress, Internet-Draft,
          draft-dong-teas-enhanced-vpn-vtn-scalability-04, 25
          October 2021, <https://www.ietf.org/archive/id/draft-dong-
          teas-enhanced-vpn-vtn-scalability-04.txt>.

[I-D.ietf-ccamp-l1csm-yang]
          Lee, Y., Lee, K., Zheng, H., Dios, O. G. D., and D.
          Ceccarelli, "A YANG Data Model for L1 Connectivity Service
          Model (L1CSM)", Work in Progress, Internet-Draft, draft-
          ietf-ccamp-l1csm-yang-17, 10 July 2022,
          <https://www.ietf.org/archive/id/draft-ietf-ccamp-l1csm-
          yang-17.txt>.

[I-D.ietf-teas-actn-pm-telemetry-autonomics]
          Lee, Y., Dhody, D., Vilalta, R., King, D., and D.
          Ceccarelli, "YANG models for Virtual Network (VN)/TE
          Performance Monitoring Telemetry and Scaling Intent
          Autonomics", Work in Progress, Internet-Draft, draft-ietf-
          teas-actn-pm-telemetry-autonomics-09, 11 July 2022,
          <https://www.ietf.org/archive/id/draft-ietf-teas-actn-pm-
          telemetry-autonomics-09.txt>.

[I-D.ietf-teas-actn-vn-yang]
          Lee, Y., Dhody, D., Ceccarelli, D., Bryskin, I., and B. Y.

Yoon, "A YANG Data Model for Virtual Network (VN)
Operations", Work in Progress, Internet-Draft, draft-ietf-
teas-actn-vn-yang-15, 11 July 2022,
<https://www.ietf.org/archive/id/draft-ietf-teas-actn-vn-
yang-15.txt>.

[I-D.ietf-teas-enhanced-vpn]
Dong, J., Bryant, S., Li, Z., Miyasaka, T., and Y. Lee, "A
Framework for Enhanced Virtual Private Network (VPN+)
Services", Work in Progress, Internet-Draft, draft-ietf-
teas-enhanced-vpn-10, 6 March 2022,
<https://www.ietf.org/archive/id/draft-ietf-teas-enhanced-
vpn-10.txt>.

[I-D.ietf-teas-ietf-network-slice-nbi-yang]
Wu, B., Dhody, D., Rokui, R., Saad, T., and L. Han, "IETF
Network Slice Service YANG Model", Work in Progress,
Internet-Draft, draft-ietf-teas-ietf-network-slice-nbi-
yang-02, 11 July 2022, <https://www.ietf.org/archive/id/
draft-ietf-teas-ietf-network-slice-nbi-yang-02.txt>.

[I-D.ietf-teas-ietf-network-slices]
Farrel, A., Drake, J., Rokui, R., Homma, S., Makhijani,
K., Contreras, L. M., and J. Tantsura, "Framework for IETF
Network Slices", Work in Progress, Internet-Draft, draft-
ietf-teas-ietf-network-slices-14, 3 August 2022,
<https://www.ietf.org/archive/id/draft-ietf-teas-ietf-
network-slices-14.txt>.

[I-D.ietf-teas-rfc3272bis]
Farrel, A., "Overview and Principles of Internet Traffic
Engineering", Work in Progress, Internet-Draft, draft-
ietf-teas-rfc3272bis-20, 11 July 2022,
<https://www.ietf.org/archive/id/draft-ietf-teas-
rfc3272bis-20.txt>.

[I-D.ietf-teas-te-service-mapping-yang]
Lee, Y., Dhody, D., Fioccola, G., Wu, Q., Ceccarelli, D.,
and J. Tantsura, "Traffic Engineering (TE) and Service
Mapping YANG Data Model", Work in Progress, Internet-
Draft, draft-ietf-teas-te-service-mapping-yang-11, 11 July
2022, <https://www.ietf.org/archive/id/draft-ietf-teas-te-
service-mapping-yang-11.txt>.

[I-D.ietf-teas-yang-te]
Saad, T., Gandhi, R., Liu, X., Beeram, V. P., Bryskin, I.,
and O. G. D. Dios, "A YANG Data Model for Traffic
Engineering Tunnels, Label Switched Paths and Interfaces",
Work in Progress, Internet-Draft, draft-ietf-teas-yang-te-
30, 11 July 2022, <https://www.ietf.org/archive/id/draft-
ietf-teas-yang-te-30.txt>.

[RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed.,
and A. Bierman, Ed., "Network Configuration Protocol
(NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011,
<https://www.rfc-editor.org/info/rfc6241>.

[RFC7665] Halpern, J., Ed. and C. Pignataro, Ed., "Service Function

                    Chaining (SFC) Architecture", RFC 7665,
                    DOI 10.17487/RFC7665, October 2015,
                    <https://www.rfc-editor.org/info/rfc7665>.

        [RFC8040]   Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF
                    Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017,
                    <https://www.rfc-editor.org/info/rfc8040>.

        [RFC8299]   Wu, Q., Ed., Litkowski, S., Tomotaki, L., and K. Ogaki,
                    "YANG Data Model for L3VPN Service Delivery", RFC 8299,
                    DOI 10.17487/RFC8299, January 2018,
                    <https://www.rfc-editor.org/info/rfc8299>.

        [RFC8309]   Wu, Q., Liu, W., and A. Farrel, "Service Models
                    Explained", RFC 8309, DOI 10.17487/RFC8309, January 2018,
                    <https://www.rfc-editor.org/info/rfc8309>.

        [RFC8453]   Ceccarelli, D., Ed. and Y. Lee, Ed., "Framework for
                    Abstraction and Control of TE Networks (ACTN)", RFC 8453,
                    DOI 10.17487/RFC8453, August 2018,
                    <https://www.rfc-editor.org/info/rfc8453>.

        [RFC8454]   Lee, Y., Belotti, S., Dhody, D., Ceccarelli, D., and B.
                    Yoon, "Information Model for Abstraction and Control of TE
                    Networks (ACTN)", RFC 8454, DOI 10.17487/RFC8454,
                    September 2018, <https://www.rfc-editor.org/info/rfc8454>.

        [RFC8466]   Wen, B., Fioccola, G., Ed., Xie, C., and L. Jalil, "A YANG
                    Data Model for Layer 2 Virtual Private Network (L2VPN)
                    Service Delivery", RFC 8466, DOI 10.17487/RFC8466, October
                    2018, <https://www.rfc-editor.org/info/rfc8466>.

        [RFC8639]   Voit, E., Clemm, A., Gonzalez Prieto, A., Nilsen-Nygaard,
                    E., and A. Tripathy, "Subscription to YANG Notifications",
                    RFC 8639, DOI 10.17487/RFC8639, September 2019,
                    <https://www.rfc-editor.org/info/rfc8639>.

        [RFC8640]   Voit, E., Clemm, A., Gonzalez Prieto, A., Nilsen-Nygaard,
                    E., and A. Tripathy, "Dynamic Subscription to YANG Events
                    and Datastores over NETCONF", RFC 8640,
                    DOI 10.17487/RFC8640, September 2019,
                    <https://www.rfc-editor.org/info/rfc8640>.

        [RFC8641]   Clemm, A. and E. Voit, "Subscription to YANG Notifications
                    for Datastore Updates", RFC 8641, DOI 10.17487/RFC8641,
                    September 2019, <https://www.rfc-editor.org/info/rfc8641>.

        [RFC8650]   Voit, E., Rahman, R., Nilsen-Nygaard, E., Clemm, A., and
                    A. Bierman, "Dynamic Subscription to YANG Events and
                    Datastores over RESTCONF", RFC 8650, DOI 10.17487/RFC8650,
                    November 2019, <https://www.rfc-editor.org/info/rfc8650>.

Authors' Addresses

    Daniel King
    Old Dog Consulting
    Email: daniel@olddog.co.uk

John Drake
Juniper Networks
Email: jdrake@juniper.net

Haomian Zheng
Huawei Technologies
Email: zhenghaomian@huawei.com

Adrian Farrel
Old Dog Consulting
Email: adrian@olddog.co.uk