OPSAWG Working Group Internet-Draft Intended status: Standards Track Expires: 30 December 2023 Y. Liu ZTE 28 June 2023

Export of Network Resource Partition (NRP) Information in IP Flow Information Export (IPFIX) draft-liu-opsawg-ipfix-network-slice-00

#### Abstract

This document introduces new IP Flow Information Export (IPFIX)
Information Elements Element to identify report the Network Resource
Partition (NRP)

over which that the network slice traffican observed flow is related with forwarded.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at https://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 30 December 2023.

## Copyright Notice

Copyright (c) 2023 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (https://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

## Table of Contents

1.	Introduction	2
2.	Terminology	2
3.	New IPFIX Information Element	3
4.	Usecases	3
5.	IANA Considerations	3
6.	Security Considerations	4
7.	References	4

**Commenté [BMI1]:** I know the file name is not important, but this draft is about NRPs.

#### Commenté [BMI2]: Only one is defined

**Commenté [BMI3]:** To avoid that this is interpreted as the slice identification itself can be inferred from the NRP-ID.

Please remember that NRP is an optional component + many slices can use the same NRP + connectivity constructs of a slice can use distinct NRPs.

7.1.	Normative	Re	efe:	ren	ce	S										4
7.2.	Informativ	те	Re	fer	en	ces	3									4
Author's	s Address															

#### 1. Introduction

The definition of the IETF Network Slice, a framework, and the general principles

of network slicing in the IETF context are specifieddiscussed\_in
[I-D.ietf-teas-ietf-network-slices]. As described in
[I-D.ietf-teas-ietf-network-slices], an IETF Network SliceService
enables

connectivity between a set of Service Demarcation Points (SDPs) with specific Service Level Objectives (SLOs) and Service Level Expectations (SLEs) over a common underlay network. To meet the connectivity and performance requirements, network slice services needs map to be mapped to a Network Resource Partitions (NRPs). An NRP is

a collection of resources (bufferage, queuing, scheduling, etc.) in the underlay network.

As introduced in [I-D.ietf-teas-ns-ip-mpls], each an NRP can be idenified using a unique NRP-ID in control plane and management plane. And tAhe NRP-ID may also be encapsulated in data packets to guide the NRP-specific packet forwarding.

This document defines new IPFIX Information Elements within the "IPFIX Information Elements" <a href="registry">registry</a> [RFC7012] to <a href="redeted-tidentsty-report">identify</a> report the <a href="Network Resource Partition">Network Resource Partition</a> (NRP) that <a href="the-network slice traffic is related withis associated with a Flow.

## 2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119][RFC8174] when, and only when, they appear in all capitals, as shown here.

This document uses the IPFIX-specific terminology (Information Element, Template, Collector, Data Record, Flow Record, Exporting Process, Collecting Process, etc.) defined in Section 2 of [RFC7011].

As in [RFC7011], these IPFIX-specific terms have the first letter of a word capitalized.

# 3. New IPFIX Information Element

This section defines and describes the the following new IPFIX  $IE_{\overline{+}\underline{:}}$ 

- \* Name: nrpIdentifierNRPIdentifier
- \* ElementID: TBD1
- \* Description: The NRP ID as defined in [I-D.ietf-teas-ns-ip-mpls].
- \* Abstract Data Type: unsigned32
- \* Data Type Semantics: identifier

Commenté [BMI4]: Please remember that NRP is an optional component

Commenté [BMI5]: I'm afraid this is too brief.

**Commenté [BMI6]:** This ID is defined ins sevral I-Ds. Please check

https://datatracker.ietf.org/doc/html/draft-boucadair-teasietf-slicing-overview-01#name-nrp-6

Where an implementation has to look to export the ID? These matters are not defined in ip-mpls spec.

**Commenté [BMI7]:** Please note that some variants do not use a 32-bit identifier. There is a need to sync and have consistent encoding. This is beyond this draft.

# 4. Use <del>cases</del>Cases

A typical use\_case scenario is to monitoring the network slice traffic that is forwarded based on NRP specific resource-aware segments [I-D.ietf-spring-resource-aware-segments] that operate over SR-MPLS or SRv6 data planesdataplanes. By looking at the SID itself, it is not always

clear as to which NRP it belongs.

Another use\_case is the monitoring of the network slice traffic whose NRP-ID is encapsulated in data packet to determine the Network Resource Partition Per Hop Behavior.

By using nrpIdentifierNRPIdentifier (TBD1), and some counters information, it is possible to answer the following questions (amongst others):

- \* How many packets are forwarded or dropped?
- \* If dropped, for which reasons?
- \* Which NRP is the traffic related with?
- 5. IANA Considerations

This document requests IANA to add a new IE to the "IPFIX Information Elements" registry [RFC7012] available at [IANA-IPFIX].

ElementID	Name	Reference
TBD1	NRP-ID	This document

6. Security Considerations

There exists no significant extra security considerations regarding the allocation of these new IPFIX IEs compared to [RFC7012].

- 7. References
- 7.1. Normative References

[I-D.ietf-teas-ns-ip-mpls]

Saad, T., Beeram, V. P., Dong, J., Wen, B., Ceccarelli, D., Halpern, J. M., Peng, S., Chen, R., Liu, X., Contreras, L. M., Rokui, R., and L. Jalil, "Realizing Network Slices in IP/MPLS Networks", Work in Progress, Internet-Draft, draft-ietf-teas-ns-ip-mpls-02, 13 March 2023, <a href="https://datatracker.ietf.org/doc/html/draft-ietf-teas-ns-ip-mpls-02">https://datatracker.ietf.org/doc/html/draft-ietf-teas-ns-ip-mpls-02</a>.

**Commenté [BMI8]:** The use cases are similar to the use of other IEs.

I'm not sure there is a value in having this section.

## 7.2. Informative References

## [I-D.ietf-spring-resource-aware-segments]

Dong, J., Bryant, S., Miyasaka, T., Zhu, Y., Qin, F., Li, Z., and F. Clad, "Introducing Resource Awareness to SR Segments", Work in Progress, Internet-Draft, draft-ietf-spring-resource-aware-segments-07, 31 May 2023, <a href="https://datatracker.ietf.org/doc/html/draft-ietf-spring-resource-aware-segments-07">https://datatracker.ietf.org/doc/html/draft-ietf-spring-resource-aware-segments-07</a>.

## [I-D.ietf-teas-ietf-network-slices]

Farrel, A., Drake, J., Rokui, R., Homma, S., Makhijani, K., Contreras, L. M., and J. Tantsura, "A Framework for IETF Network Slices", Work in Progress, Internet-Draft, draft-ietf-teas-ietf-network-slices-21, 15 June 2023, <a href="https://datatracker.ietf.org/doc/html/draft-ietf-teas-ietf-network-slices-21">https://datatracker.ietf.org/doc/html/draft-ietf-teas-ietf-network-slices-21</a>.

## [IANA-IPFIX]

"IANA, "IP Flow Information Export (IPFIX) Entities"", <a href="https://www.iana.org/assignments/ipfix/ipfix.xhtml">https://www.iana.org/assignments/ipfix/ipfix.xhtml</a>.

## Author's Address

Yao Liu ZTE Nanjing China Email: liu.yao71@zte.com.cn