

BESS Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: 23 January 2025

V. Govindan  
M. Mudigonda  
A. Sajassi  
Cisco Systems  
G. Mirsky  
Ericsson  
D. Eastlake  
Independent  
22 July 2024

EVPN Network Layer Fault Management  
draft-ietf-bess-evpn-bfd-07

Abstract

This document specifies **proactive, in-band network layer OAM mechanisms** to detect loss of continuity faults that affect unicast and multi-destination paths (used by Broadcast, Unknown Unicast, and Multicast traffic) in an Ethernet VPN (**EVPN, RFC 7432bis**) network. The mechanisms specified in the **draft-document** use the widely adopted Bidirectional Forwarding Detection (RFC 5880) protocol **and other protocols as necessary**.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 23 January 2025.

Copyright Notice

Copyright (c) 2024 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are

- Commenté [BMI1]:** I fail to find this defined in RFC7432 or 7432bis. I think that you are referring to the layering in 2.1 of 9062.
- I'm not asking to make a change here, but for the readers convenience, you can consider adding a sentence in the introduction about 2.1 of 9062 to poision the layer you are considering.
- Commenté [BMI2]:** This is the only mention in the document. I would delete or elaborate on this aspect in the main text.
- Commenté [BMI3]:** Any reason why the bis is cited explicitly here? Are there parts of the spec that are not applicable to 7432?  
Please clarify in the doc.
- Commenté [BMI4]:** Unless you cite those, I'm not sure this adds much to the readers.

provided without warranty as described in the Revised BSD License.

## Table of Contents

1. Introduction . . . . .	2
1.1. Terminology . . . . .	3
2. Scope of this Document . . . . .	4
3. Motivation for Running BFD at the EVPN Network Layer . . . . .	5
4. Fault Detection for Unicast Traffic . . . . .	5
5. Fault Detection for BUM Traffic . . . . .	6
5.1. Ingress Replication . . . . .	6
5.2. P2MP Tunnels (Label Switched Multicast) . . . . .	7
6. BFD Packet Encapsulation . . . . .	8
6.1. MPLS Encapsulation . . . . .	8
6.1.1. Unicast MPLS Encapsulation . . . . .	8
6.1.2. MPLS Ingress Replication . . . . .	10
6.1.3. MPLS LSM (Label Switched Multicast, P2MP) . . . . .	10
6.2. VXLAN Encapsulation . . . . .	10
6.2.1. Unicast VXLAN Encapsulation . . . . .	10
6.2.2. VXLAN Ingress Replication . . . . .	12
6.2.3. VXLAN P2MP . . . . .	12
7. Scalability Considerations . . . . .	12
8. IANA Considerations . . . . .	12
8.1. Pseudowire Associated Channel Type . . . . .	12
8.2. BFD Discriminator Attribute Mode . . . . .	13
9. Security Considerations . . . . .	13
10. Normative References . . . . .	13
11. Informative References . . . . .	15
Acknowledgements . . . . .	16
Authors' Addresses . . . . .	16

## 1. Introduction

[RFC9062] outlines the OAM requirements of Ethernet VPN networks (EVPN) [rfc7432bis]. This document specifies mechanisms for proactive fault detection at the network (overlay) layer of EVPN, that is to say between PEs (Provider Edge (PE) nodes). The mechanisms proposed-specified in this document use the widely adopted

Bidirectional

Forwarding Detection (BFD) [RFC5880] protocol, which is a lightweight protocol using fixed length messages suitable for implementation in hardware, and other protocols as necessary. EVPN restoration mechanisms (redundancy and recovery/convergence) are the most logical clients for BFD sessions specified herein.

EVPN fault detection mechanisms need to consider unicast traffic separately from Broadcast, Unknown Unicast, and Multicast (BUM) traffic since they map to different Forwarding Equivalency Classes (FECs) in EVPN. Hence this document proposes-specifies somewhat different

continuity fault detection mechanisms depending on the type of traffic and the type of tunnel used as follows:

\* Using BFD [RFC5880] for unicast traffic and BUM traffic via Multipoint to Point (MP2P) tunnels.

\* Using BFD Multipoint [RFC8562] or BFD Multipoint Active Tails

Commenté [BMI5]: "networks" is redundant with "N"

Commenté [BMI6]: To be consistent in the doc about expanding terms.

Commenté [BMI7]: Wouldn't you need 5881-5884 as well?

Commenté [BMI8]: Is this really needed?

Commenté [BMI9]: I don't parse what is meant here as "client" has a specific meaning in BFD.

Commenté [BMI10]: Can we back this with a requirement in rfc9062?

Commenté [BMI11]: ?

Commenté [BMI12]: Pointing to 2.3 of 9062 would be helpful to digest these cases.

[RFC8563] [ietf-mp-ls-p2mp-bfd] for BUM traffic via a Point to Multipoint (P2MP) tunnel.

Packet loss and packet delay measurement are out of scope ~~for this document~~. See [ietf-bmwg-evpn-test] for EVPN benchmarking guidance.

**Commenté [BMI13]:** Any specific need to cite this? This document is tagged with "(IESG: Dead)"

I would remove this citation unless we explicit which parts of that doc are relevant here.

### 1.1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

The following acronyms are used in this document.

BFD - Bidirectional Forwarding Detection ~~[RFC5880]~~

BUM - Broadcast, ~~Unknown-unknown Unicast~~unicast, and ~~Multicast~~multicast

**Commenté [BMI14]:** Per 7432

CC - Continuity Check

CE - Customer Edge

EVI - EVPN Instance

EVPN - Ethernet VPN ~~[rfc7432bis]~~

FEC - Forwarding Equivalency Class

GAL - Generic Associated Channel Label [RFC5586]

**Commenté [BMI15]:** This is used only once in the doc.

LSM - Label Switched Multicast ~~(P2MP)~~

LSP - Label Switched Path

~~MP2MP~~ - Multi-~~P~~oint-to-Multi-~~P~~oint

**Commenté [BMI16]:** Used only once in the doc.

MP2P - Multipoint to Point~~Multi-Point-to-Point~~

**Commenté [BMI17]:** For consistency with 9062

OAM - Operations, Administration, and Maintenance

P2MP - Point to Multipoint~~Point-to-Multi-Point (LSM)~~

**Commenté [BMI18]:** For consistency with 9062

P2P - Point to Point

PE - Provider Edge ~~node~~

**Commenté [BMI19]:** Please check rfc4026

VXLAN - Virtual eXtensible Local Area Network ~~[RFC7348]~~

### 2. Scope of this Document

This document specifies ~~BFD~~-based mechanisms for proactive fault detection for EVPN as specified in [rfc7432bis] and also for EVPN using VXLAN encapsulation [RFC8365]. Specifically, the document ~~it~~ covers the following:

- \* Unicast traffic using Point-to-Point (P2P) and Multi-Point-to-Point (MP2P) tunnels.
- \* BUM traffic using ingress replication via Point-to-Point (P2P) and Multi-Point-to-Point (MP2P) tunnels.
- \* BUM traffic using Point-to-Multi-Point (P2MP) tunnels (Label Switched Multicast (LSM)).
- \* MPLS and VXLAN encapsulation.

This document does not discuss BFD mechanisms for:

- \* The PBB-EVPN [RFC7623] EVPN variant. It is intended to address this in future versions of this document.
- \* Integrated Routing and Bridging (IRB) solution based on EVPN [RFC9135]. It is intended to address this in future versions of this document.
- \* EVPN using other encapsulations such as NVGRE or MPLS over GRE [RFC8365].
- \* BUM traffic using MP2MP tunnels.

This document specifies procedures for BFD asynchronous mode. BFD demand mode is outside the scope of this specification except as it is used in [RFC8563]. The use of the BFD Echo function is outside the scope of this specification.

### 3. Motivation for Running BFD at the EVPN Network Layer

The choice of running BFD at the network layer of the OAM model for EVPN [RFC9062] was made after considering the following:

- \* In addition to detecting link failures in the an EVPN network, BFD sessions at the network layer can be used to monitor the successful setup, such as label programming, of MP2P and P2MP EVPN tunnels transporting Unicast and BUM traffic. The scope of reachability detection covers the ingress and the egress EVPN ~~PEs (Provider Edge) nodes~~ and the network connecting them.
- \* Monitoring a representative set of ~~path(s)~~ paths or a particular path among multiple paths available between two EVPN ~~PEs nodes~~ could be done by exercising entropy mechanisms such as ~~entropy labels, when they are used, or~~ VXLAN source port ~~numbers~~. However, paths that cannot be realized by entropy variations cannot be monitored. The fault monitoring requirements outlined by [RFC9062] are addressed by the mechanisms ~~proposed-defined-by-in this draftdocument~~.

BFD testing between EVPN ~~PEs nodes~~ does not guarantee that the EVPN service is functioning. (This can be, e.g., monitored at the service level, that is CE (Customer Edge) to CE.) For example, an egress ~~EVPN PE/EVPN-PE~~ could understand EVPN labeling received but could switch data to an

**Commenté [BMI20]:** I guess you meant other documents?

**Commenté [BMI21]:** Is it the intent to cover this here or leave this to a separate document?

I would simply delete the sentence

**Commenté [BMI22]:** May be call out specific sections, e.g., 5.2 of 8365?

**Commenté [BMI23]:** Please clarify as I don't see any BFD discussion in that RFC.

**Commenté [BMI24]:** This smells like an operational recommendation, while I think that "choice" is up to the operators. The spec should reason about describing how BFD can be used + provided features.

I would reword accordingly.

**Commenté [BMI25]:** Consider adding pointers/RFCs.

**Commenté [BMI26]:** Which specific requirements are you referring to? Please explicit it in the text. Thanks.

**Commenté [BMI27]:** Please point to th 9062 for the service layer matters.

**Commenté [BMI28]:** For consistency with rfc9062

**Commenté [BMI29]:** What does that mean technically? Maintain a state?

Please reword.

incorrect interface. However, BFD testing in the EVPN Network Layer does provide additional confidence that data transported using those tunnels will reach the expected egress node. When BFD testing in the EVPN overlay fails, that can be used as an indication of a Loss-of-Connectivity defect in the EVPN underlay that would cause EVPN service failure.

#### 4. Fault Detection for Unicast Traffic

The mechanisms specified in BFD for MPLS Label Switched Paths (LSPs) [RFC5884] [RFC7726] and BFD for VXLAN [RFC8971] are, except as otherwise provided herein, applied to test loss of continuity for unicast EVPN traffic. The MPLS control plane can be verified against the data plane as specified in [RFC8029]. When the discriminators required for de-multiplexing the BFD sessions are not otherwise available, they can be advertised through BGP using the BFD Discriminator Attribute [RFC9026]. Discriminators are needed for MPLS since the label stack does not contain enough information to identify the sender of thea packet.

The usage of MPLS entropy labels [RFC6790] or various VXLAN source Portport numbers takes care of the requirement to monitor various paths of the multi-path server layer network. Each unique realizable path between the participating PEs routers MAY be monitored separately when such entropy is used. At least one path of multi-path connectivity between two PEs routers MUST be tracked with BFD, but in that case the granularity of fault-detection will be coarser.

To support unicast fault management to a PE-node, that PE MUST allocate or be configured with a BFD discriminator to be used as Your

Discriminator (Section 4.1 of [RFC5880]) in the BFD messages to it. By default, it-a PE advertises this discriminator with BGP using the BFD Discriminator Attribute [RFC9026] with BFD Mode TBD2 in an EVPN Ethernet Autodiscovery Route [rfc7432bis] or MAC/IP Advertisement Route as long as it advertises it in at least one route. It-A PE extracts its peer's discriminator from such an attribute. However, these discriminators MAY be exchanged out-of-band or through some other mechanism outside the scope of this document.

Once a PE knows a unicast route and a discriminator for another PE and if it is the higher priority of the two PEs to initiate BFD and is configured to do so, it endeavors to bring UP and maintain a BFD session to that other PE.

Once the BFD session is UP, the ends of the BFD session MUST NOT change the local discriminator values of the BFD Control packets they generate, unless they first bring down the session as specified in [RFC5884]. The BFD session is brought down if a PE is no longer configured to maintain it or if a route and discriminator are no longer available.

a mis en forme : Surlignage

Commenté [BMI30]: Such as?

I wonder if you can cite an example of such case.

Commenté [BMI31]: Not sure what is meant here. Do you mean "varying the source port number"?

Commenté [BMI32]: Not sure what is meant here. Please reword. Thanks.

Commenté [BMI33]: Which server? Do you meant service layer? If son, why network is also cited?

Please clarify in the text.

Commenté [BMI34]: Not sure the normative language is justified here. Please check

Commenté [BMI35]: This does not "proactively" help detecting loss of other available paths that might be used to forward data.

Commenté [BMI36]: Can we cite rfc9127 here as an example?

Commenté [BMI37]: This text and the sentence right after smell like a SHOULD. Wonder if it is clearer to use a normative language here.

Commenté [BMI38]: Initiate BFD session?

a mis en forme : Surlignage

Commenté [BMI39]: I guess your are referring to this part of Section 7 of 5884:

"Note that once the BFD session for the MPLS LSP is UP, either end of the BFD session MUST NOT change the source IP address and the local discriminator values of the BFD Control packets it generates, unless it first brings down the session."

I would add an explicit pointer to that specific section.

Also, the use of the normative language here is redundant with the first sentence in this section:

" The mechanisms specified in BFD for MPLS LSPs [RFC5884] [RFC7726] and BFD for VXLAN [RFC8971] are ... applied to test loss of continuity for unicast EVPN traffic. "

## 5. Fault Detection for BUM Traffic

Section 5.1 ~~below~~ discusses BUM traffic fault detection for P2P and MP2P tunnels using ingress replication and Section 5.2 discusses such fault detection for P2MP tunnels.

### 5.1. Ingress Replication

Ingress replication uses separate P2P or MP2P tunnels for transporting BUM traffic from the ingress PE (head) to a set of one or more egress PEs (tails). The fault detection mechanism specified by this document takes advantage of the fact that the head makes a unique copy for each tail.

**Commenté [BMI40]:** Any reference to cite here? Maybe rfc7432#section-11?

a mis en forme : Surlignage

Another key aspect to be considered in EVPN is the advertisement of the Inclusive Multicast Ethernet Tag Route [\[rfc7432bis\]](#). The BUM traffic flows from a head node to a particular tail only after the head receives such an inclusive multicast route from the tail. This route contains the BUM EVPN MPLS label (downstream allocated) corresponding to the MP2P tunnel for MPLS encapsulation and contains the IP address of the PE originating the inclusive multicast route for use in VXLAN encapsulation. It also contains a BFD Discriminator Attribute [\[RFC9026\]](#) with BFD Mode TDB4 giving the BFD discriminator that will be used by the tail. This is the P2P mode BFD Discriminator Attribute since a P2P BFD session is used in both the P2P and MP2P cases with ingress replication.

**Commenté [BMI41]:** Please help readers and cite the exact section to look at. Thanks

**Commenté [BMI42]:** Internal consistency: Previous sections state that 9026 is not mandatory and other mechanisms can be used. This text seems to assume that it is always used.

There MAY exist multiple BFD sessions between a head PE and an individual tail due to (1) the usage of MPLS entropy labels [\[RFC6790\]](#) or VXLAN source port numbers for an inclusive multicast FEC and (2) due to multiple MP2P tunnels indicated by different tail labels for MPLS or different IP addresses for VXLAN encapsulation. If a PE is configured to do so, once a PE knows a multicast route and discriminator for another PE it endeavors to bring UP and maintain a BFD session to that other PE. Once a BFD session for a path is UP, the ends of the BFD session MUST NOT change the local discriminator values of the BFD Control packets they generate, unless they first bring down the session as specified in [\[RFC5884\]](#). The BFD session is brought down if a PE is no longer configured to maintain it or if a route and discriminator are no longer available.

**Commenté [BMI43]:** Not sure the normative language is justified here.

### 5.2. P2MP Tunnels (Label Switched Multicast)

Fault detection for BUM traffic distributed using a P2MP tunnel uses BFD Multipoint Active Tails [\[RFC8563\]](#) in one of the three methods providing head notification. Which method is used depends on the local configuration. Sections 5.2.2 and 5.2.3 of [\[RFC8563\]](#) describe two of these methods ("Head Notification and Tail Solicitation with Multipoint Polling" and "Head Notification with Composite Polling"). The third method ("Head Notification without Polling") is touched on in Section 5.2.1 of [\[RFC8563\]](#) and fully specified in [\[ietf-mpls-p2mp-bfd\]](#). All ~~three of these~~ three modes assume the existence of a unicast return path from each tail to the head. In addition, Head Notification with Composite Polling assumes a head to tail unicast path disjoint from the path used by the P2MP tunnel.

a mis en forme : Surlignage

The BUM traffic flows from a head node to the tails after the head transmits an Inclusive Multicast Tag Route [rfc7432bis] if local configuration so directs. This route contains the BUM EVPN MPLS label (upstream allocated) corresponding to the P2MP tunnel for MPLS encapsulation. The route also includes a BFD Discriminator Attribute [RFC9026] with the BFD Mode set to 1 and a Source IP Address TLV, which gives the address associated with the MultiPoint Head of the P2MP session. This BFD discriminator advertised by the head in the Inclusive Multicast route or otherwise configured at or communicated to a tail MUST be used in any reverse BFD control message as Your Discriminator so the head can determine the tail of which P2MP BFD session is responding. If a PE is configured to do so, once a PE knows a

P2MP multicast route and the needed discriminators, it brings UP and maintains a P2MP BFD active tails session to the tails. The BFD session is brought down if a PE is no longer configured to maintain it or the multicast route and discriminators are no longer available.

For MPLS encapsulation of the head to tails BFD, Label Switched Multicast is used. For VXLAN encapsulation, BFD is delivered to the tails through underlay multicast using an outer multicast IP address.

## 6. BFD Packet Encapsulation

The following subsections below discuss describe the MPLS and VXLAN encapsulations of BFD for EVPN network layer fault management.

### 6.1. MPLS Encapsulation

This section describes use of the Generic Associated Channel Label (GAL) for BFD encapsulation in ~~MPLS-MPLS~~-based EVPN network layer fault management. Since the use of BFD specified in this document is encapsulated between PEs, it is treated as single hop and uses the single hop BFD port number [RFC5881].

#### 6.1.1. Unicast MPLS Encapsulation

As shown in Figure 1, ~~the-a~~ packet initially contains the following labels: LSP label (transport), the optional entropy label, the EVPN Unicast label, and then the Generic Associated Channel label with the G-ACh type set to TBD1. The G-ACh payload of the packet MUST contain the destination ~~L2-Layer 2~~ header (in overlay space) followed by the

IP header that encapsulates the BFD packet. The MAC address of the inner packet is used to validate the <EVI, MAC> in the receiving node.

\* The destination MAC address MUST be the dedicated unicast MAC address TBD3 (see Section 8) or the MAC address of the destination PE.

\* The destination IP address MUST be 127.0.0.1/32 for IPv4 [~~RFC1812~~] or ::1/128 for IPv6 [RFC4291].

\* The destination UDP port number MUST be 3784 [RFC5881].

Commenté [BMI44]: Idem as a previous comment

Commenté [BMI45]: What does mean initially here?

Commenté [BMI46]: Which one? Src?

a mis en forme : Surlignage

Commenté [BMI47]: There is no such requested value in IANA section

Commenté [BMI48]: I would use rfc6890, instead

- \* The source UDP port number MUST be in the range 49152 through 65535.
- \* The discriminator values for BFD are obtained as discussed in Section 4.
- \* IPv4 TTL or IPv6 Hop Limit MUST be set to 255 according to [RFC5082].




Figure 1: MPLS Unicast Encapsulation

6.1.2. MPLS Ingress Replication

The ~~A~~ packet initially contains the following labels: LSP label (transport), optionally the entropy label, the BUM label, and the split horizon label [rfc7432bis] (where applicable). The G-ACh type is set to TBD1. The G-ACh payload of the packet is as described in Section 6.1.1 except that the destination MAC address is the dedicated multicast MAC address TBD2.

Commenté [BMI49]: Idem as above.

Commenté [BMI50]: But TBD2 is about "P2P BFD Session". Please double check.

a mis en forme : Surlignage



6.1.3. MPLS LSM (Label Switched Multicast, P2MP)

The encapsulation is the same as in Section 6.1.2 for ingress replication except that the transport label identifies the P2MP tunnel, in effect the set of tail PEs, rather than identifying a single destination PE at the end of an MP2P tunnel.


6.2. VXLAN Encapsulation

This section describes the use of the VXLAN [RFC7348] [RFC8365] for BFD encapsulation in VXLAN based EVPN fault management.

6.2.1. Unicast VXLAN Encapsulation

Figure 2 below shows the unicast VXLAN encapsulation on the wire on an Ethernet link. The outer and inner IP headers have a unicast source and destination IP addresses that are the addresses of the PEs that are the BFD message source and destination. If the BFD source has multiple IP addresses, entropy MAY be further obtained by using any of those addresses assuming the source is prepared for responses directed to the IP address used.

- \* The outer destination UDP port number MUST be 4789 [RFC7348].
- \* The inner destination UDP port number MUST be 3784 [RFC5881].
- \* The outer and inner source UDP port numbers MUST each be in the range 49152 through 65535.
- \* The inner destination MAC address MUST be the MAC address of the destination PE or the dedicated unicast MAC TBD3 (see Section 8).



a mis en forme : Surlignage

Commenté [BMI51]: Independent of the address family?

Commenté [BMI52]: There is no such requested value in IANA section



slowing down or speeding up BFD timer values can be used by an administrator or a network management entity to maintain the overhead incurred due to fault monitoring at an acceptable level.

Commenté [BM154]: Do you mean increase/decrease? If so, please reword.

## 8. IANA Considerations

~~The following IANA Actions are requested.~~

### 8.1. Pseudowire Associated Channel Type

IANA is requested to assign a channel type from the "Pseudowire Associated Channel Types" registry in [RFC4385] as follows.

Value	Description	Reference
TBD1	BFD-EVPN OAM	[this document]

### 8.2. BFD Discriminator Attribute Mode

IANA is requested to assign a value from the IETF Review range in the BFD Mode sub-registry on the Border Gateway Protocol Parameters Registry web page as follows:

Value	Description	Reference
TBD2	P2P BFD Session	[this document]

## 9. Security Considerations

Security considerations discussed in [RFC5880], [RFC5883], and [RFC8029] apply.

MPLS security considerations [RFC5920] apply to BFD Control packets encapsulated in a MPLS label stack. When ~~BPD-BFD~~ Control packets are routed, the authentication considerations discussed in [RFC5883] should be followed.

VXLAN BFD security considerations in [RFC8971] apply to BFD packets encapsulate in VXLAN.

## 10. Normative References

- [ietf-mppls-p2mp-bfd]  
Mirsky, G., Mishra, G., and D. Eastlake, "BFD for Multipoint Networks over Point-to-Multi-Point MPLS LSP", December 2022, <<https://datatracker.ietf.org/doc/draft-ietf-mppls-p2mp-bfd/>>.
- [rfc7432bis]  
Sajassi, A., Burdet, LA., Drake, J., and J. Rabadan, "BGP MPLS-Based Ethernet VPN", 13 March 2023, <<https://datatracker.ietf.org/doc/draft-ietf-bess-rfc7432bis/>>.
- [RFC1812] Baker, F., Ed., "Requirements for IP Version 4 Routers", RFC 1812, DOI 10.17487/RFC1812, June 1995, <<https://www.rfc-editor.org/info/rfc1812>>.

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC4291] Hinden, R. and S. Deering, "IP Version 6 Addressing Architecture", RFC 4291, DOI 10.17487/RFC4291, February 2006, <<https://www.rfc-editor.org/info/rfc4291>>.
- [RFC4385] Bryant, S., Swallow, G., Martini, L., and D. McPherson, "Pseudowire Emulation Edge-to-Edge (PWE3) Control Word for Use over an MPLS PSN", RFC 4385, DOI 10.17487/RFC4385, February 2006, <<https://www.rfc-editor.org/info/rfc4385>>.
- [RFC5586] Bocci, M., Ed., Vigoureux, M., Ed., and S. Bryant, Ed., "MPLS Generic Associated Channel", RFC 5586, DOI 10.17487/RFC5586, June 2009, <<https://www.rfc-editor.org/info/rfc5586>>.
- [RFC5880] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD)", RFC 5880, DOI 10.17487/RFC5880, June 2010, <<https://www.rfc-editor.org/info/rfc5880>>.
- [RFC5881] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD) for IPv4 and IPv6 (Single Hop)", RFC 5881, DOI 10.17487/RFC5881, June 2010, <<https://www.rfc-editor.org/info/rfc5881>>.
- [RFC5883] Katz, D. and D. Ward, "Bidirectional Forwarding Detection (BFD) for Multihop Paths", RFC 5883, DOI 10.17487/RFC5883, June 2010, <<https://www.rfc-editor.org/info/rfc5883>>.
- [RFC5884] Aggarwal, R., Kompella, K., Nadeau, T., and G. Swallow, "Bidirectional Forwarding Detection (BFD) for MPLS Label Switched Paths (LSPs)", RFC 5884, DOI 10.17487/RFC5884, June 2010, <<https://www.rfc-editor.org/info/rfc5884>>.
- [RFC6790] Kompella, K., Drake, J., Amante, S., Henderickx, W., and L. Yong, "The Use of Entropy Labels in MPLS Forwarding", RFC 6790, DOI 10.17487/RFC6790, November 2012, <<https://www.rfc-editor.org/info/rfc6790>>.
- [RFC7348] Mahalingam, M., Dutt, D., Duda, K., Agarwal, P., Kreeger, L., Sridhar, T., Bursell, M., and C. Wright, "Virtual eXtensible Local Area Network (VXLAN): A Framework for Overlaying Virtualized Layer 2 Networks over Layer 3 Networks", RFC 7348, DOI 10.17487/RFC7348, August 2014, <<https://www.rfc-editor.org/info/rfc7348>>.
- [RFC7726] Govindan, V., Rajaraman, K., Mirsky, G., Akiya, N., and S. Aldrin, "Clarifying Procedures for Establishing BFD Sessions for MPLS Label Switched Paths (LSPs)", RFC 7726, DOI 10.17487/RFC7726, January 2016, <<https://www.rfc-editor.org/info/rfc7726>>.
- [RFC8029] Kompella, K., Swallow, G., Pignataro, C., Ed., Kumar, N., Aldrin, S., and M. Chen, "Detecting Multiprotocol Label Switched (MPLS) Data-Plane Failures", RFC 8029,

DOI 10.17487/RFC8029, March 2017,  
<<https://www.rfc-editor.org/info/rfc8029>>.

- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8365] Sajassi, A., Ed., Drake, J., Ed., Bitar, N., Shekhar, R., Uttaro, J., and W. Henderickx, "A Network Virtualization Overlay Solution Using Ethernet VPN (EVPN)", RFC 8365, DOI 10.17487/RFC8365, March 2018, <<https://www.rfc-editor.org/info/rfc8365>>.
- [RFC8562] Katz, D., Ward, D., Pallagatti, S., Ed., and G. Mirsky, Ed., "Bidirectional Forwarding Detection (BFD) for Multipoint Networks", RFC 8562, DOI 10.17487/RFC8562, April 2019, <<https://www.rfc-editor.org/info/rfc8562>>.
- [RFC8563] Katz, D., Ward, D., Pallagatti, S., Ed., and G. Mirsky, Ed., "Bidirectional Forwarding Detection (BFD) Multipoint Active Tails", RFC 8563, DOI 10.17487/RFC8563, April 2019, <<https://www.rfc-editor.org/info/rfc8563>>.
- [RFC9026] Morin, T., Ed., Kebler, R., Ed., and G. Mirsky, Ed., "Multicast VPN Fast Upstream Failover", RFC 9026, DOI 10.17487/RFC9026, April 2021, <<https://www.rfc-editor.org/info/rfc9026>>.

## 11. Informative References

- [ietf-bmwg-evpntest] Jacob, S. and K. Tiruveedhula, "Benchmarking Methodology for EVPN and PBB-EVPN", June 2021, <<https://datatracker.ietf.org/doc/draft-ietf-bmwg-evpntest/>>.
- [RFC5082] Gill, V., Heasley, J., Meyer, D., Savola, P., Ed., and C. Pignataro, "The Generalized TTL Security Mechanism (GTSM)", RFC 5082, DOI 10.17487/RFC5082, October 2007, <<https://www.rfc-editor.org/info/rfc5082>>.
- [RFC5920] Fang, L., Ed., "Security Framework for MPLS and GMPLS Networks", RFC 5920, DOI 10.17487/RFC5920, July 2010, <<https://www.rfc-editor.org/info/rfc5920>>.
- [RFC7623] Sajassi, A., Ed., Salam, S., Bitar, N., Isaac, A., and W. Henderickx, "Provider Backbone Bridging Combined with Ethernet VPN (PBB-EVPN)", RFC 7623, DOI 10.17487/RFC7623, September 2015, <<https://www.rfc-editor.org/info/rfc7623>>.
- [RFC8971] Pallagatti, S., Ed., Mirsky, G., Ed., Paragiri, S., Govindan, V., and M. Mudigonda, "Bidirectional Forwarding Detection (BFD) for Virtual eXtensible Local Area Network (VXLAN)", RFC 8971, DOI 10.17487/RFC8971, December 2020, <<https://www.rfc-editor.org/info/rfc8971>>.
- [RFC9062] Salam, S., Sajassi, A., Aldrin, S., Drake, J., and D. Eastlake 3rd, "Framework and Requirements for Ethernet VPN

(EVPN) Operations, Administration, and Maintenance (OAM)",  
RFC 9062, DOI 10.17487/RFC9062, June 2021,  
<<https://www.rfc-editor.org/info/rfc9062>>.

[RFC9135] Sajassi, A., Salam, S., Thoria, S., Drake, J., and J.  
Rabadan, "Integrated Routing and Bridging in Ethernet VPN  
(EVPN)", RFC 9135, DOI 10.17487/RFC9135, October 2021,  
<<https://www.rfc-editor.org/info/rfc9135>>.

#### Acknowledgements

The authors wish to thank the following for their comments and  
suggestions:

Mach Chen, Jorge Rabadan, and Alexander Vainshtein.

#### Authors' Addresses

Vengada Prasad Govindan  
Cisco Systems  
Email: [venggovi@cisco.com](mailto:venggovi@cisco.com)

Mudigonda Mallik  
Cisco Systems  
Email: [mmudigon@cisco.com](mailto:mmudigon@cisco.com)

Ali Sajassi  
Cisco Systems  
170 West Tasman Drive  
San Jose, CA 95134  
United States of America  
Email: [sajassi@cisco.com](mailto:sajassi@cisco.com)

Gregory Mirsky  
Ericsson  
Email: [gregmirsky@gmail.com](mailto:gregmirsky@gmail.com)

Donald E. Eastlake 3rd  
Independent  
2386 Panoramic Circle  
Apopka, FL 32703  
United States of America  
Phone: +1-508-333-2270  
Email: [d3e3e3@gmail.com](mailto:d3e3e3@gmail.com)

